

PRODUCT NO.
72477-WXY1
72477-WXY1LF

STANDARD LATCH

SHORT LATCH

COVER LATCH SIDE


OPTIONAL CODING KEYS

CONNECTOR SUB-ASSEMBLY


COVER NON-LATCH SIDE

PRODUCT NO.
72477-W1Y1PRODUCT NO.
72477-W2Y1

CABLE TIE POSITION



STANDARD LATCH FINGER
FOR CABLE TIE BELOW
LATCH FINGER AND EASIEST
ACCESS TO LATCH FINGER



SHORT LATCH FINGER
FOR CABLE TIE ABOVE
LATCH FINGER AND LARGER
CABLE SIZE CAPACITY

mat'l. code				surface		tolerance	projection	product family	
SEE NOTES				ASME Y14.5	✓	ASME Y14.5		METRAL CABLE	
ltr	ecr no	dr	date	tolerances unless otherwise specified			MM	title	
A	V71561	JRV	11/5/97	angles	linear	X ±3		4X12 UNSHIELDED	
B	V12695	EPK	11/14/01			XX ±18	scale 1:1	CABLE CONNECTOR KIT	
C	V05-0599	VS	09/08/05	0° ±2°		XXX ±051		dwg no	
D	V06-0613	JRV	2006-06-22	dr	J.VOLSTROF	11/5/97	FCI	sheet 1 of 3	
				engr	J.VOLSTROF	11/5/97		72477	
				chr	J.VOLSTROF	11/5/97		size	
				appd	J.VOLSTROF	11/5/97		A4	
sheet	revision	D	D	D				type	
index	sheet	1	2	3				CUSTOMER Drawing	

PRODUCT NO.
 72477-WXY1LF

SEE NOTE 6

ORDERING INFORMATION FOR KITS AND PARTS
 EACH KIT (CONNECTOR) CONSISTS OF:
 2 CONNECTOR SUB-ASSEMBLIES
 1 COVER, NON-LATCH SIDE
 1 COVER, LATCH SIDE
 1 LATCH FINGER

ORDER KITS 72477-WXY1LF WHERE

PLATING ON CONTACT AREA.

W=1 FOR 0.8 um GOLD

W=2 FOR 2.0 um GOLD

W=3 FOR 1.3 um GOLD

W=9 FOR 0.8 um GXT

LATCH FINGER SIZE

X=1 FOR STANDARD LATCH FINGER

X=2 FOR SHORT LATCH FINGER

COPPER WIRE SIZE

Y=1 FOR 26 TO 24 GAGE

Y=2 FOR 30 TO 28 GAGE

MATERIAL

INSULATORS, COVERS AND KEYS

GLASS FILLED 612 POLYAMIDE (UL 94 V-0)

LATCH FINGERS

POLYETHERIMIDE (UL 94 V-0)

CONTACTS

PHOSPHOR BRONZE

SN SOLDER FINISH ON IDC DIMPLES (LEAD FREE)

OPTIONAL CODING KEYS

PART NUMBER 72388-OAA1LF

18 VARIETIES AA = 01 TO 18

USE IN CONJUNCTIONS WITH HEADER CODING

KEYS 70274-001 KEYS 1 TO 18 RESPECTIVELY

COMPONENT PART NUMBERS AND INFORMATION

CONNECTOR SUBASSEMBLY

PART NUMBER 72394-W2Y1LF

* 2 REQUIRED PER CONNECTOR

PLATING ON CONTACT AREA.

W=1 FOR 0.8 um GOLD

W=2 FOR 2.0 um GOLD

W=3 FOR 1.3 um GOLD

W=9 FOR 0.8 um GXT

COPPER WIRE SIZE

Y=1 FOR 26 TO 24 GAGE

Y=2 FOR 30 TO 28 GAGE

COVER, LATCH SIDE

PART NUMBER 72513-0021LF

COVER, NON-LATCH SIDE

PART NUMBER 72513-0011LF

SHORT LATCH FINGER

PART NUMBER 72389-0011LF

STANDARD LATCH FINGER

PART NUMBER 70289-001LF

mat'l. code				surface		tolerance	projection	product family	
SEE NOTES				ASME Y14.5	✓	ASME Y14.5		METRAL CABLE	
ltr	ecr no	dr	date	tolerances unless otherwise specified				title	
D				angles	fe	X #3		4X12 UNSHIELDED	
						.XX ±.18	MM	CABLE CONNECTOR KIT	
				0° ±2°		.XXX ±.051	scale 1:1	dwg no	
				dr	J.VOLSTROF	11/5/97		sheet 3 of 3	
				engr	J.VOLSTROF	11/5/97		72477	
				chr	J.VOLSTROF	11/5/97		size	
				appd	J.VOLSTROF	11/5/97		A4	
sheet	revision							type	
index	sheet							CUSTOMER Drawing	



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.