








3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length 3 and Extended Length 4



RECOMMENDED PCB HOLE PATTERN
TOLERANCE = 0.05 [.002]



PERFORMANCE 5 7	
CURRENT:	1A, 6 LINES ENERGIZED
INSULATION RESISTANCE:	>1 X 10 ⁹ OHMS AT 500 VDC
WITHSTANDING VOLTAGE:	500 VACrms AT SEA LEVEL
TEMPERATURE RATING:	-55° C TO +105° C
SOLDER PROCESS TEMPERATURE:	260° C MAX PER IPC/JEDEC J-STD-020D

REFERENCE TABLE ON SHEET 4
FOR AVAILABLE POSITIONS AND
SOLDER TAIL LENGTHS

METRIC [ENGLISH]

- NOTES
- 1

MATERIAL:
BODY: HIGH TEMPERATURE
GLASS FILLED LCP, BLACK
UL94V-0
CONTACTS: COPPER ALLOY
- 2

PLATING:
2.03-3.81 μ m [80-150 μ in]
NICKEL UNDERPLATE.
0.38 μ m [15 μ in] OR
0.76 μ m [30 μ in] AVG GOLD
ON WIPING AREA.
5.08 μ m [200 μ in] MIN
MATTE TIN ON SOLDER TAILS.
- 3

STANDARD LENGTH HEADERS
MATE WITH 3M™ SOCKETS,
158 SERIES (REFERENCE 3M
DRAWING 78-5100-2358-9).
- 4

EXTENDED LENGTH HEADERS
MATE WITH 3M™ SOCKETS,
870 SERIES.
- 5




FOR PRODUCT
SPECIFICATIONS AND
WARRANTY INFORMATION SEE
3M 78-5102-0078-1.
- 6

SEE THE REGULATORY
INFORMATION APPENDIX (RIA)
IN THE "RoHS COMPLIANCE"
SECTION OF
WWW.3MCONNECTOR.COM FOR
COMPLIANCE INFORMATION
(RIA E1 & C1 APPLY).
- 7



IN THE EVENT OF CONFLICT
BETWEEN THIS DATA AND
THAT CONTAINED IN THE
PRODUCT SPECIFICATION,
THE PRODUCT SPECIFICATION
TAKES PRECEDENT.

DESIGN REFERENCE		NEXT ASSEMBLY		A		30741		OCT 28, 2010				LDS		SF	
DISTRIBUTION CODES				REV		ECO		INITIAL RELEASE				DRFT		CHKD	
				DRFT		L. SCHMIDT		DATE		JUL 29, 2010		MFG		DATE	
				CHKD				DATE				APPR		S FELDMAN	
												DATE		AUG 09, 2010	
DIVISION				DIVISION CODE				© 3M COPYRIGHT 2010		3M Center St. Paul, MN 55144					
DO NOT SCALE DRAWING		SCALE -6 1		TOLERANCES EXCEPT AS NOTED				THIS document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized sales purposes. All rights reserved.							
				INCHES .0 + 0.000 - 0.000 / 1000 ±				TITLE 3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES							
THIRD ANGLE PROJECTION				MILLIMETERS 0 + 0.0 - 0.0 / 254 ±				CAGE NUMBER D78-5100-2359-7				REV. A			
INTERPRET PER ASME Y14.5 - 1994								SIZE D							
MAX SURFACE ROUGHNESS 125 / ☐ ALL SURFACES ☒ MARKED ONLY				ANGLES ± 1°				DRAWING NO.							
								MODEL				DET. LISTS		YES ☒ NO	
												SHT 1		OF 4	


3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length [3] and Extended Length [4]




RECOMMENDED PCB HOLE PATTERN
TOLERANCE = ±0.05 [.002]



POLARIZATION SLOT
RIGHT ANGLE HEADER
6-12 POSITIONS ONLY





POLARIZATION SLOT AND
DUAL FRICTION LATCHES
RIGHT ANGLE HEADER
14-50 POSITIONS







SINGLE FRICTION LATCH
RIGHT ANGLE HEADER
6-12 POSITIONS ONLY

REFERENCE TABLE ON SHEET 4
FOR AVAILABLE POSITIONS AND
SOLDER TAIL LENGTHS


METRIC [ENGLISH]

A 30741				OCT 28, 2010				LDS		SF																					
				INITIAL RELEASE																											
DESIGN REFERENCE				NEXT ASSEMBLY				REV				ECO				ISSUE DATE AND DESCRIPTION				DRFT		CHKD									
DISTRIBUTION CODES								DRFT L. SCHMIDT				DATE 29, 2010				MFG DATE				DATE		DATE									
								CHKD								DATE				DATE		DATE									
																S FELDMAN				AUG 09, 2010											
DIVISION				DIVISION CODE																© 2010 COPYRIGHT 2010											
DO NOT SCALE DRAWING				SCALE 4 1				TOLERANCES EXCEPT AS NOTED				3M 3M Center St. Paul, MN 55144								This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.											
								INCHES				TITLE 3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES																			
THIRD ANGLE PROJECTION								MILLIMETERS																							
INTERPRET PER ASME Y14.5 - 1994								.00 ±																							
MAX SURFACE ROUGHNESS 125				□ ALL SURFACES				.000 ±																							
125				X MARKED ONLY				ANGLES ± 1 °																							
												CAGE NUMBER				SIZE				DRAWING NO.				REV.							
												D				78-5100-2359-7				A											
												MODEL								DET. LISTS				YES X NO				SHT 2 OF 4			


3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length [3] and Extended Length [4]




RECOMMENDED PCB PAD PATTERN
TOLERANCE = ±0.08 [.003]



POLARIZATION SLOT
SURFACE MOUNT HEADER
6-12 POSITIONS ONLY



POLARIZATION SLOT AND
DUAL FRICTION LATCHES
SURFACE MOUNT HEADER
14-50 POSITIONS



SINGLE FRICTION LATCH
SURFACE MOUNT HEADER
6-12 POSITIONS ONLY


REFERENCE TABLE ON SHEET 4
FOR AVAILABLE POSITIONS

METRIC [ENGLISH]


DESIGN REFERENCE		NEXT ASSEMBLY		A 30741		OCT 28, 2010		LDS	SF
REV		ECO		ISSUE DATE AND DESCRIPTION		DRFT		CHKD	
L. SCHMIDT		JUL 29, 2010		MFG		DATE		DATE	
CHKD		S. FELDMAN		APPROV		DATE		DATE	
DIVISION		DIVISION CODE		3M		3M Center		St. Paul, MN 55144	
DO NOT SCALE DRAWING		SCALE 4/1		TOLERANCES EXCEPT AS NOTED		INCHES		MILLIMETERS	
THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 1994		MAX SURFACE ROUGHNESS		125/		ALL SURFACES	
X MARKED ONLY		ANGLES ±1°		CAGE NUMBER		DRAWING NO.		REV.	
D		78-5100-2359-7		MODEL		DET		YES	
SHT 3 OF 4		NO		SHT 3 OF 4		SHT 3 OF 4		SHT 3 OF 4	

3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Standard Length 3


STANDARD LENGTH HEADERS
ARE AVAILABLE




STANDARD LENGTH,
POLARIZATION SLOT,
VERTICAL HEADER
6-12 POSITIONS ONLY




STANDARD LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
VERTICAL HEADER
14-50 POSITIONS




STANDARD LENGTH,
SINGLE FRICTION LATCH,
VERTICAL HEADER
6-12 POSITIONS




STANDARD LENGTH,
POLARIZATION SLOT,
RIGHT ANGLE HEADER
6-12 POSITIONS




STANDARD LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
RIGHT ANGLE HEADER
14-50 POSITIONS




STANDARD LENGTH,
SINGLE FRICTION LATCH,
RIGHT ANGLE HEADER
6-12 POSITIONS



STANDARD LENGTH,
POLARIZATION SLOT,
SURFACE MOUNT HEADER
6-12 POSITIONS




STANDARD LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
SURFACE MOUNT HEADER
14-50 POSITIONS




STANDARD LENGTH,
SINGLE FRICTION LATCH,
SURFACE MOUNT HEADER
6-12 POSITIONS

3M™ Shrouded Board Mount Header 2 mm X 2 mm Pitch 159 Series, Extended Length 4


CALL 3M INTERCONNECT SOLUTIONS
AT 800-225-5373 FOR AVAILABILITY
OF EXTENDED LENGTH HEADERS




EXTENDED LENGTH,
POLARIZATION SLOT,
VERTICAL HEADER
6-12 POSITIONS




EXTENDED LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
VERTICAL HEADER
14-50 POSITIONS




EXTENDED LENGTH,
SINGLE FRICTION LATCH,
VERTICAL HEADER
6-12 POSITIONS




EXTENDED LENGTH,
POLARIZATION SLOT,
RIGHT ANGLE HEADER
6-12 POSITIONS




EXTENDED LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
RIGHT ANGLE HEADER
14-50 POSITIONS




EXTENDED LENGTH,
SINGLE FRICTION LATCH,
RIGHT ANGLE HEADER
6-12 POSITIONS



EXTENDED LENGTH,
POLARIZATION SLOT,
SURFACE MOUNT HEADER
6-12 POSITIONS



EXTENDED LENGTH,
POLARIZATION SLOT,
DUAL FRICTION LATCHES,
SURFACE MOUNT HEADER
14-50 POSITIONS



EXTENDED LENGTH,
SINGLE FRICTION LATCH,
SURFACE MOUNT HEADER
6-12 POSITIONS

ORDERING INFORMATION

TIER 1 - BEST
1591XX-XXXX

TIER 1 = BEST 0.76 μ m
[30 μ in] GOLD

POSITION COUNT (SEE TABLE)

PART CONFIGURATION
2 = VERTICAL SMT
5 = RIGHT ANGLE THRU HOLE
6 = VERTICAL THRU HOLE

BODY LENGTH
0 = STANDARD LENGTH
(MATES TO 158 SERIES)
1 = EXTENDED LENGTH
(MATES TO 870 SERIES)

CONTACT TAIL LENGTH
2 = 2.84 mm [.112]
3 = 3.94 mm [.155]

POLARIZATION/LATCHING
0 = POLARIZATION SLOT AND
DUAL FRICTION LATCHES
(14-50 POSITIONS ONLY)
1 = POLARIZATION SLOT
(6-12 POSITIONS ONLY)
2 = SINGLE FRICTION LATCH
(6-12 POSITIONS ONLY)

TIER 2 - BETTER
1592XX-XXXX

TIER 2 = BETTER 0.38 μ m
[15 μ in] GOLD

POSITION COUNT (SEE TABLE)

PART CONFIGURATION
2 = VERTICAL SMT
5 = RIGHT ANGLE THRU HOLE
6 = VERTICAL THRU HOLE

BODY LENGTH
0 = STANDARD LENGTH
(MATES TO 158 SERIES)
1 = EXTENDED LENGTH
(MATES TO 870 SERIES)

CONTACT TAIL LENGTH
2 = 2.84 mm [.112]
3 = 3.94 mm [.155]

POLARIZATION/LATCHING
0 = POLARIZATION SLOT AND
DUAL FRICTION LATCHES
(14-50 POSITIONS ONLY)
1 = POLARIZATION SLOT
(6-12 POSITIONS ONLY)
2 = SINGLE FRICTION LATCH
(6-12 POSITIONS ONLY)

NUMBER OF POSITIONS	SHROUDED BOX HEADER						
	DIM A		DIM B	DIM C		DIM D	
	STANDARD	EXTENDED		STANDARD	EXTENDED		
6	8.35 [.329]	9.52 [.375]	4.00 [.157]	6.83 [.269]	7.99 [.315]	2.84 [.112]	3.94 [.155]
8	10.35 [.407]	11.52 [.453]	6.00 [.236]	8.83 [.347]	9.99 [.393]	2.84 [.112]	3.94 [.155]
10	12.35 [.486]	13.52 [.532]	8.00 [.315]	10.83 [.426]	11.99 [.472]	2.84 [.112]	3.94 [.155]
12	14.35 [.565]	15.52 [.611]	10.00 [.394]	12.83 [.505]	13.99 [.551]	2.84 [.112]	3.94 [.155]
14	16.36 [.644]	17.52 [.690]	12.00 [.472]	14.83 [.584]	15.99 [.630]	2.84 [.112]	3.94 [.155]
16	18.35 [.722]	19.52 [.768]	14.00 [.551]	16.83 [.662]	17.99 [.708]	2.84 [.112]	3.94 [.155]
20	22.35 [.880]	23.52 [.926]	18.00 [.709]	20.83 [.820]	21.99 [.866]	2.84 [.112]	3.94 [.155]
22	24.35 [.959]	25.52 [1.005]	20.00 [.787]	22.83 [.899]	23.99 [.945]	2.84 [.112]	3.94 [.155]
24	26.35 [1.037]	27.52 [1.083]	22.00 [.866]	24.83 [.977]	25.99 [1.023]	2.84 [.112]	3.94 [.155]
26	28.35 [1.116]	29.52 [1.162]	24.00 [.945]	26.83 [1.056]	27.99 [1.102]	2.84 [.112]	3.94 [.155]
30	32.35 [1.274]	33.52 [1.320]	28.00 [1.102]	30.83 [1.214]	31.99 [1.260]	2.84 [.112]	3.94 [.155]
34	36.35 [1.431]	37.52 [1.477]	32.00 [1.260]	34.83 [1.371]	35.99 [1.417]	2.84 [.112]	3.94 [.155]
40	42.35 [1.667]	43.52 [1.713]	38.00 [1.496]	40.83 [1.607]	41.99 [1.653]	2.84 [.112]	3.94 [.155]
44	46.35 [1.825]	47.52 [1.871]	42.00 [1.654]	44.83 [1.765]	45.99 [1.811]	2.84 [.112]	3.94 [.155]
50	52.35 [2.061]	53.52 [2.107]	48.00 [1.890]	50.83 [2.001]	51.99 [2.047]	2.84 [.112]	3.94 [.155]

METRIC [ENGLISH]

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
10 DISTRIBUTION CODES				DRFT	L. SCHMIDT	DATE	JUL 29, 2010	MFG	DATE
DIVISION		DIVISION CODE		CHKD		DATE		APPROV	DATE
								S. FELDMAN	AUG 09, 2010
DO NOT SCALE DRAWING	SCALE 4 1	TOLERANCES EXCEPT AS NOTED		3M Center St. Paul, MN 55144					
THIRD ANGLE PROJECTION		INCHES		© 3M COPYRIGHT 2010					
		MILLIMETERS		This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.					
INTERPRET PER ASME Y14.5 - 1994		0 ± .00 ± .002 ± .0000 ±		TITLE					
MAX SURFACE ROUGHNESS 125 / ALL SURFACES MARKED ONLY		0 ± .00 ± .000 ±		3M SHROUDED BOARD MOUNT HEADER 2 MM X 2 MM PITCH 159 SERIES					
		ANGLES ±1°		CAGE NUMBER		SIZE	DRAWING NO.	REV.	
				D78-5100-2359-7				A	
				MODEL		LISTS		YES NO SHT 4 OF 4	



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.