MAXM17505

4.5V to 60V, 1.7A High-Efficiency, DC-DC Step-Down Power Module with Integrated Inductor

General Description

The *Himalaya* series of voltage regulator ICs and power modules enable cooler, smaller, and simpler power supply solutions. The MAXM17505 is an easy-to-use, step-down power module that combines a switching power supply controller, dual n-channel MOSFET power switches, fully shielded inductor, and the compensation components in a low-profile, thermally-efficient, system-in-package (SiP). The device operates over a wide input voltage range of 4.5V to 60V and delivers up to 1.7A continuous output current with excellent line and load regulation over an output voltage range of 0.9V to 12V. The device only requires five external components to complete the total power solution. The high level of integration significantly reduces design complexity, manufacturing risks, and offers a true plug-and-play power supply solution, reducing time-to-market.

The device can be operated in the pulse-width modulation (PWM), pulse-frequency modulation (PFM), or discontinuous conduction mode (DCM) control schemes.

The MAXM17505 is available in a low-profile, highly thermal-emissive, compact, 29-pin 9mm x 15mm x 2.8mm SiP package that reduces power dissipation in the package and enhances efficiency. The package is easily soldered onto a printed circuit board and suitable for automated circuit board assembly. The device can operate over the industrial temperature range from -40°C to +125°C.

Applications

- Industrial Power Supplies
- Distributed Supply Regulation
- FPGA and DSP Point-of-Load Regulator
- Base Station Point-of-Load Regulator
- HVAC and Building Control

Features and Benefits

- Reduces Design Complexity, Manufacturing Risks, and Time-to-Market
  - Integrated Switching Power Supply Controller and Dual-MOSFET Power Switches
  - Integrated Inductor
  - Integrated Compensation Components
  - Integrated Thermal-Fault Protection
  - Integrated Peak Current Limit
- Saves Board Space in Space-Constrained Applications
  - Complete Integrated Step-Down Power Supply in a Single Package
  - Small Profile 9mm x 15mm x 2.8mm SiP Package
  - Simplified PCB Design with Minimal External BOM Components
- Offers Flexibility for Power-Design Optimization
  - Wide Input Voltage Range from 4.5V to 60V
  - Output-Voltage Adjustable Range from 0.9V to 12V
  - Adjustable Frequency with External Frequency Synchronization (100kHz to 1.8MHz)
  - Soft-Start Programmable
  - Autoswitch PWM, PFM, or DCM Current-Mode Control
  - Optional Programmable EN/UVLO

***Ordering Information* appears at end of data sheet.**

Typical Application Circuit



Absolute Maximum Ratings (Notes 1, 2)

IN to PGND (Note 2) .....-0.3V to +65V
EN to SGND (Note 2).....-0.3V to +65V
V_{CC}.....-0.3V to min (V_{IN} + 0.3V, 6.5V)
FB, $\overline{RESET}$, SS, CF, MODE,
SYNC, RT to SGND .....-0.3V to +6.5V
OUT to PGND (V_{IN} < 25V).....-0.3V to (V_{IN} + 0.3V)
OUT to PGND (V_{IN} ≥ 25V).....-0.3V to +25V
LX to PGND.....-0.3V to (V_{IN} + 0.3V)
BST to PGND .....-0.3V to +70V
BST to V_{CC} .....-0.3V to +65V
BST to LX.....-0.3V to +6.5V
Operating Temperature Range..... -40°C to +125°C
Junction Temperature.....+125°C
Storage Temperature Range..... -65°C to +125°C
Lead Temperature (soldering, 10s) .....+245°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Package Thermal Characteristics (Note 3)

Junction-to-Ambient Thermal Resistance (θ_{JA}) .....25.2°C/W
Junction-to-Top-Case Thermal Resistance (Ψ_{JT}) .....5.2°C/W

Note 1: SGND and PGND are internally connected.
Note 2: See *Pin Description* for the connection of the backside exposed pad.
Note 3: Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to **www.maximintegrated.com/thermal-tutorial**.

Electrical Characteristics

(V_{IN} = V_{EN} = 24V, R_{RT} = 40.2kΩ (500kHz) to SGND, V_{PGND} = V_{MODE} = V_{SYNC} = V_{SGND} = 0V, V_{CC} = LX = SS = $\overline{RESET}$ = OUT = open, V_{BST} to V_{LX} = 5V, V_{FB} = 1V, T_A = T_J = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C. All voltages are referenced to SGND, unless otherwise noted.) (Note 4)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
INPUT SUPPLY (V_{IN})						
IN Input Voltage Range	V_{IN}		4.5		60	V
Input Shutdown Current	I_{IN_SH}	V_{EN} = 0V		10.5	13	µA
Input Quiescent Current	$I_{Q_PFM_HIB}$	MODE = RT = open		125		µA
	I_{Q_DCM}	MODE = V_{CC}		1.16	1.8	mA
	I_{Q_PWM}	Normal switching mode, no load		9.5		mA
LOGIC INPUTS						
EN Threshold	V_{ENR}	V_{EN} rising	1.192	1.215	1.26	V
	V_{ENF}	V_{EN} falling	1.068	1.09	1.131	V
Enable Pullup Resistor	R_{ENP}	Pullup resistor between IN and EN pins	3.15	3.3	3.45	MΩ
LDO						
V_{CC} Output Voltage Range	V_{CC}	6V < V_{IN} < 60V, 1mA < I_{VCC} < 25mA	4.75	5	5.25	V
V_{CC} Current Limit	I_{VCC_MAX}	V_{IN} = 6V, V_{CC} = 4.3V	26.5	60	100	mA
V_{CC} Dropout	V_{CC_DO}	V_{IN} = 4.5V, I_{VCC} = 20mA	4.2			V
V_{CC} UVLO	V_{CC_UVR}	V_{CC} rising	4.05	4.2	4.3	V
	V_{CC_UVF}	V_{CC} falling	3.65	3.8	3.9	
OUTPUT SPECIFICATIONS						
Line Regulation Accuracy		V_{IN} = 6.5V to 60V, V_{OUT} = 5V		0.1		mV/V
Load Regulation Accuracy		Tested with I_{OUT} = 0A and 1A		1		mV/A

Electrical Characteristics (continued)

(V_{IN} = V_{EN} = 24V, R_{RT} = 40.2kΩ (500kHz) to SGND, V_{PGND} = V_{MODE} = V_{SYNC} = V_{SGND} = 0V, V_{CC} = LX = SS = $\overline{RESET}$ = OUT = open, V_{BST} to V_{LX} = 5V, V_{FB} = 1V, T_A = T_J = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C. All voltages are referenced to SGND, unless otherwise noted.) (Note 4)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
FB Regulation Voltage	V_{FB_REG}	MODE = SGND	0.887		0.910	V
		MODE = open	0.890	0.915	0.936	
FB Input Bias Current	I_{FB}	0V < V_{FB} < 1V, T_A = +25°C	-50		+50	nA
FB Undervoltage Trip Level to Cause Hiccup	V_{FB_HICF}		0.56	0.58	0.65	V
Hiccup Timeout				32,768		Cycles
SOFT-START (SS)						
Charging Current	I_{SS}	V_{SS} = 0.5V	4.7	5	5.3	µA
RT AND SYNC						
Switching Frequency	f_{SW}	R_{RT} = 210kΩ	90	100	110	kHz
		R_{RT} = 9.76kΩ		1800		
		R_{RT} = open	450	500	550	
SYNC Frequency Range			1.1 x f_{SW}		1.4 x f_{SW}	kHz
SYNC Pulse Width			50			ns
SYNC Threshold	V_{IH}		2.1			V
	V_{IL}				0.8	
MODE						
MODE Threshold	V_{M_DCM}	MODE = V_{CC} (DCM mode)	V_{CC} - 1.6			V
	V_{M_PFM}	MODE = open (PFM mode)		V_{CC}/2		
	V_{M_PWM}	MODE = GND (PWM mode)			1.4	
CURRENT LIMIT						
Average Current-Limit Threshold	I_{AVG_LIMIT}	V_{OUT} = V_{FB} = 0.8V, f_{SW} = 200kHz		2.4		A
$\overline{RESET}$						
$\overline{RESET}$ Output Level Low		$I_{\overline{RESET}}$ = 10mA			0.4	V
$\overline{RESET}$ Output Leakage Current		$V_{\overline{RESET}}$ = 5.5V, T_A = T_J = +25°C	-0.1		+0.1	µA
FB Threshold for $\overline{RESET}$ Assertion	V_{FB_OKF}	V_{FB} falling	90.5	92	94.6	%
FB Threshold for $\overline{RESET}$ Deassertion	V_{FB_OKR}	V_{FB} rising	93.8	95	97.8	%
$\overline{RESET}$ Deassertion Delay After FB Reaches 95% Regulation				1024		Cycles
THERMAL SHUTDOWN						
Thermal-Shutdown Threshold		Temperature rising		+165		°C
Thermal-Shutdown Hysteresis				10		°C

Note 4: All limits are 100% tested at T_A = +25°C. Maximum and minimum limits are guaranteed by design and characterized over temperature.

Typical Operating Characteristics

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 12V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 12V, PWM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 5V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 5V, PWM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 3.3V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 3.3V, PWM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 2.5V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 2.5V, PWM MODE



Typical Operating Characteristics (continued)

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 1.2V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 1.2V, PWM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 0.9V, PFM MODE



EFFICIENCY vs. OUTPUT CURRENT
V_{OUT} = 0.9V, PWM MODE



LOAD REGULATION
V_{OUT} = 3.3V, PFM MODE



LOAD REGULATION
V_{OUT} = 3.3V, PWM MODE



LOAD REGULATION
V_{OUT} = 5V, PFM MODE



LOAD REGULATION
V_{OUT} = 5V, PWM MODE



Typical Operating Characteristics (continued)

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

LOAD REGULATION
V_{OUT} = 12V, PFM MODE



LOAD REGULATION
V_{OUT} = 12V, PWM MODE



OUTPUT VOLTAGE RIPPLE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 1.7A, MODE = SGND



OUTPUT VOLTAGE RIPPLE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 1.7A, MODE = SGND



INPUT VOLTAGE RIPPLE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 1.7A, MODE = SGND



INPUT VOLTAGE RIPPLE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 1.7A, MODE = SGND



LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0.05A - 0.85A, MODE = OPEN



LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0.05A - 0.85A, MODE = SGND



Typical Operating Characteristics (continued)

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0.05A - 0.85A, MODE = V_{CC}



LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0.05A - 0.85A, MODE = OPEN



LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0.05A - 0.85A, MODE = SGND



LOAD CURRENT TRANSIENT RESPONSE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0.05A - 0.85A, MODE = V_{CC}



STARTUP THROUGH ENABLE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0A, MODE = SGND



STARTUP WITH 2.5V PREBIAS
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0A, MODE = SGND



STARTUP WITH 2.5V PREBIAS
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0A, MODE = OPEN



SHUTDOWN THROUGH ENABLE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0A, MODE = SGND



Typical Operating Characteristics (continued)

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

STARTUP THROUGH INPUT SUPPLY
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 1.7A, MODE = SGND



SHUTDOWN THROUGH INPUT SUPPLY
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 1.7A, MODE = SGND



STARTUP THROUGH ENABLE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0A, MODE = SGND



SHUTDOWN THROUGH ENABLE
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0A, MODE = SGND



STARTUP THROUGH INPUT SUPPLY
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 1.7A, MODE = SGND



SHUTDOWN THROUGH INPUT SUPPLY
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 1.7A, MODE = SGND



Typical Operating Characteristics (continued)

(V_{IN} = 4.5V to 60V, V_{OUT} = 0.9V to 12V, I_{OUT} = 0A to 1.7A, T_A = +25°C, unless otherwise noted.)

OUTPUT SHORT IN STEADY STATE
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 0A to SHORT
MODE = SGND



OUTPUT SHORT DURING STARTUP
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = SHORT, MODE = SGND



SYNC FREQUENCY AT 740 KHZ
V_{IN} = 24V, V_{OUT} = 5V, I_{OUT} = 0A, MODE = GND



CLOSED-LOOP BODE PLOT
V_{IN} = 24V, V_{OUT} = 3.3V, I_{OUT} = 1.7A, MODE = SGND



OUTPUT CURRENT
VS. AMBIENT TEMPERATURE
V_{IN} = 24V NO AIR FLOW



Pin Configuration



Pin Description

PIN	NAME	FUNCTION
1, 7	N.C.	No Connection
2	SYNC	Frequency Synchronization. The device can be synchronized to an external clock using this pin. See the *External Frequency Synchronization* section for more details.
3	SS	Soft-Start Input. Connect a capacitor from SS to SGND to set the soft-start.
4	CF	Compensation Filter. Connect capacitor from CF to FB to correct frequency response in applications using non-ceramic output capacitors with switching frequency below 500kHz. Leave CF open otherwise.
5	FB	Feedback Input. Connect FB to the center tap of an external resistor-divider from the OUT to SGND to set the output voltage. See the *Adjusting Output Voltage* section for more details.
6	RT	Frequency Set. Connect a resistor from RT to SGND to set the regulator's switching frequency. Leave RT open for the default 500kHz frequency.
8	MODE	Light-Load Mode Selection. The MODE pin configures the MAXM17505 to operate in PWM, PFM, or DCM mode of operation. Leave MODE unconnected for PFM operation (pulse skipping at light loads). Connect MODE to SGND for constant-frequency PWM operation at all loads. Connect MODE to V_{CC} for DCM operation. See the *MODE Setting* section for more details.
9	V_{CC}	5V LDO Output. No external connection.
10	SGND	Analog Ground. Internally-shorted to PGND. Connect it to PGND through a single point at output capacitor.
11, 26	PGND	Power Ground. Connect the PGND pins externally to the power ground plane.
12–18	OUT	Regulator Output Pin. Connect a capacitor from OUT to PGND. See the *PCB Layout Guidelines* section for more connection details.
19–24	LX	Internally Connected to EP2. Do not connect these pins to external components for any reason.
25	BST	Boost Flying Cap Node. No external connection.
27	IN	Input Supply Connection. Bypass to PGND with a capacitor; place the capacitor close to the IN and PGND pins. See Table 1 for more details.
28	EN	Enable/Undervoltage-Lockout Input. Default enable through the pullup 3.3MΩ resistor between EN and IN. Connect a resistor from EN to SGND to set the UVLO threshold. If the EN/UVLO pin is driven by an external signal, a 50Ω damping resistor in series with the signal line driving EN/UVLO is required.
29	$\overline{\text{RESET}}$	Open-Drain $\overline{\text{RESET}}$ Output. The $\overline{\text{RESET}}$ output is driven low if FB drops below 92% of its set value. $\overline{\text{RESET}}$ goes high 1024 clock cycles after FB rises above 95% of its set value.
EP1	SGND	Analog Ground. Connect this pad to 1in x 1in copper island with a lot of vias for cooling.
EP2	LX	Switching Node. Connect this pad to a small copper area of 1in x 1in under the device for thermal relief.
EP3	OUT	Connect this pad to the OUT pins and copper area of 1in x 1in.

Functional Diagram



Design Procedure

Setting the Output Voltage

The MAXM17505 supports an adjustable output voltage range of 0.9V to 12V from an input voltage range of 4.5V to 60V by using a resistive feedback divider from OUT to FB. Table 1 provides the feedback dividers for desired input and output voltages. Other adjustable output voltages can be calculated by following the procedure to choose the resistive voltage-divider values:

Calculate resistor R_U from the output to FB as follows:

$$R_U = \frac{216 \times 1000}{f_C \times C_{OUT}}$$

where R_U is in kΩ, crossover frequency (f_C) is in kHz, and output capacitor (C_{OUT}) is in µF. Choose f_C to be 1/9th of the switching frequency (f_{SW}) if the switching frequency is less than or equal to 500kHz. If the switching frequency is more than 500kHz, select f_C to be 55kHz.

$$R_B = \frac{R_U \times 0.9}{V_{OUT} - 0.9} k\Omega, \text{where } R_B \text{ is in } k\Omega.$$



Figure 1. Adjustable Output Voltage

Input Voltage Range

Due to the limitation of minimum and maximum duty cycle, the maximum value ($V_{IN\ (MAX)}$) and minimum value ($V_{IN\ (MIN)}$) must accommodate the worst-case conditions, accounting for the input voltage rises and drops. To simplify, Table 1 provides operating input voltage ranges of different desired output voltages.

Input Capacitor Selection

The input capacitor serves to reduce the current peaks drawn from the input power supply and reduces switching noise to the IC. The input capacitor values in Table 1 are the minimum recommended values for desired input and output voltages. Applying capacitor values larger than those indicated in Table 1 are acceptable to improve the dynamic response. For further operating conditions, the total input capacitance must be greater than or equal to the value given by the following equation in order to keep the input-voltage ripple within specifications and minimize the high-frequency ripple current being fed back to the input source:

$$C_{IN} = \frac{(I_{IN_AVG}) \times (1 - D)}{(\Delta V_{IN}) \times f_{SW}}$$

where:

I_{IN_AVG} is the average input current given by:

$$I_{IN_AVG} = \frac{P_{OUT}}{\eta \times V_{IN}}$$

D is the operating duty cycle, which is approximately equal to V_{OUT}/V_{IN}.

ΔV_{IN} is the required input voltage ripple.

f_{SW} is the operating switching frequency.

P_{OUT} is the out power, which is equal to V_{OUT} x I_{OUT}.

η is the efficiency.

The input capacitor must meet the ripple-current requirement imposed by the switching currents. The RMS input ripple current is given by:

$$I_{RMS} = I_{OUT} \times \sqrt{D \times (1 - D)}$$

The worst-case RMS current requirement occurs when operating with D = 0.5. At this point, the above equation simplifies to I_{RMS} = 0.5 x I_{OUT}.

For the MAXM17505 system (IN) supply, ceramic capacitors are preferred due to their resilience to inrush surge currents typical of systems, and due to their low parasitic inductance that helps reduce the high-frequency ringing on the IN supply when the internal MOSFETs are turned off. Choose an input capacitor that exhibits less than +10°C temperature rise at the RMS input current for optimal circuit longevity.

Table 1. Selection Component Values

V_{IN} (V)	V_{OUT} (V)	C_{IN}	C_{OUT}	R_U (kΩ)	R_B (kΩ)	f_{SW} (kHz)	R_T (kΩ)
4.5 to 15	0.9	3 x 2.2µF 1206 100V	2 x 100µF 1210 4V	35.7	Open	300	68.1
4.5 to 15	1	3 x 2.2µF 1206 100V	2 x 100µF 1210 4V	39.2	357	300	68.1
4.5 to 15	1.2	3 x 2.2µF 1206 100V	1 x 100µF 1 x 47µF 1210 4V	47.5	143	350	57.6
4.5 to 15	1.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	59	88.7	350	57.6
4.5 to 15	1.8	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	69.8	69.8	350	57.6
4.5 to 15	2.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	97.6	54.9	350	57.6
4.5 to 15	3.3	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	127	47.5	400	49.9
6.5 to 15	5	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	196	43.2	500	Open
11 to 15	8	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	309	39.2	800	23.7
4.5 to 28	0.9	3 x 2.2µF 1206 100V	3 x 100µF 1210 4V	35.7	Open	200	100
4.5 to 28	1	3 x 2.2µF 1206 100V	2 x 100µF 1 x 47µF 1210 4V	39.2	357	238	86.6
4.5 to 28	1.2	3 x 2.2µF 1206 100V	1 x 100µF 1 x 47µF 1210 4V	47.5	143	285	71.5
4.5 to 28	1.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	59	88.7	350	57.6
4.5 to 28	1.8	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	69.8	69.8	350	57.6
4.5 to 28	2.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	97.6	54.9	350	57.6
4.5 to 28	3.3	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	127	47.5	400	49.9
6.5 to 28	5	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	196	43.2	500	Open
11 to 28	8	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	309	39.2	800	23.7
18.5 to 28	12	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	475	38.3	1200	15.8
4.5 to 40	1.2	3 x 2.2µF 1206 100V	2 x 100µF 1210 4V	47.5	143	200	100
4.5 to 40	1.5	3 x 2.2µF 1206 100V	1 x 100µF 1 x 47µF 1210 4V	59	88.7	250	82.5
4.5 to 40	1.8	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	69.8	69.8	300	68.1
4.5 to 40	2.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	97.6	54.9	350	57.6
4.5 to 40	3.3	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	127	47.5	400	49.9
6.5 to 40	5	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	196	43.2	500	Open
11 to 40	8	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	309	39.2	800	23.7
18.5 to 40	12	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	475	38.3	1200	15.8
4.5 to 60	1.8	3 x 2.2µF 1206 100V	2 x 100µF 1210 4V	69.8	69.8	200	100.0
6 to 60	2.5	3 x 2.2µF 1206 100V	1 x 100µF 1210 4V	97.6	54.9	277	73.2
8 to 60	3.3	3 x 2.2µF 1206 100V	2 x 47µF 1210 10V	127	47.5	366	54.9
11 to 60	5	2 x 2.2µF 1206 100V	1 x 47µF 1210 10V	196	43.2	500	Open
17 to 60	8	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	309	39.2	888	21.5
25 to 60	12	2 x 2.2µF 1206 100V	1 x 10µF 1210 16V	475	38.3	1200	15.8

Output Capacitor Selection

The X7R ceramic output capacitors are preferred due to their stability over temperature in industrial applications. The minimum recommended output capacitor values in Table 1 are for desired output voltages to support a dynamic step load of 50% of the maximum output current in the application. For additional adjustable output voltages, the output capacitance value is derived from the following equation:

$$C_{OUT} = \frac{I_{STEP} \times t_{RESPONSE}}{2 \times \Delta V_{OUT}}$$

$$t_{RESPONSE} \approx \frac{0.33}{f_C} + \frac{1}{f_{SW}}$$

where I_{STEP} is the step load transient, $t_{RESPONSE}$ is the response time of the controller, ΔV_{OUT} is the allowable output ripple voltage during load transient, f_C is the target closed-loop crossover frequency, and f_{SW} is the switching frequency. Select f_C to be 1/9th of f_{SW} or 55kHz if the f_{SW} is greater than 500kHz.

Loop Compensation

The MAXM17505 integrates the internal compensation to stabilize the control loop. Only the device requires a combination of output capacitors and feedback resistors to program the closed-loop crossover frequency (f_C) at 1/9th of switching frequency. Use Table 1 to select component values to compensate with appropriating operating switching frequency. Connect capacitor from CF to FB to correct frequency response in applications using nonceramic output capacitors with switching frequency below 500kHz. Place a 2.2pF for switching frequency below 300kHz, and 1.2pF for switching frequency range of 300kHz to 400kHz.

Setting the Switching Frequency (RT)

The switching frequency range of 100kHz to 1.8MHz are recommended from Table 1 for desired input and output voltages. The switching frequency of MAXM17505 can be programmed by using a single resistor (R_{RT}) connected from the RT pin to SGND. The calculation of R_{RT} resistor is given by the following equation:

$$R_{RT} \approx \frac{21000}{f_{SW}} - 1.7$$

where R_{RT} is in kΩ and f_{SW} is in kHz. Leaving the RT pin open to operate at the default switching frequency of 500kHz.

Soft-Start Capacitor Selection

The device implements an adjustable soft-start operation to reduce inrush current during startup. A capacitor (C_{SS}) connected from the SS pin to SGND to program the soft-start time.

The selected output capacitance (C_{SEL}) and the output voltage (V_{OUT}) determine the minimum value of C_{SS}, as shown by the following equation:

$$C_{SS} \geq 28 \times 10^{-3} \times C_{SEL} \times V_{OUT}$$

where C_{SS} is in nF and C_{SEL} is in µF.

The value of the soft-start capacitor is calculated from the desired soft-start time as follows:

$$t_{SS} \approx \frac{10^6 \times C_{SS}}{5.55}$$

where t_{SS} is in ms and C_{SS} is in nF.

Detailed Description

The MAXM17505 is a complete step-down DC-DC power supply that delivers up to 1.7A output current. The device provides a programmable output voltage to regulate up to 12V through external resistor dividers from an input voltage range of 4.5V to 60V. The recommended input voltage in Table 1 is selected highly enough to support the desired output voltage and load current. The device includes an adjustable frequency feature range from 100kHz to 1.8MHz to reduce sizes of input and output capacitors. The *Functional Diagram* shows a complete internal block diagram of the MAXM17505 power module.

Input Undervoltage-Lockout Level

The MAXM17505 contains an internal pullup resistor (3.3MΩ) from EN to IN to have a default startup voltage. The device offers an adjustable input undervoltage-lockout level to set the voltage at which the device is turned on by a single resistor connecting from EN/UVLO to SGND as equation:

$$R_{ENU} \approx \frac{3.3 \times 1215}{(V_{INU} - 1.215)}$$

where R_{ENU} is in kΩ and V_{INU} is the voltage at which the device is required to turn on the device. Ensure that V_{INU} is high enough to support the V_{OUT}. See Table 1 to set the proper V_{INU} voltage greater than or equal the minimum input voltage for each desired output voltage.

Mode Selection (MODE)

The MAXM17505 features a MODE pin to configure the device operating in PWM, PFM, or DCM control schemes. The device operates in PFM mode at light loads if the MODE pin is open. If the MODE pin connects to ground, the device operates in constant-frequency PWM mode at all loads. The device operates in constant-frequency DCM mode at light loads when the MODE pin connects to V_{CC}. State changes of the MODE operation are only at power-up and ignore during normal operation.

PWM Mode Operation

In PWM mode, the step-down controller is switching a constant-frequency at all loads with a minimum sink current limit threshold (-1.8A, typ) at light load. The PWM mode of operation gives lower efficiency at light loads compared to PFM and DCM modes of operation. However, the PWM mode of operation is useful in applications sensitive to switching frequency.

PFM Mode Operation

In PFM mode, the controller forces the peak inductor current in order to feed the light loads and maintain high efficiency. If the load is lighter than the average PFM value, the output voltage will exceed 102.3% of the feedback threshold and the controller enters into a hibernation mode, turning off most of the internal blocks. The device exits hibernation mode, and starts switching again, once the output voltage is discharged to 101.1% of the feedback threshold. The device then begins the process of delivering pulses of energy to the output repeatedly until it reaches 102.3% of the feedback threshold. In this mode, the behavior resembles PWM operation (with occasional pulse-skipping), where the inductor current does not need to reach the light-load level.

PFM mode offers the advantage of increased efficiency at light loads due to a lower quiescent current drawn from the supply. However, the output-voltage ripple is also increased as compared to the PWM or DCM modes of operation, and the switching frequency is not constant at light loads.

DCM Mode Operation

DCM mode features constant frequency operation down to lighter loads than PFM mode, accomplished by not skipping pulses. DCM efficiency performance lies between the PWM and PFM modes.

External Frequency Synchronization (SYNC)

The device can be synchronized by an external clock signal on the SYNC pin. The external synchronization clock frequency must be between 1.1 x f_{SW} and 1.4 x f_{SW}, where f_{SW} is the frequency programmed by the RT resistor. The minimum external clock high pulse width and amplitude should be greater than 50ns and 2.1V respectively. The minimum external clock low pulse width should be greater than 160ns, and the maximum external clock low pulse amplitude should be less than 0.8V. Table 1 provides recommended synchronous frequency ranges for desired output voltages. Connect the SYNC pin to SGND if it is not used.

$\overline{\text{RESET}}$ Output

The device includes a $\overline{\text{RESET}}$ comparator to monitor the output for undervoltage and overvoltage conditions. The open-drain $\overline{\text{RESET}}$ output requires an external pullup resistor from 10kΩ to 100kΩ to V_{CC} pin or maximum 6V voltage source. $\overline{\text{RESET}}$ goes high impedance after the regulator output increases above 95% of the designed nominal regulated voltage. $\overline{\text{RESET}}$ goes low when the regulator output voltage drops below 92% of the nominal regulated voltage. $\overline{\text{RESET}}$ also goes low during thermal shutdown.

Thermal Fault Protection

The MAXM17505 features a thermal-fault protection circuit. When the junction temperature rises above +165°C (typ), a thermal sensor activates the fault latch, pulls down the $\overline{\text{RESET}}$ output, and shuts down the regulator. The thermal sensor restarts the controllers after the junction temperature cools by 10°C (typ). The soft-start resets during thermal shutdown.

Power Dissipation and Output-Current Derating

The MAXM17505 output current needs to be derated if the device needs to be operated in a high ambient-temperature environment. The amount of current-derating depends upon the input voltage, output voltage, and ambient temperature. The derating curves in TOC43 from the *Typical Operating Characteristics* section can be used as guidelines. The curves are based on simulating thermal resistance model (ψ_{JT}), measuring thermal resistance (ψ_{TA}), and measuring power dissipation (P_{DMAX}) on the bench.

The maximum allowable power losses can be calculated using the following equation:

$$P_{DMAX} = \frac{T_{JMAX} - T_A}{\theta_{JA}}$$

where:

P_{DMAX} is the maximum allowed power losses with maximum allowed junction temperature.

T_{JMAX} is the maximum allowed junction temperature.

T_A is operating ambient temperature.

θ_{JA} is the junction to ambient thermal resistance.

PCB Layout Guidelines

Careful PCB layout is critical to achieving low switching losses and clean, stable operation.

Use the following guidelines for good PCB layout:

- Keep the input capacitors as close as possible to the IN and PGND pins.
- Keep the output capacitors as close as possible to the OUT and PGND pins.
- Keep the resistive feedback dividers as close as possible to the FB pin.
- Connect all of the PGND connections to as large as copper plane area as possible on the top layer.
- Connect EP1 to PGND and GND planes on bottom layer.
- Use multiple vias to connect internal PGND planes to the top layer PGND plane.
- Do not keep any solder mask on EP1, EP2, and EP3 on bottom layer. Keeping solder mask on exposed pads decreases the heat dissipating capability.
- Keep the power traces and load connections short. This practice is essential for high efficiency. Using thick copper PCBs (2oz vs. 1oz) can enhance full-load efficiency. Correctly routing PCB traces is a difficult task that must be approached in terms of fractions of centimeters, where a single milliohm of excess trace resistance causes a measurable efficiency penalty.

Layout Recommendation



Chip Information

PROCESS: BiCMOS

Ordering Information

PART	TEMP RANGE	MSL	PIN-PACKAGE
MAXM17505ALJ+T	-40°C to +125°C	3	29 SiP

+Denotes a lead(Pb)-free/RoHS-compliant package.
T = Tape and reel.

Package Information

For the latest package outline information and land patterns (footprints), go to **www.maximintegrated.com/packages**. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

PACKAGE TYPE	PACKAGE CODE	OUTLINE NO.	LAND PATTERN NO.
29 SiP	L32915+1	21-0879	90-0459

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	11/14	Initial release	—
1	4/15	Added application recommendation to avoid potential latch-up issue on EN pin and added MSL 3 rating	11, 18

For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at www.maximintegrated.com.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Maxim Integrated and the Maxim Integrated logo are trademarks of Maxim Integrated Products, Inc. © 2015 Maxim Integrated Products, Inc.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.