

Ordering Information						
System Voltage/Poles	230V/1	230V/1	230V/1	400V/1	600V/1	230V/1*
Max. Continuous operating AC voltage (MCOV) [U _C]	275V	320V	385V	440V	600V	255V
Catalog Numbers: Without Remote Signaling	BSPM1275TN	BSPM1320TN	BSPM1385TN	BSPM1440TN	BSPM1600TN	BSPG1255NPE
(Base + Modules) With Remote Signaling	BSPM1275TNR	BSPM1320TNR	BSPM1385TNR	BSPM1440TNR	BSPM1600TNR	BSPG1255NPER
Replacement Modules	BPM275IEC	BPM320IEC	BPM385IEC	BPM440IEC	BPM600IEC	BPG255NPE
Specifications						
Line system type	TN / TT	TN / TT	TN / TT	TN	TN	TT
Max. Continuous operating DC voltage [U _C]	350V	420V	500V	585V	600V	- -
Voltage protection level [U _p]	≤ 1.25kV	≤ 1.5kV	≤ 1.75kV	≤ 2kV	≤ 2.5kV	≤ 1.5kV
Voltage protection level at 5kA [U _p]	≤ 1kV	≤ 1.2kV	≤ 1.35kV	≤ 1.7kV	≤ 2kV	- -
Max. mains-side overcurrent protection	125A gL/gG	125A gL/gG	125A gL/gG	125A gL/gG	100A gL-gG	- -
Short-circuit withstand capability for max. mains-side overcurrent protection	50kA _{rms}	25kA _{rms}	25kA _{rms}	25kA _{rms}	25kA rms	- -
Temporary overvoltage (TOV) [U _T]	335V/5 sec.	335V/5 sec.	385V/5 sec.	580V/5 sec.	600V/5 sec.	1200V/200 ms
Response time [t _A]	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 100 ns
Follow current extinguishing capability [I _{fi}]	- -	- -	- -	- -	- -	100A _{rms}
Lightning impulse current (10/350 μs) [I _{imp}]	- -	- -	- -	- -	- -	12kA
Nominal discharge current (8/20 μs) [I _n]	20kA	20kA	20kA	20kA	15kA	20kA
Max. Discharge current (8/20 μs) [I _{max}]	40kA	40kA	40kA	40kA	30kA	40kA
Standards Information	KEMA	KEMA, CSA	KEMA, CSA	KEMA, CSA	KEMA	KEMA
Capacity	1 mod., DIN 43880					
SPD according to EN 61643-11	Type 2					
SPD according to IEC 61643-1	Class II					
TOV characteristics	Withstand					
Operating temperature range [T _U]	-40°C to +80°C					
Operating state/fault indication	Green (good) / Red (replace)					
Number of ports	1					
Cross-sectional area (min.)	1.5mm²/14AWG solid/flexible					
Cross-sectional area (max.)	35mm²/2AWG stranded-25mm²/4AWG flexible					
Mounting	35mm DIN Rail per EN 60715					
Enclosure material	Thermoplastic, UL 94V0					
Location category	Indoor					
Degree of protection	IP20					
Product Warranty	Five Years**					
Remote Contact Signaling						
Remote Contact Signaling Type	Changeover Contact					
AC Switching Capacity (Volts/Amps)	250V/0.1A					
DC Switching Capacity (Volts/Amps)	250V/0.1A; 125V/0.2A; 75V/0.5A					
Conductor Ratings and Cross-Sectional Area for Remote Contact Signal Terminals	60/75°C Max. 1.5mm²/14AWG Solid/Flexible					
Ordering Information	Order from Catalog Numbers Above					

* N-PE Surge arrester for location between neutral conductor and protective conductor in TT systems.

** See Cooper Bussmann SPD Limited Warranty Statement (3A1502) for details at www.cooperbussmann.com/surge.

Recommended Cooper Bussmann Back Up Fuses		
DIN Fuse Size	TT / TN System NH Fuse Part Numbers	
	275, 320, 385, 440V	600V
00	125NHG00B	100NHG00B-690
0	125NHG0B	100NHG0B-690
01	125NHG01B	- -
1	- -	100NHG1B-690
02	125NHG02B	- -
2	- -	100NHG2B-690

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.