

Magnetic Jacks

Molex magnetic jacks are available supporting 10/100 and Gigabit transmission. Additionally Molex offers Power over Ethernet (PoE) magnetic jacks. These are offered with and without PoE controllers for both power source equipment or power device applications.

Cat5/5e

Molex's broad range of Modular Jacks and Plugs, with more than 1000 different parts, provides versatile solutions to meet today's increasing demand for information flow with greater bandwidth requirements.

Cat3

The extensive breadth of products offer exceptional performance and reliability for voice, data and high-speed networking applications and are the ideal solution for consumer, office, medical, commercial and industrial applications.

Reference Information

Circuit sizes: 4, 6, 8 contacts

Mating direction:

Right angle, vertical

Shielding: With and without


Number of ports: Single, multiport

Soldering: Through hole, SMT

Magnetics: LEDs, light pipes

Speeds: Cat3, Cat5, Cat5E, Cat6a

Large variety of modular jacks in the industry



Quality/Price competitive




Competitive prices within most ranges

Fully automated manufacturing plant in Lincoln, NE, USA






Delivery

Short lead time

Packaging Types



Orientation Types



Ordering Information

	Series	Orientation	Ports	Category	PCB attachment		Shielding	LED	Positions/ Loaded Contacts	Height (mm)	Description					
					Signal tails	Body tails										
	95502	Bottom entry	1	3	Through hole	Through hole	X	No	4/4 6/4 6/6 8/8	12.58	Bottom entry					
	44915	N/A		6	N/A	N/A	None		8/8	N/A	Long body plug					
	48253			5e			External			16.15	In-line coupler					
	90075	Plug		3			X		4/4 6/4 6/6 8/8	N/A	Short body modular plug					
	95043			5			External shield		8/8		Short body modular plug					
	95009	Right angle		3	Through hole	Through hole	X		4/4 6/4 6/6 8/8	16.00	Flush or flange					
	95501				Through hole, SMT					Through hole	External shield	11.50	Optional Key			
	95622					Through hole, SMT	Internal shield	8/8	13.00			Shield tabs and solder pins				
	95540								SMT	X	4/4 6/4 6/6 8/8	11.50	SMT or through hole shield tabs/nails			
	85502				Through hole, SMT	Through hole	External shield	8/8	13.00	Shield tabs						
	85542				SMT					Through hole	Through hole shield nails					
	93242				Through hole, SMT	Through hole, SMT	X			11.50	Unshielded through hole					
	85543			5		Internal shield		Internally shielded								
	85503						Gig Magnetic	Through hole	Through hole	External shield	Yes	13.87	Gig magnetic PoE+ PDjack			
	85504			3		External, none							No	4/2, 4/4, 6/2, 6/4, 6/6, 8/2, 8/4, 8/6, 8/8, 8/10	11.58/ 11.81.12.09	Ultra-low profile
	85505															SMT

Ordering Information

	Series	Orientation	Ports	Category	PCB attachment		Shielding	LED	Positions/ Loaded Contacts	Height (mm)	Description		
					Signal tails	Body tails							
	43860	Right angle	1		Through hole	Through hole	External, none	Lightpipes & N	6/2, 6/4, 6/6, 8/4, 8/8	13.21/ 13.53/13.54	Inverted, available with or without lightpipes		
	44144				SMT	SMT	None	No	6/2, 6/4, 6/6, 8/2, 8/4, 8/6, 8/8	11.73	Inboard fitting nails		
	44282						8/8		12.19	Low profile			
	44380				Through hole		External, none	Lightpipes & N	6/4, 6/6, 8/4, 8/6, 8/8	13.21/ 13.53	Mini PCIe available with or without lightpipes		
	44620							1 Lightpipe	8/8	13.21/13.46	RJ-11 keep-out feature, single lightpipe		
	44050							No		12.83/ 13.06	Option to omit side tabs for side-to-side stacking		
	44661									9.19/ 9.53	Three different shielding options		
	48146						External	LED		13.21	Shortened leads		
	48074							Yes	13.45	10/100			
	48025						External, none	Yes, No	26.6/13.3				
	43814		2	3			Through hole		None	No	6/2, 6/4, 6/6	12.70	Inverted flangeless
	43841				6/2, 6/4, 6/6, 8/4, 8/6, 8/8	11.80					Outboard fitting nails		
	44193										Inboard fitting nails		
	43223		2, 3, 4, 5, 6, 8	3	External, none	No			6/2, 6/4, 6/6, 8/4, 8/6, 8/8, 8/10	12.83/13.31	Multi-port, low profile		
	44560		2, 4	5e					8/8	9.19/9.53	Low profile		
	44150	Right angle	2, 4, 6, 8	5e	External, none	No			8/8	12.83/13.31	Press-fit or snap-fit pegs		
	44248		2, 4	3		Lightpipes			6/4, 6/6, 8/8	13.21/13.45	Inverted		
	67838		8, 12, 16	3	External	Lightpipes			8/8	27.20	Press-fit or snap-fit pegs		
	44170			5e		No				25.41			
	44520												
	85726												
	85727												

Ordering Information

	Series	Orientation	Ports	Category	PCB attachment		Shielding	LED	Positions/ Loaded Contacts	Height (mm)	Description
					Signal tails	Body tails					
	85735	Right angle	8	Gig Magnetic	Through hole	Through hole	External shield	Yes	8/8	25.46	Ganged Gig PoE+ integrated magnetic jack
	85734		12								Ganged Gig magnetic jack
	85717										Ganged Gig PoE+ enabled magnetic jack
	85718										
	85728		8 or 12								Ganged Gig magnetic jack
	85732										Ganged Gig PoE+ enabled magnetic jack
	85731										
	95503	Vertical	1	3	Through hole, SMT	Through hole	X	No	4/4 6/4 6/6 8/8	12.7 or 15.7	Flush or flange. Low or high profile
	95522				Through hole					16.25	Flush or flange
	95551										6/6
	95552						8/8		Internally shielded flush or flange		
	95623				16.50				Shielded top entry		
	85510			3	SMT	SMT	X		4/4 6/4 6/6 8/8	15.70	SMT solder tabs, optional pick & place tape
	85513				12.70						
	85506			5	Through hole	Through hole	Internal shield		8/8	16.30	Unshielded through hole
	85507									16.25	Flush or flange
	85508									16.50	Shielded top entry
	85511						X			12.70 or 15.70	Low and high profile
	42410			3	Through hole	Through hole	External		4/2, 4/4, 6/2, 6/4, 6/6, 8/2, 8/4, 8/6, 8/8	16.38	Flush/flangeless
	42878						None			8/2, 8/4, 8/6, 8/8, 8/10	
	43090					No					8/8, 8,10



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.