

Vishay Siliconix

1.1 V to 5.5 V, Slew Rate Controlled Load Switch in TSOT23-6

DESCRIPTION

The SiP32508 and SiP32509 are a slew rate controlled load switches designed for 1.1 V to 5.5 V operation.

The switch element is of n-channel device that provides low ${\sf R}_{ON}$ of 44 m\Omega typically over a wide range of input.

The devices guarantee low switch on-resistance at 1.2 V input. They feature a controlled soft-on slew rate of typical 2.5 ms that limits the inrush current for designs of heavy capacitive load and minimizes the resulting voltage droop at the power rails.

These devices feature a low voltage control logic interface (On/Off interface) that can interface with low voltage control signals without extra level shifting circuit.

SiP32508 and SiP32509 have exceptionally low shutdown current and provides reverse blocking to prevent high current flowing into the power source.

SiP32509 integrates a switch OFF output discharge circuit. Both SiP32508 and SiP32509 are available in TSOT23-6 package.

FEATURES

- 1.1 V to 5.5 V operation voltage range
- Flat low R_{ON} down to 1.2 V
- 44 mΩ typical from 1.5 V to 5 V
- Slew rate controlled turn-on: 2.5 ms at 3.6 V
 - Low quiescent current < 1 μ A when disabled 10.5 μ A typical at V_{IN} = 1.2 V
- Reverse current blocking when switch is off, with guaranteed less than 2 μA leakage
- Material categorization: For definitions of compliance please see <u>www.vishay.com/doc?99912</u>

APPLICATIONS

- PDAs/smart phones
- Ultrabook and notebook computer
- Tablet devices
- · Portable media players
- Digital camera
- GPS navigation devices
- Data storage devices
- · Optical, industrial, medical, and healthcare devices
- Peripherals
- Office automation
- Networking





ORDERING INFORMATION				
Temperature Range	Package	Package Marking Part Nu		
- 40 °C to 85 °C	TSOT23-6	LD	SiP32508DT-T1-GE3	
		LE	SiP32509DT-T1-GE3	

Note:

GE3 denotes halogen-free and RoHS compliant

Document Number: 62754

S12-2647-Rev. A, 05-Nov-12

For technical questions, contact: powerictechsupport@vishav.com

This document is subject to change without notice. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000



RoHS

COMPLIANT

HALOGEN

FREE

TYPICAL APPLICATION CIRCUIT

Vishay Siliconix



ABSOLUTE MAXIMUM RATINGS

Parameter	Limit	Unit		
Supply Input Voltage (V _{IN})	- 0.3 to 6			
Enable Input Voltage (V _{EN})	- 0.3 to 6	V		
Output Voltage (V _{OUT})	- 0.3 to 6			
Maximum Continuous Switch Current (I _{max.}) ^c	3			
Maximum Repetitive Pulsed Current (1 ms, 10 % Duty Cycle) ^c	6	А		
Maximum Non-Repetitive Pulsed Current (100 μs, EN = Active) ^c	12			
ESD Rating (HBM)	> 8	kV		
Junction Temperature (T _J)	- 40 to 150	°C		
Thermal Resistance $(\theta_{JA})^a$	150	°C/W		
Power Dissipation (P _D) ^{a,b}	833	mW		

Notes:

a. Device mounted with all leads and power pad soldered or welded to PC board, see PCB layout.

b. Derate 6.66 mW/°C above T_{A} = 25 °C, see PCB layout.

c. $T_A = 25 \degree C$, see PCB layout

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating/conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING RANGE				
Parameter	Limit	Unit		
Input Voltage Range (V _{IN})	1.1 to 5.5	V		
Operating Junction Temperature Range (T _J)	- 40 to 125	°C		

SPECIFICATIONS

SF LOIFIDATIONS							
		Test Conditions Unless Specified Limits					
		V _{IN} = 5 V, T _A = - 40 °C to 85 °C - 40 °C to 85 °C		°C			
Parameter	Symbol	(Typical values are at $T_A = 25 \text{ °C}$)	Min. ^a	Typ. ^b	Max. ^a	Unit	
Operating Voltage ^c	V _{IN}		1.1	-	5.5	V	
		V_{IN} = 1.2 V, EN = active	-	10.5	17		
		$V_{IN} = 1.8 V$, EN = active	-	21	30		
Quioscont Current		$V_{IN} = 2.5 V, EN = active$	-	34	50		
	'Q	$V_{IN} = 3.6 V, EN = active$	-	54	90		
	-	$V_{IN} = 4.3 V$, EN = active	-	68	110	μΑ	
		V _{IN} = 5 V, EN = active	-	105	180	1	
Off Supply Current	I _{Q(off)}	EN = inactive, OUT = open	-	-	1		
Off Switch Current	I _{DS(off)}	EN = inactive, OUT = GND	-	-	1		
Reverse Blocking Current	I _{RB}	$V_{OUT} = 5 V$, $V_{IN} = 0 V$, $V_{EN} = inactive$	-	-	10		
On-Resistance	R _{DS(on)}	V_{IN} = 1.2 V, I _L = 100 mA, T _A = 25 °C	-	47	54		
		$V_{IN} = 1.8 \text{ V}, I_L = 100 \text{ mA}, T_A = 25 ^\circ\text{C}$	-	44	52		
		V_{IN} = 2.5 V, I_L = 100 mA, T_A = 25 °C	-	44	52	mΩ	
		V_{IN} = 3.6 V, I _L = 100 mA, T _A = 25 °C	-	44	52		
		V_{IN} = 4.3 V, I _L = 100 mA, T _A = 25 °C	-	44	52		
		V_{IN} = 5 V, I _L = 100 mA, T _A = 25 °C	-	46	52		
On-Resistance TempCoefficient	TC _{RDS}		-	3570	-	ppm/°C	

For technical questions, contact: powerictechsupport@vishay.com

Document Number: 62754 S12-2647-Rev. A, 05-Nov-12



Vishay Siliconix

SPEC	CIFIC	ATI	ONS
------	-------	-----	-----

SPECIFICATIONS						
		Test Conditions Unless Specified		Limits		
		$V_{IN} = 5 V$, $I_A = -40 C to 85 C$	- 40 °C to 85 °C			
Parameter	Symbol	(Typical values are at T _A = 25 °C)	Min. ^a	Тур. ^ь	Max. ^a	Unit
	V	V _{IN} = 1.2 V	-	-	0.3	
		V _{IN} = 1.8 V	-	-	0.4 ^d	
EN Input Low Voltage		V _{IN} = 2.5 V	-	-	0.5 ^d	
EN Input Low Voltage	VIL	V _{IN} = 3.6 V	-	-	0.6 ^d	
		V _{IN} = 4.3 V	-	-	0.7 ^d	
		V _{IN} = 5 V	-	-	0.8 ^d	V
EN Input High Voltage ^c	VIH	V _{IN} = 1.2 V	0.9 ^d	-	-	V
		V _{IN} = 1.8 V	1.2 ^d	-	-	
		V _{IN} = 2.5 V	1.4 ^d	-	-	
		V _{IN} = 3.6 V	1.6 ^d	-	-	
		V _{IN} = 4.3 V	1.7 ^d	-	-	
		V _{IN} = 5 V	1.8	-	-	
EN Input Leakage	I _{SINK}	V _{EN} = 5.5 V -		-	1	μA
Output Pulldown Resistance	R _{PD}	EN = inactive, $T_A = 25 \degree C$, (for SiP32509 only) -		217	280	Ω
Output Turn-On Delay Time	t _{d(on)}		-	1.8	-	
Output Turn-On Rise Time	t _(on)	V _{IN} = 3.6 V, R _{LOAD} = 10 Ω, T _A = 25 °C 1.2		2.5	3.8	ms
Output Turn-Off Delay Time	t _{d(off)}		-	-	0.001	

Notes:

a. The algebraic convention whereby the most negative value is a minimum and the most positive a maximum.

b. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.

c. For V_{IN} outside this range consult typical EN threshold curve.

d. Not tested, guarantee by design.

PIN CONFIGURATION



Top View Figure 2 - TSOT23-6 Package

PIN DESCRIPTION				
Pin Number	Name	Function		
1, 2	OUT	These are output pins of the switch		
3	EN	Enable input		
4	GND	Ground connection		
5, 6	IN	These are input pins of the switch		

Vishay Siliconix

BLOCK DIAGRAM



TYPICAL CHARACTERISTICS (internally regulated, 25 °C, unless otherwise noted)



Figure 4 - Quiescent Current vs. Input Voltage



Figure 5 - Off Supply Current vs. Input Voltage



Figure 6 - Quiescent Current vs. Temperature



Figure 7 - Off Supply Current vs. Temperature

Document Number: 62754 S12-2647-Rev. A, 05-Nov-12

VISHA



TYPICAL CHARACTERISTICS (internally regulated, 25 °C, unless otherwise noted)











Figure 11 - Off Switch Current vs. Temperature



Figure 12 - R_{DS(on)} vs. Temperature



Figure 13 - Output Pull Down vs. Temperature

Document Number: 62754 S12-2647-Rev. A, 05-Nov-12 For technical questions, contact: powerictechsupport@vishay.com

VISHAY

Vishay Siliconix

TYPICAL CHARACTERISTICS (internally regulated, 25 °C, unless otherwise noted)



Figure 14 - Reverse Blocking Current vs. Output Voltage







Figure 16 - Turn-On Delay Time vs. Temperature



Figure 17 - Turn-Off Delay Time vs. Temperature



Figure 18 - EN Threshold Voltage vs. Input Voltage



Vishay Siliconix

TYPICAL WAVEFORMS



Figure 19 - Typical Turn-on Delay, Rise Time C_{OUT} = 0.1 $\mu F,\,C_{IN}$ = 4.7 $\mu F,\,I_{OUT}$ = 1.5 A



2 V/Div, 0.25 A/Div, 2 ms/Div

Figure 20 - Typical Turn-on Delay, Rise Time C_{OUT} = 0.1 $\mu F,$ C_{IN} = 4.7 $\mu F,$ R_{OUT} = 10 Ω





Figure 22 - Typical Fall Time $C_{OUT} = 0.1 \ \mu\text{F}, \ C_{IN} = 4.7 \ \mu\text{F}, \ I_{OUT} = 1.5 \ \text{A}$



Figure 23 - Typical Fall Time C_{OUT} = 0.1 µF, C_{IN} = 4.7 µF, R_{OUT} = 10 Ω



Document Number: 62754 S12-2647-Rev. A, 05-Nov-12 For technical questions, contact: powerictechsupport@vishay.com

Vishay Siliconix



DETAILED DESCRIPTION

SiP32508 and SiP32509 are advanced slew rate controlled high side load switches consisted of a n-channel power switches. When a device is enable the gate of the power switch is turned on at a controlled rate to avoid excessive in-rush current. Once fully on the gate to source voltage of the power switch is biased at a constant level. The design gives a flat on resistance throughout the operating voltages. When the device is off, the reverse blocking circuitry prevents current from flowing back to input if output is raised higher than input. The reverse blocking mechanism also works in case of no input applied.

APPLICATION INFORMATION

Input Capacitor

SiP32508 and SiP32509 do not require input capacitor. To limit the voltage drop on the input supply caused by transient inrush currents, a input bypass capacitor is recommended. A 2.2 μ F ceramic capacitor placed as close to the V_{IN} and GND should be enough. Higher values capacitor can help to further reduce the voltage drop. Ceramic capacitors are recommended for their ability to withstand input current surge from low impedance sources such as batteries in portable devices.

Output Capacitor

While these devices work without an output capacitor, an 0.1 μ F or larger capacitor across V_{OUT} and GND is recommended to accommodate load transient condition. It also helps preventing parasitic inductance from forcing V_{OUT} below GND when switching off. Output capacitor has minimal affect on device's turn on slew rate time. There is no requirement on capacitor type and its ESR.



Enable

The EN pin is compatible with both TTL and CMOS logic voltage levels. Enable pin voltage can be above IN once it is within the absolute maximum rating range.

Protection Against Reverse Voltage Condition

Both SiP32508 and SiP32509 contain reverse blocking circuitry to protect the current from going to the input from the output in case where the output voltage is higher than the input voltage when the main switch is off. Reverse blocking works for input voltage as low as 0 V.

Thermal Considerations

SiP32508 and SiP32509 are designed to maintain a constant output load current. Due to physical limitations of the layout and assembly of the device the maximum switch current is 3 A, as stated in the Absolute Maximum Ratings table. However, another limiting characteristic for the safe operating load current is the thermal power dissipation of the package. To obtain the highest power dissipation (and a thermal resistance of 150 °C/W) the IN and OUT pins of the device should be connected to heat sinks on the printed circuit board. Figure 21 shows a typical PCB layout. All copper traces and vias for the IN and OUT pins should be sized adequately to carry the maximum continuous current.

The maximum power dissipation in any application is dependant on the maximum junction temperature, $T_{J(max.)} = 125 \text{ °C}$, the junction-to-ambient thermal resistance for the TSOT23-6 package, $\theta_{J-A} = 150 \text{ °C/W}$, and the ambient temperature, T_A , which may be formulaically expressed as:

P (max.) =
$$\frac{T_{J} (max.) - T_{A}}{\theta_{J-A}} = \frac{125 - T_{A}}{150}$$

www.vishay.com 8 For technical questions, contact: powerictechsupport@vishay.com

Document Number: 62754 S12-2647-Rev. A, 05-Nov-12

Vishay Siliconix



It then follows that, assuming an ambient temperature of 70 $^{\circ}$ C, the maximum power dissipation will be limited to about 367 mW.

So long as the load current is below the 3 A limit, the maximum continuous switch current becomes a function of two things: the package power dissipation and the $R_{DS(on)}$ at the ambient temperature.

As an example let us calculate the worst case maximum load current at $T_A = 70$ °C. The worst case $R_{DS(on)}$ at 25 °C occurs at an input voltage of 1.2 V and is equal to 55 m Ω . The $R_{DS(on)}$ at 70 °C can be extrapolated from this data using the following formula:

 $R_{DS(on)}$ (at 70 °C) = $R_{DS(on)}$ (at 25 °C) x (1 + T_C x DT)

Where T_{C} is 3570 ppm/°C. Continuing with the calculation we have

 $R_{DS(on)}$ (at 70 °C) = 52 mΩ x (1 + 0.00357 x (70 °C - 25 °C)) = 60 mΩ

The maximum current limit is then determined by

$$I_{LOAD}$$
 (max.) < $\sqrt{\frac{P(max.)}{R_{DS}(ON)}}$

which in this case is 2.4 A. Under the stated input voltage condition, if the 2.4 A current limit is exceeded the internal die temperature will rise and eventually, possibly damage the device.



Active EN Pull Down for Reverse Blocking

When an internal circuit detects the condition of V_{OUT} 0.8 V higher than V_{IN}, it will turn on the pull down circuit connected to EN, forcing the switching OFF. The pull down value is about 1 k Ω .

Pulse Current Capability

The device is mounted on the evaluation board shown in the PCB layout section. It is loaded with pulses of 5 A and 1 ms for periods of 4.6 ms.



The SiP32508 and SiP32509 can safely support 5 A pulse current repetitively at 25 $^{\circ}\text{C}.$

Switch Non-Repetitive Pulsed Current

The SiP32508 and SiP32509 can withstand inrush current of up to 12 A for 100 μ s at 25 °C when heavy capacitive loads are connected and the part is already enabled.

Recommended Board Layout

For the best performance, all traces should be as short as possible to minimize the inductance and parasitic effects. The input and output capacitors should be kept as close as possible to the input and output pins respectively.

Connecting the central exposed pad to GND, using wide traces for input, output, and GND help reducing the case to ambient thermal impedance.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?62754.



Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.