

N-Channel Power MOSFET

60V, 35A, 22mΩ

FEATURES



- Low $R_{DS(ON)}$ to minimize conductive losses
- Low gate charge for fast power switching
- 100% UIS and R_g tested.
- 175°C Operating Junction Temperature
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

KEY PERFORMANCE PARAMETERS

| PARAMETER | VALUE | UNIT | |
|--------------------|----------------|------|----|
| V_{DS} | 60 | V | |
| $R_{DS(on)}$ (max) | $V_{GS} = 10V$ | 22 | mΩ |
| Q_g | 23 | nC | |

APPLICATIONS

- BLDC Motor Control
- Battery Power Management
- DC-DC converter
- Secondary Synchronous Rectification



Note: MSL 1 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

| PARAMETER | SYMBOL | LIMIT | UNIT |
|--|----------------|---------------------------|------------------|
| Drain-Source Voltage | V_{DS} | 60 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | V |
| Continuous Drain Current (Note 1) | I_D | $T_C = 25^\circ\text{C}$ | 35 |
| | | $T_A = 25^\circ\text{C}$ | 8 |
| Pulsed Drain Current | I_{DM} | 140 | A |
| Single Pulse Avalanche Current (Note 2) | I_{AS} | 15 | A |
| Single Pulse Avalanche Energy (Note 2) | E_{AS} | 33.8 | mJ |
| Total Power Dissipation | P_D | $T_C = 25^\circ\text{C}$ | 68 |
| | | $T_C = 125^\circ\text{C}$ | 23 |
| Total Power Dissipation | P_D | $T_A = 25^\circ\text{C}$ | 3.1 |
| | | $T_A = 125^\circ\text{C}$ | 1 |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | - 55 to +175 | $^\circ\text{C}$ |

THERMAL PERFORMANCE

| PARAMETER | SYMBOL | LIMIT | UNIT |
|--|-----------------|-------|--------------------|
| Junction to Case Thermal Resistance | $R_{\theta JC}$ | 2.2 | $^\circ\text{C/W}$ |
| Junction to Ambient Thermal Resistance | $R_{\theta JA}$ | 48 | $^\circ\text{C/W}$ |

Thermal Performance Note: $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case-thermal reference is defined at the solder mounting surface of the drain pins. $R_{\theta JA}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. The $R_{\theta JA}$ limit presented here is based on mounting on a 1 in² pad of 2 oz copper.

| ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | |
|---|---|--------------|-----|------|-----------|---------------|
| PARAMETER | CONDITIONS | SYMBOL | MIN | TYP | MAX | UNIT |
| Static | | | | | | |
| Drain-Source Breakdown Voltage | $V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$ | BV_{DSS} | 60 | -- | -- | V |
| Gate Threshold Voltage | $V_{GS} = V_{DS}, I_D = 250\mu\text{A}$ | $V_{GS(TH)}$ | 2 | 3.3 | 4 | V |
| Gate-Source Leakage Current | $V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$ | I_{GSS} | -- | -- | ± 100 | nA |
| Drain-Source Leakage Current | $V_{GS} = 0\text{V}, V_{DS} = 60\text{V}$ | I_{DSS} | -- | -- | 1 | μA |
| | $V_{GS} = 0\text{V}, V_{DS} = 60\text{V}$ $T_J = 125^\circ\text{C}$ | | -- | -- | 100 | |
| Drain-Source On-State Resistance (Note 3) | $V_{GS} = 10\text{V}, I_D = 8\text{A}$ | $R_{DS(on)}$ | -- | 19 | 22 | m Ω |
| Forward Transconductance (Note 3) | $V_{DS} = 10\text{V}, I_D = 8\text{A}$ | g_{fs} | -- | 35 | -- | S |
| Dynamic (Note 4) | | | | | | |
| Total Gate Charge | $V_{GS} = 10\text{V}, V_{DS} = 30\text{V},$ $I_D = 8\text{A}$ | Q_g | -- | 23 | - | nC |
| Gate-Source Charge | | Q_{gs} | -- | 6.5 | -- | |
| Gate-Drain Charge | | Q_{gd} | -- | 5.4 | -- | |
| Input Capacitance | $V_{GS} = 0\text{V}, V_{DS} = 30\text{V}$ $f = 1.0\text{MHz}$ | C_{iss} | -- | 1454 | -- | pF |
| Output Capacitance | | C_{oss} | -- | 90 | -- | |
| Reverse Transfer Capacitance | | C_{rss} | -- | 24 | -- | |
| Gate Resistance | $f = 1.0\text{MHz}$ | R_g | 0.6 | 2 | 4 | Ω |
| Switching (Note 4) | | | | | | |
| Turn-On Delay Time | $V_{GS} = 10\text{V}, V_{DS} = 30\text{V},$ $I_D = 8\text{A}, R_G = 2\Omega$ | $t_{d(on)}$ | -- | 3 | -- | ns |
| Turn-On Rise Time | | t_r | -- | 19 | -- | |
| Turn-Off Delay Time | | $t_{d(off)}$ | -- | 10 | -- | |
| Turn-Off Fall Time | | t_f | -- | 18 | -- | |
| Source-Drain Diode | | | | | | |
| Forward Voltage (Note 3) | $V_{GS} = 0\text{V}, I_S = 8\text{A}$ | V_{SD} | -- | -- | 1.2 | V |
| Reverse Recovery Time | $I_S = 8\text{A},$ $di/dt = 100\text{A}/\mu\text{s}$ | t_{rr} | -- | 16 | -- | ns |
| Reverse Recovery Charge | | Q_{rr} | -- | 11 | -- | nC |

Notes:

- Silicon limited current only.
- $L = 0.3\text{mH}, V_{GS} = 10\text{V}, V_{DD} = 30\text{V}, R_G = 25\Omega, I_{AS} = 15\text{A},$ Starting $T_J = 25^\circ\text{C}$
- Pulse test: Pulse Width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

| PART NO. | PACKAGE | PACKING |
|------------------|---------|---------------------|
| TSM220NB06CR RLG | PDFN56 | 2,500pcs / 13" Reel |


CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature




On-Resistance vs. Gate-Source Voltage




CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area, Junction-to-Case



Source-Drain Diode Forward Current vs. Voltage




Normalized Thermal Transient Impedance, Junction-to-Case




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

PDFN56



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



- G** = Halogen Free
- Y** = Year Code
- WW** = Week Code (01~52)
- F** = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.