



Order Code	ØID1 min. (mm)	ØID2 internal (mm)	t max. after shrinking (mm)	Packaging Unit (m/Reel)
71201216	1,2	0,6	0,45	150
71201616	1,6	0,8	0,45	150
71202416	2,4	1,2	0,50	150
71203216	3,2	1,6	0,50	150
71204816	4,8	2,4	0,50	75
71206416	6,4	3,2	0,65	75
71209516	9,5	4,8	0,65	75
71212716	12,7	6,4	0,65	50
71216016	16,0	8,0	0,65	50
71219016	19,1	9,5	0,75	30
71225416	25,4	12,7	0,90	30
71232016	32,0	16,0	0,95	30
71238116	38,1	19,0	1,00	30
71250816	50,8	25,4	1,15	30
71276216	76,2	38,1	1,25	15
71210116	101,6	50,8	1,30	15

Temperature Resistance: -55°C up to +125°C
 Shrink Temperature: min. 90°C
 Specifications: UL 224 125°C
 Rate of shrinking: 2:1

Würth Elektronik eiSos GmbH & Co. KG
 EMC & Inductive Solutions

Max-Eyth-Str. 1
 74638 Waldenburg
 Germany
 com. +49 79 42 945 - 0

www.we-online.de
 eiSos@we-online.de



CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD 	SCALE 3 : 1
DESCRIPTION AShST Heat Shrinking Tubes		MATERIAL Polyolefin, black		
ORDER CODE 712 xxx 16				
SIZE Type N55	WEIGHT xxx	STATUS Released	DATE 2015-08-17	BUSINESS UNIT eiCan
				PAGE 1 / 1

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.