FAIRCHILD SEMICONDUCTOR™

September 1991
Revised November 1999

100315
Low Skew Quad Clock Driver

General Description

The 100315 contains four low skew differential drivers, designed for generation of multiple, minimum skew differential clocks from a single differential input. This device also has the capability to select a secondary single-ended clock source for use in lower frequency system level testing. The 100315 is a 300 Series redesign of the 100115 clock driver.

Features

- Low output-to-output skew (≤50 ps)
- Differential inputs and outputs
- Secondary clock available for system level testing
- 2000V ESD protection
- Voltage compensated operating range: –4.2V to –5.7V

Ordering Code:

Order Number	Package Number	Package Descriptions
100315SC	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Logic Diagram



Connection Diagram



Pin Descriptions

Pin Names	Description
CLKIN, $\overline{\text{CLKIN}}$	Differential Clock Inputs
$CLK_{1–4}$, $\overline{CLK}_{1–4}$	Differential Clock Outputs
TCLK	Test Clock Input (Note 1)
CLKSEL	Clock Input Select (Note 1)

Note 1: TCLK and CLKSEL are single-ended inputs, with internal 50 kΩ pull-down resistors.

Truth Table

CLKSEL	CLKIN	$\overline{\text{CLKIN}}$	TCLK	CLK_n	$\overline{CLK}_n$
L	L	H	X	L	H
L	H	L	X	H	L
H	X	X	L	L	H
H	X	X	H	H	L

L = LOW Voltage Level
H = HIGH Voltage Level
X = Don't Care

© 1999 Fairchild Semiconductor Corporation

Absolute Maximum Ratings (Note 2)

Storage Temperature	−65°C to +150°C
Maximum Junction Temperature (T_J)	+150°C
Case Temperature under Bias (T_C)	0°C to +85°C
V_{EE} Pin Potential to Ground Pin	−7.0V to +0.5V
Input Voltage (DC)	V_{CC} to +0.5V
Output Current (DC Output HIGH)	−50 mA
Operating Range (Note 2)	−5.7V to −4.2V
ESD (Note 3)	≥2000V

Recommended Operating Conditions

Case Temperature (T_C)	0°C to +85°C
Supply Voltage (V_{EE})	−5.7V to −4.2V

Note 2: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum rating. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 3: ESD testing conforms to MIL-STD-883, Method 3015.

DC Electrical Characteristics (Note 4)

V_{EE} = −4.2V to −5.7V, V_{CC} = V_{CCA} = GND, T_C = 0°C to +85°C

Symbol	Parameter	Min	Typ	Max	Units	Conditions	
V_{OH}	Output HIGH Voltage	−1025	−955	−870	mV	V_{IN} = $V_{IH(Max)}$	Loading with
V_{OL}	Output LOW Voltage	−1830	−1705	−1620		or $V_{IL(Min)}$	50Ω to −2.0V
V_{OHC}	Output HIGH Voltage	−1035			mV	V_{IN} = $V_{IH(Min)}$	Loading with
V_{OLC}	Output LOW Voltage			−1610		or $V_{IL(Max)}$	50Ω to −2.0V
V_{IH}	Single-Ended Input HIGH Voltage	−1165		−870	mV	Guaranteed HIGH Signal for All Inputs	
V_{IL}	Single-Ended Input LOW Voltage	−1830		−1475	mV	Guaranteed LOW Signal for All Inputs	
I_{IL}	Input LOW Current	0.50			µA	V_{IN} = $V_{IL(Min)}$	
I_{IH}	Input HIGH Current					V_{IN} = $V_{IH(Max)}$	
	CLKIN, $\overline{\text{CLKIN}}$			150	µA		
	TCLK			250	µA		
	CLKSEL			250	µA		
V_{DIFF}	Input Voltage Differential	150			mV	Required for Full Output Swing	
V_{CM}	Common Mode Voltage	V_{CC} − 2V		V_{CC} − 0.5V	V		
I_{CBO}	Input Leakage Current	−10			µA	V_{IN} = V_{EE}	
I_{EE}	Power Supply Current	−67		−35	mA		

Note 4: The specified limits represent the "worst case" value for the parameter. Since these "worst case" values normally occur at the temperature extremes, additional noise immunity and guard banding can be achieved by decreasing the allowable system operating ranges.

AC Electrical Characteristics

V_{EE} = −4.2V to −4.8, V_{CC} = V_{CCA} = GND

Symbol	Parameter	T_C = 0°C		T_C = +25°C		T_C = +85°C		Units	Conditions
		Min	Max	Min	Max	Min	Max		
f_{MAX}	Maximum Clock Frequency	750		750		750		MHz	
t_{PLH}	Propagation Delay CLKIN,								
t_{PHL}	$\overline{\text{CLKIN}}$ to $CLK_{(1–4)}$, $\overline{CLK}_{(1–4)}$								
	Differential	0.59	0.79	0.62	0.82	0.67	0.87	ns	Figures 1, 3
	Single-Ended	0.59	0.99	0.62	1.02	0.67	1.07		
t_{PLH}	Propagation Delay, TCLK	0.50	1.20	0.50	1.20	0.50	1.20	ns	Figures 1, 2
t_{PHL}	to $CLK_{(1–4)}$, $\overline{CLK}_{(1–4)}$								
t_{PLH}	Propagation Delay, CLKSEL	0.80	1.60	0.80	1.60	0.80	1.60	ns	Figures 1, 2
t_{PHL}	to $CLK_{(1–4)}$, $\overline{CLK}_{(1–4)}$								
t_{TLH}	Transition Time	0.30	0.80	0.30	0.80	0.30	0.80	ns	Figures 1, 4
t_{THL}	20% to 80%, 80% to 20%								
t_{OST}	Maximum Skew Opposite Edge								
DIFF	Output-to-Output Variation		50		50		50	ps	(Note 5)
	Data to Output Path								

Note 5: Output-to-Output Skew is defined as the absolute value of the difference between the actual propagation delay for any outputs within the same packaged device. The specifications apply to any outputs switching in the same direction either HIGH-to-LOW (t_{OSHL}), or LOW-to-HIGH (t_{OSLH}), or in opposite directions both HL and LH (t_{OST}). Parameters t_{OST} and t_{PS} guaranteed by design.

Test Circuit



Note:

Shown for testing CLKIN to CLK1 in the differential mode.

L1, L2, L3 and L4 = equal length 50Ω impedance lines.

All unused inputs and outputs are loaded with 50Ω in parallel with ≤3 pF to GND.

Scope should have 50Ω input terminator internally.

FIGURE 1. AC Test Circuit

Switching Waveforms



FIGURE 2. Propagation Delay, TCLK, CLKSEL to Outputs



FIGURE 3. Propagation Delay, CLKIN/$\overline{\text{CLKIN}}$ to Outputs



FIGURE 4. Transition Times

Physical Dimensions inches (millimeters) unless otherwise noted



16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow
Package Number M16A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.