

SB700 EX

2-Port Serial to Ethernet Server

100 Version



DATASHEET

Key Points

- Serial to Ethernet server
- SSL and SSH data encryption to protect from unauthorized monitoring
- RS-232 and RS-422/485 serial device support
- Works out of the box - no programming is required
- Metal enclosure
- Rebrand with your custom product label
- Customize with development kit

Features

- SSH, SSL, HTTPS, certificate support
- 10/100Mbps Ethernet
- TCP/UDP/Telnet modes
- DHCP/Static IP modes
- Web based configuration
- 32-bit performance
- Standard and custom baud rates with factory application

Optional

The following options are available with the optional development kit:

- Customize any aspect of operation including web pages, data filtering, or custom network applications
- Real-time clock
- MicroSD/MMC Card interface with included flash file system

The following optional software modules are not included with kit and are sold separately:

- Embedded SSL & SSH Security Suite (Module License Version)
- SNMP



Factory Application Specifications

Serial Port Baud Rate

Factory application supports up to 921,600 bps. Custom rates available with development kit.

Serial Protocols Supported

RS-232, RS-422, and RS-485

Serial Configurations

The two UARTs can be configured in the following ways:

- Two RS-232 ports
- One RS-232 port, one RS-485/422 port

Hardware Specifications

Processor & Memory

32-bit Freescale ColdFire 5270 running at 147.5MHz with 2Mbytes of on-chip flash, 8Mbytes SDRAM.

Storage

MicroSD/MMC Flash Card Interface (with SDHC support)

Network Interface

10/100 BaseT with RJ-45 connector

Data I/O Interface

- Two UARTs
- Real-time clock

LEDs

Link, speed/data, power

Physical Characteristics

Dimensions (inches): 4.20" x 3.25" x 1.00"

Power

DC Input Voltage: 7V-24V DC
12V @ 90mA

Environmental Operating Temperature

-40° to 85° C (SB700EX-100IR version)
0° to 70° C (SB700EX-100CR version)

RoHS Compliance

The Restriction of Hazardous Substances guidelines ensure that electronics are manufactured with fewer environment harming materials.

Agency Approvals

UL, C/UL, CE, FCC



Front and Back Panel



Connector Interface Description and Pinouts

The back panel has two DB9 ports which enable you to connect to a serial device. Tables 1 and 2 provide descriptions of the function of each pin for Port 0 and Port 1.

Table 1: Serial Port Connector (Port 0) Pinout and Signal Description¹

Pin	RS-232 Function	RS-485 Function	Description	Max Voltage
1	CD	-	Carrier Detect	RS-232
2	RX	FD TX- / HD-	Receive or Full Duplex Transmit- / Half Duplex-	RS-232 or RS-422/485
3	TX	FD TX+ / HD+	Transmit or Full Duplex Transmit+ / Half Duplex+	RS-232 or RS-422/485
4	DTR	-	Data Terminal Ready	RS-232
5	GND	GND	Ground	-
6	DSR	FD RX-	Data Set Ready or Full Duplex Recieve-	RS-232 or RS-422/485
7	RTS	FD RX+	Ready to Send or Full Duplex+	RS-232 or RS-422/485
8	CTS	-	Clear to Send	RS-232
9	RI	-	Ring Indicator	RS-232

Note:

1. Port 0 can be configured to as RS-232 or RS-485

Table 2: Serial Port Connector (Port 1) Pinout and Signal Description

Pin	Port 1 RS-232	Description	Max Voltage
1	CD	Carrier Detect	RS-232
2	RX	Recieve	RS-232
3	TX	Transmit	RS-232
4	DTR	Data Terminal Ready	RS-232
5	GND	Ground	-
6	DSR	Data Set Ready	RS-232
7	RTS	Ready to Send	RS-232
8	CTS	Clear to Send	RS-232
9	RI	Ring Indicator	RS-232

Part Numbers

SB700 EX 2-Port Serial to Ethernet Server

Part Number: SB700EX-100IR

DIN Rail Mounting Kit (100 Version, double sided)

Part Number: DIN-100

DIN Rail Mounting Kit (200 Version, single sided)

Part Number: DIN-200

SB700 EX Development Kit

Part Number: NNDK-SB700EX-KIT

Kit includes all the hardware and software you need to customize the included platform hardware. See NetBurner Store product page for package contents.

Embedded SSL & SSH Security Suite (Module License Version)

Part Number: NBLIC-SSL-MODULE

Only required if you are using a development kit (SSH/SSL functionality is included in the pre-programmed application).

SNMP V1 (Module License Version)

Part Number: NBLIC-SNMP

Available as an option if you are using a development kit.

Ordering Information

E-mail: sales@netburner.com

Online Store: www.NetBurner.com

Telephone: 1-800-695-6828



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.