| REVISIONS | | | |
|---|---|---|---|
| LTR | DESCRIPTION | DATE (YR-MO-DA) | APPROVED |
| A | Drawing updated to reflect current requirements. - lgt | 02-01-08 | Raymond Monnin |

| | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV STATUS | | | | REV | | | A | A | A | A | A | A | A | A | | | | | | |
| OF SHEETS | | | | SHEET | | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | | | | | | |

PMIC N/A

PREPARED BY
Marcia B. Kelleher

**DEFENSE SUPPLY CENTER COLUMBUS**
**COLUMBUS, OHIO 43216**
**http://www.dscc.dla.mil**

**STANDARD MICROCIRCUIT DRAWING**

THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE

AMSC N/A

CHECKED BY
Rajesh Pithadia

APPROVED BY
Michael A. Frye

DRAWING APPROVAL DATE
94-05-18

MICROCIRCUIT, LINEAR, RMS-TO-DC CONVERTER, MONOLITHIC SILICON

| REVISION LEVEL | SIZE | CAGE CODE | |
|---|---|---|---|
| A | A | **67268** | **5962-89805** |

SHEET 1 OF 8

DSCC FORM 2233
APR 97

5962-E161-02

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1. SCOPE

1.1 Scope. This drawing describes device requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A.

1.2 Part or Identifying Number (PIN). The complete PIN is as shown in the following example:

| 5962-89805 | 01 | C | X |
|---|---|---|---|
| Drawing number | Device type (see 1.2.1) | Case outline (see 1.2.2) | Lead finish (see 1.2.3) |

1.2.1 Device type(s). The device type(s) identify the circuit function as follows:

| Device type | Generic number | Circuit function |
|---|---|---|
| 01 | MX536A | RMS-TO-DC converter |

1.2.2 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

| Outline letter | Descriptive designator | Terminals | Package style |
|---|---|---|---|
| C | GDIP1-T14 or CDIP2-T14 | 14 | Dual-in-line |
| I | MACY1-X10 | 10 | Can |
| 2 | CQCC1-N20 | 20 | Square leadless chip carrier |

1.2.3 Lead finish. The lead finish is as specified in MIL-PRF-38535, appendix A.

1.3 Absolute maximum ratings. 1/

Supply voltage ($+V_S$) ..... +18 V dc
Input voltage ($+V_{IN}$) ..... +25 V dc
Output short circuit duration ..... Indefinite
Power dissipation, $T_A$ = 70°C ($P_D$):
  Case outline C ..... 727 mW 2/
  Case outline I ..... 533 mW 3/
  Case outline 2 ..... 727 mW 4/
Storage temperature range ..... -65°C to +150°C
Lead temperature (soldering, 10 seconds) ..... 300°C
Junction temperature ($T_J$) ..... +150°C
Thermal resistance, junction-to-case ($\theta_{JC}$) ..... See MIL-STD-1835
Thermal resistance, junction-to-ambient ($\theta_{JA}$):
  Case outline C ..... 110°C/W
  Case outline I ..... 150°C/W
  Case outline 2 ..... 110°C/W

1.4 Recommended operating conditions.

Ambient operating temperature range ($T_A$) ..... -55°C to +125°C
Input voltage ($V_{IN}$) ..... 15 V dc

1/ All voltages are with respect to GND.
2/ Derate at 9.09 mW/°C for $T_A$ above 70°C.
3/ Derate at 6.67 mW/°C for $T_A$ above 70°C.
4/ Derate at 9.09 mW/°C for $T_A$ above 70°C.

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-38535 -- Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-883 - Test Method Standard Microcircuits.
MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-103 -- List of Standard Microcircuit Drawings.
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein. Product built to this drawing that is produced by a Qualified Manufacturer Listing (QML) certified and qualified manufacturer or a manufacturer who has been granted transitional certification to MIL-PRF-38535 may be processed as QML product in accordance with the manufacturers approved program plan and qualifying activity approval in accordance with MIL-PRF-38535. This QML flow as documented in the Quality Management (QM) plan may make modifications to the requirements herein. These modifications shall not affect form, fit, or function of the device. These modifications shall not affect the PIN as described herein. A "Q" or "QML" certification mark in accordance with MIL-PRF-38535 is required to identify when the QML flow option is used.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535, appendix A and herein.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-PRF-38535, appendix A. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-HDBK-103 (see 6.6 herein). For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device.

3.5.1 Certification/compliance mark. A compliance indicator “C” shall be marked on all non-JAN devices built in compliance to MIL-PRF-38535, appendix A. The compliance indicator “C” shall be replaced with a "Q" or "QML" certification mark in accordance with MIL-PRF-38535 to identify when the QML flow option is used.

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-PRF-38535, appendix A and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DSCC-VA shall be required in accordance with MIL-PRF-38535, appendix A.

3.9 Verification and review. DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.

(2) $T_A$ = +125°C, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

TABLE I. Electrical performance characteristics.

| Test | Symbol | Conditions<br>$-55°C \le T_A \le +125°C$<br>$V_S = \pm 15$ V,<br>unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|---|---|---|---|---|---|---|---|
| | | | | | Min | Max | |
| Total error | $E_r$ | $V_{IN} = \pm 300$ mV to $\pm 10$ V,<br>$T_A = +25°C$ | 1 | 01 | | $\pm 5$ +<br>$\pm 0.5$ | mV +<br>% of reading |
| Total error vs. temperature | $\Delta E_r/\Delta T$ | $T_A = +125°C, +25°C$ | 1, 2 | 01 | | $\pm 0.3$ +<br>0.005 | mV +<br>% of reading<br>/°C |
| | | $T_A = -55°C$ | 3 | | | $\pm 0.1$ +<br>0.005 | |
| Buffer-output offset voltage | $V_{OS}$ | $I_{OUT}$ to BUFIN, $V_{IN} = 0$ V,<br>$T_A = +25°C$ | 1 | 01 | | $\pm 2$ | mV |
| Buffer-output offset drift | $\Delta V_{OS}/\Delta T$ | $I_{OUT}$ to BUFIN, $V_{IN} = 0$ V,<br>$T_A = -55°C, T_A = +125°C$ | 2, 3 | 01 | | $\pm 0.2$ | mV/°C |
| Buffer-output voltage swing | $V_{CP}$ | $I_{OUT}$ to BUFIN, $V_S = \pm 15$ V,<br>$T_A = +25°C$ | 1 | 01 | 11 | | V |
| | | $I_{OUT}$ to BUFIN, $V_S = \pm 5$ V,<br>$T_A = +25°C$ | | | 2 | | |
| dB output error | $E_{OB}$ | $\pm 7$ mV $\le V_{IN} \le 7$ V,<br>$T_A = +25°C$ | 1 | 01 | | $\pm 0.6$ | dB |
| $I_{REF}$ for 0 dB = 1 $V_{RMS}$ | $I_{REF\Delta}$ | $T_A = +25°C$ | 1 | 01 | 5 | 80 | µA |
| $I_{REF}$ range | $I_{REF}$ | $T_A = +25°C$ | 1 | 01 | 1 | 100 | µA |
| Buffer-input offset voltage | $V_{IOS}$ | $T_A = +25°C$ | 1 | 01 | | $\pm 4$ | mV |
| Buffer-input bias current | $I_S$ | $T_A = +25°C$ | 1 | 01 | | 60 | nA |
| Power supply range, dual voltage | $V_{SD}$ | $T_A = +25°C$ | 1 | 01 | -18 | +18 | V |
| Power supply range, single voltage | $V_{SS}$ | $T_A = +25°C$ | 1 | 01 | | 36 | V |
| Quiescent current | $I_Q$ | $\pm 5$ V $\le V_S \le \pm 18$ V | 1, 2, 3 | 01 | | 2 | mA |

| Device type | 01 | | |
|---|---|---|---|
| Case outline | C | I | 2 |
| Terminal number | Terminal symbol | | |
| 1 | $V_{IN}$ | $R_L$ | NC |
| 2 | NC | COMMON | $V_{IN}$ |
| 3 | $V_{S-}$ | $V_{s+}$ | NC |
| 4 | CAV | $V_{IN}$ | $V_{S-}$ |
| 5 | dB | $V_{S-}$ | NC |
| 6 | BUFOUT | CAV | CAV |
| 7 | BUFIN | dB | NC |
| 8 | $I_{OUT}$ | BUFOUT | dB |
| 9 | $R_L$ | BUFIN | BUFOUT |
| 10 | COMMON | $I_{OUT}$ | BUFIN |
| 11 | NC | ------- | NC |
| 12 | NC | ------- | $I_{OUT}$ |
| 13 | NC | ------- | $R_L$ |
| 14 | $V_{S+}$ | ------- | COMMON |
| 15 | ------- | ------- | NC |
| 16 | ------- | ------- | NC |
| 17 | ------- | ------- | NC |
| 18 | ------- | ------- | NC |
| 19 | ------- | ------- | NC |
| 20 | ------- | ------- | $V_{S+}$ |

FIGURE 1. Terminal connections.

TABLE II. Electrical test requirements.

| MIL-STD-883 test requirements | Subgroups (in accordance with MIL-STD-883, method 5005, table I) |
|---|---|
| Interim electrical parameters (method 5004) | 1 |
| Final electrical test parameters (method 5004) | 1*, 2, 3 |
| Group A test requirements (method 5005) | 1, 2, 3 |
| Groups C and D end-point electrical parameters (method 5005) | 1 |

* PDA applies to subgroup 1.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 4, 5, 6, 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test conditions, method 1005 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.

(2) $T_A$ = +125°C, minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535, appendix A.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.4 Record of users. Military and industrial users shall inform Defense Supply Center Columbus when a system application requires configuration control and the applicable SMD. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.5 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43216-5000, or telephone (614) 692-0547.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 02-01-08

Approved sources of supply for SMD 5962-89805 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535.

| Standard microcircuit drawing PIN 1/ | Vendor CAGE number | Vendor similar PIN 2/ |
|---|---|---|
| 5962-8980501CA | IES66 | MX536ASQ/883B |
| | 24355 | AD536ASD/883B |
| 5962-8980501CC | IES66 | MX536ASD/883B |
| 5962-8980501IA | 24355 | AD536ASH/883B |
| 5962-8980501IC | IES66 | MX536ASH/883B |
| 5962-89805012A | 24355 | AD536ASE/883B |
| 5962-89805012C | IES66 | MX536ASE/883B |

1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.

2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

| Vendor CAGE number | Vendor name and address |
|---|---|
| 24355 | Analog Devices, Inc.<br>Rt. 1 Industrial Park<br>P.O. Box 9106<br>Norwood, MA 02062<br>Point of Contact:<br>804 Woburn Street<br>Wilmington, MA 01887-3462 |
| 1ES66 | Maxim Integrated Products<br>120 San Gabriel Dr<br>Sunnyvale, CA 94086-5125 |

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.