

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT — By —

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	ECR-16-014363	11OCT2016	FL	SY

NOTE:

1. MATERIAL:

HOUSING (SEE TABLE): PA46 OR PA9T, UL94 V-0, COLOR: BLACK.

CONTACTS: PHOSPHOR BRONZE.

BOARDLOCK: BRASS.

2. FINISH:

2.1 CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA,
2.54um [100u"] MIN. MATTE-TIN ON SOLDER TAIL,
WITH ENTIRE CONTACT UNDERPLATED 1.27um [50u"] MIN. NICKEL.2.2 BOARDLOCK: 2.54um [100u"] MATTE-TIN PLATING ALL OVER
NICKEL 1.27um[50u"] MIN. UNDERPLATED OVERALL.

3. WAVE SOLDER CAPABLE TO 265°C MAX. PER TE SPEC. 109-202, CONDITION B.

4. WEIGHT:

36 POS.: 2.55 GRAMS


64 POS.: 3.90 GRAMS

98 POS.: 5.50 GRAMS

164 POS.: 8.80 GRAMS

5. REFLOW SOLDER CAPABLE TO 260°C PER TE SPEC. TEC-109-201, CONDITION B.

HARD TRAY	NOTE 3 & 5	PA9T	2.30	0.381μm[15μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	6—	—2
TRAY	NOTE 3	PA46	3.10	0.762μm[30μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	5—	—2
				0.381μm[15μ"] MIN.							4—	—6
			2.30	GOLD FLASH	71.65	70.0	73.15	71.35	89.0	164	4—	—5
				0.762μm[30μ"] MIN.							4—	—4
			3.10	0.381μm[15μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	4—	—3
				GOLD FLASH							4—	—2
			2.30	0.762μm[30μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	4—	—1
				0.381μm[15μ"] MIN.							3—	—6
			3.10	GOLD FLASH	71.65	70.0	73.15	71.35	89.0	164	3—	—5
				0.762μm[30μ"] MIN.							3—	—4
			2.30	0.381μm[15μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	3—	—3
				GOLD FLASH							3—	—2
			3.10	0.762μm[30μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	3—	—1
				0.381μm[15μ"] MIN.							2—	—6
			2.30	GOLD FLASH	71.65	70.0	73.15	71.35	89.0	164	2—	—5
				0.762μm[30μ"] MIN.							2—	—4
			3.10	0.381μm[15μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	2—	—3
				GOLD FLASH							2—	—2
			2.30	0.762μm[30μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	2—	—1
				0.381μm[15μ"] MIN.							1—	—6
			3.10	GOLD FLASH	71.65	70.0	73.15	71.35	89.0	164	1—	—5
				0.762μm[30μ"] MIN.							1—	—4
			2.30	0.381μm[15μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	1—	—3
				GOLD FLASH							1—	—2
			3.10	0.762μm[30μ"] MIN.	71.65	70.0	73.15	71.35	89.0	164	1—	—1
				0.381μm[15μ"] MIN.							1—	—0
			2.30	GOLD FLASH	71.65	70.0	73.15	71.35	89.0	164	1—	—0
				0.762μm[30μ"] MIN.							1—	—0
PACKAGING	SOLDER CAPACITY	HOUSING MATERIAL	DIM L	GOLD PLATING	DIM E	DIM D	DIM C	DIM B	DIM A	POS.	PART NUMBER	



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN B. HSING 21MAY2009

CHK S. CHIEN 21MAY2009

APVD W. KODAMA 21MAY2009

PRODUCT SPEC

108-57375

APPLICATION SPEC

—

WEIGHT 0


CUSTOMER DRAWING

STE TE ConnectivityNAME
PCI EXPRESS CARD EDGE CONNECTOR
VERTICAL, DIP TYPE,(BOARD-LOCK FUNCTION)

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C-1775801

SCALE 1:1 SHEET 1 OF 4 REV D

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	± —
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	± —
ANGLES	± 3°

MATERIAL SEE NOTE

FINISH SEE NOTE

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT — By —

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	—	SEE SHEET 1	—	—	—

NOTES :

1. MATERIAL :

TRAY : PVC, COLOR: TRANSPARENT.

CARTON: CORRUGATED FIBER

BOX: CORRUGATED FIBER

2. DIMENSION :












TRAY: SEE DRAWING

CARTON: SEE DRAWING

BOX : SEE DRAWING

3. QUANTITY : SEE TABLE

4. WEIGHT : SEE TABLE



9.6 KG	7.6 KG	30	10	3	900	164
8.5 KG	6.5 KG	40	10	3	1200	98
9.1 KG	7.1 KG	60	10	3	1800	64
7.7 KG	5.7 KG	70	10	3	2100	36
GROSS WEIGHT	NET WEIGHT	PCS/ TRAY	TRAY/ CARTON	CARTON/ BOX	PCS/ BOX	POS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ± —
	1 PLC ± —
	2 PLC ± —
	3 PLC ± —
	4 PLC ± —
	ANGLES ± —
MATERIAL	FINISH
—	—

DWN	B. HSING	21MAY2009
CHK	S. CHIEN	21MAY2009
APVD	W. KODAMA	21MAY2009
PRODUCT SPEC	—	
APPLICATION SPEC	—	
WEIGHT	0	

CUSTOMER DRAWING



TE Connectivity


PCI EXPRESS CARD EDGE CONNECTOR
VERTICAL, DIP TYPE,(BOARD-LOCK FUNCTION)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1775801	—

SCALE	SHEET	REV
1:1	3 OF 4	D

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-


- NOTES :
- PACKING MATERIAL MET TE SPEC TEC-138-702.
- * CADMIUM AND CADMIUM COMPOUNDS CONTENT:
5 PPM UNDER (PLASTIC, RUBBER, INK, PIGMENT, PAINT)
 - * LEAD, CADMIUM, CHROM VI AND MERCURY IN PACKAGING MATERIALS CONTENT: 100 PPM (COMBINED) UNDER.
1. MATERIAL :
TRAY: HIPS, COLOR: BLACK.
CARTON: CORRUGATED FIBER
BOX: CORRUGATED FIBER
TRANSPARENT BAG: PE, SIZE: 500mm*380mm*0.06mm
640mm*510mm*0.06mm
2. EACH BAG SHALL BE INCLUDED:
* DESICCANT



11.5 Kg	7.0 Kg	40	10	2	800	164
GROSS WEIGHT	NET WEIGHT	PCS/ TRAY	TRAY/ CARTON	CARTON/ BOX	PCS/ BOX	POS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. HSING	21MAY2009	 TE Connectivity		
		CHK S. CHIEN	21MAY2009			
		APVD W. KODAMA	21MAY2009	NAME		
		PRODUCT SPEC		PCI EXPRESS CARD EDGE CONNECTOR VERTICAL, DIP TYPE,(BOARD-LOCK FUNCTION)		
		APPLICATION SPEC				
		WEIGHT	0	SIZE	CAGE CODE	DRAWING NO
		CUSTOMER DRAWING		A3	00779	C-1775801
		SCALE	1:1	SHEET	4 of 4	REV D

DIMENSIONS:
mm



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -
FINISH -

MATERIAL

-



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.