

## Type CJT Series

### Key Features

- Modular versions available
- Environmental protection to IP54
- Up to 2000W power rating
- Aluminium enclosure
- Vibration resistant

### Applications

- Power supplies
- Inverters
- Servo systems
- Electrical systems in difficult environments



TE Connectivity (TE) is a leading supplier of standard and custom-designed power resistors for industrial, control and general-purpose applications. The CJT Series of resistors are advantageous to conventional ceramic resistors in the terms of weather proofing, oscillation-resistance and safety. They are widely applied to a range of electrical circuits including power supplies, inverters and servo systems. With easy airtight fitting and the ability to fit a heatsink the resistor is highly suited to challenging environmental conditions.

### Characteristics - Electrical

| Type  | CJT60             | CJT80 | CJT100 | CJT120 | CJT150 | CJT200 | CJT300 |
|---|-------------------|-------|--------|--------|--------|--------|--------|
| Rated Power in Free Air (W)                     | 60                | 80    | 100    | 120    | 150    | 200    | 300    |
| Ohmic Value - Min                               | 1R0               |       |        |        |        |        |        |
| Ohmic Value Max                                 | 2K7               |       |        |        |        |        |        |
| Tolerance                                       | 5%                |       |        |        |        |        |        |
| Temp. Coefficient of Resistance                 | 440ppm            |       |        |        |        |        |        |
| Resistor Element Max Working Voltage            | 1kV               |       |        |        |        |        |        |
| Dielectric Voltage                              | AC2.5kV/1min 50Hz |       |        |        |        |        |        |
| Insulation Resistance (Megohm)                  | R≥100MΩ           |       |        |        |        |        |        |
| Max. Surface Temp. at Rated Power Free Air (°C) | 206°C             | 221°C | 254°C  | 267°C  | 286°C  | 306°C  | 334°C  |
| Weight  | 150g              | 185g  | 240g   | 280g   | 300g   | 445g   | 600g   |
| Termination                                     | Lead              |       |        |        |        |        |        |
| Lead Length                                     | 500mm             |       |        |        |        |        |        |
| Lead Diameter                                   | 1.5mm             |       |        |        |        |        |        |
| Terminal Creep Distance                         | n/a               |       |        |        |        |        |        |

| Type  | CJT400            | CJT500 | CJT800 | CJT1000       | CJT1200 | CJT1500 | CJT2000 |
|---|-------------------|--------|--------|---------------|---------|---------|---------|
| Rated Power in Free Air (W)                     | 400               | 500    | 800    | 1000          | 1200    | 1500    | 2000    |
| Ohmic Value - Min                               | 1R0               |        |        |               |         |         |         |
| Ohmic Value Max                                 | 2K7               |        |        |               |         |         |         |
| Tolerance                                       | 5%                |        |        |               |         |         |         |
| Temp. Coefficient of Resistance                 | 440ppm            |        |        |               |         |         |         |
| Resistor Element Max Working Voltage            | 1kV               |        |        |               |         |         |         |
| Dielectric Voltage                              | AC2.5kV/1min 50Hz |        |        |               |         |         |         |
| Insulation Resistance (Megohm)                  | R≥100MΩ           |        |        |               |         |         |         |
| Max. Surface Temp. at Rated Power Free Air (°C) | 370°C             | 358°C  | 311°C  | 372°C         | 406°C   | 419°C   | 453°C   |
| Weight  | 765g              | 965g   | 1.18kg | 3.46kg        | 3.885kg | 4.31kg  | 4.89kg  |
| Termination                                     | Lead              |        |        | Lead/Terminal |         |         |         |
| Lead Length                                     | 500mm             |        |        |               |         |         |         |
| Lead Diameter                                   | 1.5mm             |        |        | 4mm           |         |         |         |
| Terminal Creep Distance                         | n/a               |        | 30mm   | 42mm          | 42mm    | 42mm    | 42mm    |

### Type CJT Series

#### Derating Curve



#### Temperature Rise



#### Dimensions - CJT Series



| Rated Power (W) | Dimensions (mm) |     |    |     |
|-----------------|-----------------|-----|----|-----|
|                 | A               | B   | C  | D   |
| 60              | 115             | 98  | 40 | 20  |
| 80              | 140             | 123 | 40 | 20  |
| 100             | 165             | 148 | 40 | 20  |
| 120             | 190             | 173 | 40 | 20  |
| 150             | 215             | 197 | 40 | 20  |
| 200             | 165             | 147 | 60 | 30  |
| 300             | 215             | 197 | 60 | 30  |
| 400             | 265             | 247 | 60 | 30  |
| 500             | 335             | 317 | 60 | 30  |
| 800             | 400             | 382 | 61 | 59  |
| 1000            | 400             | 384 | 50 | 107 |
| 1200            | 450             | 434 | 50 | 107 |
| 1500            | 485             | 470 | 50 | 107 |
| 2000            | 550             | 532 | 50 | 107 |

## Type CJT Series

### Dimensions - CJTM Series



| Type   | Rated Power (W) | Resistance (Ω) |      | Dimensions (mm) |     |     |     |    |    | Connecting Wire (mm <sup>2</sup> ) | Lead Length (mm) |
|--------|-----------------|----------------|------|-----------------|-----|-----|-----|----|----|------------------------------------|------------------|
|        |                 | Min            | Max  | A               | A1  | B   | B1  | G  | H  |                                    |                  |
| CJTM1U | 200             | 1              | 2K7  | 268             | 253 | 64  | 30  | 20 | 54 | 2.5                                | 500              |
| CJTM1U | 300             | 1              | 2K7  | 318             | 303 | 64  | 30  | 20 | 54 | 2.5                                | 500              |
| CJTM1U | 400             | 1              | 2K7  | 368             | 353 | 64  | 30  | 20 | 54 | 2.5                                | 500              |
| CJTM1U | 500             | 1              | 2K7  | 438             | 423 | 64  | 30  | 20 | 54 | 2.5                                | 500              |
| CJTM1U | 600             | 1              | 2K7  | 503             | 488 | 64  | 30  | 20 | 54 | 2.5                                | 500              |
| CJTM2U | 800             | 2              | 5K4  | 372             | 355 | 84  | 49  | 20 | 84 | 2.5                                | 500              |
| CJTM2U | 1000            | 2              | 5K4  | 442             | 425 | 84  | 49  | 20 | 84 | 2.5                                | 500              |
| CJTM2U | 1200            | 2              | 5K4  | 507             | 490 | 84  | 49  | 20 | 84 | 2.5                                | 500              |
| CJTM3U | 1200            | 3              | 8K1  | 372             | 355 | 134 | 75  | 20 | 84 | 2.5                                | 500              |
| CJTM3U | 1500            | 3              | 8K1  | 442             | 425 | 134 | 75  | 20 | 84 | 2.5                                | 500              |
| CJTM3U | 1800            | 3              | 8K1  | 507             | 490 | 134 | 75  | 20 | 84 | 2.5                                | 500              |
| CJTM4U | 1600            | 4              | 10K8 | 372             | 355 | 184 | 125 | 20 | 84 | 2.5                                | 500              |
| CJTM4U | 2000            | 4              | 10K8 | 442             | 425 | 184 | 125 | 20 | 84 | 4                                  | 500              |
| CJTM4U | 2400            | 4              | 10K8 | 507             | 490 | 184 | 125 | 20 | 84 | 4                                  | 500              |
| CJTM5U | 2000            | 5              | 13K5 | 372             | 355 | 234 | 175 | 20 | 84 | 4                                  | 500              |
| CJTM5U | 2500            | 5              | 13K5 | 442             | 425 | 234 | 175 | 20 | 84 | 4                                  | 500              |
| CJTM5U | 3000            | 5              | 13K5 | 507             | 490 | 234 | 175 | 20 | 84 | 4                                  | 500              |

### How to Order

|   |   |   |   |                          |
|---|---|---|---|--------------------------|
| <b>CJT</b>                                    | <b>60</b>   | <b>1K0</b>  | <b>J</b>  | <b>J</b>                 |
| <b>Common Part</b>                            | <b>Power Rating</b>   | <b>Resistance Value</b>   | <b>Tolerance</b>  | <b>Connection</b>        |
| CJT - Single Aluminium Housed Power Resistors | 60 - 60 Watt<br>80 - 80 Watt<br>100 - 100 Watt<br>120 - 120 Watt<br>etc.    | 1 Ohm (1000 Milliohms)<br>1R0<br>10 Ohms (10 Ohms)<br>10R<br>100R Ohms (100 Ohms)<br>100R<br>1k Ohms (1000 Ohms)<br>1K0 | J - ±5%   | M - Terminal<br>J - Lead |
| <b>CJTM</b>                                   | <b>1U</b>   | <b>200</b>  | <b>1R0</b>  | <b>J</b>                 |
| <b>Common Part</b>                            | <b>No. of Units</b>   | <b>Power Rating</b>   | <b>Resistance Value</b>   | <b>Tolerance</b>         |
| CJTM - Multi Aluminium Housed Power Resistors | 1U - 1 Unit<br>2U - 2 Units<br>3U - 3 Units<br>4U - 4 Units<br>5U - 5 Units | 200 to 3000 Watts   | 1 Ohm (1000 Milliohms)<br>1R0<br>10 Ohms (10 Ohms)<br>10R<br>100R Ohms (100 Ohms)<br>100R<br>1k Ohms (1000 Ohms)<br>1K0 | J - ±5%<br>K - ±10%      |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.