

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.


LOC	DIST
DF	A0


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	S	REVISED PER ECO-13-014822	25OCT13	MGM	CT









	INSERT ARRANGEMENT			
	26	32C2	67	106
"A" MAX	1.525 [38.74]	1.700 [43.18]	1.525 [38.74]	1.279 [32.49]

1. MATERIAL AND FINISH
   SHELL: DIE CAST ALUM. ALLOY PER FED SPEC QQ-A-591
   FINISH: TYPE II CADMIUM PLATE (YELLOW) PER QQ-P-416
   INSULATOR HARD: EPOXY PER MIL-M-24325; SOFT: SILICONE RUBBER
   GROMMET PROTECTORS: ALUM. ALLOY, FINISH: BLUE EPOXY
   POLARIZING KEYING INSERTS & SCREWS: STAINLESS STEEL
   FEMALE JACKSCREW: STAINLESS STEEL
   SCREWS & WASHERS: STEEL. FINISH: CAD. PLATED PER QQ-P-416
   DUST CAPS: CONDUCTIVE BLACK THERMOPLASTIC

△2 CONTACTS SHOWN IN POSITION FOR ILLUSTRATION ONLY, ARE INCLUDED IN A CONTAINER WITHIN CONNECTOR PACKAGE FOR SHIPMENT, EXCEPT P/N'S 1-207595-2 THRU 2-207595-1

3. CONNECTOR MEETS AMP PRODUCT SPEC 108-10, 019

4. COAX CONTACTS & SEALING BOOTS MUST BE ORDERED SEPARATELY

△6 ALL METRIC DIMENSIONS ARE SHOWN IN PARENTHESIS

7. FOR MATING CONNECTOR SEE 207596

△8 CONNECTORS ORDERED LESS CONTACTS WILL BE MARKED WITH SAME P/N AS CONNECTORS ORDERED WITH CONTACTS

	PART NO.	ARRANGEMENT		PART NO △8 LESS CONTACTS	
		MODULE A	MODULE B		
	207595-1	106P	67S	1-207595-2	
	207595-2	106P	26S	1-207595-3	
	207595-3	106P	106P	1-207595-4	
OBSOLETE	207595-4	106P	106S	1-207595-5	OBSOLETE
	207595-5	106S	106S	1-207595-6	
	207595-6	106S	26P	1-207595-7	OBSOLETE
	207595-7	106S	67P	1-207595-8	OBSOLETE
OBSOLETE	207595-8	67S	67S	1-207595-9	
	207595-9	106S	32C2P	2-207595-0	OBSOLETE
	1-207595-0	106P	32C2S	2-207595-1	
	1-207595-1	NO INSERT	NO INSERT	-	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES △6

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .010
4 PLC ± .0050
ANGLES ± -

MATERIAL -
FINISH -

DWN C.C.THOMAS 21MAR02
CHK J.MARKEY 3-25-02
APVD J.MARKEY 3-25-02
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME RECEPTACLE CONNECTOR INSTALLATION (WITH CENTER FEMALE JACKSCREW)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-207595	-

CUSTOMER DRAWING | SCALE 2:1 | SHEET 1 OF 1 | REV S


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.