






RECOMMENDED PCB DIMENSIONS

NOTES:

1.MATERIAL:

CONTACTS—COPPER ALLOY

SHELL—COPPER ALLOY

HOUSING—UL 94—V-0 RATED THERMOPLASTIC.

2.PLATING:

CONTACTS: SEE PRODUCT NUMBER CODE;

SHELL: SEE PRODUCT NUMBER CODE.



③ DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

4.RECOMMENDED PC BOARD THICKNESS OF 1.57mm.

5.P/N SEE PRODUCT NUMBER CODE.

(TO BE CONTINUED)


mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family USB HPL511				
ltr	ecn no	dr	date	tolerances unless otherwise specified			title			UNIV. SERIAL BUS DOUBLE DECK RECEPTACLE				
AK	ELX-N-26385	LZ	2017/03/17	angles		linear		mm 						
AD	N05-0106	PH	04/13/05											
AE	N06-0101	HB	04/13/06	0°±3'				scale 1:1						
AF	N06-0133	HB	05/17/06	dr	Laurence.Zang	2017/03/17		dwg no						sheet 1 of 4
AG	N08-0198	RB	2008/09/10	eng	Laurence.Zang	2017/03/17		Amphenol FCI			72309			A3
AH	N08-0238	RB	2008/11/01	chr	LQ Lei	2017/03/17								
AJ	ELX-N-004653	A.ZH	2011/07/26	app	Tim Yao	2017/03/17		type Product Customer Drawing						
sheet	revision	AK												
index	sheet	1~4												





ASSEMBLY WITHOUT BACK SHIELD
72309-XX3XX SHOWN

(CONTINUED)


6. FOR LEAD FREE P/N, A LEAD FREE LABEL WILL APPEAR AT PACKING.
7. FOR LEAD FREE P/N, THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
8. FOR LEAD FREE P/N, THE PRODUCT MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008
9. PACKAGING SPECIFICATION PER GS-14-393.
10. PRODUCT SPECIFICATION PER GS-12-095.



mat'l. code				surface	tolerance	projection	product family	
				ISO 1302	ISO 406	ISO 1101	USB HPL511	
ltr	ecr	no	dr	date	tolerances unless otherwise specified		title	
AK					angles	.0±.3	UNIV. SERIAL BUS DOUBLE DECK RECEPTACLE	
					linear	.00±.20		
					0°±3'	.000±.10		
					dr	Laurence.Zang	2017/03/17	dwg no
					eng	Laurence.Zang	2017/03/17	
					chr	LQ Lei	2017/03/17	
					app	Tim Yao	2017/03/17	
sheet	revision	AK						type
index	sheet	1~4						Product Customer Drawing



ASSEMBLY WITH BACK SHIELD
72309 - XX4XX SHOWN



mat'l. code				surface	tolerance	projection	product family	
				ISO 1302	ISO 406	ISO 1101	USB HPL511	
ltr	ecr	no	dr	date	tolerances unless otherwise specified		title	
AK					angles	.0±.3	UNIV. SERIAL BUS DOUBLE DECK RECEPTACLE	
					linear	.00±.20		
					0°±3°	.000±.10		
					dr	Laurence.Zang	2017/03/17	dwg no
					eng	Laurence.Zang	2017/03/17	
					chr	LQ Lei	2017/03/17	
					app	Tim Yao	2017/03/17	
sheet	revision	AK						type
index	sheet	1~4						
								Product Customer Drawing

PRODUCT NUMBER CODE

72309 - X X X X X P S LF

BASE PRODUCT NUMBER

HOUSING COLOR + SHELL PLATING OPTIONS

- 0 - WHITE + NICKEL & TIN LEAD PLATING
- 1 - BLACK + NICKEL & TIN LEAD PLATING
- 2 - WHITE + NICKEL PLATING ONLY
- 3 - BLACK + NICKEL PLATING ONLY
- 4 - WHITE + NICKEL PLATING ONLY + LCP HSG
- 5 - BLACK + NICKEL PLATING ONLY + LCP HSG
- 6 - BLACK + NICKEL & TIN LEAD PLATING + LCP HSG
- 7 - BLACK + NICKEL & BRIGHT TIN PLATING
- 8 - WHITE + NICKEL & BRIGHT TIN PLATING
- 9 - BLACK + NICKEL & BRIGHT TIN PLATING +LCP HSG
- A - BLACK + NICKEL & MATTE TIN PLATING +LCP HSG
- S - BLACK + NICKEL PLATING ONLY + LCP HSG

SHELL PLATING OPTION

- 0 - BARREL-PLATING
- 1 - PRE-PLATING

SHELL OPTIONS

- 1 - NO BACK SHIELD, NO ARMS, FRONT GROUNDING ARMS
- 2 - BACK SHIELD, NO FRONT GROUNDING ARMS
- 3 - NO BACK SHIELD, FRONT GROUNDING ARMS
- 4 - BACK SHIELD, FRONT GROUNDING ARMS

TERMINAL OPTION

- 3 - 50u" Ni UNDERPLATE,30u" GXT CONTACT AREA,100u" MATTE TIN TAIL AREA
2.80mm TAIL LENGTH
- 4 - 50u" Ni UNDERPLATE,30u" GXT CONTACT AREA,100u" MATTE TIN TAIL AREA
2.80mm TAIL LENGTH
- 5 - 50u" Ni UNDERPLATE,30u" GOLD CONTACT AREA,100u" MATTE TIN TAIL AREA
3.94mm TAIL LENGTH

PACKAGING OPTIONS

- B - TUBES
- R - TAPE & REEL
- Q - SPECIAL TUBES (LENGTH 600MM MAX)

WITH DATE CODE

ONLY FOR PANASONIC

LEAD FREE MARK

LEAD FREE CONVERSION RULES -
HOUSING COLOR AND SHELL PLATING OPTION: 0 TO 8, 1 TO 7, 6 TO 9
TERMINAL PLATING OPTION: 0 TO 4, 2 TO 3
SPECIFIC SHELL MATERIAL FOR 12K CYCLES DURABILITY,
PART NUMBER: 72309-S033XPLF/-S034XPLF

NOTE:

AVAILABLE P/N'S IN FCI NOW FOLLOWED:

72309-0010X/8014XLF 72309-2010X/2014XLF
72309-0012X/8013XLF 72309-2012X/2013XLF
72309-0020X/8024XLF 72309-2020X/2024XLF
72309-0022X/8023XLF 72309-2022X/2023XLF
72309-0030X/8034XLF 72309-2030X/2034XLF
72309-0032X/8033XLF 72309-2032X/2033XLF
72309-0040X/8044XLF 72309-2040X/2044XLF
72309-0042X/8043XLF 72309-2042X/2043XLF
72309-1010X/7014XLF 72309-3010X/3014XLF
72309-1012X/7013XLF 72309-3012X/3013XLF
72309-1020X/7024XLF 72309-3020X/3024XLF
72309-1022X/7023XLF 72309-3022X/3023XLF
72309-1030X/7034XLF 72309-3030X/3034XLF
72309-1032X/7033XLF 72309-3032X/3033XLF
72309-1040X/7044XLF 72309-3040X/3044XLF
72309-1042X/7043XLF 72309-3042X/3043XLF
72309-0110X/8114XLF 72309-4040X/4044XLF
72309-0112X/8113XLF 72309-5012X/5013XLF
72309-0120X/8124XLF 72309-5030X/5034XLF
72309-0122X/8123XLF 72309-5040X/5044XLF/5044XSFL
72309-0130X/8134XLF 72309-5140X/5144XLF
72309-0132X/8133XLF 72309-6220X/9224XLF
72309-0140X/8144XLF 72309-A034XLF
72309-0142X/8143XLF 72309-3015XLF
72309-1110X/7114XLF 72309-3045XLF
72309-1112X/7113XLF 72309-S033XPLF
72309-1120X/7124XLF 72309-S034XPLF
72309-1122X/7123XLF
72309-1130X/7134XLF
72309-1132X/7133XLF
72309-1140X/7144XLF
72309-1142X/7143XLF

mat'l. code				surface	tolerance	projection	product family
				ISO 1302	ISO 406	ISO 1101	USB HPL511
ltr	ecn	no	dr	tolerances unless otherwise specified			title
AK				angles	.0±.3	mm	UNIV. SERIAL BUS
				linear	.00±.20		DOUBLE DECK RECEPTACLE
				0°±3'	.000±.10	scale 1:1	
				dr	Laurence.Zang	2017/03/17	dwg no
				eng	Laurence.Zang	2017/03/17	sheet 4 of 4
				chr	LQ Lei	2017/03/17	size
				app	Tim Yao	2017/03/17	A3
sheet	revision	AK					type Product Customer Drawing
index	sheet	1~4					



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.