

### 452/454 Series Fuse



#### Agency Approvals

| AGENCY                                                                            | AGENCY FILE NUMBER | AMPERE RANGE |
|-----------------------------------------------------------------------------------|--------------------|--------------|
|  | E10480             | 0.375A - 12A |
|  | 29862              | 0.375A - 12A |
|  | NBK030205-E10480B  | 1A - 5A      |

#### Electrical Characteristics for Series

| % of Ampere Rating | Opening Time                    |
|--------------------|---------------------------------|
| 100%               | 4 hours, Minimum                |
| 200%               | 1 sec., Min.; 60 sec., Max.     |
| 300%               | 0.2 sec., Min.; 3 sec., Max     |
| 800%               | 0.02 sec., Min.; 0.1 sec., Max. |

#### Electrical Specifications by Item

| Ampere Rating (A) | Amp Code | Max Voltage Rating (V) | Interrupting Rating                                       | Nominal Cold Resistance (Ohms) | Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec) | Agency Approvals                                                                      |                                                                                       |                                                                                       |
|-------------------|----------|------------------------|-----------------------------------------------------------|--------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                   |          |                        |                                                           |                                |                                                       |  |  |  |
| 0.375             | .375     | 125                    | 50A @ 125 VAC/VDC<br>300A @ 32 VDC<br>PSE: 100A @ 100 VAC | 1.2000                         | 0.101                                                 | x                                                                                     | x                                                                                     |                                                                                       |
| 0.500             | .500     | 125                    |                                                           | 0.7000                         | 0.240                                                 | x                                                                                     | x                                                                                     |                                                                                       |
| 0.750             | .750     | 125                    |                                                           | 0.3600                         | 0.904                                                 | x                                                                                     | x                                                                                     |                                                                                       |
| 001.              | 001.     | 125                    |                                                           | 0.2250                         | 1.98                                                  | x                                                                                     | x                                                                                     | x                                                                                     |
| 1.50              | 01.5     | 125                    |                                                           | 0.0930                         | 3.65                                                  | x                                                                                     | x                                                                                     | x                                                                                     |
| 2.00              | 002.     | 125                    |                                                           | 0.0625                         | 8.20                                                  | x                                                                                     | x                                                                                     | x                                                                                     |
| 2.50              | 02.5     | 125                    |                                                           | 0.0450                         | 15.0                                                  | x                                                                                     | x                                                                                     | x                                                                                     |
| 3.00              | 003.     | 125                    |                                                           | 0.0340                         | 20.16                                                 | x                                                                                     | x                                                                                     | x                                                                                     |
| 3.50              | 03.5     | 125                    |                                                           | 0.0224                         | 26.53                                                 | x                                                                                     | x                                                                                     | x                                                                                     |
| 4.00              | 004.     | 125                    |                                                           | 0.0186                         | 34.40                                                 | x                                                                                     | x                                                                                     | x                                                                                     |
| 5.00              | 005.     | 125                    |                                                           | 0.0136                         | 53.72                                                 | x                                                                                     | x                                                                                     | x                                                                                     |
| 7.00              | 007.     | 75                     | 50A @ 72 VAC<br>50A @ 60 VDC<br>100A @ 75 VDC             | 0.0105                         | 123.83                                                | x                                                                                     | x                                                                                     |                                                                                       |
| 8                 | 008.     | 75                     |                                                           | 0.0088                         | 137.34                                                | x                                                                                     | x                                                                                     |                                                                                       |
| 12                | 012.     | 75                     |                                                           | 0.0061                         | 260.46                                                | x                                                                                     | x                                                                                     |                                                                                       |

#### Notes:

- I<sup>2</sup>t calculated at 8ms.
- Resistance is measured at 10% of rated current, 25°C

#### Description

The NANO<sup>2</sup>® Slo-Blo® fuse has enhanced inrush withstand characteristics over the NANO<sup>2</sup>® Fast-Acting fuse. The unique time delay feature of this fuse design helps solve the problem of nuisance “opening” by accommodating inrush currents that normally cause a fast-acting fuse to open.


#### Features

- Small size
- Wide range of current rating available (0.375A to 12A)
- Wide operating temperature range
- Low temperature derating
- RoHS compliant and Halogen Free

#### Applications

- Notebook PC
- LCD/PDP TV
- LCD monitor
- LCD/PDP panel
- LCD backlight inverter
- Portable DVD player
- Power supply
- Networking
- PC server
- Cooling fan system
- Storage system
- Telecom system
- Wireless basestation
- White goods
- Game console
- Office Automation equipment
- Battery charging circuit protection
- Industrial equipment


## Temperature Re-rating Curve



Note:


1. Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

## Average Time Current Curves



## Soldering Parameters

|                                                       |                                    |                                        |
|-------------------------------------------------------|------------------------------------|----------------------------------------|
| Reflow Condition                                      |                                    | Pb – Free assembly                     |
| Pre Heat                                              | - Temperature Min ( $T_{s(min)}$ ) | 150°C                                  |
|                                                       | - Temperature Max ( $T_{s(max)}$ ) | 200°C                                  |
|                                                       | - Time (Min to Max) ( $t_s$ )      | 60 – 120 secs                          |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak |                                    | 5°C/second max.                        |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                  |                                    | 5°C/second max.                        |
| Reflow                                                | - Temperature ( $T_L$ ) (Liquidus) | 217°C                                  |
|                                                       | - Temperature ( $t_L$ )            | 60 – 90 seconds                        |
| Peak Temperature ( $T_p$ )                            |                                    | 260 <sup>+0/-5</sup> °C                |
| Time within 5°C of actual peak Temperature ( $t_p$ )  |                                    | 20 – 40 seconds                        |
| Ramp-down Rate                                        |                                    | 5°C/second max.                        |
| Time 25°C to peak Temperature ( $T_p$ )               |                                    | 8 minutes max.                         |
| Do not exceed                                         |                                    | 260°C                                  |
| Wave Soldering Parameters                             |                                    | 260°C Peak Temperature, 3 seconds max. |




### Product Characteristics

|                                              |                                                                                                                                                 |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Materials</b>                             | <b>Body:</b> Ceramic<br><b>Terminations:</b><br>Gold-plated Caps / Sn-dipped Silver Plated Caps (452 Series)<br>Silver-plated Caps (454 Series) |
| <b>Product Marking</b>                       | Brand, Ampere Rating                                                                                                                            |
| <b>Operating Temperature</b>                 | -55°C to 125°C                                                                                                                                  |
| <b>Moisture Sensitivity Level</b>            | Level 1, J-STD-020                                                                                                                              |
| <b>Solderability</b>                         | MIL-STD-202, Method 208                                                                                                                         |
| <b>Insulation Resistance (after Opening)</b> | MIL-STD-202, Method 302, Test Condition A (10,000 ohms minimum)                                                                                 |

|                                     |                                                                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Thermal Shock</b>                | MIL-STD-202, Method 107, Test Condition B, 5 cycles, -65°C / +125°C, 15 minutes @ each extreme                              |
| <b>Mechanical Shock</b>             | MIL-STD-202, Method 213, Test I: Deenergized. 100G's pk amplitude, sawtooth wave 6ms duration, 3 cycles XYZ+xyz = 18 shocks |
| <b>Vibration</b>                    | MIL-STD-202, Method 201: 0.03" amplitude, 10-55 Hz in 1 min. 2hrs each XYZ=6hrs                                             |
| <b>Moisture Resistance</b>          | MIL-STD-202, Method 106, 10 cycles                                                                                          |
| <b>Salt Spray</b>                   | MIL-STD-202, Method 101, Test Condition B (48hrs)                                                                           |
| <b>Resistance to Soldering Heat</b> | MIL-STD-202, Method 210, Test condition B (10 sec at 260°C)                                                                 |

### Dimensions



### Part Numbering System

|                                                                 |                                                                                                                                                                                                                                                                   |             |          |          |          |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|----------|----------|----------|
|                                                                 | <b>0452</b>                                                                                                                                                                                                                                                       | <b>001.</b> | <b>M</b> | <b>R</b> | <b>L</b> |
| <b>SERIES</b>                                                   |                                                                                                                                                                                                                                                                   |             |          |          |          |
| <b>AMP Code</b>                                                 | Refer to Amp Code column in the Electrical Specifications table. The dot is positioned at the end of the number sequence with whole ratings and within for fractional ratings.<br><b>Example:</b> 0.375 Amp product is 0452. <b>375</b> MRL (1 amp product shown) |             |          |          |          |
| <b>QUANTITY Code</b>                                            | M = 1000 pcs<br>N = 5000 pcs                                                                                                                                                                                                                                      |             |          |          |          |
| <b>PACKAGING Code</b>                                           | R = Tape and Reel                                                                                                                                                                                                                                                 |             |          |          |          |
| <b>L - RoHS Compliant &amp; Halogen Free (Gold Plated Caps)</b> |                                                                                                                                                                                                                                                                   |             |          |          |          |
| <b>SN-RoHS Compliant &amp; Halogen Free (Sn-dipped Caps)</b>    |                                                                                                                                                                                                                                                                   |             |          |          |          |

Notes:  
 452 series may be ordered as "RoHS and HF (Gold Plated Caps)" ("L" suffix).  
 454 series is available only as "RoHS and HF" version and does not require "L" suffix.  
 Please do not include "L" suffix within 454 series ordering instructions.

### Packaging

| Packaging Option   | Packaging Specification        | Quantity | Quantity & Packaging Code |
|--------------------|--------------------------------|----------|---------------------------|
| 12mm Tape and Reel | EIA RS-481-1 (IEC 286, part 3) | 5000     | NR                        |
| 12mm Tape and Reel | EIA RS-481-1 (IEC 286, part 3) | 1000     | MR                        |

### Additional Information



**Datasheet**  
452 Series



**Resources**  
452 Series



**Samples**  
452 Series



**Datasheet**  
454 Series



**Resources**  
454 Series



**Samples**  
454 Series



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.