

# Features

## Regulated Converters

- DIP16, Mini DIP16 or SMD package style
- 1kVDC, 2kVDC or 3kVDC isolation
- Continuous short circuit protected
- Low ripple and noise
- IEC/EN60950-1 certified
- Efficiency up to 83%



## RW2

## 2 Watt MINI DIP16, DIP16 or SMD Single & Dual Output



IEC/EN60950-1 certified

### Description

High power-density, 2:1 input voltage range and a wide temperature range of -40°C to +85°C are just some of the characteristics of this versatile DIP16 converter, ideal for highly sophisticated industrial designs where a regulated converter is required but space is at a premium. Three different case styles and isolation options are available.

### Selection Guide

| Part Number | Input Voltage Range [VDC] | Output Voltage [VDC] | Output Current [mA] | Efficiency typ. <sup>(1)</sup> [%] | max. Capacitive Load <sup>(2)</sup> [μF] |
|-------------|---------------------------|----------------------|---------------------|------------------------------------|------------------------------------------|
| RW2-053.3S  | 4.5-9                     | 3.3                  | 500                 | 68                                 | 4700                                     |
| RW2-0505S   | 4.5-9                     | 5                    | 400                 | 73                                 | 1000                                     |
| RW2-0512S   | 4.5-9                     | 12                   | 166                 | 75                                 | 1000                                     |
| RW2-0515S   | 4.5-9                     | 15                   | 134                 | 75                                 | 1000                                     |
| RW2-123.3S  | 9-18                      | 3.3                  | 500                 | 69                                 | 4700                                     |
| RW2-1205S   | 9-18                      | 5                    | 400                 | 75                                 | 1000                                     |
| RW2-1212S   | 9-18                      | 12                   | 166                 | 80                                 | 1000                                     |
| RW2-1215S   | 9-18                      | 15                   | 134                 | 80                                 | 1000                                     |
| RW2-243.3S  | 18-36                     | 3.3                  | 500                 | 70                                 | 4700                                     |
| RW2-2405S   | 18-36                     | 5                    | 400                 | 78                                 | 1000                                     |
| RW2-2412S   | 18-36                     | 12                   | 166                 | 83                                 | 1000                                     |
| RW2-2415S   | 18-36                     | 15                   | 134                 | 83                                 | 1000                                     |
| RW2-483.3S  | 36-72                     | 3.3                  | 500                 | 73                                 | 4700                                     |
| RW2-4805S   | 36-72                     | 5                    | 400                 | 76                                 | 1000                                     |
| RW2-4812S   | 36-72                     | 12                   | 166                 | 81                                 | 1000                                     |
| RW2-4815S   | 36-72                     | 15                   | 134                 | 81                                 | 1000                                     |
| RW2-0505D   | 4.5-9                     | ±5                   | ±200                | 73                                 | ±680                                     |
| RW2-0509D   | 4.5-9                     | ±9                   | ±111                | 74                                 | ±680                                     |
| RW2-0512D   | 4.5-9                     | ±12                  | ±83                 | 75                                 | ±680                                     |
| RW2-0515D   | 4.5-9                     | ±15                  | ±67                 | 75                                 | ±680                                     |
| RW2-1205D   | 9-18                      | ±5                   | ±200                | 75                                 | ±680                                     |
| RW2-1209D   | 9-18                      | ±9                   | ±111                | 78                                 | ±680                                     |
| RW2-1212D   | 9-18                      | ±12                  | ±83                 | 80                                 | ±680                                     |
| RW2-1215D   | 9-18                      | ±15                  | ±67                 | 80                                 | ±680                                     |
| RW2-2405D   | 18-36                     | ±5                   | ±200                | 78                                 | ±680                                     |
| RW2-2409D   | 18-36                     | ±9                   | ±111                | 81                                 | ±680                                     |
| RW2-2412D   | 18-36                     | ±12                  | ±83                 | 83                                 | ±680                                     |
| RW2-2415D   | 18-36                     | ±15                  | ±67                 | 83                                 | ±680                                     |
| RW2-4805D   | 36-72                     | ±5                   | ±200                | 78                                 | ±680                                     |
| RW2-4809D   | 36-72                     | ±9                   | ±111                | 81                                 | ±680                                     |
| RW2-4812D   | 36-72                     | ±12                  | ±83                 | 83                                 | ±680                                     |
| RW2-4815D   | 36-72                     | ±15                  | ±67                 | 83                                 | ±680                                     |

#### Notes:

Note1: Efficiency is tested at nominal input and full load at +25°C ambient

Note2: Maximum capacitive load is defined as the capacitive load that will allow start up in under 1 second without damage on the converter

**Model Numbering**



**Notes:**

Note3: „/H2“ = 2kVDC isolation; „/H3“ = 3kVDC isolation; without suffix standard 1kVDC isolation

Note4: add suffix „/SMD“ for SMD package or „/B“ for Mini DIP16 THT package;  
without suffix = standard DIP16 package (refer to “DIP16”)

**Ordering Examples:**

|                   |          |         |        |                 |                    |
|-------------------|----------|---------|--------|-----------------|--------------------|
| RW2-2405S/B:      | 18-36Vin | 5Vout   | Single | 1kVDC Isolation | Mini DIP16 Package |
| RW2-1212D/H2:     | 9-18Vin  | ±12Vout | Dual   | 2kVDC Isolation | DIP16 Package      |
| RW2-0515D/H3/SMD: | 4.5-9Vin | ±15Vout | Dual   | 3kVDC Isolation | SMD Package        |
| RW2-4812S/H2/B    | 36-72Vin | 12Vout  | Single | 2kVDC Isolation | Mini DIP16 Package |

**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

| BASIC CHARACTERISTICS                                                                                         |                 |        |      |         |
|---------------------------------------------------------------------------------------------------------------|-----------------|--------|------|---------|
| Parameter                                                                                                     | Condition       | Min.   | Typ. | Max.    |
| Input Voltage Range                                                                                           | 5VDC            | 4.5VDC |      | 9VDC    |
|                                                                                                               | nom. Vin= 12VDC | 9VDC   |      | 18VDC   |
|                                                                                                               | 24VDC           | 18VDC  |      | 36VDC   |
|                                                                                                               | 48VDC           | 36VDC  |      | 72VDC   |
| Minimum Load (5)                                                                                              |                 | 10%    |      |         |
| Internal Operating Frequency                                                                                  |                 | 100KHz |      | 700kHz  |
| Output Ripple and Noise                                                                                       | 20MHz BW        |        |      | 50mVp-p |
| <b>Notes:</b><br>Note5: Operation below 10% load won't harm the converter, but specifications may not be met. |                 |        |      |         |

**REGULATIONS**

| Parameter       | Condition        | Value      |
|-----------------|------------------|------------|
| Output Accuracy |                  | ±2.0% typ. |
| Line Regulation |                  | ±0.5% max. |
| Load Regulation | 20% to 100% load | 0.5% typ.  |

**PROTECTION**

| Parameter             | Type                    |                                           | Value                 |
|-----------------------|-------------------------|-------------------------------------------|-----------------------|
| Isolation Voltage (6) | standard without suffix | tested for 1 second<br>rated for 1 minute | 1kVDC<br>500VAC/60Hz  |
|                       | /H2 version             | tested for 1 second<br>rated for 1 minute | 2kVDC<br>1kVAC/60Hz   |
|                       | /H3 version             | tested for 1 second<br>rated for 1 minute | 3kVDC<br>1.5kVAC/60Hz |
| Isolation Resistance  |                         |                                           | 1GΩ min.              |
| Isolation Capacitance |                         |                                           | 30pF max.             |
| Insulation Grade      |                         |                                           | functional            |

**Notes:**

Note6: For repeat Hi-Pot testing, reduce the time and/or the test voltage

Note7: Refer to local safety regulations if input over-current protection is also required. Recommended fuse: slow blow type


**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**ENVIRONMENTAL**

| Parameter                   | Condition                                   |                | Value                                                       |
|-----------------------------|---------------------------------------------|----------------|-------------------------------------------------------------|
| Operating Temperature Range | full load @ free air convection (see graph) |                | -40°C to +85°C                                              |
| Maximum Case Temperature    |                                             |                | +100°C                                                      |
| Operating Altitude          |                                             |                | 2000m                                                       |
| Operating Humidity          | non-condensing                              |                | 95% RH max.                                                 |
| Pollution Degree            |                                             |                | PD2                                                         |
| MTBF                        | according to MIL-HDBK-217F, G.B.            | +25°C<br>+85°C | 4366 x 10 <sup>3</sup> hours<br>658 x 10 <sup>3</sup> hours |

**Derating Graph**

(@ Chamber and free air convection)




**SAFETY AND CERTIFICATIONS**

| Certificate Type (Safety)                                                             | Report / File Number | Standard                                                            |
|---------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------|
| Information Technology Equipment, General Requirements for Safety                     | SPCLVD1605077-10     | IEC60950-1:2005, 2nd Edition + A2:2013<br>EN60950-1:2006 + A2:2013  |
| Medical Electric Equipment, General Requirements for Safety and Essential Performance | WD-SE-R-180675-A0    | IEC60601-1:2005, 3rd Edition + A1:2012<br>EN60601-1:2006 + A12:2014 |
| EAC                                                                                   | RU-AT.AB49.B.09571   | TP TC 004/2011                                                      |
| RoHS 2+                                                                               | TWNC00635328         | RoHS-2011/65/EU                                                     |

| EMC Compliance                                                                               | Condition                                             | Standard / Criterion                 |
|----------------------------------------------------------------------------------------------|-------------------------------------------------------|--------------------------------------|
| Electromagnetic compatibility of multimedia equipment - Emission requirements <sup>(8)</sup> | with external filter<br>(see filter suggestion below) | EN55032, Class A<br>EN55032, Class B |

**EMC Filtering Suggestions according to EN55032**



**Notes:**

Note8: Filter suggestions are valid for indicated part numbers only.  
For other part numbers, please contact RECOM tech support for advice.

**Component List Class A**

| Models           | C1                | C2    | L1                                  |
|------------------|-------------------|-------|-------------------------------------|
| RW2-1212S/H2/SMD | 10µF/100V<br>MLCC | 330pF | <a href="#">5.6µH choke RLS-567</a> |
| RW2-2405S/H2     |                   |       |                                     |

**Component List Class B**

| Models           | C1                | C2    | L1                                 |
|------------------|-------------------|-------|------------------------------------|
| RW2-1212S/H2/SMD | 10µF/100V<br>MLCC | 330pF | <a href="#">22µH choke RLS-226</a> |
| RW2-2405S/H2     |                   |       |                                    |





**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

### DIMENSION AND PHYSICAL CHARACTERISTICS

| Parameter         | Type       | Value                                    |
|-------------------|------------|------------------------------------------|
| Material          | case       | non-conductive black plastic, (UL94 V-0) |
|                   | potting    | epoxy, (UL94 V-0)                        |
|                   | PCB        | FR4, (UL94 V-0)                          |
| Dimension (LxWxH) | Mini DIP16 | 22.1 x 12.55 x 8.50mm                    |
|                   | DIP16      | 24.2 x 14.50 x 9.70mm                    |
|                   | SMD        | 24.2 x 14.50 x 10.20mm                   |
| Weight            |            | 6.4g typ.                                |

#### Dimension Drawing (mm)

##### DIP16







#### Pinning information

| Pin # | Single | Dual  |
|-------|--------|-------|
| 1     | -Vin   | -Vin  |
| 7     | NC     | NC    |
| 8     | NC     | Com   |
| 9     | +Vout  | +Vout |
| 10    | -Vout  | -Vout |
| 16    | +Vin   | +Vin  |

Tolerance: xx.x= ±0.5mm  
xx.xx= ±0.35mm

##### Mini DIP16 (/B)



#### Pinning information

| Pin # | Single | Dual  |
|-------|--------|-------|
| 1     | -Vin   | -Vin  |
| 7     | NC     | NC    |
| 8     | NC     | Com   |
| 9     | +Vout  | +Vout |
| 10    | -Vout  | -Vout |
| 16    | +Vin   | +Vin  |




Tolerance: xx.x= ±0.5mm  
xx.xx= ±0.35mm

continued on next page


**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**Dimension Drawing SMD (mm)**

SMD (/SMD)



**Recommended Footprint Details**



**Pinning information**

| Pin # | Single | Dual  |
|-------|--------|-------|
| 1     | -Vin   | -Vin  |
| 7     | NC     | NC    |
| 8     | NC     | Com   |
| 9     | +Vout  | +Vout |
| 10    | -Vout  | -Vout |
| 16    | +Vin   | +Vin  |

Tolerance: xx.x=±0.5mm  
xx.xx=±0.35mm

**PACKAGING INFORMATION**

| Parameter                   | Type                        | Value                 |
|-----------------------------|-----------------------------|-----------------------|
| Packaging Dimension (LxWxH) | tube                        | 530.0 x 21.0 x 18.0mm |
| Packaging Quantity          | DIP16 and SMD<br>Mini DIP16 | 20pcs<br>22pcs        |
| Storage Temperature Range   |                             | -55°C to +125°C       |
| Storage Humidity            | non-condensing              | 95% RH max.           |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.