



Product: [3076F](#)

Fieldbus, 1 Pr #18 Str TC, PP Ins, OS, PVC Jkt, Flexible SUN RES OIL RES, PLTC-ER, ITC-ER, CMX-Outdoor, CM

[Request Sample](#)

Product Description

Fieldbus, 1 Pair 18AWG (7x26) Tinned Copper, PP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, Flexible SUN RES OIL RES, PLTC-ER, ITC-ER, CMX-Outdoor, CM

Technical Specifications

Suitable Applications: exposure to rodent, crush, or cut through force, harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	18	7x26	TC - Tinned Copper

Insulation

Element	Material	Thickness [in.]	Color Code
Pair(s)	PP - Polypropylene	0.022	Blue & Orange

Outer Shield Material

Shield Type	Material	Coverage	Drainwire Type
Tape	Alum / Poly	100%	20 AWG (7x28) TC

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.050 in	0.280 in

Cable Diameter (Nominal): 0.280 in

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Shield	Max. Capacitance Unbalance	Characteristic Impedance	Nom. Velocity of Prop.	Max. Current
Pair(s)	5.86 Ohm/1000ft	45 pF/ft	1.2 pF/ft	100 Ohm	66%	5.2 Amps per Conductor

Nom Outer Shield DCR: 7.5 Ohm/1000ft

High Frequency (Nominal/Typical)

Element	Nom. Insertion Loss
Pair(s)	0.08 dB/100ft

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Max./Min. Input Impedance (unFitted)
0.031 MHz	0.091 dB/100ft	100 Ohm

Voltage

UL Voltage Rating
300 V (CM, PLTC-ER), 150 V (ITC)

Temperature

UL Rating	Operating
105°C	-40°C to +105°C

Bend Radius**Stationary Min.**

2.5 in

Max. Pull Tension:	60 lbs
Bulk Cable Weight:	38 lbs/1000ft
Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance, Oil Resistance, Oil Resistance, Burial
Flammability / Fire Resistance:	UL1666 Riser, FT4, 1202, IEC 60332-1-2
NEC / UL Compliance:	Article 725, Article 727, Article 800, CM, CMX-Outdoor, ITC-ER, PLTC-ER
CEC / C(UL) Compliance:	CMG
IEEE Compliance:	1202, IEEE 383 Vertical Tray Flame Test (70,000 BTU)
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
Other Standard Compliance(s):	ISA/SP-50 Type A
Notes:	Fieldbus: Orange jacket. Profibus PA: Intrinsically Safe Blue jacket. Jacket diameter tolerance: +/- .010
Update and Revision:	Revision Number: 0.367 Revision Date: 07-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.