

LOW DROPOUT VOLTAGE REGULATOR

■ GENERAL DESCRIPTION


The NJU7780/81 is a low dropout voltage regulator with ON/OFF Control.

Advanced CMOS technology achieves low quiescent current.

It is suitable for battery operating applications.

NJU7781 features shunt switch which improves turn off response of output voltage when ON/OFF control is used.

■ PACKAGE OUTLINE




NJU7780/81U1



■ FEATURES

- High Ripple Rejection 65dB typ. (f=400Hz, Vo=3V)
- Low quiescent Current Iq=20μA (Io=0mA, V_{CONT}=V_{IN})
- Output capacitor with 1.0μF ceramic capacitor
- Output Current Io(max)=300mA
- High Precision Output Vo±1.0%
- Low Dropout Voltage 0.15V typ. (Io=150mA, Vo=3.0V)
- ON/OFF Control (Active High)
- Shunt Switch Only NJU7781
- Internal Over Current Protection
- Internal Thermal Overload Protection
- CMOS technology
- Package outline SOT-89-5

■ PIN CONFIGURATION



■ EQUIVALENT CIRCUIT



NJU7780/81

■ OUTPUT VOLTAGE RANK LIST (1.5V~5.0V : 0.1V step)

Device Name	V _{OUT}	Device Name	V _{OUT}	Device Name	V _{OUT}
NJU778xU1-15	1.5V	NJU778xU1-28	2.8V	NJU778xU1-04	4.0V
NJU778xU1-18	1.8V	NJU778xU1-29	2.9V	NJU778xU1-05	5.0V
NJU778xU1-21	2.1V	NJU778xU1-03	3.0V		
NJU778xU1-25	2.5V	NJU778xU1-33	3.3V		

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Input Voltage	V _{IN}	+10	V
Control Voltage	V _{CONT}	+10(*1)	V
Power Dissipation	P _D	350(*2)	mW
Operating Temperature	T _{opr}	-40 ~ +85	°C
Storage Temperature	T _{stg}	-40 ~ +125	°C
OFF-state Output Sink Current (*3)	I _o	10	mA

(*1): When input voltage is less than +10V, the absolute maximum control voltage is equal to the input voltage.

(*2): Device itself.

(*3): This maximum rating is applied to NJU7781.

■ Operating voltage

V_{IN}=+2.3 ~ +9V (In case of Vo<2.1V version)

■ ELECTRICAL CHARACTERISTICS

(V_{IN}=Vo+1V, C_{IN}=0.1μF, C_O=0.1μF, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	I _O =30mA		-1.0%	-	+1.0%	V
Input Voltage	V _{IN}			-	-	9	V
Quiescent Current	I _Q	I _O =0mA, V _{CONT} =V _{IN}		-	20	40	μA
Quiescent Current at Control OFF	I _{Q(OFF)}	V _{CONT} =0V		-	-	1	μA
Output Current	I _O	V _O - 0.1V(V _O <2.1V) V _O - 0.3V(V _O ≥2.1V)		300	-	-	mA
Short Current Limit	I _{LIM}	V _O =0V		-	120	-	mA
Line Regulation	ΔV _O /ΔV _{IN}	V _{IN} =V _O +1V~V _O +6V(V _O <3.0), V _{IN} =V _O +1V~V _O +9V(V _O ≥3.0), I _O =30mA		-	-	0.10	%/V
Load Regulation	ΔV _O /ΔI _O	I _O =0~300mA		-	-	0.015	%/mA
Dropout Voltage(*4)	ΔV _{I-O}	I _O =150mA	2.1 ≤ V _O ≤ 2.6V	-	0.18	0.25	V
			2.7 ≤ V _O ≤ 3.3V	-	0.15	0.22	
			3.4 ≤ V _O ≤ 5.0V	-	0.12	0.2	
Ripple Rejection	RR	e _{in} =200mVrms, f=400Hz, I _O =10mA, V _O =3.0V		-	65	-	dB
Average Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a	T _a =0~85°C, I _O =10mA		-	±100	-	ppm/ ^o C
Output Noise Voltage	V _{NO}	F=10Hz~80kHz, I _O =10mA, V _O =3.0V		-	80	-	μVrms
Pull-Down Resistance	R _{CONT}			1.5	5	10	MΩ
Control Voltage for ON-state	V _{CONT(ON)}			1.6	-	-	V
Control Voltage for OFF-state	V _{CONT(OFF)}			-	-	0.3	V
Pull-down Resistance at OFF-state(*5)	R _{O(OFF)}	V _{CONT} =0V (V _O =3.0V Version)		—	190	—	Ω


(*4): The output voltage excludes under 2.1V.

(*5) This electrical characteristics is applied to NJU7781.

The above specification is a common specification for all output voltages.


Therefore, it may be different from the individual specification for a specific output voltage.

■ TEST CIRCUIT



■ TYPICAL APPLICATION


① In the case where ON/OFF Control is not required:



*7: $V_O \leq 2.0V$ version, $C_O = 2.2 \mu F$

Connect control terminal to V_{IN} terminal

② In use of ON/OFF CONTROL:








*7: $V_O \leq 2.0V$ version, $C_O = 2.2 \mu F$

State of control terminal:

- "H" $\rightarrow$ output is enabled.
- "L" or "open" $\rightarrow$ output is disabled.





■ ELECTRICAL CHARACTERISTICS

● DC CHARACTERISTICS









■ ELECTRICAL CHARACTERISTICS

● AC CHARACTERISTICS





■ ELECTRICAL CHARACTERISTICS

● TEMPERATURE CHARACTERISTICS









■ ELECTRICAL CHARACTERISTICS

● TEMPERATURE CHARACTERISTICS



■ TYPICAL CHARACTERISTICS

● TRANSIENT RESPONSE



[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJU7780U1-05-TE1](#) [NJU7780U1-25-TE1](#) [NJU7781U1-03-TE1](#) [NJU7781U1-21-TE1](#) [NJU7781U1-25-TE1](#)
[NJU7780U1-03-TE1](#) [NJU7780U1-33-TE2](#) [NJU7780U1-15-TE2](#) [NJU7780U1-21-TE1](#) [NJU7781U1-05-TE1](#)
[NJU7780U1-33-TE1](#) [NJU7781U1-33-TE1](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.