0.5 Ω, CMOS, 1.8 V to 5.5 V, 2:1 Mux/SPDT Switch

Data Sheet **ADG819**

FEATURES

- Low on resistance: 0.8 Ω maximum at 125°C
- 0.25 Ω maximum on resistance flatness
- 1.8 V to 5.5 V single supply
- 200 mA current carrying capability
- Automotive temperature range: −40°C to +125°C
- Rail-to-rail operation
- 6-lead SOT-23, 8-lead MSOP, and 6-ball WLCSP packages
- Fast switching times
- Typical power consumption (<0.01 µW)
- TTL-/CMOS-compatible inputs
- Pin compatible with the ADG719

APPLICATIONS

- Power routing
- Battery-powered systems
- Communication systems
- Data acquisition systems
- Cellular phones
- Modems
- PCMCIA cards
- Hard drives
- Relay replacement

GENERAL DESCRIPTION

The ADG819 is a monolithic, CMOS, single-pole, double-throw (SPDT) switch. This switch is designed on a submicron process that provides low power dissipation yet gives high switching speed, low on resistance, and low leakage currents.

Low power consumption and an operating supply range of 1.8 V to 5.5 V make the ADG819 ideal for battery-powered, portable instruments.

Each switch of the ADG819 conducts equally well in both directions when on. The ADG819 exhibits break-before-make switching action, thus preventing momentary shorting when switching channels.

The ADG819 is available in a 6-lead SOT-23 package, an 8-lead MSOP package, and in a 6-ball WLCSP package. This chip occupies only a 1.14 mm × 2.18 mm area, making it the ideal candidate for space-constrained applications.

FUNCTIONAL BLOCK DIAGRAM



Figure 1.

PRODUCT HIGHLIGHTS

1. Very low on resistance, 0.5 Ω typical.
2. 1.8 V to 5.5 V single-supply operation.
3. High current carrying capability.
4. Tiny 6-lead SOT-23, 8-lead MSOP, and 6-ball, 1.14 mm × 2.18 mm WLCSP packages.

Rev. A
Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113 ©2002–2012 Analog Devices, Inc. All rights reserved.

TABLE OF CONTENTS

Features 1
Applications 1
Functional Block Diagram 1
General Description 1
Product Highlights 1
Revision History 2
Specifications 3
Absolute Maximum Ratings 5
ESD Caution 5
Pin Configurations and Function Descriptions 6
Typical Performance Characteristics 7
Test Circuits 9
Terminology 11
Outline Dimensions 12
Ordering Guide 13

REVISION HISTORY

5/12—Rev. 0 to Rev. A

Updated Format ..... Universal
Deleted ADG820 ..... Universal
Changes to General Description 1
Changes to Table 1 3
Changes to Table 2 4
Change to WLCSP θ_{JA} Thermal Impedance Parameter, Table 3 5
Added Table 5 and Table 6; Renumbered Sequentially 6
Deleted Test Circuit 6; Renumbered Sequentially 8
Changes to Figure 11 to Figure 14 8
Changes to Terminology Section 11
Updated Outline Dimensions 12
Changes to Ordering Guide 13

5/02—Revision 0: Initial Version

SPECIFICATIONS

V_{DD} = 5 V ± 10%, GND = 0 V, unless otherwise noted.

Table 1.

Parameter	25°C	−40°C to +85°C	−40°C to +125°C	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 V to V_{DD}	V	
On Resistance, R_{ON}[1]	0.5			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA; see Figure 16
	0.6	0.7	0.8	Ω max	
On Resistance Match Between Channels, ΔR_{ON}[1]	0.06			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA
	0.08	0.1	0.12	Ω max	
On Resistance Flatness, $R_{FLAT(ON)}$[1]	0.1			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA
	0.17	0.2	0.25	Ω max	
LEAKAGE CURRENTS					V_{DD} = 5.5 V
Source Off Leakage, I_S (Off)	±0.01			nA typ	V_S = 4.5 V/1 V, V_D = 1 V/4.5 V; see Figure 17
	±0.25	±3	±10	nA max	
Channel On Leakage, I_D, I_S (On)	±0.01			nA typ	V_S = V_D = 1 V, or V_S = V_D = 4.5 V; see Figure 18
	±0.25	±3	±25	nA max	
DIGITAL INPUTS					
Input High Voltage, V_{INH}			2.0	V min	
Input Low Voltage, V_{INL}			0.8	V max	
Input Current					
I_{INL} or I_{INH}	0.005			μA typ	V_{IN} = V_{INL} or V_{INH}
			±0.1	μA max	
Digital Input Capacitance, C_{IN}	5			pF typ	
DYNAMIC CHARACTERISTICS[2]					
t_{ON}	35			ns typ	R_L = 50 Ω, C_L = 35 pF, V_S = 3 V; see Figure 19
	45	50	55	ns max	
t_{OFF}	10			ns typ	R_L = 50 Ω, C_L = 35 pF, V_S = 3 V; see Figure 19
	16	18	21	ns max	
Break-Before-Make Time Delay, t_{BBM}	5			ns typ	R_L = 50 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 3 V; see Figure 20
			1	ns min	
Charge Injection	20			pC typ	V_S = 2.5 V, R_S = 0 Ω, C_L = 1 nF; see Figure 21
Off Isolation	−71			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 100 kHz; see Figure 22
Channel-to-Channel Crosstalk	−72			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 100 kHz; see Figure 24
Bandwidth, −3 dB	17			MHz typ	R_L = 50 Ω, C_L = 5 pF; see Figure 23
C_S (Off)	80			pF typ	f = 1 MHz
C_D, C_S (On)	300			pF typ	f = 1 MHz
POWER REQUIREMENTS					V_{DD} = 5.5 V, digital inputs = 0 V or 5.5 V
I_{DD}	0.001			μA typ	
		1.0	2.0	μA max	

[1] On resistance parameters tested with I_S = 10 mA.
[2] Guaranteed by design; not subject to production test.

V_{DD} = 2.7 V to 3.6 V, GND = 0 V, unless otherwise noted.

Table 2.

Parameter	25°C	−40°C to +85°C	−40°C to +125°C	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 V to V_{DD}	V	
On Resistance, R_{ON}[1]	0.7			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA; see Figure 16
	1.4	1.5	1.6	Ω max	
On Resistance Match Between Channels, ΔR_{ON}[1]	0.06			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA
		0.13	0.13	Ω max	
On Resistance Flatness, $R_{FLAT(ON)}$[1]	0.25			Ω typ	V_S = 0 V to V_{DD}, I_S = 100 mA
LEAKAGE CURRENTS					V_{DD} = 3.6 V
Source Off Leakage, I_S (Off)	±0.01			nA typ	V_S = 3.3 V/1 V, V_D = 1 V/3.3 V; see Figure 17
	±0.25	±3	±10	nA max	
Channel On Leakage, I_D, I_S (On)	±0.01			nA typ	V_S = V_D = 1 V, or V_S = V_D = 3.3 V; see Figure 18
	±0.25	±3	±25	nA max	
DIGITAL INPUTS					
Input High Voltage, V_{INH}			2.0	V min	
Input Low Voltage, V_{INL}			0.8	V max	
Input Current					
I_{INL} or I_{INH}	0.005			μA typ	V_{IN} = V_{INL} or V_{INH}
			±0.1	μA max	
Digital Input Capacitance, C_{IN}	5			pF typ	
DYNAMIC CHARACTERISTICS[2]					
t_{ON}	40			ns typ	R_L = 50 Ω, C_L = 35 pF, V_S = 1.5 V; see Figure 19
	60	65	70	ns max	
t_{OFF}	10			ns typ	R_L = 50 Ω, C_L = 35 pF, V_S = 1.5 V; see Figure 19
	16	18	21	ns max	
Break-Before-Make Time Delay, t_{BBM}	40			ns typ	R_L = 50 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 1.5 V; see Figure 20
			1	ns min	
Charge Injection	10			pC typ	V_S = 1.5 V, R_S = 0 Ω, C_L = 1 nF; see Figure 21
Off Isolation	−71			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 100 kHz; see Figure 22
Channel-to-Channel Crosstalk	−72			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 100 kHz; see Figure 24
Bandwidth, −3 dB	17			MHz typ	R_L = 50 Ω, C_L = 5 pF; see Figure 23
C_S (Off)	80			pF typ	f = 1 MHz
C_D, C_S (On)	300			pF typ	f = 1 MHz
POWER REQUIREMENTS					V_{DD} = 3.6 V, digital Inputs = 0 V or 3.6 V
I_{DD}	0.001			μA typ	
		1.0	2.0	μA max	

[1] On resistance parameters tested with I_S = 10 mA.
[2] Guaranteed by design; not subject to production test.

ABSOLUTE MAXIMUM RATINGS

T_A = 25°C, unless otherwise noted

Table 3.

Parameter	Rating
V_{DD} to GND	−0.3 V to +7 V
Analog Inputs[1]	−0.3 V to V_{DD} + 0.3 V or 30 mA, whichever occurs first
Digital Inputs[1]	−0.3 V to V_{DD} + 0.3 V or 30 mA, whichever occurs first
Peak Current, Sx or D	400 mA (pulsed at 1 ms, 10% duty cycle maximum)
Continuous Current, Sx or D	200 mA
Operating Temperature Range	
Industrial	−40°C to +85°C
Automotive	−40°C to +125°C
Storage Temperature Range	−65°C to +150°C
Junction Temperature	150°C
MSOP	
θ_{JA} Thermal Impedance	206°C/W
θ_{JC} Thermal Impedance	44°C/W
SOT-23 (4-Layer Board)	
θ_{JA} Thermal Impedance	119°C/W
WLCSP (4-Layer Board)	
θ_{JA} Thermal Impedance	80°C/W
Lead Temperature, Soldering (10 sec)	300°C
IR Reflow, Peak Temperature (<20 sec)	235°C

[1] Overvoltages at IN, Sx, or D are clamped by internal diodes. Current should be limited to the maximum ratings given.

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Only one absolute maximum rating can be applied at any one time.

Table 4. Truth Table for the ADG819

IN	Switch S1	Switch S2
0	On	Off
1	Off	On

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATIONS AND FUNCTION DESCRIPTIONS



Figure 2. 6-Lead SOT-23 Pin Configuration



Figure 3. 6-Ball WLCSP Pin Configuration

Table 5. 6-Lead SOT-23 and 6-Ball WLCSP Pin Function Descriptions

Pin No.			
SOT-23	**WLCSP**	**Mnemonic**	**Description**
1	6	IN	Logic Control Input.
2	5	V_{DD}	Most Positive Power Supply Potential.
3	4	GND	Ground (0 V) Reference.
4	3	S1	Source Terminal. Can be an input or output.
5	2	D	Drain Terminal. Can be an input or output.
6	1	S2	Source Terminal. Can be an input or output.



Figure 4. 8-Lead MSOP Pin Configuration

Table 6. 8-Lead MSOP Pin Function Descriptions

Pin No.	Mnemonic	Description
1	D	Drain Terminal. Can be an input or output.
2	S1	Source Terminal. Can be an input or output.
3	GND	Ground (0 V) Reference.
4	V_{DD}	Most Positive Power Supply Potential.
5	NC	No Connect. Do not connect to this pin.
6	IN	Logic Control Input.
7	NC	No Connect. Do not connect to this pin.
8	S2	Source Terminal. Can be an input or output.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 5. On Resistance vs. V_D, V_S



Figure 6. On Resistance vs. V_D, V_S



Figure 7. Leakage Currents vs. Temperature



Figure 8. On Resistance vs. V_D, V_S for Different Temperatures



Figure 9. On Resistance vs. V_D, V_S for Different Temperatures



Figure 10. t_{ON}/t_{OFF} Times vs. Temperature



Figure 11. Charge Injection vs. V_S (Source Voltage)



Figure 12. Off Isolation vs. Frequency



Figure 13. Crosstalk vs. Frequency



Figure 14. On Response vs. Frequency



Figure 15. Logic Threshold Voltage vs. Supply Voltage

TEST CIRCUITS



Figure 16. On Resistance



Figure 17. Off Leakage



Figure 18. On Leakage



Figure 19. Switching Times



Figure 20. Break-Before-Make Time Delay, t_{BBM}



Figure 21. Charge Injection



Figure 22. Off Isolation



Figure 23. Bandwidth



Figure 24. Channel-to-Channel Crosstalk

TERMINOLOGY

R_{ON}
Ohmic resistance between D and Sx.

ΔR_{ON}
On resistance match between any two channels, that is, R_{ON} maximum − R_{ON} minimum.

$R_{FLAT(ON)}$
Flatness is defined as the difference between the maximum and minimum value of on resistance as measured over the specified analog signal range.

I_S (Off)
Source leakage current with the switch off.

I_D, I_S (On)
Channel leakage current with the switch on.

V_D (V_S)
Analog voltage on Terminal D and Terminal S.

V_{INL}
Maximum input voltage for Logic 0.

V_{INH}
Minimum input voltage for Logic 1.

I_{INL} (I_{INH})
Input current of the digital input.

C_S (Off)
Off switch source capacitance.

C_D, C_S (On)
On switch capacitance.

t_{ON}
Delay between applying the digital control input and the output switching on.

t_{OFF}
Delay between applying the digital control input and the output switching off.

t_{BBM}
Off time or on time measured between the 90% points of both switches when switching from one address state to another.

Charge Injection
A measure of the glitch impulse transferred from the digital input to the analog output during switching.

Channel-to-Channel Crosstalk
A measure of unwanted signal coupled through from one channel to another as a result of parasitic capacitance.

Off Isolation
A measure of unwanted signal coupling through an off switch.

Bandwidth
Frequency at which the output is attenuated by −3 dB.

On Response
Frequency response of the on switch.

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MO-178-AB

Figure 25. 6-Lead Small Outline Transistor Package [SOT-23]
(RJ-6)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MO-187-AA

Figure 26. 8-Lead mini Small Outline Package [MSOP]
(RM-8)
Dimensions shown in millimeters



Figure 27. 6-Ball Wafer Level Chip Scale Package [WLCSP]
(CB-6-1)
Dimensions shown in millimeters

ORDERING GUIDE

Model[1]	Notes	Temperature Range	Package Description	Package Option	Branding[2]
ADG819BCBZ-REEL	[3]	–40°C to +85°C	6-Ball Wafer Level Chip Package [WLCSP]	CB-6-1	SBC
ADG819BCBZ-REEL7	[3]	–40°C to +85°C	6-Ball Wafer Level Chip Package [WLCSP]	CB-6-1	SBC
ADG819BRM		–40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	SNB
ADG819BRM-REEL		–40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	SNB
ADG819BRMZ		–40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	SBC
ADG819BRMZ-REEL7	[3]	–40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	SBC
ADG819BRT-500RL7	[3]	–40°C to +125°C	6-Lead Small Outline Transistor Package [SOT-23]	RJ-6	SNB
ADG819BRT-REEL7	[3]	–40°C to +125°C	6-Lead Small Outline Transistor Package [SOT-23]	RJ-6	SNB
ADG819BRTZ-500RL7	[3]	–40°C to +125°C	6-Lead Small Outline Transistor Package [SOT-23]	RJ-6	SBC
ADG819BRTZ-REEL	[3]	–40°C to +125°C	6-Lead Small Outline Transistor Package [SOT-23]	RJ-6	SBC
ADG819BRTZ-REEL7	[3]	–40°C to +125°C	6-Lead Small Outline Transistor Package [SOT-23]	RJ-6	SBC

[1] Z = RoHS Compliant Part.
[2] Branding on these packages is limited to three characters due to space constraints.
[3] Contact factory for availability.

NOTES

NOTES

NOTES

©2002–2012 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D02801-0-5/12(A)

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.