

# EPCOS Sample Kit 2012 SMD NTC Thermistors

for LED Applications



# Why thermal sensing?

Today's LED system designers face the challenge of reducing costs whilst satisfying the increasing demands for high lumen efficiency and long lifetime requirements.

The efficiency of LEDs depends very much on the LED junction temperature. Temperature extremes must be avoided, as these lead to faster power degradation, flux reduction, color shift, shortened life time, and even fatal damage to the LED. For maximum efficiency, the LED temperature must be controlled at its specific optimum. The LED temperature is finally an essential indicator of lumen efficiency and the thermal sensor is a key component in the control circuit.

### Benefits of thermal sensing with SMD NTC thermistors

SMD NTC thermistors can be used as an integral part of the LED module and can easily be integrated in the assembly process. Small size, good thermal contact to the PCB and negligible self warming make SMD NTC thermistors very sensitive and accurate sensors. If an SMD NTC is integrated into an LED module, any deviation from the optimum operating temperature of the LED will cause a significant resistance change of the NTC. This will change the current flow through the SMD NTC thermistor and hence change the voltage drop across it. This change can be read by the comparator of the LED driver to adjust the LED driving current which will reduce the power dissipation in the LED increasing its' life-time.

### Features

- Highly accurate temperature sensing with low resistance tolerance down to ±1%
- High temperature capability up to +125 °C standard and +150 °C automotive
- Excellent long-term aging stability in high-temperature environments
- Nickel barrier termination and lead-free solderability
- Automotive product range AEC-Q200 qualified
- Resistance values 10 k $\Omega$  up to 470 k $\Omega$
- Small EIA case sizes 0402 and 0603
- PSpice library available

Important information: Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products. We expressly point out that these statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. It is incumbent on the customer to check and decide whether a product is suitable for use in a particular application. This publication is only a brief product survey which may be changed from time to time. Our products are described in detail in our data sheets. The *Important notes* (www.epcos.com /ImportantNotes) and the product-specific *Cautions and warnings* must be observed. All relevant information is available through our sales offices.

# Components



Automotive LED illumination (T $_{\rm op}$  –40 ... +150 °C)

B57232	B57251	B57332	B57332	B57352	B57352	B57352	B57352	B57352
V5103F360	V5103J060	V5103F360	V5103J360	V5103J060	V5223J060	V5473J060	V5104F360	V5104J360
_								_



General LED illumination (T $_{\rm op}$  –40 ... +125 °C)

B57230	B57261	B57221	B57330	B57321	B57371	B57371	B57374	B57371
V2103F260	V2223J060	V2473J060	V2103F260	V2103J60	V2223J60	V2473J60	V2104F60	V2474J60

# Product range



Electrical specifications and ordering codes

Temperature	R <sub>25</sub>	Δ <b>R</b> <sub>R</sub>	<b>B</b> <sub>25/50</sub>	<b>B</b> <sub>25/85</sub>	B <sub>25/100</sub>	Ordering code			
[°C]	[kΩ]	%	[K]	[K]	[К]				
EIA case size 0402 – automotive LED illumination									
-40 + 150	10	±1	3380	3435	3455 ±1%	B57232V5103F360			
-40 + 150	10	±5	3380	3435	3455 ±1%	B57232V5103J360			
-40 + 150	10	±5	3940	3980	4000 ±3%	B57251V5103J060			
EIA case size 0603	- automotiv	e LED illumi	nation						
-40 + 150	10	±1	3380	3435	3455 ±1%	B57332V5103F360			
-40 + 150	10	±5	3380	3435	3455 ±1%	B57332V5103J360			
-40 + 150	10	±3	4386	4455	4480 ±3%	B57352V5103H060			
-40 + 150	10	±5	4386	4455	4480 ±3%	B57352V5103J060			
-40 + 150	22	±3	4386	4455	4480 ±3%	B57352V5223H060			
-40 + 150	22	±5	4386	4455	4480 ±3%	B57352V5223J060			
-40 + 150	47	±3	4386	4455	4480 ±3%	B57352V5473H060			
-40 + 150	47	±5	4386	4455	4480 ±3%	B57352V5473J060			
-40 + 150	100	±1	4386	4455	4480 ±1%	B57352V5104F360			
-40 + 150	100	±5	4386	4455	4480 ±1%	B57352V5104J360			
EIA case size 0402 – general LED illumination									
-40 + 125	10	±1	3380	3435	3455 ±1%	B57230V2103F260			
-40 + 125	10	±5	3380	3435	3455 ±1%	B57230V2103J260			
-40 + 125	10	±5	3940	3980	4000 ±3%	B57221V2103J060			
-40 + 125	22	±5	4473	4548	4575 ±3%	B57261V2223J060			
-40 + 125	47	±5	3940	3980	4000 ±3%	B57221V2473J060			
EIA case size 0603 – general LED illumination									
-40 + 125	10	±1	3380	3435	3455 ±1%	B57330V2103F260			
-40 + 125	10	±5	3380	3435	3455 ±1%	B57330V2103J260			
-40 + 125	10	±3	3940	3980	4000 ±3%	B57321V2103H060			
-40 + 125	10	±5	3940	3980	4000 ±3%	B57321V2103J060			
-40 + 125	22	±3	4386	4455	4480 ±3%	B57371V2223H060			
-40 + 125	22	±5	4386	4455	4480 ±3%	B57371V2223J060			
-40 + 125	47	±3	4386	4455	4480 ±3%	B57371V2473H060			
-40 + 125	47	±5	4386	4455	4480 ±3%	B57371V2473J060			
-40 + 125	100	±1	4386	4455	4480 ±1%	B57374V2104F060			
-40 + 125	100	±5	4386	4455	4480 ±1%	B57374V2104J060			
-40 + 125	470	±3	4386	4455	4480 ±3%	B57371V2474H060			
-40 + 125	470	±5	4386	4455	4480 ±3%	B57371V2474J060			

The table is a selection of recommended types. Special tolerances at selected working temperature can be offered upon request. See enclosed CD-ROM for data sheets and further details.

### Application examples for SMD NTC thermistors

### Characteristics



#### Application examples

#### Simplified circuit example: LED module



#### Simplified circuit example: RGB backlight



- LED modules for indoor and outdoor illumination
- LED retrofit bulbs and tubes
- LED for consumer and entertainment applications
- LED automotive lighting
- LED industrial applications

CTVS is a ceramic transient voltage suppressor for the ESD protection of LEDs. More information about CTVS for LED applications is available upon request.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.