



PC BOARD VERSIONS		
PRODUCTNR:	PCB THICKNESS	DIM"A"
70230-X01/X01LF	1.6	2.90
70230-X11/X11LF	2.4	3.53






PRODUCT AFTER HOT RIVETTING.







RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.

NOTES:
1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 um SnPb 90-97 OR 2-8 um PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
7 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
8 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.


PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
-1YY/1YYLF	TELCORDIA CO
-2YY/2YYLF	CUSTOMER SPECIAL
-3YY/3YYLF	CUSTOMER SPECIAL


mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY	FCI www.fciconnect.com
ltr	ecn no	dr	date	linear			projection	title: RA FEMALE SIGNAL STB 96 mm VERSION
K	DG04-0104	CLu	041221					
L	DG06-0477	Cenh	11/20/060					
M	DG07-0168	Cenh	05/10/07	angles			mm	product family: METRAL(tm)
N	DG09-0068	Cenh	06/06/09	dr	R.Trippe	900918		code: 213
				engn	H. Bouwknegt	940308		size: A2 dwg no: 70230
H	V00578	LLA	000316	chk	A van Zanten	900918	scale 5:1	sheet: 1 of 3
J	V00847	LLA	000530	appd	W van Woensel	900918		
sheet index	revision sheet	N 1	N 2	N 3				


All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. © F C I b.v.
Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. © F C I b.v.


PDM: Rev:N STATUS: Released Printed: May 19, 2011

PC BOARD VERSIONS		
PRODUCTNR:	PCB THICKNESS	DIM"A"
70230-X02/X02LF	1.6	2.90
70230-X12/X12LF	2.4	3.53











RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.





PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
-1YY/1YYLF	TELCORDIA CO
-2YY/2YYLF	CUSTOMER SPECIAL
-3YY/3YYLF	CUSTOMER SPECIAL

NOTES:

1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 鍍 SnPb 90-97 OR 2-8 鍍 PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 SET BACK FOR PRESS BLOCK.
7 TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO 0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE TAIL LENGTH BEFORE APPLICATION TO A BOARD
8 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
9 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
10 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.


mat'l. code				tolerances unless otherwise specified				CUSTOMER COPY	FCI www.fciconnect.com
ltr	ecn	nodr	date						
N				linear				projection	title: RA FEMALE SIGNAL STB 96 mm VERSION
				angles					
				dr	D. de Bil	970529		mm	product family: METRAL(tm) / code:
				engr	P. Schalk	970529			size: A2 / dwg no: 70230 / code: 213
				chr	P. Schalk	970529		scale 5:1	sheet 2 of-
				appd	H. Cooijmans	970529			
sheet index	revision sheet								


All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. @ F C I b.v.

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. @ F C I b.v.


PDM: Rev:N STATUS: Released Printed: May 19, 2011


PC BOARD VERSIONS		
PRODUCTNR:	PCB THICKNESS	DIM"A"
70230-X03/X03LF	1.6	2.90
70230-X13/X13LF	2.4	3.53






PRODUCT AFTER HOT RIVETTING.





RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.



PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
−1YY/1YYLF	TELCORDIA CO
−2YY/2YYLF	CUSTOMER SPECIAL
−3YY/3YYLF	CUSTOMER SPECIAL

NOTES:
1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 鍍 SnPb 90-97 OR 2-8 鍍 PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
7 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
8 DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY	FCI www.fciconnect.com	
ltr	ecn	nodr	date						
N				linear			projection	title RA FEMALE SIGNAL STB 96 mm VERSION	
				angles					
				dr	Heaven Cen	11/20/06	mm	product family METRAL(tm)	code 213
				engr	Collins Lu	11/20/06		size A2 dwg no 70230	
				chr	Beer Fu	11/20/06	scale 5:1		sheet 3 of-
				appd	Joseph Hsia	11/20/06			
sheet index	revision sheet								

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. @ F C I b.v.
All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. @ F C I b.v.

PDM: Rev:N STATUS: Released Printed: May 19, 2011


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.