


Automotive-grade 5-line transient voltage suppressor (TVS) for ESD protection

Datasheet - production data



Applications

This device is used to protect equipment in which ESD and EOS transient overvoltage may damage electronic circuits.

Description

This device is a monolithic voltage suppressor designed to protect components connected to data and transmission lines against ESD.

It clamps the voltage just above the logic level supply for positive transients, and to a diode drop below ground for negative transients.

Features

- AEC-Q101 qualified
- 5 unidirectional TVS functions
- UL 94 V-0
- J-STD-020 MSL level 1




Benefits

- Suitable for high density boards

Complies with the following standards

- ISO 10605 / IEC 61000-4-2: C = 150 pF, R = 330 Ω
 - 30 kV (air discharge)
 - 18 kV (contact discharge)
- ISO 10605: C = 330 pF, R = 330 Ω
 - 20 kV (air discharge)
 - 13 kV (contact discharge)
- ISO 7637-3
 - Pulse 3a: $V_S = -150$ V
 - Pulse 3b: $V_S = +100$ V

Figure 1: Pin configuration



1 Characteristics

Table 1: Absolute ratings (Tamb = 25 °C)

Symbol	Parameter		Value	Unit
V _{pp}	Peak pulse voltage	ISO 10605 / IEC 61000-4-2 (C = 150 pF, R = 330 Ω)	30	kV
		Contact discharge	18	
		Air discharge		
		ISO10605 (C = 330 pF, R = 330 Ω)	20	
		Contact discharge	13	
		Air discharge		
I _{pp}	Peak pulse current	8/20μs	7	A
P _{pp}	Peak pulse power		80	W
T _{stg}	Storage temperature range		-65 to +150	°C
T _j	Operating junction temperature range		-40 to +150	
T _L	Maximum temperature for soldering during 10 s		260	°C

Figure 2: Electrical characteristics (definitions)





Table 2: Electrical characteristics - values (Tamb = 25 °C)

Order code	V _{BR} at I _R			I _{RM} at V _{RM}		V _{CL} at I _{pp} ⁽¹⁾		V _F at I _F		αT ⁽²⁾	C _{line}
	Min.	Max.		Max.		Max.		Max.		Max.	Typ.
	V	V	mA	μA	V	V	A	V	mA	10 ⁻⁴ /°C	pF
ESDA6V1-5SC6Y	6.1	7.2	1	1	5.2	11.4	7	1.25	200	6	50

Notes:

⁽¹⁾8/20 μs waveform⁽²⁾V_{BR} at T_j = V_{BR} at 25 °C x (1 + αT x (T_j - 25))

Figure 3: Pulse definition for electrical characteristics



1.1 Characteristics (curves)

Figure 4: Pulse power versus junction temperature




Figure 5: Peak pulse power versus exponential pulse duration




Figure 6: Clamping voltage versus peak pulse current




Figure 7: Leakage current versus junction temperature




Figure 8: ESD response to IEC 61000-4-2 (+8 kV contact discharge)




Figure 9: ESD response to IEC 61000-4-2 (-8 kV contact discharge)






Figure 10: ISO7637-3 pulse 3a response ($V_S = -150\text{ V}$)**Figure 11: ISO7637-3 pulse 3b response ($V_S = 100\text{ V}$)**

2 Application and design guidelines

Further information can be found in AN2689 titled: "Protection of automotive electronics from electrical hazards, guidelines for design and component selection".

3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

- Epoxy meets UL 94,V0
- Lead-free package

3.1 SOT23-6L package information

Figure 12: SOT23-6L package outline







Table 3: SOT23-6L package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.9		1.45	0.0354		0.0571
A1	0		0.15	0		0.0059
A2	0.9		1.3	0.0354		0.0512
b	0.30		0.5	0.0118		0.0197
c	0.09		0.2	0.0035		0.0079
D	2.8		3.05	0.1102		0.1201
E	1.5		1.75	0.0591		0.0689
e		0.95			0.0374	
H	2.6		3	0.1024		0.1181
L	0.3		0.6	0.0118		0.0236
θ	0		10	0		0.3937

Figure 13: Footprint recommendations, dimensions in mm (inches)**Figure 14: Marking layout (refer to ordering information table for marking)****Figure 15: Package orientation in reel**

Pin 1 located according to EIA-481

Note: Pocket dimensions are not on scale
Pocket shape may vary depending on package




Figure 16: Tape and reel orientation**Figure 17: Reel dimensions (mm)****Figure 18: Inner box dimensions (mm)**

Figure 19: Tape and reel outline




Table 4: Tape and reel mechanical data

Ref.	Dimensions		
	Millimeters		
	Min.	Typ.	Max.
P1	3.9	4	4.1
P0	3.9	4	4.1
D0	1.45	1.5	1.6
D1	1		
F	3.45	3.5	3.55
K0	1.3	1.4	1.6
P2	1.95	2	2.05
W	7.9	8	8.3

4 Ordering information

Figure 20: Ordering information scheme




Table 5: Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
ESDA6V1-5SC6Y	EC6Y	SOT23-6L	14 mg	3000	Tape and reel

5 Revision history

Table 6: Document revision history

Date	Revision	Changes
08-Nov-2016	1	Initial release.
15-Mar-2017	2	Updated title and description in cover page. Minor text changes to improve readability.
03-May-2017	3	Formatting improvement, no content changes.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.