


# NGB8206AN - 20 A, 350 V, N-Channel Ignition IGBT, D<sup>2</sup>PAK



**20 Amps, 350 Volts**  
 $V_{CE(on)} \leq 1.3 \text{ V @}$   
 $I_C = 10\text{A}, V_{GE} \geq 4.5 \text{ V}$

### Maximum Ratings ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	$V_{CES}$	390	V
Collector–Gate Voltage	$V_{CER}$	390	V
Gate–Emitter Voltage	$V_{GE}$	$\pm 15$	V
Collector Current–Continuous @ $T_C = 25^\circ\text{C}$ – Pulsed	$I_C$	20 50	$A_{DC}$ $A_{AC}$
Continuous Gate Current	$I_G$	1.0	mA
Transient Gate Current ( $t \leq 2 \text{ ms}, f \leq 100 \text{ Hz}$ )	$I_G$	20	mA
ESD (Charged–Device Model)	ESD	2.0	kV
ESD (Human Body Model) $R = 1500 \Omega, C = 100 \text{ pF}$	ESD	8.0	kV
ESD (Machine Model) $R = 0 \Omega, C = 200 \text{ pF}$	ESD	500	V
Total Power Dissipation @ $T_C = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	150 1.0	Watts $\text{W}/^\circ\text{C}$
Operating and Storage Temperature Range	$T_J, T_{stg}$	$-55$ to $+175$	$^\circ\text{C}$

### Description

This Logic Level Insulated Gate Bipolar Transistor (IGBT) features monolithic circuitry integrating ESD and Over–Voltage clamped protection for use in inductive coil drivers applications. Primary uses include Ignition, Direct Fuel Injection, or wherever high voltage and high current switching is required.


### Features

- Ideal for Coil–on–Plug and Driver–on–Coil Applications
- Gate–Emitter ESD Protection
- Temperature Compensated Gate–Collector Voltage Clamp Limits Stress Applied to Load
- Integrated ESD Diode Protection
- Low Threshold Voltage for Interfacing Power Loads to Logic or Microprocessor Devices
- Low Saturation Voltage
- High Pulsed Current Capability
- These are Pb–Free Devices

### Applications

- Ignition Systems

### Functional Diagram



### Additional Information



Datasheet



Resources



Samples

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

**Unclamped Collector–To–Emitter Avalanche Characteristics ( $-55^{\circ} \leq T_J \leq 175^{\circ}\text{C}$ )**

	Symbol	Value	Unit
Single Pulse Collector–to–Emitter Avalanche Energy			
$V_{CC} = 50\text{ V}, V_{GE} = 5.0\text{ V}, P_k I_L = 16.7\text{ A}, R_G = 1000\ \Omega, L = 1.8\text{ mH}, \text{Starting } T_J = 25^{\circ}\text{C}$	$E_{AS}$	250	mJ
$V_{CC} = 50\text{ V}, V_{GE} = 5.0\text{ V}, P_k I_L = 14.9\text{ A}, R_G = 1000\ \Omega, L = 1.8\text{ mH}, \text{Starting } T_J = 150^{\circ}\text{C}$		200	
$V_{CC} = 50\text{ V}, V_{GE} = 5.0\text{ V}, P_k I_L = 14.1\text{ A}, R_G = 1000\ \Omega, L = 1.8\text{ mH}, \text{Starting } T_J = 175^{\circ}\text{C}$		180	
Reverse Avalanche Energy			
$V_{CC} = 100\text{ V}, V_{GE} = 20\text{ V}, P_k I_L = 25.8\text{ A}, L = 6.0\text{ mH}, \text{Starting } T_J = 25^{\circ}\text{C}$	$E_{AS(R)}$	2000	mJ

1. When surface mounted to an FR4 board using the minimum recommended pad size.

**Thermal Characteristics**

Rating	Symbol	Value	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.0	$^{\circ}\text{C}/\text{W}$
Thermal Resistance, Junction to Ambient (Note 1)	$R_{\theta JA}$	62.5	$^{\circ}\text{C}/\text{W}$
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	$T_L$	275	$^{\circ}\text{C}$

**Electrical Characteristics - OFF**

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
Collector–Emitter Clamp Voltage	$BV_{CES}$	$I_C = 2.0 \text{ mA}$	$T_J = -40^\circ\text{C}$ to $150^\circ\text{C}$	325	350	375	V
		$I_C = 10 \text{ mA}$	$T_J = -40^\circ\text{C}$ to $150^\circ\text{C}$	340	365	390	
Zero Gate Voltage Collector Current	$I_{CES}$	$V_{CE} = 15 \text{ V},$ $V_{GE} = 0 \text{ V},$	$T_J = 25^\circ\text{C}$	-	0.1	1.0	$\mu\text{A}$
			$T_J = 25^\circ\text{C}$	0.5	1.5	10	
		$V_{CE} = 175 \text{ V}$ $V_{GE} = 0 \text{ V}$	$T_J = 175^\circ\text{C}$	1.0	25	100*	
Reverse Collector–Emitter Clamp Voltage	$BV_{CES(R)}$	$I_C = -75 \text{ mA}$	$T_J = 25^\circ\text{C}$	30	35	39	V
			$T_J = 175^\circ\text{C}$	32	37	42	
			$T_J = -40^\circ\text{C}$	29	32	37	
Reverse Collector–Emitter Leakage Current	$I_{CES(R)}$	$V_{CE} = -24 \text{ V}$	$T_J = 25^\circ\text{C}$	0.05	0.25	1.0	mA
			$T_J = 175^\circ\text{C}$	1.0	12.5	25	
			$T_J = -40^\circ\text{C}$	0.005	0.03	0.25	
Gate–Emitter Clamp Voltage	$BV_{GES}$	$I_G = \pm 5.0 \text{ mA}$	$T_J = -40^\circ\text{C}$ to $175^\circ\text{C}$	12	12.5	14	V
Gate–Emitter Leakage Current	$I_{GES}$	$V_{GE} = \pm 5.0 \text{ V}$	$T_J = -40^\circ\text{C}$ to $175^\circ\text{C}$	200	300	350*	$\mu\text{A}$
Gate Resistor	$R_G$	-	$T_J = -40^\circ\text{C}$ to $175^\circ\text{C}$	-	-	-	$\Omega$
Gate Emitter Resistor	$R_{GE}$	-	$T_J = -40^\circ\text{C}$ to $175^\circ\text{C}$	14.25	16	25	k $\Omega$

**Electrical Characteristics - ON (Note 3)**

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
Gate Threshold Voltage	$V_{GE(th)}$	$I_C = 1.0 \text{ mA},$ $V_{GE} = V_{CE}$	$T_J = 25^\circ\text{C}$	1.5	1.8	2.1	V
			$T_J = 175^\circ\text{C}$	0.7	1.0	1.3	
			$T_J = -40^\circ\text{C}$	1.7	2.0	2.3*	
Threshold Temperature Coefficient (Negative)	-	-	-	3.8	4.6	6.0	mV/ $^\circ\text{C}$

\*Maximum Value of Characteristic across Temperature Range.

3. Pulse Test: Pulse Width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

**Electrical Characteristics - ON (Note 4)**

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
Collector-to-Emitter On-Voltage	$V_{CE(on)}$	$I_C = 6.5\text{ A},$ $V_{GE} = 3.7\text{ V}$	$T_J = 25^\circ\text{C}$	0.95	1.15	1.35	V
			$T_J = 175^\circ\text{C}$	0.70	0.95	1.15	
			$T_J = -40^\circ\text{C}$	1.0	1.30	1.40	
		$I_C = 9.0\text{ A},$ $V_{GE} = 3.9\text{ V}$	$T_J = 25^\circ\text{C}$	0.95	1.25	1.45	
			$T_J = 175^\circ\text{C}$	0.8	1.05	1.25	
			$T_J = -40^\circ\text{C}$	1.1	1.4	1.50	
		$I_C = 7.5\text{ A},$ $V_{GE} = 4.5\text{ V}$	$T_J = 25^\circ\text{C}$	0.85	1.15	1.4	
			$T_J = 175^\circ\text{C}$	0.7	0.95	1.2	
			$T_J = -40^\circ\text{C}$	1.0	1.3	1.6*	
		$I_C = 10\text{ A},$ $V_{GE} = 4.5\text{ V}$	$T_J = 25^\circ\text{C}$	0.9	1.2	1.6	
			$T_J = 175^\circ\text{C}$	0.8	1.05	1.4	
			$T_J = -40^\circ\text{C}$	1.0	1.2	1.7*	
		$I_C = 15\text{ A},$ $V_{GE} = 4.5\text{ V}$	$T_J = 25^\circ\text{C}$	1.0	1.3	1.7	
			$T_J = 175^\circ\text{C}$	1.0	1.3	1.55	
			$T_J = -40^\circ\text{C}$	1.1	1.35	1.8*	
		$I_C = 20\text{ A},$ $V_{GE} = 4.5\text{ V}$	$T_J = 25^\circ\text{C}$	1.3	1.6	1.9	
			$T_J = 175^\circ\text{C}$	1.2	1.5	1.8	
			$T_J = -40^\circ\text{C}$	1.4	1.75	2.0*	
Forward Transconductance	gfs	$V_{CE} = 5.0\text{ V},$ $I_C = 6.0\text{ A}$	$T_J = 25^\circ\text{C}$	10	18	25	Mhos

\*Maximum Value of Characteristic across Temperature Range.

3. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

**Dynamic Characteristics**

Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit
Input Capacitance	$C_{ISS}$	$V_{CE} = 25\text{ V}$ $f = 10\text{ kHz}$	$T_J = 25^\circ\text{C}$	1100	1300	1500	pF
Output Capacitance	$C_{OSS}$			70	80	90	
Transfer Capacitance	$C_{RSS}$			18	20	22	

**Switching Characteristics**


Characteristic	Symbol	Test Conditions	Temperature	Min	Typ	Max	Unit	
Turn–Off Delay Time (Resistive)	$t_{d(off)}$	$V_{CC} = 300\text{ V}$ , $I_C = 9\text{ A}$ , $R_G = 1.0\text{ k}\Omega$ , $R_L = 33\ \Omega$ , $V_{GE} = 5.0\text{ V}$	$T_J = 25^\circ\text{C}$	6.0	8.0	10	μSec	
			$T_J = 175^\circ\text{C}$	6.0	8.0	10		
Fall Time (Resistive)	$t_f$		$T_J = 25^\circ\text{C}$	4.0	6.0	8.0		
			$T_J = 175^\circ\text{C}$	8.0	10.5	14		
Turn–Off Delay Time (Inductive)	$t_{d(off)}$		$V_{CC} = 300\text{ V}$ , $I_C = 9\text{ A}$ , $R_G = 1.0\text{ k}\Omega$ , $L = 300\ \mu\text{H}$ , $V_{GE} = 5.0\text{ V}$	$T_J = 25^\circ\text{C}$	3.0	5.0		7.0
				$T_J = 175^\circ\text{C}$	5.0	7.0		9.0
Fall Time (Inductive)	$t_f$	$T_J = 25^\circ\text{C}$		1.5	3.0	4.5		
		$T_J = 175^\circ\text{C}$		5.0	7.0	10		
Turn–On Delay Time	$t_{d(on)}$	$V_{CC} = 14\text{ V}$ , $I_C = 9.0\text{ A}$ , $R_G = 1.0\text{ k}\Omega$ , $R_L = 1.5\ \Omega$ , $V_{GE} = 5.0\text{ V}$		$T_J = 25^\circ\text{C}$	1.0	1.5	2.0	
				$T_J = 175^\circ\text{C}$	1.0	1.5	2.0	
Rise Time	$t_r$		$T_J = 25^\circ\text{C}$	4.0	6.0	8.0		
			$T_J = 175^\circ\text{C}$	3.0	5.0	7.0		

2. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .


\*Maximum Value of Characteristic across Temperature Range.

**Ratings and Characteristic Curves**


**Figure 1. Self Clamped Inductive Switching**




**Figure 2. Open Secondary Avalanche Current vs. Temperature**




**Figure 3. Collector-to-Emitter Voltage vs. Junction Temperature**




**Figure 4. Collector Current vs. Collector-to-Emitter Voltage**




**Figure 5. Collector Current vs. Collector-to-Emitter Voltage**




**Figure 6. Collector Current vs. Collector-to-Emitter Voltage**




**Figure 7. Transfer Characteristics**




**Figure 8. Collector-to-Emitter Leakage Current vs. Temperature**




**Figure 9. Gate Threshold Voltage vs. Temperature**




**Figure 10. Capacitance vs. Collector-to-Emitter Voltage**




**Figure 11. Resistive Switching Fall Time vs. Temperature**



**Figure 12. Inductive Switching Fall Time vs. Temperature**




**Figure 13. Minimum Pad Transient Thermal Resistance (Non-normalized Junction-to-Ambient)**





**Dimensions**




Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.035	0.51	0.89
E	0.045	0.055	1.14	1.40
F	0.310	0.350	7.87	8.89
G	0.100 BSC		2.54 BSC	
H	0.080	0.110	2.03	2.79
J	0.018	0.025	0.46	0.64
K	0.090	0.110	2.29	2.79
L	0.052	0.072	1.32	1.83
M	0.280	0.320	7.11	8.13
N	0.197 REF		5.00 REF	
P	0.079 REF		2.00 REF	
R	0.039 REF		0.99 REF	
S	0.575	0.625	14.60	15.88
V	0.045	0.055	1.14	1.40


**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 418B-01 THRU 418B-03 OBSOLETE, NEW STANDARD 418B-04.

**Soldering Footprint**



**Part Marking System**



GB8206AN = Device Code

- A= Assembly Location
- Y= Year
- WW = Work Week
- G = Pb-Free Package

**ORDERING INFORMATION**

Device	Package	Shipping
NGB8206ANT4G	D <sup>2</sup> PAK (Pb-Free)	800 / Tape & Reel
NGB8206ANTF4G		700 / Tape & Reel
NGB8206ANSL3G		50 Units / Rail

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.