



For more Information
please call

1-800-Belden1



General Description:

The shielded jacketed 9L283XX series provides shielding from external electrical interference and allows for greater flexibility, ease of termination, while providing exterior protection from the environment.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 9 | 28 | 7x36 | TC - Tinned Copper |

Total Number of Conductors: 9

Conductor Spacing Center to Center: .050 +/- .002

Conductor Spacing Outside Center to Outside Center: .40 +/- .008

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | .010 |

Insulation Resistance: >10,000 Megaohms

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|---|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape (Foil Side In) | 100.000 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|------|-----------|-------------------------------|
| 2-28 | 7x36 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .038 |

Overall Cable

Overall Nominal Thickness: .115 +/- .015

Overall Nominal Width: .520 +/- .035

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +105°C

Bulk Cable Weight: 44 lbs/1000 ft.

Min. Bend Radius/Minor Axis: 1.250 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating: UL AWM Style 2651, 20081

CSA Specification: AWM II A 105°C 300 V

CSA Rating: 105°C, 300 V RMS, FT1

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 10/01/2005

EU Directive 2002/96/EC (WEEE): Yes

| | |
|-----------------------------------|-----|
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|-----------------|------|
| UL Flame Test: | VW-1 |
| CSA Flame Test: | FT1 |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Description | Impedance (Ohm) |
|----------------------------|-----------------|
| (GSG) with shield grounded | 45 |

Nom. Inductance:

| Description | Inductance (µH/ft) |
|------------------------------------|--------------------|
| @ 1 MHz (GSG) with shield grounded | .11 |

Nom. Capacitance Conductor to Conductor:

| Description | Capacitance (pF/ft) |
|------------------------------------|---------------------|
| @ 1 kHz (GSG) with shield grounded | 70 |
| @ 1 MHz (GSG) with shield grounded | 50 |

Nominal Velocity of Propagation:

| Description | VP (%) |
|-------------|--------|
| | 60 |

Nominal Delay:

| Delay (ns/ft) |
|---------------------------------------|
| 1.7 NS/FT. (GSG) with shield grounded |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 68.2 OHMS/1000 FT. MAX. |

Nom. Attenuation:

| Description | Freq. (MHz) | Attenuation (dB/100 ft.) |
|----------------------------|-------------|--------------------------|
| (GSG) with shield grounded | 10 | 6 |
| (GSG) with shield grounded | 20 | 9.5 |
| (GSG) with shield grounded | 30 | 12.5 |
| (GSG) with shield grounded | 40 | 14.9 |
| (GSG) with shield grounded | 50 | 17.2 |
| (GSG) with shield grounded | 60 | 19 |
| (GSG) with shield grounded | 70 | 21.5 |
| (GSG) with shield grounded | 80 | 23 |
| (GSG) with shield grounded | 90 | 24.5 |
| (GSG) with shield grounded | 100 | 26 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Current |
|----------------------------|
| 1 Amp per conductor @ 20°C |

Typical Unbalanced Crosstalk:

| Description | Pulse Rise Time (NS) (MHz) | Near End % (MHz) | Far End % (MHz) |
|--|----------------------------|------------------|-----------------|
| 10 ft. sample length with ground connected to shield | 3 | 1.5 | 2 |
| 10 ft. sample length with ground connected to shield | 5 | .9 | 1.5 |
| 10 ft. sample length with ground connected to shield | 7 | .7 | 1.2 |

Notes (Overall)

Notes: GSG=Ground-Signal-Ground Mode

Polarity Identification (Overall)

Polarity Identification: RED POLARITY STRIPE ON #1 CONDUCTOR

Put Ups and Colors:

9L28309 Flat - Shielded Jacketed 9L283XX Series

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|--------|-------------|-------|-------|-------------------------|
| 9L28309 010100 | 100 FT | 4.800 LB | BLACK | E | 9 #28 PVC FS PVC RIBBON |

Notes:

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 3 Revision Date: 11-08-2012

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.