


TE CONNECTIVITY RESERVES THE RIGHT TO AMEND THIS DRAWING AT ANY TIME. USERS SHOULD EVALUATE THE SUITABILITY OF THE PRODUCT FOR THEIR APPLICATION.

| REVISIONS |                           |         |          |
|-----------|---------------------------|---------|----------|
| LTR       | DESCRIPTION               | DATE    | APPROVED |
| G1        | REVISED PER ECO-11-005139 | 29MAR11 | HMR      |
| H         | REVISED PER ECO-12-021161 | 04DEC12 | G.WELLS  |



CODE 41 TINEL-LOCK ADAPTER

NOTES:

1. THIS PRODUCT IS DESIGNED TO TERMINATE A BRAIDED CABLE SHIELD AND A HEAT SHRINKABLE LIPPED BOOT TO A CONNECTOR.
2. SEE CH00-0250-008 FOR ORDERING INFORMATION, MODIFICATIONS AND ADDITIONAL DIMENSIONS.
- ③ SEE DRAWING "TR" FOR DETAILS ON TINEL-LOCK RING. RINGS ARE DESIGNED TO BE HEATED ELECTRICALLY. ALL RINGS ARE MARKED WITH THERMOCHROMIC PAINT WHICH CHANGES COLOR WHEN INSTALLATION TEMPERATURE IS REACHED.
4. ADAPTER TO BE PERMANENTLY MARKED WITH CODE IDENT. NO. AND PART NO. LESS RING DESIGNATOR (E.G.: 06090-TXR41AB00-1206). RINGS SHALL BEAR NO MARKING.
- ⑤ FOR LARGER ENTRY SIZES, A 2 PIECE ADAPTER (TYPE II) IS SUPPLIED.
- ⑥ ADAPTER MATES TO MIL-C-38999, SERIES I & II, CLASS E AND T, MS27466, MS27467, MS27468, MS27472, MS27473, MS27474, MS27479, MS27480, MS27481, MS27484, MS27497, MS27652, MS27653, MS27656 CONNECTORS.
- ⑦ THESE DIMENSIONS APPLY IF A SELF-LOCKING COUPLING NUT IS USED. (MOD. CODE "S").

If this document is printed it becomes uncontrolled. Check for the latest revision

© 2006-12 Tyco Electronics Corporation, a TE connectivity Ltd. company. All rights reserved.

Raychem Adapters  
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES.  
METRIC DIMENSIONS ARE  
IN BRACKETS.

DECIMALS

.XXX ± 0.005 [ 0.13 mm]  
.XX ± 0.01 [ 0.25 mm]  
.X ± 0.1 [ 0.50 mm]

ANGLES

.X ± 0.5 DEG

DRAWN R. RAMIREZ 03-18-93


CHECKED --- ---

APPROVED W.C. GAY 05-19-93

REVISED MFORONDA 5/22/06

CAD NAME: txr41\_1\_h\_cd\_H

THIRD ANGLE  
PROJECTION



TE Connectivity

TITLE

TINEL-LOCK™ ADAPTER







SIZE CODE IDENT. NO. DWG. NO.

A 06090

TXR41

DO NOT SCALE THIS DRAWING

SHEET 1 OF 3



Raychem Adapters  
CUSTOMER DRAWING

If this document is printed it becomes uncontrolled. Check for the latest revision

© 2006-12 Tyco Electronics Corporation, a TE connectivity Ltd. company. All rights reserved.

| SIZE                      | CODE IDENT. NO. | DWG. NO.                 | REV          |
|---------------------------|-----------------|--------------------------|--------------|
| A                         | 06090           | TXR41                    | H            |
| DO NOT SCALE THIS DRAWING |                 | CAD NAME: txr41_2_h_cd_H | SHEET 2 OF 3 |

TABLE I

| ORDER NO. | SHELL SIZE  |       | MAX ENTRY SIZE  TYPE I | A UNIFIED THD CLASS 2B | B DIA MAX        | B DIA MAX  | C MAX         | D MAX          | E MAX          | W MAX          |
|-----------|----------------------------------------------------------------------------------------------|-------|---------------------------------------------------------------------------------------------------------|------------------------|------------------|----------------------------------------------------------------------------------------------|---------------|----------------|----------------|----------------|
|           | SER 1                                                                                        | SER 2 |                                                                                                         |                        |                  |                                                                                              |               |                |                |                |
| 08        | 9                                                                                            | 8     | 04                                                                                                      | .438-28 UNEF           | .750<br>[19.1]   | .969<br>[24.6]                                                                               | .69<br>[17.5] | .91<br>[23.1]  | 1.15<br>[29.2] | .85<br>[21.6]  |
| 10        | 11                                                                                           | 10    | 06                                                                                                      | .562-24 UNEF           | .850<br>[21.6]   | 1.063<br>[27.0]                                                                              | .72<br>[18.3] | .93<br>[23.6]  | 1.21<br>[30.7] | .97<br>[24.6]  |
| 12        | 13                                                                                           | 12    | 08                                                                                                      | .688-24 UNEF           | 1.000<br>[24.4]  | 1.219<br>[31.0]                                                                              | .74<br>[18.8] | .96<br>[24.4]  | 1.28<br>[32.5] | 1.10<br>[27.9] |
| 14        | 15                                                                                           | 14    | 10                                                                                                      | .812-20 UNEF           | 1.142<br>[29.00] | 1.406<br>[35.7]                                                                              | .76<br>[19.3] | .98<br>[24.9]  | 1.34<br>[34.0] | 1.22<br>[31.0] |
| 16        | 17                                                                                           | 16    | 12                                                                                                      | .938-20 UNEF           | 1.250<br>[31.8]  | 1.469<br>[37.3]                                                                              | .79<br>[20.1] | 1.00<br>[25.4] | 1.40<br>[35.6] | 1.35<br>[34.3] |
| 18        | 19                                                                                           | 18    | 12                                                                                                      | 1.062-18 UNEF          | 1.400<br>[35.6]  | 1.594<br>[40.5]                                                                              | .81<br>[20.6] | 1.03<br>[26.2] | 1.46<br>[37.1] | 1.41<br>[35.8] |
| 20        | 21                                                                                           | 20    | 14                                                                                                      | 1.188-18 UNEF          | 1.500<br>[38.1]  | 1.750<br>[44.5]                                                                              | .84<br>[21.3] | 1.06<br>[26.9] | 1.53<br>[38.9] | 1.53<br>[38.9] |
| 22        | 23                                                                                           | 22    | 16                                                                                                      | 1.312-18 UNEF          | 1.650<br>[41.9]  | 1.844<br>[46.8]                                                                              | .87<br>[22.1] | 1.08<br>[27.4] | 1.59<br>[40.4] | 1.66<br>[42.2] |
| 24        | 25                                                                                           | 24    | 18                                                                                                      | 1.438-18 UNEF          | 1.750<br>[44.45] | 2.031<br>[51.6]                                                                              | .89<br>[22.6] | 1.11<br>[28.2] | 1.65<br>[41.9] | 1.78<br>[45.2] |

TABLE II

| ENTRY SIZE | Z<br>+.010<br>-.020 | S DIA            |                  | Y<br>±.015<br>[±0.38] | F<br>MAX       | G<br>MAX       | H<br>MAX       | J<br>MAX       | K<br>MAX       |
|------------|---------------------|------------------|------------------|-----------------------|----------------|----------------|----------------|----------------|----------------|
| 04         | .250<br>[6.35]      | .376<br>[9.56]   | .370<br>[9.39]   | .550<br>[13.97]       | N/A            | N/A            | N/A            | N/A            | N/A            |
| 05         | .312<br>[7.92]      | .438<br>[11.13]  | .432<br>[10.97]  | .612<br>[15.54]       | .77<br>[19.6]  | .93<br>[23.6]  | 1.19<br>[30.2] | 1.16<br>[29.5] | .80<br>[20.3]  |
| 06         | .375<br>[9.52]      | .501<br>[12.73]  | .495<br>[12.57]  | .675<br>[17.14]       | .77<br>[19.6]  | .93<br>[23.6]  | 1.19<br>[30.2] | 1.16<br>[29.5] | .80<br>[20.3]  |
| 07         | .437<br>[11.09]     | .563<br>[14.31]  | .556<br>[14.12]  | .737<br>[18.71]       | .80<br>[20.3]  | .95<br>[24.1]  | 1.38<br>[35.1] | 1.22<br>[31.0] | .92<br>[23.4]  |
| 08         | .500<br>[12.70]     | .626<br>[15.91]  | .619<br>[15.72]  | .800<br>[20.32]       | .80<br>[20.3]  | .95<br>[24.1]  | 1.38<br>[35.1] | 1.22<br>[31.0] | .92<br>[23.4]  |
| 10         | .625<br>[15.87]     | .752<br>[19.11]  | .742<br>[18.84]  | .925<br>[23.49]       | .84<br>[21.3]  | 1.00<br>[25.4] | 1.51<br>[38.4] | 1.35<br>[34.3] | 1.18<br>[30.0] |
| 12         | .750<br>[19.05]     | .877<br>[22.28]  | .867<br>[22.02]  | 1.050<br>[26.67]      | .88<br>[22.4]  | 1.01<br>[25.7] | 1.63<br>[41.4] | 1.40<br>[35.6] | 1.35<br>[34.3] |
| 14         | .875<br>[22.23]     | 1.002<br>[25.46] | .991<br>[25.17]  | 1.175<br>[29.84]      | .88<br>[22.4]  | 1.04<br>[26.4] | 1.78<br>[45.2] | 1.46<br>[37.1] | 1.41<br>[35.8] |
| 16         | 1.000<br>[25.40]    | 1.127<br>[28.63] | 1.116<br>[28.34] | 1.300<br>[33.02]      | .93<br>[23.6]  | 1.06<br>[26.9] | 1.88<br>[47.8] | 1.53<br>[38.9] | 1.60<br>[40.6] |
| 18         | 1.125<br>[28.57]    | 1.252<br>[31.81] | 1.241<br>[31.52] | 1.425<br>[36.19]      | .93<br>[23.6]  | 1.09<br>[27.7] | 2.01<br>[51.1] | 1.59<br>[40.4] | 1.66<br>[42.2] |
| 20         | 1.250<br>[31.75]    | 1.377<br>[34.98] | 1.366<br>[34.69] | 1.550<br>[39.37]      | .98<br>[24.9]  | 1.13<br>[28.7] | 2.13<br>[54.1] | 1.78<br>[45.2] | 2.04<br>[51.8] |
| 22         | 1.375<br>[34.93]    | 1.502<br>[38.15] | 1.488<br>[37.79] | 1.675<br>[42.55]      | 1.03<br>[26.2] | 1.38<br>[35.1] | 2.29<br>[58.2] | 1.85<br>[47.0] | 2.23<br>[56.6] |
| 24         | 1.500<br>[38.10]    | 1.627<br>[41.33] | 1.613<br>[40.97] | 1.800<br>[45.72]      | 1.08<br>[27.4] | 1.44<br>[36.6] | 2.42<br>[61.5] | 1.92<br>[48.8] | 2.23<br>[56.6] |

Raychem Adapters  
CUSTOMER DRAWING

If this document is printed it becomes uncontrolled. Check for the latest revision

©2006-12 Tyco Electronics Corporation, a TE connectivity Ltd. company. All rights reserved.

| SIZE                                                            | CODE IDENT. NO. | DWG. NO. | REV |
|-----------------------------------------------------------------|-----------------|----------|-----|
| A                                                               | 06090           | TXR41    | H   |
| DO NOT SCALE THIS DRAWING CAD NAME: txr41_3_h_cd_H SHEET 3 OF 3 |                 |          |     |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.