


# High Speed Infrared Emitting Diode, 940 nm, GaAlAs, MQW



## FEATURES

- Package type: Surface mount
- Package form: Side view
- Dimensions (L x W x H in mm): 3 x 2 x 0.6
- AEC-Q101 qualified
- Peak wavelength:  $\lambda_p = 940$  nm
- High reliability
- High radiant power
- High radiant intensity
- High speed
- Angle of half intensity:  $\phi = \pm 75^\circ$
- Low forward voltage
- Package matches with detector VEMD11940FX01
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

## DESCRIPTION

VSMB11940X01 is an infrared, 940 nm side looking emitting diode in GaAlAs multi quantum well (MQW) technology with high radiant power and high speed, molded in clear, untinted plastic package (with lens) for surface mounting (SMD).

## APPLICATIONS

- IR touch panel
- High power emitter for low space applications
- High performance transmissive or reflective sensors

| PRODUCT SUMMARY |                      |              |                  |            |
|-----------------|----------------------|--------------|------------------|------------|
| COMPONENT       | $I_e$ (mW/sr), 20 mA | $\phi$ (deg) | $\lambda_p$ (nm) | $t_r$ (ns) |
| VSMB11940X01    | 1                    | $\pm 75$     | 940              | 15         |

### Note

- Test conditions see table “Basic Characteristics“

| ORDERING INFORMATION |               |                              |              |
|----------------------|---------------|------------------------------|--------------|
| ORDERING CODE        | PACKAGING     | REMARKS                      | PACKAGE FORM |
| VSMB11940X01         | Tape and reel | MOQ: 4000 pcs, 4000 pcs/reel | side view    |

### Note

- MOQ: minimum order quantity

| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified) |   |            |             |                  |
|---|---|------------|-------------|------------------|
| PARAMETER   | TEST CONDITION                          | SYMBOL     | VALUE       | UNIT             |
| Reverse voltage   |   | $V_R$      | 5           | V                |
| Forward current   |   | $I_F$      | 65          | mA               |
| Peak forward current  | $t_p/T = 0.5$ , $t_p = 100 \mu\text{s}$ | $I_{FM}$   | 130         | mA               |
| Surge forward current   | $t_p = 100 \mu\text{s}$                 | $I_{FSM}$  | 500         | mA               |
| Power dissipation   |   | $P_V$      | 104         | mW               |
| Junction temperature  |   | $T_j$      | 100         | $^\circ\text{C}$ |
| Operating temperature range   |   | $T_{amb}$  | -40 to +85  | $^\circ\text{C}$ |
| Storage temperature range   |   | $T_{stg}$  | -40 to +100 | $^\circ\text{C}$ |
| Soldering temperature   | according to fig. 9, J-STD-020          | $T_{sd}$   | 580         | $^\circ\text{C}$ |
| Thermal resistance junction/ambient   | J-STD-051, leads 7 mm, soldered on PCB  | $R_{thJA}$ | 450         | K/W              |




Fig. 1 - Power Dissipation Limit vs. Ambient Temperature




Fig. 2 - Forward Current Limit vs. Ambient Temperature

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |   |                  |      |            |      |               |
|---|---|------------------|------|------------|------|---------------|
| PARAMETER   | TEST CONDITION  | SYMBOL           | MIN. | TYP.       | MAX. | UNIT          |
| Forward voltage   | $I_F = 20\text{ mA}$ , $t_p = 20\text{ ms}$                         | $V_F$            | 1.1  | 1.24       | 1.5  | V             |
|   | $I_F = 65\text{ mA}$ , $t_p = 20\text{ ms}$                         | $V_F$            |      | 1.35       |      | V             |
|   | $I_F = 500\text{ mA}$ , $t_p = 100\text{ }\mu\text{s}$              | $V_F$            |      | 1.8        |      | V             |
| Temperature coefficient of $V_F$  | $I_F = 1\text{ mA}$   | $TK_{V_F}$       |      | -1.5       |      | mV/K          |
| Reverse current   | $V_R = 5\text{ V}$  | $I_R$            |      |            | 10   | $\mu\text{A}$ |
| Junction capacitance  | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$ ,<br>$E = 0\text{ mW/cm}^2$ | $C_J$            |      | 21         |      | pF            |
| Radiant intensity   | $I_F = 20\text{ mA}$ , $t_p = 20\text{ ms}$                         | $I_e$            | 0.5  | 1.0        | 1.5  | mW/sr         |
|   | $I_F = 65\text{ mA}$ , $t_p = 20\text{ ms}$                         | $I_e$            |      | 3.2        |      | mW/sr         |
|   | $I_F = 500\text{ mA}$ , $t_p = 100\text{ }\mu\text{s}$              | $I_e$            |      | 20         |      | mW/sr         |
| Radiant power   | $I_F = 100\text{ mA}$ , $t_p = 20\text{ ms}$                        | $\phi_e$         |      | 35         |      | mW            |
| Temperature coefficient of radiant power  | $I_F = 100\text{ mA}$   | $TK_{\phi_e}$    |      | -0.47      |      | %/K           |
| Angle of half intensity - horizontal  |   | $\phi_h$         |      | $\pm 77.5$ |      | deg           |
| Angle of half intensity - vertical  |   | $\phi_v$         |      | $\pm 72.5$ |      | deg           |
| Peak wavelength   | $I_F = 30\text{ mA}$  | $\lambda_p$      |      | 940        |      | nm            |
| Spectral bandwidth  | $I_F = 30\text{ mA}$  | $\Delta\lambda$  |      | 25         |      | nm            |
| Temperature coefficient of $\lambda_p$  | $I_F = 30\text{ mA}$  | $TK_{\lambda_p}$ |      | 0.3        |      | nm            |
| Rise time   | $I_F = 100\text{ mA}$ , 20 % to 80 %                                | $t_r$            |      | 15         |      | ns            |
| Fall time   | $I_F = 100\text{ mA}$ , 20 % to 80 %                                | $t_f$            |      | 15         |      | ns            |

**BASIC CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 3 - Forward Current vs. Forward Voltage




Fig. 6 - Relative Radiant Intensity vs. Ambient Temperature




Fig. 4 - Relative Forward Voltage vs. Ambient Temperature




Fig. 7 - Relative Radiant Power vs. Wavelength




Fig. 5 - Radiant Intensity vs. Forward Current




Fig. 8 - Relative Radiant Intensity vs. Angular Displacement

**REFLOW SOLDER PROFILE**




Fig. 9 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020

**DRYPACK**

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

**FLOOR LIFE**

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:

Moisture sensitivity: level 3


Floor life: 168 h

Conditions:  $T_{amb} < 30\text{ }^{\circ}\text{C}$ ,  $\text{RH} < 60\%$


**DRYING**

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or label. Devices taped on reel dry using recommended conditions 192 h at  $40\text{ }^{\circ}\text{C}$  ( $+ 5\text{ }^{\circ}\text{C}$ ),  $\text{RH} < 5\%$ .

**PACKAGE DIMENSIONS** in millimeters



Recommended Footprint





Technical drawings according to DIN specification.


Drawing- No: 6.550-5327.01-4  
Issue: Prel. 26.11.2013

Not indicated tolerances  $\pm 0.1\text{ mm}$

**TAPING AND REEL DIMENSIONS** in millimeters



Drawing refers to following types: VSMB11940  
VEMD11940F



Drawing No. 9.800-5126.01-4; Issue: Prel. 23.05.2013



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.