3M Particulate Respirator 8210*Plus*, N95

Issue Date 6/20/05

3M[™] Particulate Respirator 8210*Plus*, N95 is ideal for use in work settings that involve sanding, grinding and other dusty operations.

3M's disposable respirators are designed to help provide quality, reliable worker protection that meets the varied needs of our customers who rely on consistent product performance and service. 3M's proprietary filter media and superior product construction help provide greater worker comfort which can help increase productivity.

NIOSH approved N95

• At least 95% filtration efficiency against solid and liquid aerosols that do not contain oil.* TC-84A-0007

Features

- Durable braided comfort strap is soft against skin and won't get tangled or pull on hair
- Staple-free headband attachment is comfortable in hot and cold environments
- Advanced electret charged microfibers make breathing easier and cooler, resulting in enhanced wearer comfort
- Adjustable nose clip helps create a custom fit and reduces the potential for eyewear fogging
- Soft nose foam is comfortable on the face
- Multi-layer, durable construction contributes to increased wear time



3M[™] Particulate Respirator 8210*Plus*, N95

Suggested Applications

- Grinding
- Sanding
- Sweeping
- Bagging
- Other dusty operations
- Woodworking
- Foundries







** Based on a research study done by Burke, Inc. August 2004 of safety officers and users from 30 companies that used both 3M and competitive products as part of a limited market release.

^{*} Tested against particles approximately 0.3 micron in size (mass median aerodynamic diameter) per 42 CFR 84.

8210 <i>Plus</i> Respirators Per Box	Respirators Per Case
20	160

Use For:

- Solids such as those from processing minerals, coal, iron ore, flour, and certain other substances.
- Liquid or non-oil based particles from sprays that do not also emit harmful vapors.

Do Not Use For:

Gases and vapors, including those present in paint spray operations, asbestos, arsenic, cadmium, lead, 4,4'-methylenedianiline (MDA) or sandblasting. Aerosol concentrations that exceed 10 times the OSHA PEL, or applicable exposure limits, whichever is lower. This respirator does not supply oxygen.

Important

Before using these respirators, you must determine the following:

- 1. The type of contaminant(s) for which the respirator is being selected.
- 2. The concentration level of contaminant(s).

- 3. Whether the respirator can be properly fitted on the wearer's face. Do not use with beards, on other facial hair, or other conditions that prevent a good seal between the face and the faceseal of the respirator.
- 4. Before use of these respirators, a written respiratory protection program must be implemented, meeting all the requirements of OSHA 29 CFR 1910.134, including training, medical evaluation and fit testing.

Time Use Limitation

If respirator becomes damaged, soiled, or breathing becomes difficult, leave the contaminated area immediately and dispose of the respirator.

Additional Information

This respirator contains no components made from natural rubber latex.



3M Occupational Health and Environmental Safety Division 3M Center, Building 235-2W-70

St. Paul, MN 55144-1000

Technologies



All 3M Class N95 Particulate Respirators meet NIOSH 42 CFR 84 requirements. These respirators have a minimum filter efficiency of 95%. For more information on these and other respirator products, visit www.3M.com/occsafety.

For more information, please contact:

3M Occupational Health and Environmental Safety Division (OH&ESD)

In the U.S., contact: Sales Assistance 1-800-328-1667

Technical Assistance

1-800-243-4630 Fax On Demand 1-800-646-1655

Internet www.3M.com/occsafety For other 3M products 1-800-3M HELPS

In Canada, contact:

3M Canada Ćompany, OH&ESD P.O. Box 5757 London, Ontario N6A 4T1 Sales Assistance 1-800-265-1840, ext. 6137 Technical Assistance (Canada only)

1-800-267-4414 Fax On Demand

1-800-646-1655 Internet

www.3M.com/CA/occsafety

Technical Assistance In Mexico 01-800-712-0646 5270-2255, 5270-2119 (Mexico City only) Technical Assistance In Brazil 0800-132333 Fax On Demand O.U.S. Locations 1-651-732-6530



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.