# **Detailed Specifications & Technical Data**

**ENGLISH MEASUREMENT VERSION** 



## 9355 Coax - RG-8/U Type

Picture Not Available For more Information please call

1-800-Belden1



### **General Description:**

RG-8/U type, 11 AWG stranded (7x19) BC conductor, foam polyethylene insulation, military-type braid coverage, fitted with PL-259 connectors on both ends, PVC jacket.

| Conductor AWG:  # Coax AWG Stranding Conductor Material 1  |
|--|
| Total Number of Conductors:  Insulation Insulation Material: Insulation Material: Insulation Material FPE - Foam Polyethylene  Outer Shield Material:  Type Outer Shield Material: Outer Jacket Outer Jacket Outer Jacket Material: O |
| Total Number of Conductors:  Insulation Insulation Material: Insulation Material Insul |
| Insulation Insulation Material:  Insulation Material  FPE - Foam Polyethylene  Outer Shield Outer Shield Material:  Type Outer Shield Material:  Type Outer Shield Material:  Outer Jacket Outer Jacket Outer Jacket Material:  Outer Jacket Material:  Outer Jacket Material:  Outer Jacket Material:  Outer Jacket Material  PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter:  Outer Jacket Material  PVC - Polyvinyl Chloride  Overall Cable Overall Cable Overall Nominal Diameter:  Outer Jacket Material  PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter:  Outer Jacket Material  PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter:  Outer Jacket Material  PVC - Polyvinyl Chloride  |
| Insulation Material: Insulation Material  FPE - Foam Polyethylene  Outer Shield Outer Shield Material:  Type Outer Shield Material Coverage (%) Braid   BC - Bare Copper   97  Outer Jacket Outer Jacket Material:  Outer Jacket Material:  PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Insulation Material FPE - Foam Polyethylene  Outer Shield Outer Shield Material:  Type Outer Shield Material Coverage (%) Braid   BC - Bare Copper   97  Outer Jacket Outer Jacket Material:  Outer Jacket Material PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Outer Shield Outer Shield Material:  Type Outer Shield Material Coverage (%) Braid   BC - Bare Copper   97  Outer Jacket Outer Jacket Material:  Outer Jacket Material: PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Outer Shield Material:  Type Outer Shield Material Coverage (%) Braid BC - Bare Copper 97  Outer Jacket Outer Jacket Material:  Outer Jacket Material:  PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Outer Jacket Outer Jacket Material: Outer Jacket Material: PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: Outer Jacket Material PVC - Polyvinyl Chloride  75  |
| Outer Jacket Material: Outer Jacket Material PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: Overall Nominal Diameter: Coaxial Cable Assembly Length: 75   |
| Outer Jacket Material PVC - Polyvinyl Chloride  Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Overall Cable Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Overall Nominal Diameter: 0.403 in.  Length Coaxial Cable Assembly Length: 75  |
| Length Coaxial Cable Assembly Length: 75   |
| Coaxial Cable Assembly Length: 75  |
|  |
| Applicable One Whatter and America Onesillone (Occarill)   |
| Applicable Specifications and Agency Compliance (Overall)  |
| Applicable Standards & Environmental Programs  |
| EU Directive 2011/65/EU (ROHS II): Yes   |
| EU CE Mark: Yes  |
| EU Directive 2000/53/EC (ELV): Yes   |
| EU Directive 2002/95/EC (RoHS): Yes  |
| EU RoHS Compliance Date (mm/dd/yyyy): 10/13/2005   |
| EU Directive 2002/96/EC (WEEE): Yes  |
| EU Directive 2003/11/EC (BFR): Yes   |
| CA Prop 65 (CJ for Wire & Cable): Yes  |
| MII Order #39 (China RoHS): Yes  |
| RG Type: 8/U   |
| Plenum/Non-Plenum  |
| Plenum (Y/N): No   |
| Electrical Characteristics (Overall)   |
| Other Electrical Characteristic 1: Cable is 8214. See tech data for 8214.  |
| Notes (Overall)  |
| Notes: These cables are designed to be used with two-way systems, such as Citizens Band (CB), Commercial, Amateur, and Marine equipment applications. They provide a positive link between the transmitter and antenna or between the receiver and antenna. They are capable of handling higher power requirements with lower signal losses. Packaged Individually.  |

Page 1 of 2 04-18-2017

## **Detailed Specifications & Technical Data**

#### **ENGLISH MEASUREMENT VERSION**



9355 Coax - RG-8/U Type

#### **Put Ups and Colors:**

| Item #   | Putup | Ship Weight | Color | Notes | Item Desc             |
|----------|-------|-------------|-------|-------|-----------------------|
| 9355 010 | 1 FT  | 0.457 LB    | BLACK |       | RG/U TYPE COAX W/CONN |

Revision Number: 1 Revision Date: 09-19-2008

© 2017 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its bublication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2 04-18-2017



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

## Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001:
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина,

дом 2, корпус 4, литера А.