



Features

- 3.3" x 6.2" x 1.62" Package
- Up to 425W of Air-Cooled Power, 300W Convection
- Universal Input 90-264Vac Input Range
- 5V at 2A Isolated Standby Output
- Isolated 12V Fan Output
- Inhibit, Power Fail, DC OK Signals, Remote Sense
- Approved to CSA/EN/IEC/UL60950-1, 2nd Edition
- Compliant to high levels of EMC per EN61000-4
- Meets Class B Conducted EMI with 6db margin, Class A Radiated EMI with 3db margin
- Efficiency 90% typical
- 3 Year Warranty



Description

A Superior performance 425 Watts AC to DC power supply designed for Test and Measurement and Industrial applications. Feature rich and highly efficient TU425 product family with active current share for redundant applications can easily fit in 1U chassis and provides 300 Watts for convection or 425 Watts with moving air. Input & output monitoring alarms plus isolated 12V/1A fan output and 5V/2A standby voltage are among other standard offering of TU425 family. All models are CE marked to low voltage directive and approved to ITE standards of IEC/UL/EN60950 and CSA C22.2, 2nd edition.

Model Selection

Model Number	Volts	Output Current		Efficiency ³ (Main Output)	Ripple & Noise ⁴ (mV pk-pk)	Total Regulation	OVP Threshold	MTBF ⁷
		w/200LFM air ¹	Convection ²					
TU425S12E	12V	32.2A	22.0A	88%	120mV	±3%	14.0 ± 1.1V	389,750
	5Vsb	2.0A	2.0A		100mV	±5%	5.5V – 8.0V	
	12V Fan ⁵	1.0A	0.5A		360mV	±10%	N/A	
TU425S18E	18V	21.4A	14.6A	88%	180mV	±3%	21.0 ± 2.0V	356,330
	5Vsb	2.0A	2.0A		100mV	±5%	5.5V – 8.0V	
	12V Fan ⁵	1.0A	0.5A		360mV	±10%	N/A	
TU425S24E	24V	16.8A	11.9A	90%	240mV	±3%	28.0 ± 2.5V	355,520
	5Vsb	2.0A	2.0A		100mV	±5%	5.5V – 8.0V	
	12V Fan ⁵	1.0A	0.5A		360mV	±10%	N/A	
TU425S48E	48V	8.4A	5.9A	90%	480mV	±3%	55.0 ± 4.0V	354,722
	5Vsb	2.0A	2.0A		100mV	±5%	5.5V – 8.0V	
	12V Fan ⁵	1.0A	0.5A		360mV	±10%	N/A	
TU425S56E	56V ³	7.2A	5.1A	90%	560mV	±3%	63.0 ± 4.0V	354,560
	5Vsb	2.0A	2.0A		100mV	±5%	5.5V – 8.0V	
	12V Fan ⁵	1.0A	0.5A		360mV	±10%	N/A	

- Notes:**
1. Total power with 200lfm of forced air cooling is 425W (385W for 12V model) including 12V/1A for Fan output and 5V/2A standby.
 2. Maximum convection cooled power is limited to 280W for 12V model and 300W for other models. This includes 12V/0.5A fan output and 5V/2A standby output.
 3. Efficiency values listed are typical and are measured at 115Vac input, full load output current, at an ambient temperature of 25°C.
 4. Measured at 25°C ambient with noise probe directly at end of 6" twisted pair terminated with 0.1µF ceramic and 10µF low ESR capacitors. Values will be higher at ambient temperatures below 0°C.
 5. Fan Output: If the load on this output is other than a fan, a short circuit condition on this output can only be remedied by removing both the cause of the short circuit and the load. This will allow the output to resume normal operation.
 6. No output adjustment for 56V model.
 7. MTBF values are in hours, per Telcordia 332, Issue 6, 25°C, full rated load (w/airflow) at 110Vac input.

General Specifications

AC Input	100-240Vac, ±10%, 47-63Hz, 1Ø 120-300Vdc (external fuse required for DC input)	Turn On Time (Main Output)	<u>Main output:</u> <1 sec. max @115Vac, rise time 30mS max. <u>5Vsb</u> turn-on time is 500mS max., rise time 50mS max. Output Voltage rise is monotonic.
Input Current	115Vac: 5.2A, 230Vac: 2.5A	Hold-up Time	<u>Main Output:</u> >20ms for 300W @ 120Vac/60 Hz, >16ms for 383W (90% of 425W) @ 120v/60Hz. <u>5Vsb Output:</u> >500mS
Inrush Current	264Vac, cold start: will not exceed 40Arms within ½ cycle. I ² T = 25A ² /Sec maximum	Overtemperature Protection	Sensing transformer temperature, 135°C (55°C ambient temperature at full load), auto recovery.
Input Fuses	F1, F2: 6.3A, 250Vac	Overload Protection	130 to 170% of rating, Hiccup Mode, auto recovery.
Earth Leakage Current	<750µA@264Vac, 60Hz, NC <1.5mA@264Vac, 60Hz, SFC	Short Circuit Protection	<u>Main Output & 5Vsb:</u> Cycling type, auto recovery. <u>Fan Output:</u> recovery only after removal of short and load. See note 5 on page 1.
Power Factor	>0.99 @ 115Vac, Full Load >0.95 @ 230Vac, Full Load	Overvoltage Protection	OVP latch, see chart for trip ranges. 5V standby output (latch), see chart for trip range.
Efficiency	See Model Selection Chart on page 1.	Switching Frequency	75kHz, typical
Output Power	425W continuous, with 200 lfm airflow 300W convection cooled – See chart for specific voltage model ratings.	Isolation	Input-Output: 4000Vac Input-Ground: 1800Vac Output-Ground: 1500Vdc
Transient Response	50% load step, Δi/Δt: <0.2A/µS. Max Voltage Deviation = 5%. Recover to within 1% of nominal within 500µS	Operating Temperature	-10 to 70°C. Starts up at -40°C. The unit will meet all published specifications after a warm-up period. See Application Note for operating conditions during start-up.
Ripple and Noise	0.5%rms, 1% pk-pk, see Model Selection Chart on page 1.	Temperature Derating	Derate output power linearly above 50°C to 50% at 70°C
Common Mode Noise	<u>Line Frequency:</u> <2.5Vrms @115Vac, <5Vrms@ 230Vac, 50/60Hz. See App Note for test set-up and typical graphs. For high frequency noise, consult the factory.	Storage Temperature	-40°C to +85°C
Output Voltage	See chart on page 1. Initial setpoint within 0.5% of nominal. Adjustable +/-5% from nominal (except 56V)	Altitude	Operating: up to 5000m (derating may be required above 3000m, consult factory) Non-operating: -500 to 40,000 ft.
Minimum Load	Not required for main output or 5Vsb. Fan Output: 0.5A min required on the main output in order for the 12V Fan output to be within regulation.	Relative Humidity	5% to 95%, non-condensing
Total Regulation	See Model Selection Chart on page 1.	Shock	Operating: Half-sine, 20gpk, 10ms, 3 axes, 6 shocks total Non-Operating: Half-sine, 40 gpk, 10 ms, 3 axes, 6 shocks total
Vibration	Operating: 0.003g/Hz, 1.5grms overall, 3 axes, 10 min/axis Non-Operating: 0.026g2/Hz, 5.0grms overall, 3 axes, 1 hr/axis	Safety Standards	EN/CSA/UL/IEC 60950-1, 2nd Edition
Dimensions	W: 3.3" x L: 6.2" x H: 1.62" W: 84mm x L: 157.5mm x H: 41mm	MTBF	See Model Selection Chart on page 1.
Weight	670g	E-Cap Life	7 years, based on typical operation of 12 hours/day, 261 days/year at 40°C ambient temp.

Auxiliary Signals

DC OK:	Goes HIGH when main DC output is above 90% of nominal voltage and goes LOW when the output is below 90% of rated main output DC voltage	Power Good/ Power Fail:	Signal is high within 500mS after the main output is within regulation band upon AC turn on. Goes low with 4 mS min. before the main DC output drops below 90% of nominal value when AC turns off.
Inhibit:	Logic HIGH or open = ON Logic LOW or short to ground = OFF	Fan Output:	12V @ 1 A (air cooled) or 0.5A (convection), +/-10% regulation for load change of 0.5A to FL on the main output.
Remote Sense:	Compensates for up to 0.5V voltage drop for 48V & 56V models, and 0.16V voltage drop for 12V & 24V models. Maximum deviation of 5% (main output) any 50% step above 5% load.	Current Share¹:	Active single wire, up to 4 supplies in parallel. Paralleled output voltages must be set to within 0.5% of each other. Contact Factory for details on the required set-up for proper operation.
5V Standby Output:	5V @ 2A, +/-5% regulation over all changes in main output load current.	Current Share Accuracy¹:	5% when the load current is ≥50% of the total available load current, 10% when the load current is between 25% - 49% of the total available load current. Remote sense lines must be connected to ensure accuracy.

Notes: 1. Consult Factory for proper set-up for current sharing operation.


EMI/EMC Compliance

Conducted Emissions	EN55011/CISPR22 Class B, FCC Part 15.107, Class B, 6db margin, typical.
Radiated Emissions	EN55011/CISPR22 Class A, FCC Part 15.109, Class A, 3db margin, typical.
Static Discharge Immunity	EN55024/IEC61000-4-2, Level 4, 8kV Contact Discharge, 15kV air discharge, Criteria A
Radiated RF Immunity	EN55022/IEC61000-4-3, Level 2, 3V/m, Criteria A
EFT/Burst Immunity	EN55024/IEC61000-4-4, Level 3, 2kV (PS Output), 1kV (signal outputs), Criteria A
Line Surge Immunity	EN55024/IEC61000-4-5, Level 3, 1kV diff., 2kV common-mode, Criteria A Level 4, 2kV diff., 4kV Common-mode, Criteria C
Conducted RF Immunity	EN55022/IEC61000-4-6, Level 3, 10V/m, Criteria A
Power Frequency Magnetic Field Immunity	EN55024/IEC61000-4-8, Level 3, 10A/m, Criteria A
Voltage Dip Immunity	EN55024/IEC61000-4-11, Dips: 100%, 10ms; 30%, 500ms; 60%, 100ms; Interruptions: 100%, 5000ms; Performance Criteria A, A, B & B
Line Harmonic Emissions	EN55024/IEC61000-3-2, Class A, C & D at full load (425W output).
Flicker Test	EN55024/IEC61000-3-3, Section 5

Connector Information

Input Connector J101	Main DC Output J302, J303	Fan Output J301	Signal Connector J401
PIN 1) FG PIN 2) NC PIN 3) AC Neutral PIN 4) NC PIN 5) AC Line	Term 1 – J302: (+V) Term 2 – J303: (-V)	PIN 1) 12V Fan (+) PIN 2) 12V Fan (-)	PIN 1) Remote Sense (+) Pin 6) Power Good PIN 2) Common Pin 7) +5Vsb Output PIN 3) Remote Sense (-) Pin 8) +5Vsb Output PIN 4) Current Sharing Pin 9) DC OK PIN 5) Remote Inhibit Pin 10) Common
<u>Mating Connector:</u> Tyco/AMP 640250-5 Pins: 3-770476-1	<u>Mating Connector:</u> Molex 19141-0058 19141-0063 19141-0083	<u>Mating Connector:</u> Tyco AMP 1375820-2 Pins: 1375819-1	<u>Mating Connector:</u> Molex 90142-0010 Pins: 90119-2110

Mechanical Drawing



Notes:

1. Specifications subject to change without notice.
2. All dimensions in inches (mm), tolerance is $\pm 0.02''$ (± 0.5).
3. FG is safety ground connection
4. Specifications are for convection rating at factory settings at 115 Vac input 25 °C unless otherwise stated.
5. Warranty: 3 years.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.