Lead free　Halogen free　RoHS Compliance

Metal thin film chip resistors
(the highest reliability and precision)

■URG series　　**AEC-Q200 Compliant**

Features

- The tightest resistance tolerance: +/-0.01%
- The smallest temperature coefficient of resistance: ±1ppm/℃
- Long term stability with inorganic passivation
- Thin film structure enabling low noise and anti-sulfur

Applications

- Industrial measurement, electrical scales
- High precision sensors, medical electronics

◆Part numbering system

URG 2012 L - 102 - L - T1

- URG: Series code
- 2012: Size: URG1608, URG2012, URG3216, URG5025, URG6432
- L: Temperature coefficient of resistance
- 102: Nominal resistance value (E-24: 3 digit, E-96: 4 digit, URG3216, URG5025, URG6432: all 4 digit)
- L: Resistance tolerance
- T1: Packaging quantity: T1(1,000pcs), T05(500pcs), T01(100pcs)

◆Electrical Specification

Type	Power ratings	Temperature coefficient of resistance	Resistance range(Ω) Resistance tolerance ±0.01% (L)	±0.02% (P)	±0.05% (W)	±0.1% (B)	±0.5% (D)	Maximum voltage	Resistance value series	Operating temperature	Packaging quantity
URG1608	1/16W	±1(K) *1	250 ≦R ≦7.5K	100≦R≦7.5k				100V	E24, E96	-55℃ ~ 155℃	T1
		±2(L) *2									
URG2012	1/10W	±1(K) *1	250 ≦R ≦36K	100≦R≦36k				150V			T05
		±2(L) *2									
URG3216	1/4W	±1(K) *1	250 ≦R ≦68K	100≦R≦68k				200V			T01
		±2(L) *2									
URG5025	1/2W	±1(K) *1	250 ≦R ≦100K	100≦R≦150k				300V			
		±2(L) *2									
URG6432	3/4W	±1(K) *1	250 ≦R ≦100K	100≦R≦200k				300V			
		±2(L) *2									

*1: Applicable TCR K (±1.0) at temperature range 25℃~ 65℃
Applicable TCR K (±1.5) at temperature range -20℃~ 25℃, 65℃~125℃

*2: Applicable TCR L at temperature range -20℃~ 125℃

***Contact us for requirements not listed in above table.**

◆Dimensions



Type	Size (inch)	L	W	a	b	t
URG1608	0603	1.60±0.20	0.80+0.25/−0.20	0.30±0.20	0.30±0.20	0.40+0.15/−0.10
URG2012	0805	2.00±0.20	1.25+0.25/−0.20	0.40±0.20	0.40±0.20	0.40+0.15/−0.10
URG3216	1206	3.20±0.20	1.60±0.25	0.50±0.25	0.50±0.20	0.40+0.15/−0.10
URG5025	2010	5.00±0.20	2.50±0.25	0.60±0.25	0.60±0.25	0.45±0.10
URG6432	2512	6.40+0.20/−0.40	3.20±0.25	0.75±0.25	0.80±0.20	0.45±0.20

(unit : mm)

◆Reliability specification

Test items	Condition (test methods (MIL-PRF-55342/JIS C5201-1)	Standard
Short time overload	2.5 x rated voltage,*1 5seconds	±0.02%+0.01Ω
Life (biased)	70℃, rated voltage,*1 90min on 30min off, 2000hours	±0.02%+0.01Ω(R≧250Ω)
		±0.05%+0.01Ω(R<250Ω)
High temperature high humidity	85℃, 85%RH, 1/10 of rated power, 90min on 30min off, 1000hours	±0.05%+0.01Ω
Temperature shock	-65℃ (15min) ~ 150℃ (15min) 100cycles	±0.02%+0.01Ω
High temperature exposure	155℃, no bias, 1000hours	±0.05%+0.01Ω
Resistance to soldering heat	235±5℃, 30 seconds (reflow), (by MIL-PRF-55342)	±0.01%+0.01Ω

*1 Rated voltage is given by E= $\sqrt{R \times P}$
E= rated voltage (V), R=nominal resistance value(Ω), P=rated power(W)
If rated voltage exceeds maximum voltage /element, maximum voltage/element is the rated voltage.

Metal thin film chip resistors
(the highest reliability and precision)

■URG series

◆Reliability test data

○Biased life test





○High temperature high humidity (biased)





○Temperature shock





○High temperature exposure





◆Temperature coefficient of Resistance

○URG2012





○URG3216





◆Derating Curve



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.