



Scotchmate™ and Dual Lock™ Reclosable Fasteners Mini-Packs

MP3401/02, MP3526N/27N, MP3541/42,
MP3551/52, MP3560, MP4570

Selection Guide

March, 2005

Product Description

3M™ Reclosable Fasteners offer advanced closure alternatives to zippers, screws, snaps, bolts and more. They're often better than conventional closure methods because they offer greater design flexibility, faster product assembly, smoother and cleaner exterior surfaces and improved product performance in many applications. 3M™ Scotchmate™ and Dual Lock™ Reclosable Fasteners Mini-Packs are great for design development and small volume product requirements and can be used to inexpensively test and evaluate eight most popular 3M reclosable fasteners before making a more substantial investment.

Features

- Simplifies storage and dispensing.
- Available in both plain-backed and adhesive-backed fasteners.
- Faster, easier attachment.
- Pressure-sensitive adhesive-backed versions include both general purpose synthetic rubber and 3M™ High Performance Acrylic Adhesives.

Construction

3M™ Scotchmate™ Hook and Loop Reclosable Fasteners

Product/Color	Roll Size	Qty per pkg	Description	Attachment Method
MP3401/02 white	1 in x 4.9 yds	1 hook 1 loop	Plain-back 3M™ Scotchmate™ Reclosable Fastener	Sew-on, staple or mechanical
MP3401/02 black	1 in x 4.9 yds	1 hook 1 loop	Plain-back 3M™ Scotchmate™ Reclosable Fastener	Sew-on, staple or mechanical
MP3526N/27N white	1 in x 4.9 yds	1 hook 1 loop	General Purpose Synthetic Rubber Pressure Sensitive Adhesive	Adhesive bonds well to most substrates
MP3526N/27N black	1 in x 4.9 yds	1 hook 1 loop	General Purpose Synthetic Rubber Pressure Sensitive Adhesive	Adhesive bonds well to most substrates

3M™ Dual Lock™ Reclosable Fasteners

Product/Color	Roll Size	Qty per pkg	Description	Attachment Method
MP3541/42 black with black adhesive	1 in x 4.9 yds	1 - 3541 1 - 3542	General Purpose Synthetic Rubber Pressure Sensitive Adhesive	Adhesive bonds well to most substrates
MP3551/52 black with white adhesive	1 in x 4.9 yds	1 - 3551 1 - 3552	High Performance Acrylic Foam Pressure Sensitive Adhesive	Adhesive bonds well to high surface energy substrates
MP3560 clear with clear adhesive	1 in x 4.9 yds	2 - 3560	CLEAR 3M™ Dual Lock™ High Performance Acrylic Foam Pressure Sensitive Adhesive	Adhesive bonds well to high surface energy substrates
MP4570 clear with clear adhesive	5/8 in x 10 feet	1 - 4570	CLEAR 3M™ Dual Lock™ Low Profile with Acrylic LSE Adhesive	Adhesive bonds well to low surface energy substrates

3M™ Scotchmate™ and 3M™ Dual Lock™ Reclosable Fasteners Mini-Packs

MP3401/02, MP3526N/27N, MP3541/42, MP3551/52, MP3560, MP4570

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000 - ISO/TS 16949:2002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 and ISO/TS 16949:2002 standards.



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2005 70-0709-3865-2 (3/05)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.