FAIRCHILD SEMICONDUCTOR™

June 2001

# FDT458P

## 30V P-Channel PowerTrench® MOSFET

### General Description

This P-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers, and battery chargers.


These MOSFETs feature faster switching and lower gate charge than other MOSFETs with comparable $R_{DS(ON)}$ specifications.


### Applications

- Battery chargers
- Motor drives

### Features

- 3.4 A, –30 V. $R_{DS(ON)}$ = 130 mΩ @ $V_{GS}$ = 10 V
  $R_{DS(ON)}$ = 200 mΩ @ $V_{GS}$ = 4.5 V
- Fast switching speed
- Low gate charge (2.5 nC typical)
- High performance trench technology for extremely low $R_{DS(ON)}$
- High power and current handling capability in a widely used surface mount package




## Absolute Maximum Ratings

$T_A$=25°C unless otherwise noted

| Symbol | Parameter | | Ratings | Units |
|---|---|---|---|---|
| $V_{DSS}$ | Drain-Source Voltage | | – 30 | V |
| $V_{GSS}$ | Gate-Source Voltage | | ±20 | V |
| $I_D$ | Drain Current – Continuous | (Note 1a) | 3.4 | A |
| | – Pulsed | | 10 | |
| $P_D$ | Maximum Power Dissipation | (Note 1a) | 3.0 | W |
| | | (Note 1b) | 1.3 | |
| | | (Note 1c) | 1.1 | |
| $T_J$, $T_{STG}$ | Operating and Storage Junction Temperature Range | | –55 to +150 | °C |

## Thermal Characteristics

| | | | | |
|---|---|---|---|---|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | (Note 1a) | 42 | °C/W |
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case | (Note 1) | 12 | °C/W |

## Package Marking and Ordering Information

| Device Marking | Device | Reel Size | Tape width | Quantity |
|---|---|---|---|---|
| 458P | FDT458P | 13” | 12mm | 2500 units |

©2001 Fairchild Semiconductor Corporation


## Electrical Characteristics

$T_A$ = 25°C unless otherwise noted


| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **Off Characteristics** | | | | | | |
| $BV_{DSS}$ | Drain–Source Breakdown Voltage | $V_{GS}$ = 0 V, $I_D$ = –250 µA | –30 | | | V |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D$ = –250 µA, Referenced to 25°C | | –23 | | mV/°C |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{DS}$ = –24 V, $V_{GS}$ = 0 V | | | –1 | µA |
| $I_{GSSF}$ | Gate–Body Leakage, Forward | $V_{GS}$ = –25 V, $V_{DS}$ = 0 V | | | 100 | nA |
| $I_{GSSR}$ | Gate–Body Leakage, Reverse | $V_{GS}$ = –25 V, $V_{DS}$ = 0 V | | | –100 | nA |
| **On Characteristics** (Note 2) | | | | | | |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$ = $V_{GS}$, $I_D$ = –250 µA | –1 | –1.8 | –3 | V |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate Threshold Voltage Temperature Coefficient | $I_D$ = –250 µA, Referenced to 25°C | | 4 | | mV/°C |
| $R_{DS(on)}$ | Static Drain–Source On–Resistance | $V_{GS}$ = –10 V, $I_D$ = –3.4 A<br>$V_{GS}$ = –4.5 V, $I_D$ = –2.7 A<br>$V_{GS}$=–10 V, $I_D$ =–3.4 A, $T_J$=125°C | | 105<br>157<br>147 | 130<br>200<br>210 | mΩ |
| $I_{D(on)}$ | On–State Drain Current | $V_{GS}$ = –10 V, $V_{DS}$ = –5 V | –5 | | | A |
| $g_{FS}$ | Forward Transconductance | $V_{DS}$ = –5 V, $I_D$ = –3.4 A | | 3 | | S |
| **Dynamic Characteristics** | | | | | | |
| $C_{iss}$ | Input Capacitance | $V_{DS}$ = –15 V, $V_{GS}$ = 0 V, f = 1.0 MHz | | 205 | | pF |
| $C_{oss}$ | Output Capacitance | | | 55 | | pF |
| $C_{rss}$ | Reverse Transfer Capacitance | | | 26 | | pF |
| **Switching Characteristics** (Note 2) | | | | | | |
| $t_{d(on)}$ | Turn–On Delay Time | $V_{DD}$ = –15 V, $I_D$ = –1 A, $V_{GS}$ = –10 V, $R_{GEN}$ = 6 Ω | | 4.5 | 9 | ns |
| $t_r$ | Turn–On Rise Time | | | 12.5 | 23 | ns |
| $t_{d(off)}$ | Turn–Off Delay Time | | | 11 | 20 | ns |
| $t_f$ | Turn–Off Fall Time | | | 2 | 4 | ns |
| $Q_g$ | Total Gate Charge | $V_{DS}$ = –15 V, $I_D$ = –3.4 A, $V_{GS}$ = –10 V | | 2.5 | 3.5 | nC |
| $Q_{gs}$ | Gate–Source Charge | | | 0.7 | | nC |
| $Q_{gd}$ | Gate–Drain Charge | | | 1 | | nC |
| **Drain–Source Diode Characteristics and Maximum Ratings** | | | | | | |
| $I_S$ | Maximum Continuous Drain–Source Diode Forward Current | | | | –2.5 | A |
| $V_{SD}$ | Drain–Source Diode Forward Voltage | $V_{GS}$ = 0 V, $I_S$ = –2.5 A (Note 2) | | –0.8 | –1.2 | V |

**Notes:**


**1.** $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



a) 42°C/W when mounted on a 1in$^2$ pad of 2 oz copper



b) 95°C/W when mounted on a .0066 in$^2$ pad of 2 oz copper



c) 110°C/W when mounted on a minimum pad.

**2.** Pulse Test: Pulse Width < 300µs, Duty Cycle < 2.0%

## Typical Characteristics





**Figure 1. On-Region Characteristics.**





**Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.**





**Figure 3. On-Resistance Variation with Temperature.**





**Figure 4. On-Resistance Variation with Gate-to-Source Voltage.**





**Figure 5. Transfer Characteristics.**





**Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.**

## Typical Characteristics





**Figure 7. Gate Charge Characteristics.**





**Figure 8. Capacitance Characteristics.**





**Figure 9. Maximum Safe Operating Area.**





**Figure 10. Single Pulse Maximum Power Dissipation.**





**Figure 11. Transient Thermal Response Curve.**

**Thermal characterization performed using the conditions described in Note 1c.**
**Transient thermal response will change depending on the circuit board design.**

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | |
|---|---|---|---|
| ACEx™ | FAST ® | OPTOPLANAR™ | STAR*POWER™ |
| Bottomless™ | FASTr™ | PACMAN™ | Stealth™ |
| CoolFET™ | FRFET™ | POP™ | SuperSOT™-3 |
| *CROSSVOLT*™ | GlobalOptoisolator™ | Power247™ | SuperSOT™-6 |
| DenseTrench™ | GTO™ | PowerTrench® | SuperSOT™-8 |
| DOME™ | HiSeC™ | QFET™ | SyncFET™ |
| EcoSPARK™ | ISOPLANAR™ | QS™ | TinyLogic™ |
| $E^2CMOS^{TM}$ | LittleFET™ | QT Optoelectronics™ | TruTranslation™ |
| EnSigna™ | MicroFET™ | Quiet Series™ | UHC™ |
| FACT™ | MICROWIRE™ | SILENT SWITCHER® | UltraFET ® |
| FACT Quiet Series™ | OPTOLOGIC™ | SMART START™ | VCX™ |

STAR*POWER is used under license

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

**Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|---|---|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.