



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

SMAJ5.0
THRU
SMAJ440CA

Features

- Halogen free available upon request by adding suffix "-HF"
For Surface Mount Applications
Unidirectional And Bidirectional
Low Inductance
High Temp Soldering: 260°C for 10 Seconds At Terminals
For Bidirectional Devices Add "C" To The Suffix of The Part Number: i.e.SMAJ5.0CA for 5% Tolerance
Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
UL Recognized File # E331408

Mechanical Data

- Epoxy meets UL 94 V-0 flammability rating
Moisture Sensitivity Level 1
Polarity: Indicated by cathode band except bi-directional types

Maximum Rating:

- Operating Temperature: -55°C to +175°C
Storage Temperature: -55°C to +175°C
Typical Thermal Resistance: 100°C/W Junction to Ambient

Table with 4 columns: Parameter, Symbol, Value, Note. Rows include Peak Pulse Current, Peak Pulse Power Dissipation, Steady State Power Dissipation, and Peak Forward Surge Current.

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

- 2. Non-repetitive current pulse, per Fig.3 and derated above TA=25°C per Fig.2.
3. Mounted on 5.0mm² copper pads to each terminal.
4. 8.3ms, single half sine wave duty cycle = 4 pulses per Minutes maximum.
5. Lead temperature at TL = 75°C.
6. Peak pulse power waveform is 10/1000µS.

400 Watt
Transient Voltage
Suppressors
5.0 to 440 Volts

DO-214AC
(SMA)(LEAD FRAME)



Table with 6 columns: DIM, INCHES (MIN, MAX), MM (MIN, MAX), NOTE. Lists dimensions A through H.

SUGGESTED SOLDER PAD LAYOUT



# SMAJ5.0 thru SMAJ440CA



Fig. 1-PEAK PULSE POWER RATING CURVE




Fig. 2-PULSE RATING CURVE



Fig. 3-PULSE WAVEFORM




Fig. 4-TYPICAL JUNCTION CAPACITANCE



Fig. 5-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




Fig.6-Steady State Power Derating Curve

# SMAJ5.0 thru SMAJ440CA

## ELECTRICAL CHARACTERISTICS @25°C

| MCC PART NUMBER |           | REVERSE STAND-OFF VOLTAGE $V_{WM}$ | BREAKDOWN VOLTAGE $V_{(BR)}$ @ $I_T$ (VOLTS) |      |            | MAXIMUM CLAMPING VOLTAGE @ $I_{PP}$ | PEAK PULSE CURRENT $I_{PP}$ | MAXIMUM REVERSE LEAKAGE @ $V_{WM}$ $I_D$ | MARKING CODE |    |
|-----------------|-----------|------------------------------------|--|------|------------|-------------------------------------|-----------------------------|--|--------------|----|
| UNI-POLAR       | BI-POLAR  | (VOLTS)                            | MIN  | MAX  | $I_T$ (mA) | (VOLTS)                             | (AMPS)                      | ( $\mu$ A)                               | 1            | 2  |
| SMAJ5.0A        | SMAJ5.0CA | 5.0                                | 6.40   | 7.00 | 10         | 9.2                                 | 43.5                        | 800                                      | AE           | WE |
| SMAJ6.0A        | SMAJ6.0CA | 6.0                                | 6.67   | 7.37 | 10         | 10.3                                | 38.8                        | 800                                      | AG           | WG |
| SMAJ6.5A        | SMAJ6.5CA | 6.5                                | 7.22   | 7.98 | 10         | 11.2                                | 35.7                        | 500                                      | AK           | WK |
| SMAJ7.0A        | SMAJ7.0CA | 7.0                                | 7.78   | 8.60 | 10         | 12.0                                | 33.3                        | 200                                      | AM           | WM |
| SMAJ7.5A        | SMAJ7.5CA | 7.5                                | 8.33   | 9.21 | 1          | 12.9                                | 31.0                        | 100                                      | AP           | WP |
| SMAJ8.0A        | SMAJ8.0CA | 8.0                                | 8.89   | 9.83 | 1          | 13.6                                | 29.4                        | 50                                       | AR           | WR |
| SMAJ8.5A        | SMAJ8.5CA | 8.5                                | 9.44   | 10.4 | 1          | 14.4                                | 27.7                        | 20                                       | AT           | WT |
| SMAJ9.0A        | SMAJ9.0CA | 9.0                                | 10.0   | 11.1 | 1          | 15.4                                | 26.0                        | 10                                       | AV           | WV |
| SMAJ10A         | SMAJ10CA  | 10                                 | 11.1   | 12.3 | 1          | 17.0                                | 23.5                        | 5  | AX           | WX |
| SMAJ11A         | SMAJ11CA  | 11                                 | 12.2   | 13.5 | 1          | 18.2                                | 22.0                        | 1  | AZ           | WZ |
| SMAJ12A         | SMAJ12CA  | 12                                 | 13.3   | 14.7 | 1          | 19.9                                | 20.1                        | 1  | BE           | XE |
| SMAJ13A         | SMAJ13CA  | 13                                 | 14.4   | 15.9 | 1          | 21.5                                | 18.6                        | 1  | BG           | XG |
| SMAJ14A         | SMAJ14CA  | 14                                 | 15.6   | 17.2 | 1          | 23.2                                | 17.2                        | 1  | BK           | XK |
| SMAJ15A         | SMAJ15CA  | 15                                 | 16.7   | 18.5 | 1          | 24.4                                | 16.4                        | 1  | BM           | XM |
| SMAJ16A         | SMAJ16CA  | 16                                 | 17.8   | 19.7 | 1          | 26.0                                | 15.3                        | 1  | BP           | XP |
| SMAJ17A         | SMAJ17CA  | 17                                 | 18.9   | 20.9 | 1          | 27.6                                | 14.5                        | 1  | BR           | XR |
| SMAJ18A         | SMAJ18CA  | 18                                 | 20.0   | 22.1 | 1          | 29.2                                | 13.7                        | 1  | BT           | XT |
| SMAJ20A         | SMAJ20CA  | 20                                 | 22.2   | 24.5 | 1          | 32.4                                | 12.3                        | 1  | BV           | XV |
| SMAJ22A         | SMAJ22CA  | 22                                 | 24.4   | 26.9 | 1          | 35.5                                | 11.2                        | 1  | BX           | XX |
| SMAJ24A         | SMAJ24CA  | 24                                 | 26.7   | 29.5 | 1          | 38.9                                | 10.3                        | 1  | BZ           | XZ |
| SMAJ26A         | SMAJ26CA  | 26                                 | 28.9   | 31.9 | 1          | 42.1                                | 9.5                         | 1  | CE           | YE |
| SMAJ28A         | SMAJ28CA  | 28                                 | 31.1   | 34.4 | 1          | 45.4                                | 8.8                         | 1  | CG           | YG |
| SMAJ30A         | SMAJ30CA  | 30                                 | 33.3   | 36.8 | 1          | 48.4                                | 8.3                         | 1  | CK           | YK |
| SMAJ33A         | SMAJ33CA  | 33                                 | 36.7   | 40.6 | 1          | 53.3                                | 7.5                         | 1  | CM           | YM |
| SMAJ36A         | SMAJ36CA  | 36                                 | 40.0   | 44.2 | 1          | 58.1                                | 6.9                         | 1  | CP           | YP |
| SMAJ40A         | SMAJ40CA  | 40                                 | 44.4   | 49.1 | 1          | 64.5                                | 6.2                         | 1  | CR           | YR |
| SMAJ43A         | SMAJ43CA  | 43                                 | 47.8   | 52.8 | 1          | 69.4                                | 5.7                         | 1  | CT           | YT |
| SMAJ45A         | SMAJ45CA  | 45                                 | 50.0   | 55.3 | 1          | 72.7                                | 5.5                         | 1  | CV           | YV |
| SMAJ48A         | SMAJ48CA  | 48                                 | 53.3   | 58.9 | 1          | 77.4                                | 5.2                         | 1  | CX           | YX |
| SMAJ51A         | SMAJ51CA  | 51                                 | 56.7   | 62.7 | 1          | 82.4                                | 4.9                         | 1  | CZ           | YZ |
| SMAJ54A         | SMAJ54CA  | 54                                 | 60.0   | 66.3 | 1          | 87.1                                | 4.6                         | 1  | RE           | ZE |
| SMAJ58A         | SMAJ58CA  | 58                                 | 64.4   | 71.2 | 1          | 93.6                                | 4.3                         | 1  | RG           | ZG |
| SMAJ60A         | SMAJ60CA  | 60                                 | 66.7   | 73.7 | 1          | 96.8                                | 4.1                         | 1  | RK           | ZK |
| SMAJ64A         | SMAJ64CA  | 64                                 | 71.1   | 78.6 | 1          | 103                                 | 3.9                         | 1  | RM           | ZM |
| SMAJ70A         | SMAJ70CA  | 70                                 | 77.8   | 86.0 | 1          | 113                                 | 3.5                         | 1  | RP           | ZP |
| SMAJ75A         | SMAJ75CA  | 75                                 | 83.3   | 92.1 | 1          | 121                                 | 3.3                         | 1  | RR           | ZR |
| SMAJ78A         | SMAJ78CA  | 78                                 | 86.7   | 95.8 | 1          | 126                                 | 2.2                         | 1  | RT           | ZT |
| SMAJ85A         | SMAJ85CA  | 85                                 | 94.4   | 104  | 1          | 137                                 | 2.9                         | 1  | RV           | ZV |
| SMAJ90A         | SMAJ90CA  | 90                                 | 100  | 111  | 1          | 146                                 | 2.7                         | 1  | RX           | ZX |
| SMAJ100A        | SMAJ100CA | 100                                | 111  | 123  | 1          | 162                                 | 2.5                         | 1  | RZ           | ZZ |
| SMAJ110A        | SMAJ110CA | 110                                | 122  | 135  | 1          | 177                                 | 2.3                         | 1  | SE           | VE |
| SMAJ120A        | SMAJ120CA | 120                                | 133  | 147  | 1          | 193                                 | 2.1                         | 1  | SG           | VG |
| SMAJ130A        | SMAJ130CA | 130                                | 144  | 159  | 1          | 209                                 | 1.9                         | 1  | SK           | VK |
| SMAJ150A        | SMAJ150CA | 150                                | 167  | 185  | 1          | 243                                 | 1.6                         | 1  | SM           | VM |
| SMAJ160A        | SMAJ160CA | 160                                | 178  | 197  | 1          | 259                                 | 1.5                         | 1  | SP           | VP |
| SMAJ170A        | SMAJ170CA | 170                                | 189  | 209  | 1          | 275                                 | 1.5                         | 1  | SR           | VR |
| SMAJ180A        | SMAJ180CA | 180                                | 201  | 222  | 1          | 292                                 | 1.4                         | 1  | ST           | VT |
| SMAJ200A        | SMAJ200CA | 200                                | 224  | 247  | 1          | 324                                 | 1.2                         | 1  | SV           | VV |
| SMAJ220A        | SMAJ220CA | 220                                | 246  | 272  | 1          | 356                                 | 1.1                         | 1  | SX           | VX |
| SMAJ250A        | SMAJ250CA | 250                                | 279  | 309  | 1          | 405                                 | 1.0                         | 1  | SZ           | VZ |
| SMAJ300A        | SMAJ300CA | 300                                | 335  | 371  | 1          | 486                                 | 0.8                         | 1  | TE           | UE |
| SMAJ350A        | SMAJ350CA | 350                                | 391  | 432  | 1          | 567                                 | 0.7                         | 1  | TG           | UG |
| SMAJ400A        | SMAJ400CA | 400                                | 447  | 494  | 1          | 648                                 | 0.6                         | 1  | TK           | UK |
| SMAJ440A        | SMAJ440CA | 440                                | 492  | 543  | 1          | 713                                 | 0.6                         | 1  | TM           | UM |

For bi-directional type having  $V_{rwm}$  of 10 Volts and less, the  $I_R$  limit is double.  
For parts without A, the  $V_{BR}$  is +10%.



Micro Commercial Components

### Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 5Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

[www.mccsemi.com](http://www.mccsemi.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.