

AF8

601967-1 AF8 [M22520/1-01] Crimp Tool without Turret
 2031846-1 WA27F (Pneumatic AF8) without Turret

Image representative of type only

Features:

4/8 indent Crimp to Military standard
 Ratchet mechanism ensures complete crimp cycle
 8 Position Dial select Indent Depth control
 Many Turrets available
 Ergonomic non-slip handles



AF8 - Turret

Accurately positions Contacts in the Tool

Image representative of type only

Features:

Data plate shows compatible Contacts and settings

Use in:

601967-1 - AF8 Base Tool without Turret
 2031846-1 - Pneumatic AF8 (WA27F) without Turret



| Part Number | Description | mm ² (AWG) or other |
|-------------|---|--------------------------------|
| 601967-5 | Universal Head UH2-5 [M22520/1-05] | |
| 601967-9 | Turret TH45 | 0.15 - 1.5 [26-16] |
| 601967-2 | Turret TH1A [M22520/1-02] for ARINC contacts | 0.15 - 4.0 [26-12] |
| 1-601967-2 | Single Position Head TP465 [M22520/1-11] for M39029 | 2.5 - 4.0 [14-12] |
| 601967-4 | Turret TH4 [M22520/1-03] for MS17803; MS21097; OSI2814 contacts | 0.15 - 1.5 [26-16] |
| 601967-7 | Turret TP85 [M22520/1-07] for MS18232; MS18233 contacts | RG178/U; RG196/U |
| 601967-3 | Turret TH163 [M22520/1-04] for MS27490; MS27655 | 0.2 - 4.0 [24-12] |
| 601967-8 | Turret TH199S [M22520/1-08] for MS3343; MS90460; MS90461 contacts | 0.14 - 4.0 [26-12] |
| 1-601967-6 | Turret TH502 for Multimate TYPE II Size 16 Pin Contacts | 0.03 - 2.5 [32-14] |
| 1-601967-5 | Turret TH501 for Multimate TYPE II Size 16 Socket Contact | 0.03 - 2.5 [32-14] |
| 601967-6 | Turret TP45 [M22520/1-06] for OSI2814 type M size 16 & 22 | 0.14 - 1.5 [26-16] |
| 1-601967-1 | Turret TH128 for Type II contacts | 2.5 - 4.0 [14-12] |

AFM8

601966-1 AFM8 [M22520/2-01] Crimp Tool without Positioner
2031845-1 WA22 (Pneumatic AFM8) without Positioner

Image representative of type only

Features:

4/8 indent Crimp to Military standard
Ratchet mechanism ensures complete crimp cycle
8 Position Dial select Indent Depth control
Many Positioners available
Ergonomic non-slip handles



AFM8 - Positioner

Accurately positions Contacts in the Tool

Image representative of type only

Features:

Data plate shows compatible Contacts and settings

Use in:

601966-1 [AFM8] - Base Tool without Positioner
2031845-1 [WA22] - Pneumatic version without Positioner



| Part Number | Description | mm ² (AWG) or other |
|-------------|--|---|
| 1-601966-0 | Positioner K328 | |
| 2-601966-8 | Positioner K370 for ARINC 404 COAXICON | RG316/U; 188/U □ RG179/U □ RG178/U; 196/U |
| 601966-8 | Positioner K267 [M22520/2-23] for ARINC 404 Contacts | 0.12 - 0.4 [26-22] |
| 601966-7 | Positioner K370 [M22520/2-12] for ARINC COAXICON size 15 contacts | RG178; RG179; RG188; RG196; RG316 |
| 1-601966-6 | Positioner K345 for ARINC COAXICON size 5 contacts | .141 Semi rigid; RG58C; RG180B; RG188; RG223 |
| 2-601966-6 | Positioner K397 for ARINC COAXICON size 7 contacts | RG188 |
| 1-601966-7 | Positioner K344 for ARINC COAXICON size 7 contacts | RG58C; RG188 |
| 601966-5 | Positioner K13-1 [M22520/2-08] for ARINC size 20 Contacts | 0.2 [24] |
| 601966-6 | Positioner K42 [M22520/2-09] for ARINC size 22 Pin Contacts | 0.4 - 0.3 [22-28] |
| 966254-1 | Positioner for Coaxicon MCX Straight Plugs | |
| 1-601966-5 | Positioner K287 [M22520/2-11] for M39029/1-100; 1-101; 2-105; 3-108 | 0.15 - 0.6 [26-20] |
| 2-601966-0 | Positioner K338 [M22520/2-13] for M39029/16&18 contacts | 0.03 - 0.09 [32-28] |
| 2-601966-2 | Positioner K339 [M22520/2-16] for M39029/17 contacts | 0.03 - 0.09 [32-28] |
| 1-601966-1 | Positioner K151 [M22520/2-04] for MS18232; MS18233; MS18265; MS18266 contacts | RG178/U; RG196/U |
| 1-601966-4 | Positioner K43 [M22520/2-10] for MS27490; MS27491; MS27492; MS27493; MS27494; MS27655 contacts | 0.2 - 0.6 [24-20] |
| 1-601966-3 | Positioner K40 [M22520/2-07] for MS27490; MS27655 contacts | 0.08 - 0.4 [28-22] |
| 601966-3 | Positioner K60S [M22520/2-03] for MS3343; MS90461 contacts | 0.03 - 0.4 [32-22] |
| 601966-4 | Positioner K41 [M22520/2-06] for Size 22 Socket Contacts | 0.4 - 0.3 [22-28] |
| 601966-2 | Positioner K1S [M22520/2-02] for TERMI-BLOCK contact. | 0.6 - 0.15 [20-26] |
| 1579003-1 | Positioner for TRIAD-01 | |
| 1490038-1 | Positioner K789 for Winchester 100-54020S; 100-54028S contacts | 0.06 - 0.6 [30-20] |

FT8

608668-1 - Base Tool without Positioner

Features:

4/8 indent Crimp
 Ratchet mechanism ensures complete crimp cycle
 8 Position Dial select Indent Depth control
 Ergonomic non-slip handles

Image representative of type only

| Part Number | Description | mm ² (AWG) or other |
|-------------|--|--------------------------------|
| 608668-2 | Positioner TP731 for AMPLIMITE Size 8 Use with Hand Tool 608668-1 | 1.0 - 1.5 [18-16] |

M300 BT

608651-1 - Base Tool without Positioner

Features:

4/8 indent Crimp
 Ratchet mechanism ensures complete crimp cycle
 8 Position Dial select Indent Depth control
 Ergonomic non-slip handles

Image representative of type only

| Part Number | Description | mm ² (AWG) or other |
|-------------|---|--------------------------------|
| 608651-2 | Positioner TP1151 for AMPLIMITE Size 8 Use with Hand Tool 608651-1 | 2.5 - 10.0 [14-8] |
| 608651-3 | Positioner SP858 for AMPLIMITE Size 8 Use in hand Tool 608651-2 | 6.0 - 10.0 [10-8] |

M309

2031849-1 - Base Tool without Positioner

Features:

4/8 indent Crimp
 Ratchet mechanism ensures complete crimp cycle
 8 Position Dial select Indent Depth control
 Ergonomic non-slip handles

Image representative of type only

M310

356114-1 - Base Tool without Positioner

Features:

- 4/8 indent Crimp
- Ratchet mechanism ensures complete crimp cycle
- 8 Position Dial select Indent Depth control
- Ergonomic non-slip handles

Image representative of type only



| Part Number | Description | mm ² (AWG) or other |
|-------------|---|--------------------------------|
| 356120-1 | Positioner TP1088 Use in Hand Tool 356114-1 | |
| 356336-1 | Positioner TP944 use with Hand tool 356114-1 | 2.5 - 10.0 [14-8] |
| 356119-1 | Positioner TP1068 for Type XII contacts Use in Hand Tool 356114-1 | 10.0 [8] |
| 356337-1 | Positioner TP1013 for Universal MATE-N-Lok II High Current 2mm use with Hand tool 356114-1 | 2.5 - 6.0 [14-10] |

M317

2031853-1 - Base Tool without Positioner

Features:

- 4/8 indent Crimp
- Ratchet mechanism ensures complete crimp cycle
- 8 Position Dial select Indent Depth control
- Ergonomic non-slip handles

Image representative of type only



MH860

2031850-1 - Base Tool without Positioner

Features:

- 4/8 indent Crimp to Military standard M22520/7-01
- Ratchet mechanism ensures complete crimp cycle
- 8 Position Dial select Indent Depth control
- Many Turrets available
- Ergonomic non-slip handles

Image representative of type only



| Part Number | Description | mm ² (AWG) or other |
|-------------|--|--------------------------------|
| 2031848-1 | Positioner 86-20 for M39029 Contacts Use with hand Tool 2031850-1 | 0.2 - 0.6 [24-20] |

HX4

608650-1 - Base Tool without Positioner

Features:

- Crimp to Military standard M22520/5-01
- Ratchet mechanism ensures complete crimp cycle
- Ergonomic non-slip handles

Image representative of type only



| Part Number | Description | mm ² (AWG) or other |
|-------------|---------------------------|--------------------------------|
| 2031852-1 | Die-set Y197 - M22520/5-6 | Hex .178 / .213" A/F |
| 2031851-1 | Die-set Y178 - M22520/5-6 | Hex .429" A/F |

ERGOGRIMP - Chrome

1-1105850-8 Base Tool without Die-set (pictured)

Image representative of type only

Note: This tool is not compatible with SDE Dies

Features:

Chrome plated for greater corrosion resistance.
Interchangeable Dies
Virtually a straight action jaw closure
Ratchet mechanism ensures complete crimp cycle
Easy access ratchet release
Handle pressure adjustment with locking device
Ergonomic non-slip handles

The listed Dies can be used in the same options as regular ERGOGRIMP Dies



| Part Number | Description | mm ² (AWG) or other |
|-------------|---|--------------------------------|
| 2-1105652-8 | Die-set for HS S Contacts | 10.0 & 16.0 |
| 539744-2 | Die-set for HTS HDM | 0.2 - 0.5 |
| 1-1105652-8 | Die-set for HTS HSS Contacts | 6.0 & 25.0 |
| 1-1105851-8 | Complete Tool for HTS: HE/HA; HND; HVT Contacts | 0.14 - 4.0 |
| 1-1105852-8 | Die-set for HTS: HE/HA; HND; HVT Contacts | 0.14 - 4.0 |
| 2-1105870-8 | Die-set for HTS: HSK; HSM; HSS Contacts | 4.0 - 10.0 |
| 1-1105870-8 | Die-set for HTS: HSM; HSK; HSS Contacts | 0.75 - 2.5 |
| 539668-2 | Die-set for TYPE XII Contacts | 0.2 - 1.5 |

Hydraulic Hand Tool 30 KN

1-1105653-8 Hand tool without Die-set

Image representative of type only

Features:

Lightweight Tool with rotating head
Pump action closure with low handle force
Adjustable stroke
Automatic release with audible "click"
Manual override trigger release



| Part Number | Description | mm ² (AWG) or other |
|-------------|-----------------------------------|--------------------------------|
| 5-1105653-8 | Die-set for HF Contacts | 25.0 [4] |
| 6-1105653-8 | Die-set for HF Contacts | 35.0 [2] |
| 8-1105653-8 | Die-set for HF Contacts | 70.0 [2/0] |
| 7-1105653-8 | Die-set for HF Contacts | 50.0 [1/0] |
| 3-1105653-8 | Die-set for HS S & HF Contacts | 10.0 [8] |
| 4-1105653-8 | Die-set for HS S & HF Contacts | 16.0 [6] |
| 2-1105653-8 | Die-set for HTS: HSS; HF Contacts | 6.0 [10] |

Hydraulic Hand Tool 60 KN

1110956-1 Hand tool without Die-set supplied in plastic carry case

Image representative of type only

Features:

Rotating head
Pump action closure with low handle force
Automatic release with audible "click"
Manual override trigger release



| Part Number | Description | mm ² (AWG) or other |
|-------------|---|--------------------------------|
| 1110956-5 | Die-set for HF Contacts | 120.0 [4/0] |
| 1110956-6 | Die-set for HF Contacts | 150.0mm ² |
| 1110956-7 | Tool-set comprising; 110956-1 + 1110956-2 to -6 inclusive for HF contacts | 50.0 - 150.0 [1/0-4/0] |
| 1110956-2 | Die-set for HF Contacts | 50.0 [1/0] |
| 1110956-3 | Die-set for HF Contacts | 70.0 [2/0] |
| 1110956-4 | Die-set for HF Contacts | 95.0 [3/0] |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.