

| ITEM | QTY | PART NUMBER | PART DESCRIPTION                         |
|------|-----|-------------|--|
| 1    | 1   | SLM-XXX     | Molded Self-Retaining LED Mount          |
| 2    | 1   | 5XX-F       | T1 3/4 (5mm) Flanged LED, See Page 2 & 3 |

| REV. | DESCRIPTION                                | DATE     | APPROVED |
|------|--|----------|----------|
| B    | Updated Uncut Leads                        | 06/06/08 | M. C.    |
| C    | Updated Uncut Leads Note                   | 12/24/08 | T. Y.    |
| D    | Updated P/N's on Page 2                    | 09/16/09 | T. Y.    |
| E    | Updated LED Protrusion                     | 10/19/09 | T. Y.    |
| F    | Added Low Current & 5V LED Specs on Page 3 | 06/26/16 | J. C.    |



| PART NO. | SH ( Ref.)   | H             |
|----------|--------------|---------------|
| SLM-140  | .140 (3.6mm) | .285 (7.1mm)  |
| SLM-150  | .150 (3.8mm) | .295 (7.2mm)  |
| SLM-160  | .160 (4.1mm) | .305 (7.7mm)  |
| SLM-170  | .170 (4.3mm) | .315 (8.0mm)  |
| SLM-180  | .180 (4.6mm) | .325 (8.3mm)  |
| SLM-190  | .190 (4.8mm) | .335 (8.5mm)  |
| SLM-200  | .200 (5.1mm) | .345 (8.8mm)  |
| SLM-210  | .210 (5.3mm) | .355 (9.0mm)  |
| SLM-220  | .220 (5.6mm) | .365 (9.3mm)  |
| SLM-230  | .230 (5.8mm) | .375 (9.5mm)  |
| SLM-240  | .240 (6.1mm) | .385 (9.8mm)  |
| SLM-250  | .250 (6.4mm) | .395 (10.0mm) |
| SLM-260  | .260 (6.6mm) | .405 (10.3mm) |
| SLM-270  | .270 (6.9mm) | .415 (10.5mm) |

| PART NO. | SH ( Ref.)    | H             |
|----------|---------------|---------------|
| SLM-280  | .280 (7.1mm)  | .425 (10.8mm) |
| SLM-290  | .290 (7.4mm)  | .435 (11.0mm) |
| SLM-300  | .300 (7.6mm)  | .445 (11.3mm) |
| SLM-310  | .310 (7.9mm)  | .455 (11.6mm) |
| SLM-320  | .320 (8.1mm)  | .465 (11.8mm) |
| SLM-330  | .330 (8.4mm)  | .475 (12.1mm) |
| SLM-340  | .340 (8.6mm)  | .485 (12.3mm) |
| SLM-350  | .350 (8.9mm)  | .495 (12.6mm) |
| SLM-360  | .360 (9.1mm)  | .505 (12.8mm) |
| SLM-370  | .370 (9.4mm)  | .515 (13.1mm) |
| SLM-380  | .380 (9.7mm)  | .525 (13.3mm) |
| SLM-390  | .390 (9.9mm)  | .535 (13.6mm) |
| SLM-400  | .400 (10.2mm) | .545 (13.8mm) |
| SLM-410  | .410 (10.4mm) | .555 (14.1mm) |

| PART NO. | SH ( Ref.)    | H             |
|----------|---------------|---------------|
| SLM-420  | .420 (10.7mm) | .565 (14.3mm) |
| SLM-430  | .430 (10.9mm) | .575 (14.6mm) |
| SLM-440  | .440 (11.2mm) | .585 (14.9mm) |
| SLM-450  | .450 (11.4mm) | .595 (15.1mm) |
| SLM-470  | .470 (11.9mm) | .615 (15.6mm) |
| SLM-490  | .490 (12.4mm) | .635 (16.1mm) |
| SLM-510  | .510 (13.0mm) | .655 (16.6mm) |
| SLM-530  | .530 (13.5mm) | .675 (17.1mm) |
| SLM-550  | .550 (13.8mm) | .695 (17.5mm) |
| SLM-570  | .570 (14.5mm) | .715 (18.2mm) |
| SLM-590  | .590 (15.0mm) | .735 (18.6mm) |
| SLM-610  | .610 (15.5mm) | .755 (19.2mm) |
| SLM-630  | .630 (16.0mm) | .775 (19.7mm) |
| SLM-650  | .650 (16.5mm) | .795 (20.2mm) |

| PART NO. | SH ( Ref.)    | H              |
|----------|---------------|----------------|
| SLM-670  | .670 (17.0mm) | .815 (20.7mm)  |
| SLM-690  | .690 (17.5mm) | .835 (21.2mm)  |
| SLM-710  | .710 (18.0mm) | .855 (21.7mm)  |
| SLM-730  | .730 (18.5mm) | .875 (22.2mm)  |
| SLM-750  | .750 (19.1mm) | .895 (22.7mm)  |
| SLM-770  | .770 (19.6mm) | .915 (23.2mm)  |
| SLM-790  | .790 (20.1mm) | .935 (23.7mm)  |
| SLM-810  | .810 (20.6mm) | .955 (24.3mm)  |
| SLM-830  | .830 (21.1mm) | .975 (24.8mm)  |
| SLM-850  | .850 (21.6mm) | .995 (25.3mm)  |
| SLM-870  | .870 (22.1mm) | 1.015 (25.8mm) |
| SLM-890  | .890 (22.6mm) | 1.035 (26.3mm) |

## ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

|  |       |                     |
|--|-------|---------------------|
| REVERSE VOLTAGE                              | _____ | 5V                  |
| REVERSE CURRENT ( VR=5V)                     | _____ | 100µA               |
| OPERATING TEMPERATURE RANGE                  | _____ | -25°C ~ 85°C        |
| STORAGE TEMPERATURE                          | _____ | -30°C ~ 100°C       |
| LEAD SOLDERING TEMPERATURE (1/16" FROM BODY) | _____ | 260°C for 5 Seconds |

| STANDARD TOLERANCE<br>( UNLESS OTHERWISE SPECIFIED ) |                          |
|--|--------------------------|
| DECIMALS   | ANGULAR                  |
| .X ± .1  | X° ± 1°                  |
| .XX ± .02  |                          |
| .XXX ± .010  |                          |
| DESIGNED:<br><b>D. Beckman</b>                       | DATE:<br><b>06/14/07</b> |
| CHECKED:<br><b>T. Yin</b>                            | DATE:<br><b>06/14/07</b> |

**BIVAR**®

4 THOMAS, IRVINE, CA. 92618  
TEL: (949) 951-8808 FAX: (949) 951-3974

TITLE: MOLDED, SELF-RETAINING  
T-1 3/4 (5mm) LED MOUNT ASSEMBLY

PART NO: SLMXXX5XXX REVISION: F

CAGE CODE : 32559 SHEET # 1 OF 3  
CAD GENERATED DOCUMENT. DO NOT MEASURE DRAWING.

|      |              |      |          |
|------|--------------|------|----------|
| REV. | DESCRIPTION  | DATE | APPROVED |
|      | SEE SHEET #1 |      |          |

| Assy Part No.   | Chip      |                            |               | Lens Appearance | Electro-Optical Data |     |          | Viewing Angle<br>2 θ ½<br>(Deg) | LED Part No. |
|-----------------|-----------|----------------------------|---------------|-----------------|----------------------|-----|----------|---------------------------------|--------------|
|                 | Material  | Peak Wave Length<br>λp(nm) | Emitted Color |                 | Vf (V)               |     | Iv (mcd) |                                 |              |
|                 |           |                            |               |                 | TYP                  | MAX | TYP      |                                 |              |
| <b>STANDARD</b> |           |                            |               |                 | <b>Data @ 20mA</b>   |     |          |                                 |              |
| SLMXXX5BWC      | GaN/SiC   | 430                        | BLUE          | WATER CLEAR     | 4.0                  | 4.5 | 30       | 25                              | 5BWC-F       |
| SLMXXX5BWD      | GaN/SiC   | 430                        | BLUE          | DIFFUSED        | 4.0                  | 4.5 | 15       | 40                              | 5BWD-F       |
| SLMXXX5BWT      | GaN/SiC   | 430                        | BLUE          | TINTED          | 4.0                  | 4.5 | 30       | 25                              | 5BWT-F       |
| SLMXXX5PGC      | GaP/GaP   | 555                        | PURE GREEN    | WATER CLEAR     | 2.2                  | 2.8 | 10       | 35                              | 5PGC-F       |
| SLMXXX5PGD      | GaP/GaP   | 555                        | PURE GREEN    | DIFFUSED        | 2.2                  | 2.8 | 10       | 40                              | 5PGD-F       |
| SLMXXX5PGT      | GaP/GaP   | 555                        | PURE GREEN    | TINTED          | 2.2                  | 2.8 | 10       | 35                              | 5PGT-F       |
| SLMXXX5GC       | GaP/GaP   | 568                        | GREEN         | WATER CLEAR     | 2.1                  | 2.8 | 40       | 35                              | 5GC-F        |
| SLMXXX5GD       | GaP/GaP   | 568                        | GREEN         | DIFFUSED        | 2.1                  | 2.8 | 25       | 40                              | 5GD-F        |
| SLMXXX5GT       | GaP/GaP   | 568                        | GREEN         | TINTED          | 2.1                  | 2.8 | 40       | 35                              | 5GT-F        |
| SLMXXX5YC       | GaAsP/GaP | 590                        | YELLOW        | WATER CLEAR     | 2.0                  | 2.8 | 40       | 35                              | 5YC-F        |
| SLMXXX5YD       | GaAsP/GaP | 590                        | YELLOW        | DIFFUSED        | 2.0                  | 2.8 | 25       | 40                              | 5YD-F        |
| SLMXXX5YT       | GaAsP/GaP | 590                        | YELLOW        | TINTED          | 2.0                  | 2.8 | 40       | 35                              | 5YT-F        |
| SLMXXX5HC       | GaAsP/GaP | 625                        | HE RED        | WATER CLEAR     | 2.0                  | 2.8 | 50       | 35                              | 5HC-F        |
| SLMXXX5HD       | GaAsP/GaP | 625                        | HE RED        | DIFFUSED        | 2.0                  | 2.8 | 40       | 40                              | 5HD-F        |
| SLMXXX5HT       | GaAsP/GaP | 625                        | HE RED        | TINTED          | 2.0                  | 2.8 | 50       | 35                              | 5HT-F        |
| SLMXXX5RC       | GaP/GaP   | 700                        | RED           | WATER CLEAR     | 2.1                  | 2.8 | 2        | 35                              | 5RC-F        |
| SLMXXX5RD       | GaP/GaP   | 700                        | RED           | DIFFUSED        | 2.1                  | 2.8 | 1.5      | 40                              | 5RD-F        |
| SLMXXX5RT       | GaP/GaP   | 700                        | RED           | TINTED          | 2.1                  | 2.8 | 2        | 35                              | 5RT-F        |

|   |                          |   |  |
|---|--------------------------|---|--|
| STANDARD TOLERANCE<br>(UNLESS OTHERWISE SPECIFIED)<br>±10% ALL VALUES    ANGULAR      |                          | <br><b>BIVAR</b> <sup>®</sup><br>4 THOMAS, IRVINE, CA. 92618<br>TEL: (949) 951-8808    FAX: (949) 951-3974 |  |
|  |                          |   |  |
| DESIGNED:<br><b>D. Beckman</b>  | DATE:<br><b>06/14/07</b> | <b>PART NO:</b><br>SLMXXX5XXX   |  |
| CHECKED:<br><b>T. Yin</b>   | DATE:<br><b>06/14/07</b> | <b>REVISION:</b><br>F   |  |
|   |                          | <b>CAGE CODE :</b> 32559 <b>SHEET #</b> 2 OF 3  |  |
| CAD GENERATED DOCUMENT. DO NOT MEASURE DRAWING.                                       |                          |   |  |

|      |              |      |          |
|------|--------------|------|----------|
| REV. | DESCRIPTION  | DATE | APPROVED |
|      | SEE SHEET #1 |      |          |

| Assy Part No.      | Chip        |                                      |               | Lens Appearance | Electro-Optical Data |     |          | Viewing Angle<br>2 $\theta$ 1/2<br>(Deg) | LED Part No. |
|--------------------|-------------|--------------------------------------|---------------|-----------------|----------------------|-----|----------|--|--------------|
|                    | Material    | Peak Wave Length<br>$\lambda_p$ (nm) | Emitted Color |                 | Vf (V)               |     | Iv (mcd) |  |              |
|                    |             |                                      |               |                 | TYP                  | MAX | TYP      |  |              |
| <b>LOW CURRENT</b> |             |                                      |               |                 | <b>Data @ 2mA</b>    |     |          |  |              |
| SLMXXX5BWDL        | GaN/SiC     | 430                                  | BLUE          | DIFFUSED        | 3.8                  | 4.2 | 4        | 40                                       | 5BWDL-F      |
| SLMXXX5GDL         | GaP/GaP     | 568                                  | GREEN         | DIFFUSED        | 2.1                  | 2.6 | 4        | 40                                       | 5GDL-F       |
| SLMXXX5YDL         | GaAsP/GaP   | 590                                  | YELLOW        | DIFFUSED        | 2.0                  | 2.6 | 4        | 40                                       | 5YDL-F       |
| SLMXXX5ADL         | GaAsP/GaP   | 605                                  | AMBER         | DIFFUSED        | 2.0                  | 2.6 | 4        | 40                                       | 5ADL-F       |
| SLMXXX5HDL         | GaAsP/GaP   | 625                                  | HE RED        | DIFFUSED        | 2.0                  | 2.6 | 5        | 40                                       | 5HDL-F       |
| SLMXXX5SRDL        | GaAlAs/GaAs | 645                                  | RED           | DIFFUSED        | 1.7                  | 2.3 | 6        | 40                                       | 5SRDL-F      |

| Assy Part No. | Chip      |                                      |               | Lens Appearance | Electro-Optical Data |     |          | Viewing Angle<br>2 $\theta$ 1/2<br>(Deg) | LED Part No. |
|---------------|-----------|--------------------------------------|---------------|-----------------|----------------------|-----|----------|--|--------------|
|               | Material  | Peak Wave Length<br>$\lambda_p$ (nm) | Emitted Color |                 | Vf (V)               |     | Iv (mcd) |  |              |
|               |           |                                      |               |                 | TYP                  | MAX | TYP      |  |              |
| <b>5 VOLT</b> |           |                                      |               |                 | <b>Data @ 5V</b>     |     |          |  |              |
| SLMXXX5BWD5V  | GaN/SiC   | 430                                  | BLUE          | DIFFUSED        | -                    | 5.0 | 15       | 40                                       | 5BWD5V-F     |
| SLMXXX5GD5V   | GaP/GaP   | 568                                  | GREEN         | DIFFUSED        | -                    | 5.0 | 25       | 40                                       | 5GD5V-F      |
| SLMXXX5YD5V   | GaAsP/GaP | 590                                  | YELLOW        | DIFFUSED        | -                    | 5.0 | 25       | 40                                       | 5YD5V-F      |
| SLMXXX5AD5V   | GaAsP/GaP | 605                                  | AMBER         | DIFFUSED        | -                    | 5.0 | 25       | 40                                       | 5AD5V-F      |
| SLMXXX5HD5V   | GaAsP/GaP | 625                                  | HE RED        | DIFFUSED        | -                    | 5.0 | 30       | 40                                       | 5HD5V-F      |
| SLMXXX5RD5V   | GaP/GaP   | 700                                  | RED           | DIFFUSED        | -                    | 5.0 | 1.5      | 40                                       | 5RD5V-F      |

|   |  |   |  |
|---|--|---|--|
| STANDARD TOLERANCE<br>(UNLESS OTHERWISE SPECIFIED)<br>$\pm$ 10% ALL VALUES    ANGULAR |  | <br><b>BIVAR</b> <sup>®</sup><br>4 THOMAS, IRVINE, CA. 92618<br>TEL: (949) 951-8808    FAX: (949) 951-3974 |  |
| DESIGNED:<br><b>D. Beckman</b>  |  |   |  |
| CHECKED:<br><b>T. Yin</b>   |  | DATE:<br><b>06/14/07</b>  | TITLE: MOLDED, SELF-RETAINING<br>T-1 3/4 (5mm) LED MOUNT ASSEMBLY<br>PART NO: <b>SLMXXX5XXX</b><br>CAGE CODE : <b>32559</b> SHEET # <b>3 OF 3</b><br>CAD GENERATED DOCUMENT. DO NOT MEASURE DRAWING. |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.