# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



# AX101748 Faceplates and Panels - MediaFlex Plate, Single gang







For more Information please call

1-800-Belden1



### **General Description:**

Suitable Applications:

MediaFlex Plate, Single gang

### Usage (Overall)

Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400, 1200, Fiber and Coax.

Related Parts: Compatible with MediaFlex Inserts

### **Physical Characteristics (Connectivity)**

#### **Dimensions**

Dimensions:

Height (in.) Width (in.) Depth (in.) 4.500 3.020 0.455

### **Materials**

Materials:

**Description Material** Plastic - UL94V-0 Plate

### Color

Color: Black

#### Weight

Weight: 0.100 lbs

### **Included Parts**

**Included Parts:** windows, paper, 6-32 screws, installation guide

# **Packaging**

Packaging: Individually packaged in a suitable plastic bag

# **Mechanical Characteristics (Connectivity)**

-40°C To +70°C Storage Temperature Range: Installation Temperature Range: -10°C To +60°C -10°C To +60°C **Operating Temperature Range:** 

### Applicable Specifications and Agency Compliance (Overall)

### **Applicable Standards & Environmental Programs**

EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): EUP 50 Safety Listing: ACA, Bi-national Standard Listed Suitability Suitability - Indoor: Yes

### Notes (Overall)

Notes: For proper installation refer to Installation Guide PX102063 included with the product or visit our web site at http://www.belden.com

# **Product Family**

#### Part Numbers:

ddescription	Gray	Almond	Elec. White	Black
MediaFlex Plate Single Gang				AX101748
MediaFlex Plate Double Gang	AX101869	AX101870	AX101871	AX101872

## **Put Ups and Colors:**

Putup Ship Weight Color Notes Item De
---------------------------------------

Page 1 of 2

# **Detailed Specifications & Technical Data**





# AX101748 Faceplates and Panels - MediaFlex Plate, Single gang

AX101748	1 EA	0.062 LB	MEDIAFLEX SINGLE-	

Revision Number: 0 Revision Date: 05-29-2009

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

## Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001:
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина,

дом 2, корпус 4, литера А.