

CHEMTRONICS

Technical Data Sheet

TDS # DEL1681

Pow-R-Wash™ Delta

Electronics Contact Cleaner

PRODUCT DESCRIPTION

Pow-R-Wash™ Delta electronics contact cleaner is a highly efficient and effective solvent cleaner for electrical and electronic components and assemblies. This cleaning agent is both nonflammable, and engineered to be compatible with most metals and plastics found in electronic assemblies. This material can be used on energized equipment, is fast drying and has excellent solvency for oil, grease, dirt.


- Rapidly cleans dirt, oils, carbon, grease and other contaminants
- Nonflammable
- Excellent material compatibility
- Displaces moisture
- Evaporates fast
- Leaves no residues
- Enhances electrical signal
- Low toxicity
- Available with All-Way Spray valve

TYPICAL APPLICATIONS

Pow-R-Wash™ Delta effectively cleans and degreases:

- Printed Circuit Boards
- Circuit Breakers
- Electrical Motors
- Potentiometers
- Contacts and Relays
- Motors and Generators
- Selector Switches
- Solenoids

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

| | |
|---|---|
| Boiling Point | 99°F (Initial) |
| Evaporation Rate (butyl acetate=1) | >1 |
| Flash Point (TCC) | None |
| Appearance | Clear, Colorless Liquid |
| Odor | Ethereal |
| Specific Gravity | 1.30 |
| Vapor Pressure @68°F | 51 mmHg |
| Solubility in Water | Negligible |
| Dielectric Breakdown (ASTM D-877) | 30 kV |
| Surface Tension (dynes/cm @ 73°F) | 15 |
| Kauri Butanol Number | 60 |
| VOC* Content: | <u>Aerosol</u> |
| CARB | 73% |
| SCAQMD | 695 g/L |
| Federal | 56% |
| RoHS Compliant |  |
| Shelflife | 5 years |

*Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s).

COMPATIBILITY

Pow-R-Wash™ Delta has excellent compatibility with most materials used in the electronics industry. With any cleaning agent, compatibility with substrate should be determined on a non-critical area prior to use.

| <u>Material</u> | <u>Compatibility</u> |
|------------------------|-----------------------------|
| ABS | Not Recommended |
| Buna-N | Not recommended |
| EPDM | Good |
| Graphite | Excellent |
| HDPE | Good |
| Kynar™ | Good |
| LDPE | Good |
| Lexan™ | Good |
| Neoprene | Good |
| Noryl® | Good |
| Nylon™ 66 | Excellent |
| Cross-Linked PE | Good |
| Polypropylene | Good |
| Polystyrene | Not Recommended |
| PVC | Excellent |
| Silicone Rubber | Good |
| Teflon™ | Good |
| Viton™ | Not Recommended |

| Performance | |
|---|-------------|
| Grease & Lubricating Oil Removal per gram solvent (mg) | |
| Pow-R-Wash Delta | 12.4 |
| AK225-based Cleaner | 8.4 |

USAGE INSTRUCTIONS

For commercial use only.

Read MSDS carefully prior to use.

Spray 4-6 inches from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away dirt and dissolved oil and grease. For precise application use attached extension tube.

AVAILABILITY

DEL1681 12 oz. Aerosol

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

| ENVIRONMENTAL IMPACT DATA | | | |
|----------------------------------|------|-----|------|
| HCFC-141b | 0.0% | HFC | 49% |
| HCFC-225 | 0.0% | nPB | 0.0% |

HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. HCFC-141b is no longer produced in the US under this legislation. HCFC-225 is phased out for production as of 2015. Hydrofluorocarbons (HFCs) are not currently regulated.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Chemtronics® is a registered trademark of Chemtronics. All rights reserved. Pow-R-Wash™ is a trademark of Chemtronics. All rights reserved. All other trademarks herein are trademarks or registered trademarks of their respective owners.

CHEMTRONICS

8125 COBB CENTER DRIVE

KENNESAW, GA 30152

1-770-424-4888

REV. A (01/15)

| <u>DISTRIBUTED BY:</u> |
|-------------------------------|
| |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.