

## SNS1PF Drop Connectors - Snap-N-Seal Environmentally Sealed F Male Connectors



For more Information  
please call

1-800-Belden1



### Description:

Snap-N-Seal Environmentally Sealed F Male Connectors, Compression F

### Usage (Overall)

**Suitable Applications:** Broadband, CATV

### Physical Characteristics (Connectivity)

#### Product Family:

Part Number	Cable Type	Description	Post I.D. (in.)	Hex Nut Size (in.)	Inner Pack	Sleeve I.D. (in.)	Sleeve Color	Outer Pack	Tool
SNS1P11	RG-11	for Series 11 Cable	0.295	0.563	20	0.400	Black	240	SNSUNI, CST596711, L3011B, CST596711MV
716SNS1P11	RG-11	7/16 in. Nut for Series 11 Cable	0.295	0.438	20	0.400	Black	240	SNSUNI, CST596711, L3011B, CST596711MV
SNS1P59	RG-59	One-Piece Compression Connector	0.154	0.438	50	0.253	Orange	1000	SNSUTL, IT1000, CST596, CST596711
SNS1P59QS	RG-59 Quad Shield	One-Piece Compression Connector	0.154	0.438	50	0.275	Green	1000	SNSUTL, IT1000, CST596, CST596711
SNS1P59HEC	RG-59	One-Piece Compression Connector	0.154	0.438	50	0.290	White	1000	SNSUTL, IT1000, CST596, CST596711
SNS1P6	RG-6	One-Piece Compression Connector	0.191	0.438	50	0.290	Blue	1000	SNSUTL, IT1000, CST596, CST596711
SNS1P6QS	RG-6 Quad Shield	One-Piece Compression Connector	0.161	0.438	50	0.315	Violet	1000	SNSUTL, IT1000, CST596, CST596711

**Connector Type:** F Male One-Piece Compression

**Nut:** NiTin Plated Brass

**Collar:** NiTin Plated Brass

**Post:** Tin-Plated Brass

**Precision Terminal:** Tin-Plated Brass

**Precision Contact:** Tin-Plated Beryllium Copper

**O-Rings:** Ethylene Propylene

**Sleeve:** Thermoplastic Polymer

### Mechanical Characteristics (Connectivity)

**Cable Insertion Force (Max./lbs.):** 30

**Cable Retention Force:** 40 lbs. min. per ANSI/SCTE 99 2004

**Temperature Rating:** -40°C To +60°C, -40°F To +140°F

**Salt Fog:** Passes 1000 hours ANSI/SCTE 143 2007

**Moisture Migration:** Passes ANSI/SCTE 60 2004

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**EU Directive 2002/95/EC (RoHS):** Yes

**EU RoHS Compliance Date (mm/dd/yyyy):** 11/25/2008

## SNS1PF Drop Connectors - Snap-N-Seal Environmentally Sealed F Male Connectors

### Electrical Characteristics (Overall)

<b>Return Loss (typical):</b>	>=-27 dB up to 1 GHz
<b>Insertion Loss:</b>	<=-0.18 dB up to 1 GHz
<b>RFI Shielding (typical):</b>	-85 dB (60 percent Bonded Foil)

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 08-26-2011

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.