


# ConnectCore™ 9P



Compact high-performance 32-bit NET+ARM processor module family combines superior performance and design integration flexibility with complete embedded software platform support.



## Features/Benefits

- 240-pin core processor module in compact 60 x 44 mm form factor
- Powerful 32-bit NET+ARM processor
  - NS9750/9360 with ARM926EJ-S core
- Up to 128 MB Flash / 128 MB RAM
- On-board 10/100 Ethernet MAC/PHY
- Up to 4 high-speed serial ports
  - UART and SPI configurations
- USB host and device mode support
- Fast-mode I<sup>2</sup>C hardware interface
- On-chip LCD controller (TFT/STN)
- Integrated Real-Time Clock
  - w/support for external battery backup
- Up to 73 shared GPIO port options
- External memory bus interface
- PCI v2.2/Cardbus option (NS9750)
- Complete development platform support offers software design flexibility
  - NET+OS®, LxNETES™ Linux and Microsoft® Windows® CE 5.0

## Overview

The ConnectCore 9P modules are part of the ConnectCore embedded core processor module family combining superior performance and a complete set of integrated peripherals and component connectivity options in a compact and versatile form factor.

Built on leading NetSilicon® 32-bit NET+ARM technology, the network-enabled ConnectCore 9P family provides a modular and scalable core processor solution that significantly minimizes software and hardware design risk and dramatically improves the time-to-market aspects of your product development process.

The wide range of available embedded software platform options makes it the ideal choice for your network-enabled product solutions, whether your application requires the small footprint, fast response time, and secure networking offered by our ThreadX®-based NET+OS environment, the comprehensive and scalable set of feature-complete high-level software components and applications of Microsoft Windows CE, or the flexibility and power of the open Linux environment and its extensive software library.

Complete and royalty-free development kits supporting the NET+OS, LxNETES Linux, and Microsoft Windows CE environments are available for platform evaluation and product development use. All development kits include a development board, hardware debugging options, board support packages, sample code, documentation, cables, and related accessories.



# Features/Specifications

## HARDWARE

### ConnectCore 9P 9750

- 32-bit NET+ARM (ARM926EJ-S) high-performance RISC processor NS9750 @ 200 MHz
- Up to 128 MB NAND Flash and 64 MB SDRAM
  - Standard population 32 MB Flash and 16 MB RAM
- Integrated 32-bit PCI v2.2/Cardbus Bridge (33 MHz)
- 16 General Purpose Timers/Counters
- Up to 50 GPIO port options

### ConnectCore 9P 9360

- 32-bit NET+ARM (ARM926EJ-S) high-performance RISC processor NS9360 @ 177 MHz
- Up to 128 MB NAND Flash and 128 MB SDRAM
  - Standard population 32 MB Flash and 32 MB RAM
- 8 General Purpose Timers/Counters or 4 PWM functions
- Up to 73 GPIO port options

### ConnectCore 9P Family

- Integrated 10/100 Mbps Ethernet MAC/PHY
- Up to four serial interfaces w/UART and SPI mode
- Integrated USB 2.0 compliant host/device interface
  - Full speed (12 Mbps) and low speed (1.5 Mbps) mode
- On-chip I<sup>2</sup>C bus interface (100/400 kHz)
- Flexible LCD controller with support for TFT/STN displays
  - Up to SVGA resolution with up to 18/24 bpp
- External memory bus interface
  - 32-bit data bus and 28-bit address bus
- Real-Time Clock (RTC) w/support for external battery backup
- 8 KB serial EEPROM for configuration storage
- On-board JTAG interface

## DEVELOPMENT KITS

- NET+OS 6.1
  - Hardware debugger
  - GNU development tool chain
    - gcc v3.2.1, Insight v5.1.1
    - binutils v2.13.1, newlib v1.11.0
  - ThreadX™ RTOS
  - Fusion™ TCP/IP stack
    - DNS, SNMPv2, LDAP, POP, SMTP, PPP, FTP, SNTP, Telnet, FastIP, Fast Sockets, Multi-Homing
  - Universal IP address assignment
    - Static IP, DHCP, BOOTP, Auto-IP
  - Allegro embedded web server
  - SSL/TLS with DES/3DES/AES encryption
  - Flash/RAM file system with wear-leveling
  - SMIcng SNMP MIB compiler
  - Micro XML SAX parser
- Microsoft Windows CE 5.0
  - Complete BSP (Board Support Package) for Microsoft Windows CE 5.0 w/source code
    - Boot loader (U-Boot)
    - On-chip Ethernet
    - USB Host
    - Display driver (LCD)
    - Touch Screen
    - PCI
- LxNETES 3.1
  - Linux kernel v2.6.11
  - GNU development tool chain
    - gcc v3.3.3, gdb v6.2
    - uClibc v0.9.26, Busybox v1.00 pre-built
  - File system support for JFFS2 and NFS
  - I<sup>2</sup>C, USB, PCI, EEPROM support
  - BOA single-tasking HTTP server

All development kits provide sample code and documentation, development board with hardware support for Ethernet, RS232, USB, CAN bus, audio, LCD, touch screen, Mini PCI, CompactFlash, and a power supply.

## MODEL.....PART NUMBERS

| Model                                                                       | North America | International |
|-----------------------------------------------------------------------------|---------------|---------------|
| CC9P 9750 NET+OS 6.1 Development Kit                                        | FS-9053       | FS-9053       |
| CC9P 9750 LxNETES 3.1 Development Kit with 5.7" LCD (TFT) and touch screen  | FS-9033       | FS-9033       |
| CC9P 9750 Microsoft Windows CE 5.0 Kit with 5.7" LCD (TFT) and touch screen | FS-9034       | FS-9034       |
| CC9P 9360 LxNETES 3.1 Development Kit with 5.7" LCD (TFT) and touch screen  | FS-9065       | FS-9065       |
| CC9P 9360 Microsoft Windows CE 5.0 Kit with 5.7" LCD (TFT) and touch screen | FS-9066       | FS-9066       |

Please contact us for additional part number information or visit our website.

## ENVIRONMENTAL

- Storage temperature:
  - 50° C to +125° C (-58° F to +257° F)
- Operating temperature:
  - 0° C to +70° C (+32° F to +158° F)
- Relative humidity:
  - 5% to 90% (non-condensing)
- Altitude: 12,000 feet (3658 meters)

## POWER REQUIREMENTS

### ConnectCore 9P 9750

- 3.3VDC @ 600 mA (max)

### ConnectCore 9P 9360

- 3.3VDC @ 400 mA (max)


## ETHERNET INTERFACE

- Standard: IEEE 802.3
- Physical layer: 10/100Base-T
- Data rate: 10/100 Mbps (auto-sensing)
- Mode: Full or half duplex (auto-sensing)


## DIMENSIONS

- Length: 2.362 in (6.0 cm)
- Width: 1.732 in (4.4 cm)
- Height: 0.395 in (1.0 cm)

Bottom View



Side View



All measurements in millimeter



## DIGI SERVICE AND SUPPORT

You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. <http://support.digi.com>

**Digi International**  
11001 Bren Road E.  
Minnetonka, MN 55343, USA  
PH: 877-912-3444  
952-912-3444  
FX: 952-912-4952  
Email: [info@digi.com](mailto:info@digi.com)  
[www.digi.com](http://www.digi.com)

**Digi International GmbH**  
Joseph-von-Fraunhofer Str. 23  
D-44227 Dortmund  
Germany  
PH: +49-231-9747-0  
FX: +49-231-9747-111  
[www.digi.de](http://www.digi.de)

**Digi International (HK) Ltd.**  
Suite 1703-05, 17/F., K Wah Centre  
191 Java Road  
North Point, Hong Kong  
PH: +852-2833-1008  
FX: +852-2572-9989  
[www.digi.cn](http://www.digi.cn)

**FS Forth-Systeme GmbH**  
Kueferstrasse 8  
79206 Breisach  
Germany  
PH: +49 7667 908-0  
FX: +49 7667 908-200  
Email: [sales@fsforth.de](mailto:sales@fsforth.de)  
[www.fsforth.de](http://www.fsforth.de)

**Sistemas Embebidos S.A.**  
Calvo Sotelo 1 - 1° Dcha  
E-26003 Logroño  
(La Rioja) - España  
PH: +34 941 27 00 60  
FX: +34 941 23 77 70  
Email: [sistemas@embebidos.com](mailto:sistemas@embebidos.com)  
[www.embebidos.com](http://www.embebidos.com)

**NetSilicon**  
411 Waverley Oaks Road #304  
Waltham, MA 02452, USA  
PH: 800-243-2333  
781-647-1234  
FX: 781-893-1338  
Email: [info@netsilicon.com](mailto:info@netsilicon.com)  
[www.netsilicon.com](http://www.netsilicon.com)

© 2005 Digi International Inc.

Digi, Digi International, the Digi logo, the Making Device Networking Easy logo, ConnectCore, FS Forth, the FS Forth A Digi International company logo, NetSilicon, NET+Works, NET+, NET+OS, and LxNETES are trademarks or registered trademarks of Digi International, Inc in the United States and other countries worldwide. ARM and NET+ARM are trademarks of ARM Limited. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.

91001351  
A1/805



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.