

## PRODUCT BRIEF

Intel® SSD D5-P4320  
Data Center, PCI Express\*



# Intel® QLC 3D NAND SSD with PCIe\* Large, Affordable Capacity. Reliable Storage.

**Intel delivers the industry's first PCIe\* QLC 3D NAND SSD for the Data Center<sup>1</sup> – a new generation of large, affordable, and reliable drives**



The Intel® SSD D5-P4320 delivers big, affordable, and reliable storage to the warm data tier. With 33% more bits per cell than TLC,<sup>2</sup> the D5-P4320 drives will enable 3x storage consolidation<sup>3</sup> compared to hard disk drives (HDDs), leading to lower operational costs. As the industry's first PCIe\*-enabled QLC drive for the data center, the D5-P4320 provides the ability to scale to large capacities and deliver the performance needed for storage workload requirements.

### **Store More: Big Capacities Store Massive Quantities of Data**

Aerial density describes how many bits of data are stored in a given square millimeter of storage media. The Intel® SSD D5-P4320 with QLC technology offers an aerial density advantage of 33% more bits per cell than the prior generation of Intel® 3D NAND. The result? Higher capacity, cost-effective PCIe drives optimized for read-intensive storage workloads. The D5-P4320 is currently available in a U.2 form factor with 7.68TB capacity. Available for limited deployments is the larger capacity 15.36TB Intel® SSD D5-P4326 in the U.2 and EDSFF\* "Ruler" form factors, making them ideal for bulk storage requirements.

### **Save More: High Density Reduces Operational Cost**

Today's data center storage often relies on a mix of HDD and SSD technologies. The Intel® SSD D5-P4320 delivers high capacity and lower operational cost for the capacity or "warm" data storage layer traditionally served by hybrid or HDD arrays. With its higher density, Intel® QLC SSDs means fewer drives to support, power and cool. In addition QLC SSDs have a lower annual failure rate, which further reduces costs.

### **Do More: PCIe Accelerates Workloads at Large Capacities**

All QLC-enabled SSDs are not created equal. In addition to massive capacities, the D5-P4320 is built on the PCIe\* interface, which delivers higher maximum performance than the SATA interface. The D5-P4320 SKUs allow for much denser systems while enabling performance per TB to continue scaling well beyond SATA-based QLC SSDs. The Intel® QLC SSDs, when combined with Intel® Optane™ technology, accelerate the speed of frequently accessed data, at the price and capacity of massive storage.


### **Backed by Intel Experience and Innovation**

Intel brings longstanding expertise and leadership in data management to address the capacity and performance issues of today's data centers. Prepare for the future with Intel® QLC SSDs with PCIe, backed by Intel's technology and manufacturing leadership.

### Features At-a-Glance

Model	Intel® SSD D5-P4320
Capacity and Form Factor	U.2 2.5" (15mm): 7.68 TB
NAND Flash Memory	64-layer, Intel® QLC 3D NAND
Interface	PCIe Gen3.1 x 4
Bandwidth	Sequential R/W up to 3200/1000 MB/s
	Random R/W up to 427K/36K IOPS
Annualized Failure Rate	≤ 0.44%
Endurance Rating	Sequential write up to 12.3 PBW
	Random write up to 2.8 PBW
Power Consumption	Active: 15W
	Idle: ~5w Enhanced power-loss data protection
Operating Temperature	0° C – 70° C SMART temperature
Warranty	5-year limited warranty

For more up-to-date product specifications, visit [ark.intel.com](http://ark.intel.com)



Learn more now at [intel.com/ssd](http://intel.com/ssd)

1. Based on Intel achieving PRQ status of Intel® SD D5-P4320 on July 13, 2018
2. 33% more bits per cell. TLC (tri-level cell) contains 3 bits per cell and QLC (quad level cell) contains 4 bits per cell. Calculated as  $(4-3)/3 = 33\%$  more bits per cell.
3. Consolidate storage footprint up to 3x. Based on 4TB 3.5" HDD - [WD Gold TB Enterprise class 7200 RPM](#) SSD configuration based on 7.68TB Intel® D5-P4320 QLC SSD: 3 2U nodes per 1PB - 1,106TB total using 144 7.68TB D5-P4320 SSDs; 48 2.5" SSDs per 2U node using 2.5" U.2 from factor; 3 2U nodes for 6U total. HDD configuration based on 4TB 3.5" HDD: - 10 2U nodes per 1PB - 960TB total based on 24 3.5" HDDs per 2U. Note that 4TB HDDs are used in this comparison as we are targeting "warm" storage meaning that a certain capacity is needed, but performance is also important and 4TB HDDs perform much better than larger capacity HDDs.

Performance results are based on testing as of June 24, 2018 and may not reflect all publicly available security updates. See configuration disclosure for details. No product or component can be absolutely secure.

Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit [www.intel.com/benchmarks](http://www.intel.com/benchmarks).

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Performance varies depending on system configuration. Check with your system manufacturer or retailer or learn more at [intel.com/ssd](http://intel.com/ssd).

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

Intel and the Intel logo are trademarks of Intel Corporation in the U.S. and/or other countries.

\*Other names and brands may be claimed as the property of others.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Intel:](#)

[SSDPE2NV076T801](#) [SSDPE2NV076T810](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.