



Type A Plug 1



Type A Plug 2

USB 3.0 Type A Plug
Industrial IP67,
Plastic Version or
Metallized Plastic Version
Bayonet Locking Type

USB 3.0 Type A Plug
Industrial IP67,
Plastic Version or
Metallized Plastic Version
Bayonet Locking Type

NOTES:

1. Electrical Specifications:

- Meets USB 3.0 specifications
- Low level Contact Resistance:
- 30 mOhm max for VBUS and GND Contacts
- 50 mOhm max for all other contacts
- Insulation Resistance 1000 MOhm min.
- Current Rating: 2A max. @ 25°C
- DWV: 500V AC/60s Pin to Pin; 1000V AC/60s Pin to shell
- Connector Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Coupling Ring: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
- Plug Housing: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
- Interfacial Seal: Silicone, Color: White
- Cable Gland: PA (Black) or Brass, Nickel Plated
- Cable Gland Seal: NBR, Color: Black
- Cable Gland Insert (Metal Version): Nylon, Color: White
- USB Insulator: PBT, UL 94V-0, Color: Blue
- USB Metal Shell: SPCC, Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated
- USB Insulator: PBT +GF, UL94 V-0, Color: Blue

- 3. Cable:** UL AWM 2725, 2 x (Shielded Twist Pair AWG28 + Drain Wire)
+ 2 x Unshielded AWG28 + 2 x AWG24 + Drain Wire, Overall Braid Shield;
Outer Jack PVC, OD: 6.0 mm Color: Blue

- 4. IP67 & IP68 rated when covered or fully mated with the appropriated mating connectors**

© © Pin Assignment

Plug 1	Wire Map	Plug 2
p1	----- Red	----- p1
p2	----- White	----- p2
P3	----- Green	----- P3
P4	----- Black	----- P4
P5	----- Blue	----- P8
P6	----- Yellow	----- P9
P7	---- Drain Wire --	P7
P8	----- Purple	----- P5
P9	----- Orange	----- P6
Shell	----- Braid	----- Shell

RoHS Compliant

L	Part Number	
	Plastic Version	Metallized Plastic Version
0.3 ± 0.03 m	17-240091	17-240171
0.5 ± 0.05 m	17-240101	17-240181
0.75 ± 0.05 m	17-240111	17-240191
1 ± 0.10 m	17-240121	17-240201
2 ± 0.10 m	17-240131	17-240211
3 ± 0.10 m	17-240141	17-240221

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: N/A	Dim. in
	Name	Title	Approval Date	0 PLC ±0.58	1 PLC ±0.38		Autodesk Inventor Title: IP67 & IP68 USB Patch Cord USB 3.0 Type A Plug to USB 3.0 Type A Plug	Material: See Notes
				2 PLC ±0.25	3 PLC ±0.10			
				ANGLES ±.7				
	d	1 x d	Aug/16/2017	Vincent Ke	2015	Date	Name	Drawing No.: 17K1A578 Part No.: SEE P/N ABOVE
c	2 x c	Aug/08/2017	Vincent Ke	Draw.	Oct. 28	Vincent Ke		
b	1 x b	Jan/21/2016	Vincent Ke	Appd.	Oct. 28	Thomas Koch		
a	original							
Rev.	Changes	Date	Name					



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.