



Type A Plug 1



Type A Plug 2

USB 3.0 Type A Plug
Industrial IP67,
Plastic Version or
Metallized Plastic Version
Bayonet Locking Type

USB 3.0 Type A Plug
Industrial IP67,
Plastic Version or
Metallized Plastic Version
Bayonet Locking Type

NOTES:

1. Electrical Specifications:

- Meets USB 3.0 specifications
- Low level Contact Resistance:
- 30 mOhm max for VBUS and GND Contacts
- 50 mOhm max for all other contacts
- Insulation Resistance 1000 MOhm min.
- Current Rating: 2A max. @ 25°C
- DWV: 500V AC/60s Pin to Pin; 1000V AC/60s Pin to shell
- Connector Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Coupling Ring: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
- Plug Housing: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
- Interfacial Seal: Silicone, Color: White
- Cable Gland: PA (Black) or Brass, Nickel Plated
- Cable Gland Seal: NBR, Color: Black
- Cable Gland Insert (Metal Version): Nylon, Color: White
- USB Insulator: PBT, UL 94V-0, Color: Blue
- USB Metal Shell: SPCC, Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated
- USB Insulator: PBT +GF, UL94 V-0, Color: Blue

3. Cable: UL AWM 2725, 2 x (Shielded Twist Pair AWG28 + Drain Wire)
+ 2 x Unshielded AWG28 + 2 x AWG24 + Drain Wire, Overall Braid Shield;
Outer Jack PVC, OD: 6.0 mm Color: Blue

4. IP67 & IP68 rated when covered or fully mated with the appropriated mating connectors

Pin Assignment

Plug 1	Wire Map	Plug 2
p1	----- Red	----- p1
p2	----- White	----- p2
P3	----- Green	----- P3
P4	----- Black	----- P4
P5	----- Blue	----- P8
P6	----- Yellow	----- P9
P7	----- Drain Wire	----- P7
P8	----- Purple	----- P5
P9	----- Orange	----- P6
Shell	----- Braid	----- Shell

RoHS Compliant

L	Part Number	
	Plastic Version	Metallized Plastic Version
0.3 ± 0.03 m	17-240091	17-240171
0.5 ± 0.05 m	17-240101	17-240181
0.75 ± 0.05 m	17-240111	17-240191
1 ± 0.10 m	17-240121	17-240201
2 ± 0.10 m	17-240131	17-240211
3 ± 0.10 m	17-240141	17-240221

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:		Tolerance Unless otherwise specified			Scale: N/A	Dim. in	
	Name	Title	Approval Date	0 PLC ±0.58 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±.3		Autodesk Inventor	Material: See Notes	
				2015	Date	Name	Title: IP67 & IP68 USB Patch Cord USB 3.0 Type A Plug to USB 3.0 Type A Plug	
				Draw.	Oct. 28	Vincent Ke		
			Appd.	Oct. 28	Thomas Koch	Drawing No.: 17K1A578 Part No.: SEE P/N ABOVE		
d	1 x d	Aug/16/2017	Vincent Ke	Norm				DIN A3
c	2 x c	Aug/08/2017	Vincent Ke	D-old		Sheet 1/1		
b	1 x b	Jan/21/2016	Vincent Ke					
a	original							
Rev.	Changes	Date	Name					



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.