Miniature Rotary DIP Switch
A6K/A6KS

Miniature (7.2 × 7.2mm size) Rotary DIP Switch

- Mounting space reduced by 50%. (compared with conventional models)
- SMT and through hole type Available. Side-actuated type available.
- Gold-plated contacts ensure high reliability.
- RoHS Compliant



Ordering Information

■ Through hole type

3 × 3 Terminal, tube packaging			Top-actuated flat	Top-actuated extended shaft	Side-actuated flat	Side-actuated extended shaft
Output code	No. of positions	Quantity per tube				
BCD 1-2-4-8	10	Top: 63 Side: 60	A6K-102RF	A6K-102RS	A6KV-102RF	A6KV-102RS
BCD Hexadecimal 1-2-4-8	16		A6K-162RF	A6K-162RS	A6KV-162RF	A6KV-162RS

5 × 2 Terminal, tube packaging			Top-actuated flat	Top-actuated extended shaft	Side-actuated flat	Side-actuated extended shaft
Output code	No. of positions	Quantity per tube				
BCD 1-2-4-8	10	Top: 63 Side: 60	A6K-104RF	A6K-104RS	A6KV-104RF	A6KV-104RS
BCD Hexadecimal 1-2-4-8	16		A6K-164RF	A6K-164RS	A6KV-164RF	A6KV-164RS

■ SMT type

3 × 3 Terminal, tube packaging			Top-actuated flat	Top-actuated extended shaft
Output code	No. of positions	Quantity per tube		
BCD 1-2-4-8	10	63	A6KS-102RF	A6KS-102RS
BCD Hexadecimal 1-2-4-8	16		A6KS-162RF	A6KS-162RS

5 × 2 Terminal, tube packaging			Top-actuated flat	Top-actuated extended shaft	Side-actuated flat	Side-actuated extended shaft
Output code	No. of positions	Quantity per tube				
BCD 1-2-4-8	10	63	A6KS-104RF	A6KS-104RS	A6KSV-104RF	A6KSV-104RS
BCD Hexadecimal 1-2-4-8	16		A6KS-164RF	A6KS-164RS	A6KSV-164RF	A6KSV-164RS

3 × 3 Terminal Embossed taping Packages		Top-actuated flat		Top-actuated extended shaft	
Output code	No. of positions	Quantity per reel		Quantity per reel	
BCD 1-2-4-8	10	1450	**A6KS-102RF-P**	850	**A6KS-102RS-P**
BCD Hexadecimal 1-2-4-8	16		**A6KS-162RF-P**		**A6KS-162RS-P**

5 × 2 Terminal Embossed taping Packages		Top-actuated flat		Top-actuated extended shaft		Side-actuated flat		Side-actuated extended shaft	
Output code	No. of positions	Quantity per reel		Quantity per reel		Quantity per reel		Quantity per reel	
BCD 1-2-4-8	10	1450	**A6KS-104RF-P**	850	**A6KS-104RS-P**	750	**A6KSV-104RF-P**	750	**A6KSV-104RS-P**
BCD Hexadecimal 1-2-4-8	16		**A6KS-164RF-P**		**A6KS-164RS-P**		**A6KSV-164RF-P**		**A6KSV-164RS-P**

Specifications

■ Characteristics

Switching capacity		25 mA at 24 VDC
Minimum permissible load		10 μA at 3.5 VDC
Contact resistance		200 mΩ max.
Insulation resistance		100 MΩ min. (at 250 VDC)
Dielectric strength		250 VAC for 1 min between terminals
Operating torque		200 g-cm max. (1.96×10^{-2} N·m max.)
Vibration resistance	**Malfunction durability**	10 to 55 Hz, 1.5-mm double amplitude
Shock resistance	**Malfunction durability**	300 m/s^2 min.
Ambient operating temperature		–30 to 80°C at 60% max. (with no icing or condensation)
Ambient operating humidity		35% to 95% (at 5 to 35°C)
Electrical service life		20,000 steps min.
Weight (See note 2.)	**Through hole terminal**	Top-actuated, flat: Approx. 0.4 g, Side-actuated, flat: Approx. 0.7 g
	SMT terminal	Top-actuated, flat: Approx. 0.4 g, Side-actuated, flat: Approx. 0.4 g

Note: **1.** Data shown are of initial value.
2. Add 0.03 g for the extended-shaft version of each model.

■Output Codes

10-position Models

Type	BCD 1-2-4-8			
Terminal No. / Position	1	2	4	8
0				
1	●			
2		●		
3	●	●		
4			●	
5	●		●	
6		●	●	
7	●	●	●	
8				●
9	●			●

16-position Models

Type	BCD/hexadecimal 1-2-4-8			
Terminal No. / Position	1	2	4	8
0				
1	●			
2		●		
3	●	●		
4			●	
5	●		●	
6		●	●	
7	●	●	●	
8				●
9	●			●
A		●		●
B	●	●		●
C			●	●
D	●		●	●
E		●	●	●
F	●	●	●	●

Note: "●" indicates that the internal switch is ON.

Dimensions

Note: 1. All units are in millimeters unless otherwise indicated.
2. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions.

■ Through hole type

Top-actuated Flat Models with 3×3 Terminal Arrangement
A6K-102RF
A6K-162RF



Top-actuated Extended shaft Models with 3×3 Terminal Arrangement
A6K-102RS
A6K-162RS



Side-actuated Flat Models with 3×3 Terminal Arrangement
A6KV-102RF
A6KV-162RF



Side-actuated Extended-shaft Models with 3×3 Terminal Arrangement
A6KV-102RS
A6KV-162RS



Top-actuated Flat Models with 5×2 Terminal Arrangement
A6K-104RF
A6K-164RF



Top-actuated Extended shaft Models with 5×2 Terminal Arrangement
A6K-104RS
A6K-164RS



Side-actuated Flat Models with 5×2 Terminal Arrangement
A6KV-104RF
A6KV-164RF



Side-actuated Extended-shaft Models with 5×2 Terminal Arrangement
A6KV-104RS
A6KV-164RS



■ SMT type

Top-actuated Flat Models with 3×3 Terminal Arrangement
A6KS-102RF
A6KS-162RF



Top-actuated Extended shaft Models with 3×3 Terminal Arrangement
A6KS-102RS
A6KS-162RS



Top-actuated Flat Models With 5×2 Terminal Arrangement
A6KS-104RF
A6KS-164RF



Top-actuated Extended shaft Models with 5×2 Terminal Arrangement
A6KS-104RS
A6KS-164RS



Side-actuated Flat Models with 5×2 Terminal Arrangement
A6KSV-104RF
A6KSV-164RF



Side-actuated Extended-shaft Models with 5×2 Terminal Arrangement
A6KSV-104RS
A6KSV-164RS



■ Internal Connections

Top-actuated

3x3 Terminal Arrangement
Through hole type and SMT type



5x2 Terminal Arrangement
Through hole type and SMT type



Note: 3x3 internal diagram applies to both top and side actuated models

Side-actuated

5x2 Terminal Arrangement
Through hole type



5x2 Terminal Arrangement
SMT type



■ PCB Cutout Dimensions (Top View)

3×3 Terminal Arrangement

Through hole (Top-actuated Models)



Through hole (Side-actuated Models)



SMT (Top-actuated Models)



5×2 Terminal Arrangement

Through hole (Top-actuated Models)



Through hole (Side-actuated Models)



SMT (Top-actuated Models)



SMT (Side-actuated Models)



Through hole: Pattern prohibited area

All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON ELECTRONIC COMPONENTS LLC
55 E. Commerce Drive, Suite B
Schaumburg, IL 60173
847-882-2288

OMRON ON-LINE
Global - http://www.omron.com
USA - http://www.components.omron.com

Cat. No. X303-E-1 11/10 Specifications subject to change without notice Printed in USA

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.