Description

The GM78L00 series in positive voltage regulators are cost effective devices to provide a simple solution for a wide variety of application, which requires a regulated supply of up to 100mA

These virtually indestructible positive voltage regulators are protected by thermal shut down and internal current limiting. Most applications require no external components.


The GM78L00 is very versatile, which can be used as fixed voltage regulators in a wide range of application, including both local and on-card regulation for elimination of noise and distribution problems associated with single-point regulation. They can also be used with power pass elements to make high current voltage regulators.

The GM78L00 series offer impressive performance advantages over traditional zener diode and resistor combinations, provide lower output impedance and reduced quiescent current.

Features


- **Maximum output current up 100mA**
- **Fixed output voltage options: 5V, 6V, 8V, 9V, 10V, 12V, 15V, 18V and 24V**
- **No external components required**
- **Internal thermal overload protection**
- **Internal short circuit current limiting**
- **Available in TO-92, SOT-89 and SOP-8 packages**

Typical Application Circuit




Marking Information and Pin Configurations (Top View)


TO-92



SOT-89



SO-8



VV: Output Voltage Codes (05: 5.0V, …12:12V)
A: Assembly/Test Site Code
Y: Year
WW: Week


Ordering Information

Ordering Number	V_{OUT}	Package	Shipping
GM78L**00**T92B	**00** = 5.0V 6.0V 8.0V 9.0V 10.0V 12.0V 15.0V 18.0V 24.0V	TO-92	1,000 Units/ESD Bag
GM78L**00**T92RL		TO-92	2,000 Units/Ammo Pack (Tape)
GM78L**00**ST89R		SOT-89	1,000 Units/Tape and Reel
GM78L**00**S8T		SO-8	100 Units/Tube
GM78L**00**S8R		SO-8	2,500 Units/Tape & Reel

Absolute Maximum Ratings

PARAMETER		SYMBOL	RATINGS	UNITS
Input Voltage	GM78L05 to GM78L10	V_{IN}	30	V
	GM78L12 to GM78L18		35	
	GM78L24		40	
Operating Ambient Temperature		T_A	- 40 to 125	°C
Storage Temperature		T_{stg}	- 60 to 150	°C

Block Diagram



GM78L05 Electrical Characteristics (V_I = 10V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	4.8	5.0	5.2	V
	I_O =1mA to 40mA V_I = 7V to 20V	0°C to 125°C	4.75	5.0	5.25	
	I_O = 1mA to 70mA		4.75	5.0	5.25	
Input Regulation	V_I = 7V to 20V	25°C		32	150	mV
	V_I = 8V to 20V			26	100	
Ripple Rejection	V_I = 8V to 18V, f = 120KHz	25°C	41	49		dB
Output Regulation	I_O = 1mA to 100mA	25°C		15	60	mV
	I_O = 1mA to 40mA			8	30	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		42		μV
Bias Current		25°C		3.8	6	mA
		125°C			5.5	
Bias Current Change	V_I = 8V to 20V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L06 Electrical Characteristics (V_I = 11V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	5.75	6.0	6.25	V
	I_O =1mA to 40mA V_I = 8V to 20V	0°C to 125°C	5.70	6.0	6.30	
	I_O = 1mA to 70mA		5.70	6.0	6.30	
Input Regulation	V_I = 8V to 20V	25°C		35	175	mV
	V_I = 9V to 20V			29	125	
Ripple Rejection	V_I = 9V to 18V, f = 120KHz	25°C	10	18		dB
Output Regulation	I_O = 1mA to 100mA	25°C		16	80	mV
	I_O = 1mA to 40mA			9	40	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		46		μV
Bias Current		25°C		3.9	6	mA
		125°C			5.5	
Bias Current Change	V_I = 9V to 20V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L08 Electrical Characteristics (V_I = 14V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	7.7	8.0	8.3	V
	I_O =1mA to 40mA V_I = 10.5V to 23V	0°C to 125°C	7.6	8.0	8.4	
	I_O = 1mA to 70mA		7.6	8.0	8.4	
Input Regulation	V_I = 10.5V to 23V	25°C		42	175	mV
	V_I = 11V to 23V			36	125	
Ripple Rejection	V_I = 13V to 23V, f = 120KHz	25°C	37	46		dB
Output Regulation	I_O = 1mA to 100mA	25°C		18	80	mV
	I_O = 1mA to 40mA			10	40	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		54		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4	6	mA
		125°C			5.5	
Bias Current Change	V_I = 11V to 23V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L09 Electrical Characteristics (V_I = 16V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	8.6	9.0	9.4	V
	I_O =1mA to 40mA V_I = 12V to 24V	0°C to 125°C	8.55	9.0	9.45	
	I_O = 1mA to 70mA		8.55	9.0	9.45	
Input Regulation	V_I = 12V to 24V	25°C		45	175	mV
	V_I = 13V to 24V			40	125	
Ripple Rejection	V_I = 15V to 25V, f = 120KHz	25°C	38	44		dB
Output Regulation	I_O = 1mA to 100mA	25°C		19	90	mV
	I_O = 1mA to 40mA			11	40	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		58		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.1	6	mA
		125°C			5.5	
Bias Current Change	V_I = 13V to 24V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L10 Electrical Characteristics (V_I = 17V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	9.6	10	10.4	V
	I_O =1mA to 40mA V_I = 13V to 25V	0°C to 125°C	9.5	10	10.5	
	I_O = 1mA to 70mA		9.5	10	10.5	
Input Regulation	V_I = 13V to 25V	25°C		51	175	mV
	V_I = 14V to 24V			42	125	
Ripple Rejection	V_I = 15V to 25V, f = 120KHz	25°C	38	44		dB
Output Regulation	I_O = 1mA to 100mA	25°C		20	90	mV
	I_O = 1mA to 40mA			11	40	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		62		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.2	6	mA
		125°C			5.5	
Bias Current Change	V_I = 14V to 25V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L12 Electrical Characteristics (V_I = 19V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	11.5	12	12.5	V
	I_O =1mA to 40mA V_I = 14V to 27V	0°C to 125°C	11.4	12	12.6	
	I_O = 1mA to 70mA		11.4	12	12.6	
Input Regulation	V_I = 14.5V to 27V	25°C		55	250	mV
	V_I = 16V to 27V			49	200	
Ripple Rejection	V_I = 16V to 27V, f = 120KHz	25°C	37	42		dB
Output Regulation	I_O = 1mA to 100mA	25°C		22	100	mV
	I_O = 1mA to 40mA			13	50	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		70		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.3	6.5	mA
		125°C			6	
Bias Current Change	V_I = 16V to 27V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L15 Electrical Characteristics (V_I = 23V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	14.4	15	15.6	V
	I_O =1mA to 40mA V_I = 17.5V to 30V	0°C to 125°C	14.25	15	15.75	
	I_O = 1mA to 70mA		14.25	15	15.75	
Input Regulation	V_I = 17.5V to 30V	25°C		65	300	mV
	V_I = 19V to 30V			58	250	
Ripple Rejection	V_I = 18.5V to 28.5V, f = 120KHz	25°C	34	39		dB
Output Regulation	I_O = 1mA to 100mA	25°C		25	150	mV
	I_O = 1mA to 40mA			15	75	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		82		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.6	6.5	mA
		125°C			6	
Bias Current Change	V_I = 19V to 30V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L18 Electrical Characteristics (V_I = 26V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	17.3	18	18.7	V
	I_O =1mA to 40mA V_I = 20.5V to 33V	0°C to 125°C	17.1	18	18.9	
	I_O = 1mA to 70mA		17.1	18	18.9	
Input Regulation	V_I = 20.5V to 33V	25°C		70	360	mV
	V_I = 22V to 33V			64	300	
Ripple Rejection	V_I = 21.5V to 31.5V, f = 120KHz	25°C	32	36		dB
Output Regulation	I_O = 1mA to 100mA	25°C		27	180	mV
	I_O = 1mA to 40mA			19	90	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		89		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.7	6.5	mA
		125°C			6	
Bias Current Change	V_I = 22V to 33V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

GM78L24 Electrical Characteristics (V_I = 32V, I_O = 40mA unless otherwise noted)

Parameter	Test Condition		Min	Typ	Max	Unit
Output Voltage		25°C	23	24	25	V
	I_O =1mA to 40mA V_I = 26.5V to 39V	0°C to 125°C	22.8	24	25.2	
	I_O = 1mA to 70mA		22.8	24	25.2	
Input Regulation	V_I = 26.5V to 39V	25°C		95	480	mV
	V_I = 29V to 39V			78	400	
Ripple Rejection	V_I = 21.5V to 31.5V, f = 120KHz	25°C	32	36		dB
Output Regulation	I_O = 1mA to 100mA	25°C		41	240	mV
	I_O = 1mA to 40mA			28	120	
Output Noise Voltage	F = 10Hz to 100KHz	25°C		97		μV
Dropout Voltage		25°C		1.7		V
Bias Current		25°C		4.8	6.5	mA
		125°C			6	
Bias Current Change	V_I = 26V to 39V	0°C to 125°C			1.5	mA
	I_O = 1mA to 40mA				0.1	

Typical Performance Characteristics




Figure 1. Dropout Characteristics




Figure 2. Dropout Voltage vs. Junction Temperature




Figure 3. Input Bias Current vs. Input Voltage






Figure 4. Maximum Average Power Dissipation vs. Ambient Temperature TO-92 Package

Package Outline Dimensions – SOT 89




Package Outline Dimensions – TO 92



Dimensions are in millimeters

Package Outline Dimensions – SO 8



Ordering Number

GM	78L	05	T92	B
APM Gamma Micro	Circuit Type	Output Voltages	Package Type	Shipping Type
		05: 5.0V 06: 6.0V 08: 8.0V 09: 9.0V 10: 10V 12: 12V 15: 15V 18: 18V 24: 24V	T92: TO-92 ST89: SOT-89 S8: SO-8	B: Bag RL: Ammo Pack (Tape) T: Tube R: Tape & Reel

Note:

Pb-free products:

- RoHS compliant and compatible with the current require-ments of IPC/JEDEC J-STD-020.
- Suitable for use in Pb-free soldering processes with 100% matte tin (Sn) plating.

Green products:

- Lead-free (RoHS compliant)
- Halogen free(Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight)


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.