

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications



Type 947C series uses the most advanced metallized film technology for long life, high reliability in DC Link applications. This series delivers high capacitance, high voltage and high ripple current handling capabilities required for inverters used in wind, solar, fuel cell applications and more.

Highlights

- Non-polar dielectric
- Dry, resin filled
- High reliability and life expectancy
- Replacement for aluminum electrolytic capacitors (lower capacitance, higher current)
- High current to 100 Amps
- Low ESR
- Low Inductance

Specifications

| | |
|---|---|
| Capacitance Range | 110 to 1500 μ F |
| Capacitance Tolerance | \pm 10% standard, \pm 5% optional |
| Rated Voltage | 800 to 1300 Vdc |
| Operating Temperature Range | -40 °C to 85 °C (ambient) |
| Maximum rms Current | see data tables |
| Maximum rms Voltage | 230 Vac |
| Test Voltage between Terminals @ 25 °C | 150% rated DC voltage for 10 s |
| Test Voltage between Terminals & Case @ 25 °C | 4 kVac @ 50/60 Hz for 60 s |
| Life Test | 5000 h @ 85 °C, rated voltage |
| Life Expectancy | 200,000 h @ 60 °C, rated voltage |
| Reliability | 100 FIT typical (medium size capacitor) |
| Standards | IEC 61071, IEC 61881 |
| RoHS Compliant | |

Dimensions

Construction Details

| | |
|-------------------|--------------------------------|
| Case Material | Aluminum with Black PVC Sleeve |
| Resin Material | Dry Resin UL94V-0 |
| Terminal Material | Tin Plated Brass |






Figure 1



Figure 2




Figure 3

All Shown with Optional M12 x 1.75 THD Stud

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

Part Numbering System

| | | | | | | | | |
|-------------|----------------------|------------------|-----------------------|-------------------|-------------------|----------------------|------------------------|-----------------|
| 947C | 361 | K | 801 | C | A | M | S | - NS |
| Type | Capacitance | Tolerance | Voltage | Diameter D | Height H | Terminal | Mounting | Sleeving |
| 947C | 361 = 360 µF | K = ±10 % | 801 = 800 Vdc | C = 90 mm | T = 85 mm | I = M5 Insert | blank = no stud | Specify -NS |
| | 731 = 730 µF | J = ±5 % | 901 = 900 Vdc | B = 85 mm | A = 97 mm | Threaded | S = M12 Stud | for Bare Can |
| | 152 = 1500 µF | | 102 = 1000 Vdc | D = 116 mm | B = 120 mm | M = M8 Stud | Threaded | |
| | | | 112 = 1100 Vdc | | G = 140 mm | Threaded | | |
| | | | 122 = 1200 Vdc | | C = 145 mm | H = M6 Insert | | |
| | | | 132 = 1300 Vdc | | L = 165 mm | Threaded | | |
| | | | | | D = 170 mm | | | |

Ratings

NOTE: Other ratings, sizes and performance specifications are available. Contact us.

| Part Number | Rated | Can | Can | Lead | Current | | Thermal Resistance | | | | | | Mass (kg) | Fig |
|-----------------|-------------|------------------|-----------------|---------------|----------------|------------------------------|--------------------|--------------|--------------|------------|------------|-----|-----------|-----|
| | Cap. C (µF) | Voltage Vr (Vdc) | Diameter D (mm) | Height H (mm) | Spacing S (mm) | Case Area (mm ²) | ΔT = 40 Irms (A) | Typ ESR (mΩ) | Typ ESL (nH) | Θcc (°C/W) | Θca (°C/W) | | | |
| 947C311K801BTHS | 310 | 800 | 85 | 85 | 31.7 | 34000 | 61 | 1.9 | 29 | 2.9 | 3.4 | 0.6 | 3 | |
| 947C341K801CTMS | 340 | 800 | 90 | 85 | 45.0 | 36800 | 66 | 1.7 | 29 | 2.8 | 3.1 | 0.7 | 1 | |
| 947C341K801CTIS | 340 | 800 | 90 | 85 | 45.0 | 36800 | 66 | 1.7 | 29 | 2.8 | 3.1 | 0.7 | 2 | |
| 947C361K801CAMS | 360 | 800 | 90 | 97 | 45.0 | 40100 | 65 | 1.9 | 33 | 3.0 | 2.9 | 0.9 | 1 | |
| 947C361K801CAIS | 360 | 800 | 90 | 97 | 45.0 | 40100 | 65 | 1.9 | 33 | 3.0 | 2.9 | 0.9 | 2 | |
| 947C381K801BAHS | 380 | 800 | 85 | 97 | 31.7 | 37300 | 61 | 2.0 | 33 | 2.7 | 3.1 | 0.7 | 3 | |
| 947C411K801CAMS | 410 | 800 | 90 | 97 | 45.0 | 40100 | 65 | 1.9 | 33 | 2.7 | 2.9 | 0.7 | 1 | |
| 947C411K801CAIS | 410 | 800 | 90 | 97 | 45.0 | 40100 | 65 | 1.9 | 33 | 2.7 | 2.9 | 0.7 | 2 | |
| 947C491K801CBMS | 490 | 800 | 90 | 120 | 45.0 | 46700 | 59 | 2.6 | 41 | 2.6 | 2.5 | 1.0 | 1 | |
| 947C491K801CBIS | 490 | 800 | 90 | 120 | 45.0 | 46700 | 59 | 2.6 | 41 | 2.6 | 2.5 | 1.0 | 2 | |
| 947C511K801BBHS | 510 | 800 | 85 | 120 | 31.7 | 43400 | 59 | 2.5 | 41 | 2.3 | 2.6 | 0.8 | 3 | |
| 947C561K801CBMS | 560 | 800 | 90 | 120 | 45.0 | 46700 | 64 | 2.3 | 41 | 2.3 | 2.5 | 0.9 | 1 | |
| 947C561K801CBIS | 560 | 800 | 90 | 120 | 45.0 | 46700 | 64 | 2.3 | 41 | 2.3 | 2.5 | 0.9 | 2 | |
| 947C601K801CCMS | 600 | 800 | 90 | 145 | 45.0 | 53700 | 58 | 3.1 | 49 | 2.2 | 2.1 | 1.2 | 1 | |
| 947C601K801CCIS | 600 | 800 | 90 | 145 | 45.0 | 53700 | 58 | 3.1 | 49 | 2.2 | 2.1 | 1.2 | 2 | |
| 947C621K801DTHS | 620 | 800 | 116 | 85 | 50.0 | 52100 | 103 | 1.0 | 35 | 2.1 | 2.2 | 1.1 | 3 | |
| 947C651K801BGHS | 650 | 800 | 85 | 140 | 31.7 | 48700 | 59 | 2.9 | 49 | 2.0 | 2.4 | 0.9 | 3 | |
| 947C701K801CCMS | 700 | 800 | 90 | 145 | 45.0 | 53700 | 63 | 2.7 | 49 | 2.0 | 2.1 | 1.1 | 1 | |
| 947C701K801CCIS | 700 | 800 | 90 | 145 | 45.0 | 53700 | 63 | 2.7 | 49 | 2.0 | 2.1 | 1.1 | 2 | |
| 947C731K801CDMS | 730 | 800 | 90 | 170 | 45.0 | 60800 | 58 | 3.5 | 58 | 1.9 | 1.9 | 1.3 | 1 | |
| 947C731K801CDIS | 730 | 800 | 90 | 170 | 45.0 | 60800 | 58 | 3.5 | 58 | 1.9 | 1.9 | 1.3 | 2 | |
| 947C751K801DAHS | 750 | 800 | 116 | 97 | 50.0 | 56500 | 101 | 1.1 | 40 | 2.1 | 2 | 1.2 | 3 | |
| 947C791K801BDHS | 790 | 800 | 85 | 170 | 31.7 | 56700 | 59 | 3.3 | 58 | 1.7 | 2 | 1.1 | 3 | |
| 947C851K801CDMS | 850 | 800 | 90 | 170 | 45.0 | 60800 | 63 | 3.0 | 58 | 1.7 | 1.9 | 1.2 | 1 | |
| 947C851K801CDIS | 850 | 800 | 90 | 170 | 45.0 | 60800 | 63 | 3.0 | 58 | 1.7 | 1.9 | 1.2 | 2 | |
| 947C102K801DBHS | 1000 | 800 | 116 | 120 | 50.0 | 64900 | 97 | 1.3 | 50 | 2.0 | 1.8 | 1.4 | 3 | |
| 947C122K801DCHS | 1200 | 800 | 116 | 145 | 50.0 | 74000 | 92 | 1.6 | 60 | 1.9 | 1.6 | 1.7 | 3 | |
| 947C152K801DLHS | 1500 | 800 | 116 | 165 | 50.0 | 81300 | 93 | 1.8 | 70 | 1.7 | 1.4 | 1.9 | 3 | |
| 947C241K901BTHS | 240 | 900 | 85 | 85 | 31.7 | 34000 | 57 | 2.1 | 29 | 2.9 | 3.4 | 0.6 | 3 | |

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

| Part Number | Rated | | Can | | Lead | | Current | | Thermal Resistance | | | | | Mass (kg) | Fig |
|-----------------|------------------|-------------|-----------|-----------|-----------|----------------------------|-----------------|----------------------|--------------------|-------------------|-------------------|-----|---|--------------|-----|
| | Cap. | Voltage | Diameter | Height | Spacing | Case | $\Delta T = 40$ | Typ | Typ | Θ_{cc} | Θ_{ca} | | | | |
| | C (μF) | Vr (Vdc) | D (mm) | H (mm) | S (mm) | Area (mm ²) | Irms (A) | ESR (m Ω) | ESL (nH) | ($^{\circ}C/W$) | ($^{\circ}C/W$) | | | | |
| 947C261K901CTMS | 260 | 900 | 90 | 85 | 45.0 | 36800 | 61 | 2.0 | 29 | 2.9 | 3.1 | 0.7 | 1 | | |
| 947C261K901CTIS | 260 | 900 | 90 | 85 | 45.0 | 36800 | 61 | 2.0 | 29 | 2.9 | 3.1 | 0.7 | 2 | | |
| 947C291K901BAHS | 290 | 900 | 85 | 97 | 31.7 | 37300 | 56 | 2.3 | 33 | 2.7 | 3.1 | 0.7 | 3 | | |
| 947C321K901CAMS | 320 | 900 | 90 | 97 | 45.0 | 40100 | 61 | 2.1 | 33 | 2.7 | 2.9 | 0.7 | 1 | | |
| 947C321K901CAIS | 320 | 900 | 90 | 97 | 45.0 | 40100 | 61 | 2.1 | 33 | 2.7 | 2.9 | 0.7 | 2 | | |
| 947C401K901BBHS | 400 | 900 | 85 | 120 | 31.7 | 43400 | 56 | 2.8 | 41 | 2.3 | 2.6 | 0.8 | 3 | | |
| 947C431K901CBMS | 430 | 900 | 90 | 120 | 45.0 | 46700 | 59 | 2.6 | 41 | 2.3 | 2.5 | 0.9 | 1 | | |
| 947C431K901CBIS | 430 | 900 | 90 | 120 | 45.0 | 46700 | 59 | 2.6 | 41 | 2.3 | 2.5 | 0.9 | 2 | | |
| 947C481K901DTHS | 480 | 900 | 116 | 85 | 50.0 | 52100 | 96 | 1.1 | 35 | 2.1 | 2.2 | 1.1 | 3 | | |
| 947C511K901BGHS | 510 | 900 | 85 | 140 | 31.7 | 48700 | 56 | 3.2 | 49 | 2.0 | 2.4 | 0.9 | 3 | | |
| 947C551K901CCMS | 550 | 900 | 90 | 145 | 45.0 | 53700 | 59 | 3.0 | 49 | 2.0 | 2.1 | 1.0 | 1 | | |
| 947C551K901CCIS | 550 | 900 | 90 | 145 | 45.0 | 53700 | 59 | 3.0 | 49 | 2.0 | 2.1 | 1.0 | 2 | | |
| 947C581K901DAHS | 580 | 900 | 116 | 97 | 50.0 | 56500 | 94 | 1.3 | 35 | 2.1 | 2 | 1.2 | 3 | | |
| 947C611K901BDHS | 610 | 900 | 85 | 170 | 31.7 | 56700 | 56 | 3.7 | 58 | 1.7 | 2 | 1.1 | 3 | | |
| 947C661K901CDMS | 660 | 900 | 90 | 170 | 45.0 | 60800 | 59 | 3.4 | 58 | 1.8 | 1.9 | 1.2 | 1 | | |
| 947C661K901CDIS | 660 | 900 | 90 | 170 | 45.0 | 60800 | 59 | 3.4 | 58 | 1.8 | 1.9 | 1.2 | 2 | | |
| 947C791K901DBHS | 790 | 900 | 116 | 120 | 50.0 | 64900 | 91 | 1.5 | 50 | 2.0 | 1.8 | 1.4 | 3 | | |
| 947C102K901DCHS | 1000 | 900 | 116 | 145 | 50.0 | 74000 | 89 | 1.7 | 60 | 1.8 | 1.6 | 1.7 | 3 | | |
| 947C122K901DLHS | 1200 | 900 | 116 | 165 | 50.0 | 81300 | 89 | 2.0 | 70 | 1.6 | 1.4 | 1.9 | 3 | | |
| 947C191K102BTHS | 190 | 1000 | 85 | 85 | 31.7 | 34000 | 53 | 2.4 | 29 | 2.9 | 3.4 | 0.6 | 3 | | |
| 947C211K102CTMS | 210 | 1000 | 90 | 85 | 45.0 | 36800 | 58 | 2.2 | 29 | 2.9 | 3.1 | 0.7 | 1 | | |
| 947C211K102CTIS | 210 | 1000 | 90 | 85 | 45.0 | 36800 | 58 | 2.2 | 29 | 2.9 | 3.1 | 0.7 | 2 | | |
| 947C231K102CAMS | 230 | 1000 | 90 | 97 | 45.0 | 40100 | 54 | 2.6 | 33 | 3.0 | 2.9 | 0.9 | 1 | | |
| 947C231K102CAIS | 230 | 1000 | 90 | 97 | 45.0 | 40100 | 54 | 2.6 | 33 | 3.0 | 2.9 | 0.9 | 2 | | |
| 947C241K102BAHS | 240 | 1000 | 85 | 97 | 31.7 | 37300 | 54 | 2.5 | 33 | 2.7 | 3.1 | 0.7 | 3 | | |
| 947C251K102CAMS | 250 | 1000 | 90 | 97 | 45.0 | 40100 | 56 | 2.4 | 33 | 2.7 | 2.9 | 0.8 | 1 | | |
| 947C251K102CAIS | 250 | 1000 | 90 | 97 | 45.0 | 40100 | 56 | 2.4 | 33 | 2.7 | 2.9 | 0.8 | 2 | | |
| 947C311K102CBMS | 310 | 1000 | 90 | 120 | 45.0 | 46700 | 53 | 3.2 | 41 | 2.6 | 2.5 | 1.0 | 1 | | |
| 947C311K102CBIS | 310 | 1000 | 90 | 120 | 45.0 | 46700 | 53 | 3.2 | 41 | 2.6 | 2.5 | 1.0 | 2 | | |
| 947C321K102BBHS | 320 | 1000 | 85 | 120 | 31.7 | 43400 | 53 | 3.1 | 41 | 2.3 | 2.6 | 0.8 | 3 | | |
| 947C351K102CBMS | 350 | 1000 | 90 | 120 | 45.0 | 46700 | 57 | 2.8 | 41 | 2.3 | 2.5 | 0.9 | 1 | | |
| 947C351K102CBIS | 350 | 1000 | 90 | 120 | 45.0 | 46700 | 57 | 2.8 | 41 | 2.3 | 2.5 | 0.9 | 2 | | |
| 947C381K102DTHS | 380 | 1000 | 116 | 85 | 50.0 | 52100 | 90 | 1.3 | 35 | 2.2 | 2.2 | 1.1 | 3 | | |
| 947C391K102CCMS | 390 | 1000 | 90 | 145 | 45.0 | 53700 | 53 | 3.7 | 49 | 2.2 | 2.1 | 1.2 | 1 | | |
| 947C391K102CCIS | 390 | 1000 | 90 | 145 | 45.0 | 53700 | 53 | 3.7 | 49 | 2.2 | 2.1 | 1.2 | 2 | | |
| 947C411K102BGHS | 410 | 1000 | 85 | 140 | 31.7 | 48700 | 53 | 3.5 | 49 | 2.0 | 2.4 | 0.9 | 3 | | |
| 947C441K102CCMS | 440 | 1000 | 90 | 145 | 45.0 | 53700 | 56 | 3.3 | 49 | 2.0 | 2.1 | 1.1 | 1 | | |
| 947C441K102CCIS | 440 | 1000 | 90 | 145 | 45.0 | 53700 | 56 | 3.3 | 49 | 2.0 | 2.1 | 1.1 | 2 | | |
| 947C471K102DAHS | 470 | 1000 | 116 | 97 | 50.0 | 56500 | 90 | 1.4 | 40 | 2.1 | 2 | 1.2 | 3 | | |
| 947C471K102CDMS | 470 | 1000 | 90 | 170 | 45.0 | 60800 | 52 | 4.3 | 38 | 1.9 | 1.9 | 1.3 | 1 | | |
| 947C471K102CDIS | 470 | 1000 | 90 | 170 | 45.0 | 60800 | 52 | 4.3 | 38 | 1.9 | 1.9 | 1.3 | 2 | | |
| 947C491K102BDHS | 490 | 1000 | 85 | 170 | 31.7 | 56700 | 53 | 4.1 | 49 | 1.7 | 2 | 1.1 | 3 | | |

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

| Part Number | Rated | | Can | Can | Lead | Current | | | | | | | |
|-----------------|------------------|-------------|-----------|-----------|-----------|----------------------------|-----------------|----------------------|-------------|------------------------------------|------------------------------------|--------------|-----|
| | Cap. | Voltage | Diameter | Height | Spacing | Case | $\Delta T = 40$ | Typ | Typ | Thermal Resistance | | | |
| | C (μF) | Vr (Vdc) | D (mm) | H (mm) | S (mm) | Area (mm ²) | Irms (A) | ESR (m Ω) | ESL (nH) | Θ_{cc} ($^{\circ}C/W$) | Θ_{ca} ($^{\circ}C/W$) | Mass (kg) | Fig |
| 947C531K102CDMS | 530 | 1000 | 90 | 170 | 45.0 | 60800 | 56 | 3.8 | 58 | 1.8 | 1.9 | 1.2 | 1 |
| 947C531K102CDIS | 530 | 1000 | 90 | 170 | 45.0 | 60800 | 56 | 3.8 | 58 | 1.8 | 1.9 | 1.2 | 2 |
| 947C641K102DBHS | 640 | 1000 | 116 | 120 | 50.0 | 64900 | 87 | 1.6 | 50 | 2.0 | 1.8 | 1.4 | 3 |
| 947C801K102DCHS | 800 | 1000 | 116 | 145 | 50.0 | 74000 | 85 | 1.9 | 60 | 1.8 | 1.6 | 1.7 | 3 |
| 947C971K102DLHS | 970 | 1000 | 116 | 165 | 50.0 | 81300 | 84 | 2.2 | 70 | 1.6 | 1.4 | 1.9 | 3 |
| 947C161K112BTHS | 160 | 1100 | 85 | 85 | 31.7 | 34000 | 51 | 2.6 | 29 | 2.9 | 3.4 | 0.6 | 3 |
| 947C171K112CTMS | 170 | 1100 | 90 | 85 | 45.0 | 36800 | 54 | 2.4 | 29 | 2.9 | 3.1 | 0.7 | 1 |
| 947C171K112CTIS | 170 | 1100 | 90 | 85 | 45.0 | 36800 | 54 | 2.4 | 29 | 2.9 | 3.1 | 0.7 | 2 |
| 947C191K112BAHS | 190 | 1100 | 85 | 97 | 31.7 | 37300 | 50 | 2.9 | 33 | 2.7 | 3.1 | 0.7 | 3 |
| 947C211K112CAMS | 210 | 1100 | 90 | 97 | 45.0 | 40100 | 54 | 2.6 | 33 | 2.7 | 2.9 | 0.8 | 1 |
| 947C211K112CAIS | 210 | 1100 | 90 | 97 | 45.0 | 40100 | 54 | 2.6 | 33 | 2.7 | 2.9 | 0.8 | 2 |
| 947C261K112BBHS | 260 | 1100 | 85 | 120 | 31.7 | 43400 | 50 | 3.4 | 41 | 2.3 | 2.6 | 0.8 | 3 |
| 947C281K112CBMS | 280 | 1100 | 90 | 120 | 45.0 | 46700 | 53 | 3.2 | 41 | 2.3 | 2.5 | 0.9 | 1 |
| 947C281K112CBIS | 280 | 1100 | 90 | 120 | 45.0 | 46700 | 53 | 3.2 | 41 | 2.3 | 2.5 | 0.9 | 2 |
| 947C311K112DTHS | 310 | 1100 | 116 | 85 | 50.0 | 52100 | 85 | 1.4 | 35 | 2.2 | 2.2 | 1.1 | 3 |
| 947C331K112BCHS | 330 | 1100 | 85 | 145 | 31.7 | 50100 | 50 | 4.0 | 49 | 2.0 | 2.3 | 0.9 | 3 |
| 947C361K112CCMS | 360 | 1100 | 90 | 145 | 45.0 | 53700 | 53 | 3.7 | 49 | 2.0 | 2.1 | 1.1 | 1 |
| 947C361K112CCIS | 360 | 1100 | 90 | 145 | 45.0 | 53700 | 53 | 3.7 | 49 | 2.0 | 2.1 | 1.1 | 2 |
| 947C381K112DAHS | 380 | 1100 | 116 | 97 | 50.0 | 56500 | 84 | 1.5 | 40 | 2.2 | 2 | 1.2 | 3 |
| 947C401K112BDHS | 400 | 1100 | 85 | 170 | 31.7 | 56700 | 50 | 4.5 | 58 | 1.7 | 2 | 1.1 | 3 |
| 947C431K112CDMS | 430 | 1100 | 90 | 170 | 45.0 | 60800 | 53 | 4.2 | 58 | 1.8 | 1.9 | 1.2 | 1 |
| 947C431K112CDIS | 430 | 1100 | 90 | 170 | 45.0 | 60800 | 53 | 4.2 | 58 | 1.8 | 1.9 | 1.2 | 2 |
| 947C521K112DBHS | 520 | 1100 | 116 | 120 | 50.0 | 64900 | 82 | 1.8 | 50 | 2.0 | 1.8 | 1.4 | 3 |
| 947C661K112DCHS | 660 | 1100 | 116 | 145 | 50.0 | 74000 | 81 | 2.1 | 60 | 1.8 | 1.6 | 1.7 | 3 |
| 947C801K112DLHS | 800 | 1100 | 116 | 165 | 50.0 | 81300 | 81 | 2.4 | 70 | 1.6 | 1.4 | 1.9 | 3 |
| 947C131K122BTHS | 130 | 1200 | 85 | 85 | 31.7 | 34000 | 48 | 2.9 | 29 | 2.9 | 3.4 | 0.6 | 3 |
| 947C141K122CTIS | 140 | 1200 | 90 | 85 | 45.0 | 36800 | 51 | 2.7 | 29 | 2.9 | 3.1 | 0.7 | 1 |
| 947C141K122CTIS | 140 | 1200 | 90 | 85 | 45.0 | 36800 | 51 | 2.7 | 29 | 2.9 | 3.1 | 0.7 | 2 |
| 947C161K122BAHS | 160 | 1200 | 85 | 97 | 31.7 | 37300 | 48 | 3.1 | 33 | 2.7 | 3.1 | 0.7 | 3 |
| 947C161K122CAMS | 160 | 1200 | 90 | 97 | 45.0 | 40100 | 49 | 3.1 | 33 | 3.0 | 2.9 | 0.9 | 1 |
| 947C161K122CAIS | 160 | 1200 | 90 | 97 | 45.0 | 40100 | 49 | 3.1 | 33 | 3.0 | 2.9 | 0.9 | 2 |
| 947C171K122CAMS | 170 | 1200 | 90 | 97 | 45.0 | 40100 | 51 | 3.0 | 33 | 2.8 | 2.9 | 0.8 | 1 |
| 947C171K122CAIS | 170 | 1200 | 90 | 97 | 45.0 | 40100 | 51 | 3.0 | 33 | 2.8 | 2.9 | 0.8 | 2 |
| 947C211K122CBMS | 210 | 1200 | 90 | 120 | 45.0 | 46700 | 48 | 3.9 | 41 | 2.6 | 2.5 | 1.0 | 1 |
| 947C211K122CBIS | 210 | 1200 | 90 | 120 | 45.0 | 46700 | 48 | 3.9 | 41 | 2.6 | 2.5 | 1.0 | 2 |
| 947C221K122BBHS | 220 | 1200 | 85 | 120 | 31.7 | 43400 | 48 | 3.7 | 41 | 2.3 | 2.6 | 0.8 | 3 |
| 947C241K122CBMS | 240 | 1200 | 90 | 120 | 45.0 | 46700 | 51 | 4.0 | 49 | 2.3 | 2.5 | 0.9 | 1 |
| 947C241K122CBIS | 240 | 1200 | 90 | 120 | 45.0 | 46700 | 51 | 4.0 | 49 | 2.3 | 2.5 | 0.9 | 2 |
| 947C261K122DTHS | 260 | 1200 | 116 | 85 | 50.0 | 52100 | 82 | 1.5 | 35 | 2.2 | 2.2 | 1.1 | 3 |
| 947C271K122CCMS | 270 | 1200 | 90 | 145 | 45.0 | 53700 | 48 | 4.4 | 49 | 2.2 | 2.1 | 1.2 | 1 |
| 947C271K122CCIS | 270 | 1200 | 90 | 145 | 45.0 | 53700 | 48 | 4.4 | 49 | 2.2 | 2.1 | 1.2 | 2 |
| 947C281K122BGHS | 280 | 1200 | 85 | 140 | 31.7 | 48700 | 48 | 4.3 | 49 | 2.0 | 2.4 | 0.9 | 3 |

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

| Part Number | Rated | | Can | | Lead | | Current | | Typ | | Thermal Resistance | | Mass (kg) | Fig |
|-----------------|---------------|----------|----------|--------|---------|-----------------|-----------------|-------------------|----------|---------------------------------|---------------------------------|-----|-----------|-----|
| | Cap. | Voltage | Diameter | Height | Spacing | Case | $\Delta T = 40$ | Typ | Typ | | | | | |
| | C (μF) | Vr (Vdc) | D (mm) | H (mm) | S (mm) | Area (mm^2) | Irms (A) | ESR (m Ω) | ESL (nH) | θ_{cc} ($^{\circ}C/W$) | θ_{ca} ($^{\circ}C/W$) | | | |
| 947C301K122CCMS | 300 | 1200 | 90 | 145 | 45.0 | 53700 | 51 | 4.0 | 49 | 2.0 | 2.1 | 1.1 | 1 | |
| 947C301K122CCIS | 300 | 1200 | 90 | 145 | 45.0 | 53700 | 51 | 4.0 | 49 | 2.0 | 2.1 | 1.1 | 2 | |
| 947C321K122DAHS | 320 | 1200 | 116 | 97 | 50.0 | 56500 | 81 | 1.7 | 40 | 2.1 | 2 | 1.2 | 3 | |
| 947C321K122CDMS | 320 | 1200 | 90 | 170 | 45.0 | 60800 | 47 | 5.1 | 58 | 1.9 | 1.9 | 1.3 | 1 | |
| 947C321K122CDIS | 320 | 1200 | 90 | 170 | 45.0 | 60800 | 47 | 5.1 | 58 | 1.9 | 1.9 | 1.3 | 2 | |
| 947C331K122BDHS | 330 | 1200 | 85 | 170 | 31.7 | 56700 | 47 | 5.0 | 58 | 1.7 | 2 | 1.1 | 3 | |
| 947C361K122CDMS | 360 | 1200 | 90 | 170 | 45.0 | 60800 | 51 | 4.6 | 58 | 1.8 | 1.9 | 1.2 | 1 | |
| 947C361K122CDIS | 360 | 1200 | 90 | 170 | 45.0 | 60800 | 51 | 4.6 | 58 | 1.8 | 1.9 | 1.2 | 2 | |
| 947C431K122DBHS | 430 | 1200 | 116 | 120 | 50.0 | 64900 | 78 | 2.0 | 50 | 2.0 | 1.8 | 1.4 | 3 | |
| 947C551K122DCHS | 550 | 1200 | 116 | 145 | 50.0 | 74000 | 78 | 2.3 | 60 | 1.8 | 1.6 | 1.7 | 3 | |
| 947C661K122DLHS | 660 | 1200 | 116 | 165 | 50.0 | 81300 | 76 | 2.6 | 70 | 1.6 | 1.4 | 1.9 | 3 | |
| 947C111K132BTHS | 110 | 1300 | 85 | 85 | 31.7 | 34000 | 46 | 3.2 | 29 | 2.9 | 3.4 | 0.6 | 3 | |
| 947C121K132CTMS | 120 | 1300 | 90 | 85 | 45.0 | 36800 | 49 | 2.9 | 29 | 2.9 | 3.1 | 0.7 | 1 | |
| 947C121K132CTIS | 120 | 1300 | 90 | 85 | 45.0 | 36800 | 49 | 2.9 | 29 | 2.9 | 3.1 | 0.7 | 2 | |
| 947C131K132BAHS | 130 | 1300 | 85 | 97 | 31.7 | 37300 | 45 | 3.6 | 33 | 2.8 | 3.1 | 0.7 | 3 | |
| 947C151K132CAMS | 150 | 1300 | 90 | 97 | 45.0 | 40100 | 50 | 3.1 | 33 | 2.7 | 2.9 | 0.7 | 1 | |
| 947C151K132CAIS | 150 | 1300 | 90 | 97 | 45.0 | 40100 | 50 | 3.1 | 33 | 2.7 | 2.9 | 0.7 | 2 | |
| 947C181K132BBHS | 180 | 1300 | 85 | 120 | 31.7 | 43400 | 45 | 4.1 | 41 | 2.3 | 2.6 | 0.8 | 3 | |
| 947C201K132CBMS | 200 | 1300 | 90 | 120 | 45.0 | 46700 | 49 | 3.8 | 41 | 2.3 | 2.5 | 0.9 | 1 | |
| 947C201K132CBIS | 200 | 1300 | 90 | 120 | 45.0 | 46700 | 49 | 3.8 | 41 | 2.3 | 2.5 | 0.9 | 2 | |
| 947C221K132DTHS | 220 | 1300 | 116 | 85 | 50.0 | 52100 | 78 | 1.7 | 35 | 2.2 | 2.2 | 1.1 | 3 | |
| 947C231K132BGHS | 230 | 1300 | 85 | 140 | 31.7 | 48700 | 45 | 4.8 | 49 | 2.0 | 2.4 | 0.9 | 3 | |
| 947C251K132CCMS | 250 | 1300 | 90 | 145 | 45.0 | 53700 | 48 | 4.4 | 49 | 2.0 | 2.1 | 1.1 | 1 | |
| 947C251K132CCIS | 250 | 1300 | 90 | 145 | 45.0 | 53700 | 48 | 4.4 | 49 | 2.0 | 2.1 | 1.1 | 2 | |
| 947C271K132DAHS | 270 | 1300 | 116 | 97 | 50.0 | 56500 | 77 | 1.8 | 40 | 2.1 | 2 | 1.2 | 3 | |
| 947C281K132BDHS | 280 | 1300 | 85 | 170 | 31.7 | 56700 | 45 | 5.4 | 49 | 1.7 | 2 | 1.1 | 3 | |
| 947C311K132CDMS | 310 | 1300 | 90 | 170 | 45.0 | 60800 | 49 | 4.9 | 58 | 1.7 | 1.9 | 1.2 | 1 | |
| 947C311K132CDIS | 310 | 1300 | 90 | 170 | 45.0 | 60800 | 49 | 4.9 | 58 | 1.7 | 1.9 | 1.2 | 2 | |
| 947C371K132DBHS | 370 | 1300 | 116 | 120 | 50.0 | 64900 | 76 | 2.1 | 50 | 2.0 | 1.8 | 1.4 | 3 | |
| 947C461K132DCHS | 460 | 1300 | 116 | 145 | 50.0 | 74000 | 74 | 2.5 | 60 | 1.8 | 1.6 | 1.7 | 3 | |
| 947C561K132DLHS | 560 | 1300 | 116 | 165 | 50.0 | 81300 | 73 | 2.8 | 70 | 1.6 | 1.4 | 1.9 | 3 | |

1. Rated Current is for temperature rise of +40 °C at 1–20 kHz.
2. θ_{cc} is core-to-case thermal resistance at 0–10 kHz. For higher frequency see **Expected Lifetime Predictions**.
3. θ_{ca} is case-to-ambient thermal resistance for still air. For moving air see **Expected Lifetime Predictions**.

Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

Expected Lifetime Predictions

To use the Expected Lifetime curves calculate V_a/V_r and core temperature T. Start by estimating:

- Applied dc voltage V_a
- Ripple Current I
- Ripple Frequency f
- Ambient Temperature T_a
- Airflow speed v

Units:

- $A = m^2$
- $C = \mu F$
- $ESR = m\Omega$
- $f = kHz$
- $I = A$
- $T, T_a \& T_c = ^\circ C$
- $\theta, \theta_{ca} \& \theta_{cc} = ^\circ C/W$
- $v = m/s$
- $V_a \& V_r = V_{dc}$

NOTE: The temperature rise in the 947C is $I^2(ESR)$ times the thermal resistance θ . The ESR is mainly the metal resistance; the metal resistance is the 10 kHz ESR. The dielectric resistance needs to be considered for operation below 10kHz.

1. Start with the 10kHz ESR from the ratings table. If frequency is less than 10kHz, use the following equation: $ESR = 31.83/(10C) + 31.83/(fC)$.

2. Compute total thermal resistance θ as the sum of core-to-case thermal resistance θ_{cc} and case-to-ambient thermal resistance θ_{ca} . Both are in the Ratings table but θ_{ca} is for still air. For moving air use the capacitor surface area A and airflow speed v to calculate $\theta_{ca} = 1/[A(5+17(v+0.1)0.66)]$.

Please note that the θ_{cc} for all designs built to figures 1 and 2; θ_{cc} is for 10 kHz or less. For frequency > 10 kHz multiply θ_{cc} by $[1+(f-10)/100]$, e.g., for 75 kHz multiply θ_{cc} by 1.65.

3. Compute V_a/V_r and the core temperature T.
 $T = T_a + I^2(ESR)\theta$

4. Look up estimated lifetime from the Expected Lifetime curves.

5. If you want a longer expected lifetime, choose a capacitor with higher voltage rating or consider using multiple capacitors in

The expected lifetime predictions assume no exposure to overvoltage transients. Expected lifetime can be calculated for varying exposure to overvoltage transients. As an illustration at 50 °C the expected lifetime is 100,000 h with the 24-hour V_a/V_r profile below:

| V_a / V_r | Duration |
|-------------|------------|
| 1.67 | 100 ms |
| 1.50 | 5 minutes |
| 1.30 | 2.5 hours |
| 1.10 | 9.6 hours |
| 1.00 | 11.9 hours |




For applications with more severe 24-hour profiles, contact us.



Type 947C Polypropylene, DC Link Capacitors

High Current, High Capacitance for Inverter Applications

Typical Performance Curves



Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.