


FEATURES


- Standard 7.0mm x 5.0mm, 6-Pad Surface Mount Package
- **Low Phase Jitter, 0.5ps RMS Maximum**
- LVPECL or LVDS Output
- Fundamental and 3rd Overtone Crystal Designs
- Frequency Range 19.44 – 320 MHz
- Frequency Stability ± 50 ppm Standard
- Operating Voltages +2.5Vdc or +3.3Vdc
- Operating Temperature to -40°C to +85°C
- Output Enable Standard
- Tape & Reel Packaging Standard, EIA-418
- **RoHS/Green Compliant [6/6]**



APPLICATIONS

Model 637 is ideal for applications such as broadband access, SerDes, Ethernet/Gigabit Ethernet, SONET/SDH and optical networking.

ORDERING INFORMATION



1] Refer to document 016-1454-0, Frequency Code Tables.



3-digits required for frequencies below 100MHz and 4-digits for frequencies 100MHz or greater.

2] Consult factory for availability of 6I Stability/Temperature combination.

Not all performance combinations and frequencies may be available.
Contact your local CTS Representative or CTS Customer Service for availability.

PACKAGING INFORMATION [reference]

Device quantity is 1k pcs. maximum per 180mm reel.




ELECTRICAL CHARACTERISTICS

ELECTRICAL PARAMETERS	PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
	Maximum Supply Voltage	V_{CC}	-	-0.5	-	5.0	V
	Storage Temperature	T_{STG}	-	-40	-	+100	°C
	Frequency Range	f_0	-	19.44	-	320	MHz
	LVPECL			80.00	-	320	
	Frequency Stability	$\Delta f/f_0$	All Inclusive, see Note 1. 1st year aging	-	-	20, 25, 50, 100 3	$\pm$ ppm
	Operating Temperature	T_A	-	-20	25	+70	°C
	Commercial			-40		+85	
	Industrial						
	Supply Voltage	V_{CC}	$\pm 5\%$	2.38 3.14	2.5 3.3	2.63 3.47	V
	Supply Current	I_{CC}	Maximum Load	-	-	88	mA
	LVPECL			-	-	65	
	LVDS						
	Start Up Time	T_S	Application of V_{CC}	-	2	5	ms
	Phase Jitter	t_{jrms}	Bandwidth 12 kHz - 20 MHz	-	0.3	0.5	ps
	Period Jitter RMS	p_{jrms}	-	-	2.1	-	
	Period Jitter Pk-Pk		-	-	22	-	
	Enable Function		Standby				V
	Enable Input Voltage	V_{IH}	Pin 1 or 2 Logic '1', Output Enabled	$0.7 \cdot V_{CC}$	-	-	
	Disable Input Voltage	V_{IL}	Pin 1 or 2 Logic '0', Output Disabled	-	-	$0.3 \cdot V_{CC}$	
	Disable Time	T_{PLZ}	Pin 1 or 2 Logic '0', Output Disabled	-	-	200	ns
	Enable Time	T_{PLZ}	Pin 1 or 2 Logic '1', Output Enabled	-	-	2	ms
	LVPECL WAVEFORM						
	Output Load	R_L	Terminated to $V_{CC} - 2.0V$	-	50	-	Ohms
	Output Duty Cycle	SYM	@ $V_{CC} - 1.3V$	45	-	55	%
	Output Voltage Levels						V
	Logic '1' Level	V_{OH}	PECL Load, -20°C to +70°C	$V_{CC} - 1.025$	-	$V_{CC} - 0.880$	
	Logic '0' Level	V_{OL}	PECL Load, -20°C to +70°C	$V_{CC} - 1.810$	-	$V_{CC} - 1.620$	V
	Logic '1' Level	V_{OH}	PECL Load, -40°C to +85°C	$V_{CC} - 1.085$	-	$V_{CC} - 0.880$	
	Logic '0' Level	V_{OL}	PECL Load, -40°C to +85°C	$V_{CC} - 1.830$	-	$V_{CC} - 1.555$	
	Rise and Fall Time	T_R, T_F	@ 20% - 80% Levels	-	0.3	0.7	ns
	LVDS WAVEFORM						
	Output Load	R_L	Between Outputs	-	100	-	Ohms
	Output Duty Cycle	SYM	@ 1.25V	45	-	55	%
	Differential Output Voltage	V_{OD}	$R_L = 100$ Ohms	247	350	454	mV
	Offset Voltage	V_{OS}	LVDS Load	1.125	1.25	1.375	V
	Output Voltage Levels						V
	Logic '1' Level	V_{OH}	LVDS Load	-	1.43	1.6	
	Logic '0' Level	V_{OL}	LVDS Load	0.9	1.1	-	
	Rise and Fall Time	T_R, T_F	@ 20% - 80% Levels	-	0.4	0.7	ns

Notes:

1. Inclusive of initial tolerance at time of shipment, changes in supply voltage, load, temperature and 1st year aging.


LVPECL/LVDS OUTPUT WAVEFORM




ENABLE TRUTH TABLE

PIN 1 or Pin 2	PIN 4 & 5
Logic '1'	Output
Open	Output
Logic '0'	High Z

TEST CIRCUIT, LVPECL LOAD




TEST CIRCUIT, LVDS LOAD




MECHANICAL SPECIFICATIONS

PACKAGE DRAWING



SUGGESTED SOLDER PAD GEOMETRY

C_{BYPASS} should be $\geq 0.01 \mu F$.



MARKING INFORMATION

- ** - Manufacturing Site Code.
- YYWW - Date code, YY - year, WW - week.
- O - Output Type. P or E = LVPECL, L or V = LVDS.
- ST - Frequency stability/temperature code.
[Refer to Ordering Information.]
- V - Voltage code. 3 = 3.3V, 2 = 2.5V
- xxxx - Frequency Code.
3-digits, frequencies below 100MHz
4-digits, frequencies 100MHz or greater.

Refer to document 016-1454-0, Frequency Code Tables.

NOTES

- Complete CTS part number, frequency value and date code information must appear on reel and carton labels.
- Termination pads [e4]. Barrier-plating is nickel [Ni] with gold [Au] flash plate.
- Reflow conditions per JEDEC J-STD-020; 260°C maximum, 20 seconds.
- MSL = 1.

D.U.T. PIN ASSIGNMENTS

PIN	SYMBOL	DESCRIPTION
1	EOH or N.C.	Enable [std] or No Connect
2	N.C. or EOH	No Connect or Enable [opt]
3	GND	Circuit & Package Ground
4	Output	RF Output
5	Output	Complimentary RF Output
6	V _{CC}	Supply Voltage



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.