

P0102BL

SENSITIVE 0.25A SCRs

MAIN FEATURES:

Symbol	Value	Unit
$I_{T(RMS)}$	0.25	A
V_{DRM}/V_{RRM}	200	V
I_{GT}	200	µA





SOT-23

DESCRIPTION

Thanks to highly sensitive triggering levels, the PO102BL SCR is suitable for all applications where the available gate current is limited such as stand-by mode power supplies, smoke and alarm detectors...
Available in SOT-23, it provides optimized space saving on high density printed circuit boards.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit
$I_{T(RMS)}$	RMS on-state current (180° conduction angle)		Tamb = 30°C	0.25	A
$I_{T(AV)}$	Average on-state current (180° conduction angle)		Tamb = 30°C	0.17	A
I_{TSM}	Non repetitive surge peak on-state current	tp = 8.3 ms	Tj = 25°C	7	A
		tp = 10 ms		6	
I^2t	I^2t Value for fusing	tp = 10 ms	Tj = 25°C	0.18	A^2S
dI/dt	Critical rate of rise of on-state current I_G = 2 x I_{GT} , tr ≤ 100ns	F = 60 Hz	Tj = 125°C	50	A/µs
I_{GM}	Peak gate current	tp = 20 µs	Tj = 125°C	0.5	A
$P_{G(AV)}$	Average gate power dissipation		Tj = 125°C	0.02	W
T_{stg} Tj	Storage junction temperature range Operating junction temperature range			- 40 to + 150 - 40 to + 125	°C

ELECTRICAL CHARACTERISTICS (Tj = 25°C, unless otherwise specified)

Symbol	Test Conditions			P0102BL	Unit
I_{GT}	V_D = 12 V R_L = 140 Ω		MAX.	200	µA
V_{GT}			MAX.	0.8	V
V_{GD}	$V_D = V_{DRM}$ R_L = 3.3 kΩ R_{GK} = 1 kΩ	Tj = 125°C	MIN.	0.1	V
V_{RG}	I_{RG} = 10 µA		MIN.	8	V
I_H	I_T = 50 mA R_{GK} = 1kΩ		MAX.	6	mA
I_L	I_G = 1 mA R_{GK} = 1kΩ		MAX.	7	mA
dV/dt	V_D = 67 % V_{DRM} R_{GK} = 1kΩ	Tj = 125°C	MIN.	200	V/µs
V_{TM}	I_{TM} = 0.4 A tp = 380 µs	Tj = 25°C	MAX.	1.7	V
V_{t0}	Threshold voltage	Tj = 125°C	MAX.	1.0	V
R_d	Dynamic resistance	Tj = 125°C	MAX.	1000	mΩ
I_{DRM}	$V_{DRM} = V_{RRM}$	Tj = 25°C	MAX.	1	µA
I_{RRM}		Tj = 125°C		100	


THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to ambient (mounted on FR4 with recommended pad layout)	400	°C/W

PRODUCT SELECTOR

Part Number	Voltage	Sensitivity	Package
P0102BL	200 V	200 µA	SOT-23

ORDERING INFORMATION



OTHER INFORMATION

Part Number	Marking	Weight	Base quantity	Packing mode
P0102BL	P2B	0.01 g	3000	Tape & reel

Fig. 1: Maximum average power dissipation versus average on-state current.




Fig. 2: Average and D.C. on-state current versus ambient temperature.




Fig. 3: Relative variation of thermal impedance junction to ambient versus pulse duration.




Fig. 4: Relative variation of gate trigger current, holding current and latching current versus junction temperature (typical values).




Fig. 5: Relative variation of holding current versus gate-cathode resistance (typical values).




Fig. 6: Relative variation of dV/dt immunity versus gate-cathode resistance (typical values).




Fig. 7: Relative variation of dV/dt immunity versus gate-cathode capacitance (typical values).




Fig. 8: Surge peak on-state current versus number of cycles.




Fig. 9: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp < 10ms, and corresponding value of I^2t.




Fig. 10: On-state characteristics (maximum values).






Fig. 11: Thermal resistance junction to ambient versus copper surface under tab (Epoxy printed circuit board FR4, copper thickness: 35 µm).



PACKAGE MECHANICAL DATA


SOT-23 (Plastic)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.89	1.4	0.035	0.055
A1	0	0.1	0	0.004
B	0.3	0.51	0.012	0.02
c	0.085	0.18	0.003	0.007
D	2.75	3.04	0.108	0.12
e	0.85	1.05	0.033	0.041
e1	1.7	2.1	0.067	0.083
E	1.2	1.6	0.047	0.063
H	2.1	2.75	0.083	0.108
L	0.6 typ.		0.024 typ.	
S	0.35	0.65	0.014	0.026

FOOTPRINT DIMENSIONS (in millimeters)

SOT-23 (Plastic)



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronic

© 2000 STMicroelectronics - Printed in Italy - All Rights Reserved

STMicroelectronics GROUP OF COMPANIES
Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom

http://www.st.com


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.