




ALTERNATE GEOMETRY
SEE NOTE 10




SELECTIVE PLATING
LOCATION







CUT OFF DIM.



NOTES:
1. MATERIAL: SEE LEGEND
2. FINISH:
   909 - OVERALL HOT TIN DIP: .000100/(0.00254) MIN.
   102 - OVERALL TIN: .000200/(0.00508) MIN.
   OVERALL COPPER: .000100/(0.00254) MIN.
   132 - OVERALL TIN: .000200/(0.00508) MIN.
   OVERALL COPPER: .000200/(0.00508) MIN.
   503 - OVERALL HARD GOLD: .000030/(0.00076) MIN.
   OVERALL NICKEL: .000050/(0.00127) MIN.
   550 - SELECT HARD GOLD: .000015/(0.00038) MIN.
   OVERALL NICKEL: .000030/(0.00076) MIN.
   OVERALL HARD GOLD FLASH: .000002/(0.00005) MIN.
   555 - SELECT HARD GOLD: .000015/(0.00038) MIN.
   OVERALL NICKEL: .000030/(0.00076) MIN.
   558 - SELECT HARD GOLD: .000030/(0.00076) MIN.
   OVERALL NICKEL: .000050/(0.00127) MIN.
   OVERALL HARD GOLD FLASH: .000002/(0.00005) MIN.
   561 - SELECT HARD GOLD: .000030/(0.00076) MIN.
   OVERALL NICKEL: .000050/(0.00127) MIN.
3. PRODUCT SPECIFICATION: PS-40-02
4. PACKAGING SPECIFICATION: CHAIN FORM: SEE PK-6838-001
   LOOSE FORM: SEE PK-2759-001
5. TERMINAL FOR USE IN HOUSING SERIES 6442 AND 41695.
6. SEE 7258 SERIES FOR THIS PART WITH CRIMP FOR 22-26 AWG. WIRE.
7. CRIMP FOR 18 TO 20 GA. WIRE WITH MAX. INSULATION DIA. OF .100/(2.79),
   STRIP LENGTH OF .125/.100 / (3.18/2.54)
8. DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT
   THOSE CENTERLINES WITHIN HALF THE TOTAL TOLERANCE.
9. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
10. ALTERNATE GEOMETRY PRESENT ON SOME PART NUMBERS. SEE SHEET 2.





SECTION A-A

LEGEND: 6838-* (*) * *


MATERIAL:
(.27)/.0106 THK
BLANK=BRASS
A=PHOS BRONZE

WINDING
A= PER DETAIL A
BLANK= PER DETAIL B

FORM
BLANK= CHAIN
L= LOOSE


PLATING
SEE NOTE 2

WINDING DETAIL "A"



PAPER
INTERLEAF

WINDING DETAIL "B"



PAPER
INTERLEAF

REV	DESCRIPTION	DATE
AQ	ADD ALT. GEOMETRY EC NO: UCP2011-0681 DRWN:MKIPPER CHKD:SSOUSEK APPR:FSMITH	2010/09/14 2011/02/23 2011/02/25
2	AQ	
1	AQ	
SHT	REV	

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .010
2 PLACES	± 0.25	± .015
1 PLACE	± 0.36	± ---
ANGULAR ±1/2°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	IN/MM
SCALE	---
DESIGN UNITS	INCH
	THIRD ANGLE PROJECTION
DRAWN BY	GUZIK
DATE	11/15/89
CHECKED BY	PATEL
DATE	11/15/89
APPROVED BY	LENZ
DATE	11/15/89
MATERIAL NO.	SEE CHART
TITLE	TRIFURCON TERMINAL CRIMP TYPE, .156 CENTERS 18 TO 20 AWG WIRE
	MOLEX INCORPORATED
DOCUMENT NO.	SD-6838
SHEET NO.	1 OF 2
SIZE	D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

6838-(*)*-*		
PART NO.	ENG. NO.	
08-50-0187	6838-(P909)	SEE NOTE 1
08-50-0189	6838-(P909)L	SEE NOTE 1
08-50-0275	6838-(P909)-A	
08-50-0026	6838-(P102)	
	6838-(P102)L	
08-50-0028	6838-(102)	
08-50-0029	6838-(102)L	

6838-A(*)*-*		
PART NO.	ENG. NO.	
08-58-0187	6838-A(P558)	
08-58-0189	6838-A(P558)L	
08-60-0001	6838-A(132)	
08-60-0002	6838-A(132)L	
08-58-0102	6838-A(558)	
	6838-A(558)L	
08-58-0108	6838-A(503)	
08-58-0109	6838-A(503)L	
08-52-0112	6838-A(P909)	SEE NOTE 1
08-52-0113	6838-A(P909)L	SEE NOTE 1
08-50-0024	6838-A(102)	
08-50-0251	6838-A(102)L	
08-58-0105	6838-A(P555)	
08-58-0106	6838-A(P555)L	
08-58-0110	6838-A(P561)	SEE NOTE 1
08-58-0111	6838-A(P561)L	SEE NOTE 1
08-58-0118	6838-A(561)	
08-58-0119	6838-A(561)L	
08-58-0131	6838-A(550)	
08-58-0132	6838-A(550)L	

NOTES:

1. PART MANUFACTURED WITH ALTERNATE GEOMETRY. SEE SHEET 1.

ADD ALT. GEOMETRY 2010/09/14
EC NO: UCP2011-0681 2011/02/23
DRWN:MKIPPER 2011/02/25
CHKD:SSOUSEK
APPR:FSMITH
DESCRIPTION
REV
AQ

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: IN/MM
SCALE: ---
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION


DRAWN BY: GUZIK DATE: 11/15/89
CHECKED BY: PATEL DATE: 11/15/89
APPROVED BY: LENZ DATE: 11/15/89


TITLE: TRIFURCON TERMINAL CRIMP TYPE, .156 CENTERS 18 TO 20 AWG WIRE


MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-6838
SHEET NO.: 2 OF 2
SIZE: D


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION








NOTES:
1. MATERIAL: SEE LEGEND
2. FINISH: 909 - OVERALL HOT TIN DIP: .000100/(0.00254) MIN.
3. PRODUCT SPECIFICATION: PS-40-02
4. PACKAGING SPECIFICATION: PK-6838-001
5. PART IS FOR USE WITH 18 TO 20 GA. WIRE WITH MAX. INSULATION DIA. OF .110/(2.79), STRIP LENGTH OF .125/.100 / (3.18/2.54).
6. SEE 7258 SERIES FOR THIS PART WITH CRIMP FOR 22-26 AWG. WIRE.
7. TERMINAL FOR USE IN 6442 AND 41695 SERIES HOUSINGS.
8. DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT THOSE CENTERLINES WITHIN HALF THE TOTAL TOLERANCE.
9. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.



SECTION A-A



LEGEND: 6838-* (P909) * *


MATERIAL:
(.27)/.0106 THK
BLANK=BRASS

WINDING
BLANK= PER DETAIL B


FORM
BLANK= CHAIN

PLATING PER SDES-88
SEE NOTE 2

WINDING DETAIL "A"



WINDING DETAIL "B"



UPDATE GEOMETRY
EC NO: UCP2011-0681
DRWN:MKIPPER 2010/09/14
CHKD:SSOUSEK 2011/02/23
APPR:FSMITH 2011/02/25
DESCRIPTION
REV: C

QUALITY SYMBOLS
▽ =0
▽ =0
▽ =0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .010
2 PLACES	± 0.25	± .015
1 PLACE	± 0.36	± ---
ANGULAR ±1/2°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: IN/MM
SCALE: ---
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

DRAWN BY: JJS 07/29/04
CHECKED BY: KSS 07/29/04
APPROVED BY: YM 07/29/04

TITLE: TRIFURCON TERMINAL CRIMP TYPE, .156 CENTERS 18 TO 20 AWG WIRE
MOLEX INCORPORATED
MATERIAL NO.: 50291639
DOCUMENT NO.: SD-6838-001
SHEET NO.: 1 OF 1
SIZE: D

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.