



Turn Signals Line Guide

Expert Construction. Tailored Solutions. Honeywell Sensing and Control (S&C) turn signal switches are built to perfectly complement our line of industry-leading shifters, or can be mounted as independent units. A wide variety of operations are available — from wiper speeds, headlamp controls and buttons to auto-cancel options. And each mechanism is built to withstand harsh environments.

But the best part is Honeywell S&C's unrivaled design experience. Which means we can expertly craft customized turn signal solutions to meet any of your exacting specifications. So whether it's a standard product or a customized solution, Honeywell S&C's tradition of quality and innovation is infused throughout every turn signal shipped.

FEATURES

TURN SIGNALS

Standard and Custom Designed.

Features: Broad product line • Designed for rugged environment • Sealed against elements (IP67 rating) • Vast array of optional features • Cycle life up to one million cycles • Capable of switching solenoid loads (with arc suppression: 2 A @ 12.8 Vdc)

Benefits: Innovative designs provide economical solutions. Turn signal control levers have multi-function capability. Potential applications include agricultural equipment (utility tractors, loaders), construction (telehandlers, loader/backhoes, forklifts) and material handling equipment, on-highway vehicles (trucks, refuse trucks), off-highway trucks, motor coaches, airport ground support equipment (tugs, de-icers).

Turn Signals Line Guide



Turn to the industry leader.

From cars to trucks to motor coaches to construction equipment, Honeywell S&C turn signals are often ideal for wiper speed and head lamp controls in most any on- or off-highway applications. Whether it's a customized solution or an out-of-the-box design, Honeywell S&C not only offers up the quality, but the amenities you'd expect from the manufacturing leader.

All products are tested for shock, vibration, mechanical, electrical, environmental, durability, and performance specifications.

Turn Signals

Turn signals are built to complement the shifter, or can also be mounted as stand alone. Specifications/ratings include:

| | |
|------------------------------------|--|
| Column size | 38 mm, 45 mm, 55 mm |
| Wiper speeds | 1 speed, hi/lo, intermittent |
| Lights | turn signal, head lamp switch, head lamp dimmer, flash to pass, hazard warning |
| Buttons | wash, horn |
| Connectors | integral packard, integral deutsch, wire harness |
| Auto cancel | available |
| Operating temperature range | -40 °C to 85 °C [-40 °F to 185 °F] (0 % to 95 % relative humidity) |
| Operating voltage range | 3 V to 32 V |
| Handle dead weight limit | 160 lbs [712 Newtons] |
| Solenoid load | 2 A @ 12.8 Vdc (with arc suppression) |

Warranty. Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

For more information about Sensing and Control products, visit www.honeywell.com/sensing or call +1-217-753-7752. Email inquiries to info.sc@honeywell.com

⚠ WARNING
PERSONAL INJURY

- DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

⚠ WARNING
MISUSE OF DOCUMENTATION

- The information presented in this catalogue is for reference only. DO NOT USE this document as product installation information.
- Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

Sensing and Control
Automation and Control Solutions
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422 USA
+1-217-753-7752
www.honeywell.com/sensing

0095781-EN IL50 GLO
July 2008
Copyright © 2008 Honeywell International Inc. All rights reserved.

Honeywell



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.